



Zoya

Free-standing luminaires can be placed easily anywhere in the room, providing direct and indirect light wherever the user needs it.

ZOYA A&C are designed for floor-standing use, while **ZOYA B&D** are ideal for desk installation.

Featuring a direct and indirect optic design (UGR <16) with 75% upward and 25% downward light distribution, ZOYA delivers high visual comfort and uniformity at up to 125 lm/W efficiency.

For direct lighting, it offers both symmetrical polarized and forward polarized light options, meeting diverse lighting needs. The lamp pole includes plug-and-play connectivity, a touch-sensitive 0-10V dimmer, light sensor, PIR sensor, and USB port

Lighting functions are activated via a single button and operate fully automatically. Control modules are interchangeable, making ZOYA ideal for modern office environments.


Casambi Bluetooth wireless control enables smart lighting management via smartphone or tablet, including Tunable White functionality and brightness adjustment.

Easy and Intelligent Light Management

Key features

- Easy for assembly and maintenance
- Symmetrical polarized light and forward polarized light options
- High lighting efficiency, 125lm/W
- Precise optical design: UGR<16, up 75% & down 25% lighting
- Plug and play, light sensor, PIR sensor, USB charging functions
- Touchable 0-10V dimming
- Tunable White (Brightness and CCT adjustment) or brightness adjustment
- Easy for assembly and maintenance
- Symmetrical polarized light and forward polarized light options
- High lighting efficiency, 130lm/W
- Precise optical design: UGR<16, up 80% & down 20% lighting
- Plug and play, convenient for different position
- Casambi Bluetooth wireless control
- Tridonic DALI dimming

Mounting



Floor standing



Desk fixing

Applications

- Office
- Meeting room
- Hotel

Technical Data

Model No.	ZOYA/A-80W -DOS	ZOYA/B-80W-DOS	ZOYA/C-85W-B	ZOYA/C-75W-B1	ZOYA/D-85W-B	ZOYA/D-75W-B1
Power Consumption	80W	80W	85W	75W	85W	75W
Input Voltage	AC220-240V					
Power Factor	0.93					
Control	0-10V		0-10V, Analog/Digital dimming control, DALI, Casambi			
Sensor	PIR sensor / Daylight sensor		/			
LED Driver	Built-in					

Optic Information

LED Type	SMD 2835				
Luminous Flux (±5%)	9000-10500lm	9200-10500lm	9000-10500lm	9200-10500lm	9000-10500lm
Efficacy	125lm/W	130lm/W			
Correlated Color Temperature	3000K/4000K/5000K/5700K	2700K-6500K	3000K/4000K/5000K/5700K	2700K-6500K	3000K/4000K/5000K/5700K
Color Rendering Index	Ra80				
Beam Angle	80°x50°/60°x-60°x15°				
UGR level	<16				


Dimensions and Mounting

Product Dimension	2050x1085x240mm	1380x1115x70mm
Luminaire Net Weight	5.7kg	5.1kg
Floor Standing Net Weight	6.8kg	
Mounting Option	Pedestal mounted / Desktop mounted	
Material	PC / Aluminum	
Finish Color	White RAL 9016	
Protection Class	Class 1	
IP Rating	IP20	

Floor standing



Desk fixing



Type	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)
ZOYA Floor	1060	60	53	2026	580	240
ZOYA Desk	1060	60	53	1276	140	70

Lifespan and Warranty

Operating Temperature	-10°C to 40°C
Storage Temperature	-20°C to 60°C
Lifetime of LED	50.000hrs-L80
Warranty	5 Years

Photometry

