



Ettela


The flat, ready-to-install LED panel has been equipped with high-quality LEDs. The light guide and the matching diffuser material ensure an extremely homogeneous ceiling effect. Thanks to UGR < 22, the Ettela edge-lit panel is ideal for use in offices. With the optional accessories, both the pendant and the surface-mounted version are quick and easy to install.




Key features

- For suspended ceilings with grid dimension of 600 mm
- With pre-installed connection cable and integrated plug
- Efficiency up to 120 lm/W
- UGR < 22
- Color temperatures 3000 K, 4000 K and 6500 K
- Diffuser material Standard article: Polystyrene (PS)
- Lifetime: 30,000 hours
- 5 years guarantee

Accessories



Surface mount kit
Aluminum frame for easy surface mounting



Suspension kit
Steel wire system for suspended mounting

Technical Data @800 mA

Model No.	ETTELA 830	ETTELA 840	ETTELA 865
Power Consumption	31,7W		
Forward current (mA)	800		

Optic Information

Luminous Flux (±5%)	3800 lm		
Efficacy	112 lm/W		
Correlated Color Temperature	3000K	4000K	6500K
Color Rendering Index	> 80		
Beam Angle	110°		
UGR level	< 22		

Dimensions and Mounting

Product Dimension	600x600mm
Luminaire Net Weight	2.3 kg
Mounting Option	Surface mount, suspension mount
Material	Polystyrene (PS)
IK Rating	IK02
IP Rating	IP40 (front) / IP20 (back)

Lifespan and Warranty

Operating Temperature	-20°C to +40°C
Lifetime of LED	30.000hrs-L70
Warranty	5 years