



Roma

A modern LED luminaire with high optical and technical performance, designed for installation in suspended ceilings. It features symmetrically arranged aluminum louvers for optimized light control and visual comfort.

Light Data

| | |
|--------------------------------|--------------------------|
| Luminaire luminous flux | 1040 - 9170 lm |
| Luminous efficacy | 104 - 162 lm/W |
| Color rendering index | 80, 90 |
| Light distribution | Medium-stream, Wide beam |
| MacAdam | SDCM 3 |
| Lifetime L80B10 @25°C | 100000 h |
| Colour temperature | 2700-6500K, 3000K, 4000K |

Electrical Data

| | |
|----------------------------------|--------------|
| Light source | LED |
| Luminaire power | 10 - 60 W |
| Type of equipment | AC |
| Voltage rating | 220 - 240 V |
| Type of driver | DALI, ON/OFF |
| EM module / Motion sensor | Optional |

Mechanical Data

| | |
|-----------------------------|---------------------|
| Type of installation | For 600x600 ceiling |
| Housing material | Steel sheet |

Information Data

| | |
|------------------------------------|---------------------------|
| Colour | White |
| Operating temperature range | -15°C to + 40°C |
| IP Rating | IP20 (top), IP40 (bottom) |
| IK Rating | IK04 |

Optical Data

| | |
|-------------------------|--------------------|
| Louver/ diffuser | MPRM, OPAL |
| UGR | 14, 16, 17, 18, 19 |

Dimensions

| L (mm) | W (mm) | H (mm) |
|--------|--------|--------|
| 596 | 596 | 108 |
| 1195 | 596 | 108 |
| 596 | 295 | 108 |
| 1195 | 295 | 108 |

