



Palus


Palus bulkhead luminaire features a die-cast aluminum body and a 94-V0 fire-rated polycarbonate cover for enhanced durability and safety. Equipped with a 3-CCT selectable system via an internal switch, it offers flexibility in color temperature. An ideal solution to complete and elevate your outdoor lighting design.



Key features

- Round fixture, with 94-V0 PC cover
- Long lifetime of 50,000 hours
- CCT: 3000K 4000K 5000K 5700K
- Built-in LED driver
- High ingress protection rating: IP65, IK10, Class I
- Ideal replacement for traditional Halogen or fluorescent wall lights

Dimensions



Type	A (mm)	B (mm)	C (mm)
PALUS-10-12W	250	58	229
PALUS-10-18W	250	58	229

Applications

- Office
- Public Areas
- Stairway
- Lobby
- Reception
- Corridors

Technical Data

Model No.	PALUS-10-12W	PALUS-10-18W
Power Consumption	12W	18W
Input Voltage	AC200 - 240V	
Power Factor	0.9	
Control	Dimming (optional)	

Dimensions and Mounting

Product Dimension	Ø250x58mm
Luminaire Net Weight	1.05kg
Mounting Option	Surface mount
Material	PC / Aluminum
Finish Color	White RAL 9016 / Black RAL 9005
Protection Class	Class 1
IK Rating	IK10
IP Rating	IP65

3-CCT in 1 Lamp

A side switch allows for an instant transition of color temperature.



Optic Information

LED Type	SMD	
Luminous Flux (1-CCT) Non-DIM	1050 - 1250lm	1500 - 1850lm
Luminous Flux (3-CCT) Non-DIM	1000 - 1200lm	1450 - 1800lm
Correlated Color Temperature	3-CCT: 3000K + 4000K + 5700K	
Color Rendering Index	Ra80	
Beam Angle	110°	

Lifespan and Warranty

Operating Temperature	-20°C to 45°C
Storage Temperature	-20°C to 65°C
Lifetime of LED	50.000hrs-L80
Warranty	5 Years