



Elza

This ceiling light is a super slim design. High lumen SMD LED and lighter weight fire-rated material to ensure better heat resistance and corrosion resistance. The color is interchangeable within 3000K, 4000K and 5700K by slide switch, also dimmable with triac dimmers. Multi-functional design shares great popularity.



Technical Data

Model No.	ELZA-10-12	ELZA-14-25
Power Consumption	12W	25W
Input Voltage	AC200 - 240V	
Power Factor	0.9	
Control	Dimmable with Triac	

Key features

- High lumen efficiency
- Interchangeable CCT with slide switch
- IP54 in front
- Triac dimming
- Internal driver

Applications

- Office
- Supermarket
- Shop
- School
- Hotel
- Stairway
- Lobby

Optic Information

LED Type	SMD	
Luminous Flux	1160 - 1350lm	2300 - 2575lm
Correlated Color Temperature	3-CCT: 3000K + 4000K + 5700K	
Color Rendering Index	Ra80	
Beam Angle	120°	

Dimensions and Mounting

Product Dimension (mm)	250x250x50	350x350x41.5
Luminaire Net Weight	0.75kg	1.42kg
Mounting Option	Surface mounted	
Material	Polycarbonate (PC)	
Finish Color	White RAL 9016	
Protection Class	Class 2	
IP Rating	IP54	
IK Rating	IK10	

Lifespan and Warranty

Operating Temperature	-20°C to 45°C
Storage Temperature	-20°C to 65°C
Lifetime of LED	40.000hrs-L80
Warranty	5 Years

Dimensions

	Type	A (mm)	B (mm)	C (mm)
	ELZA-10-12	250	50	220
	ELZA-14-25	350	41.5	320