



Pia

The round, minimalist LED ceiling light PIA. Due to its simple appearance, it fits into a wide variety of interiors with surface-mount installation. Aluminum white housing can be matched with a golden decorative ring, which makes this light look elegant and textured. Opal diffuser(UL94-V2) for general lighting with maximum transmittance and homogeneous lighting.




Key features

- Interchangeable CCT(3000K+4000K+5700K) with slide switch
- IP44 waterproof
- ADC12 aluminum housing provides a great thermal management
- Internal flicker free driver

Applications

- Office
- Supermarket
- School
- Hotel
- Home

Dimensions



18W
A:Ø301 mm x B:58 mm x
C:Ø276 mm

24W
A:Ø422 mm x B:58 mm x
C:Ø396 mm

Technical Data

Model No.	PIA-12-18W	PIA-12-24W	PIA-16-24W
Power Consumption	18W	24W	24W
Input Voltage	AC200 - 240V		
Power Factor	0.9		
Dimmable	Non-dimmable		

Optic Information

LED Type	SMD	
Luminous Flux	1300 - 1700lm	2000 - 2420lm
Correlated Color Temperature	3CCT (3000K + 4000K + 5700K)	
Color Rendering Index	Ra80	
Beam Angle	120°	

Dimensions and Mounting

Product Dimension	Ø301x58 mm	Ø422x58 mm
Luminaire Net Weight	1.3 kg	2.2 kg
Mounting Option	Surface mount	
Material	Aluminium(ADC12) + PC	
Finish Color	White RAL9016 & Golden 7407U Black RAL9005 & Golden 7407U Black RAL9005 & Black RAL9005	
Protection Class	Class 2	
IP Rating	IP44	
IK Rating	IK06	

Lifespan and Warranty

Operating Temperature	-20°C to 45°C
Storage Temperature	-20°C to 60°C
Lifetime of LED	50.000hrs
Warranty	3 Years