



Roma II

Elegant recessed LED luminaire for cleanrooms and technical spaces. IP65-rated, with opal or microprismatic diffuser. Fits standard 600x600 mm ceiling grids.

Application & Mounting

Application: Laboratory, Treatment rooms, Operating theatre, Doctor's office, Infirmary, Technical room, Swimming pool, Production hall
Mounting: Modular recessed

Mechanical Data

Type of installation	Recessed
Housing material	Steel sheet

Electrical Data

Light source	LED
Luminaire power	43 - 100 W
Type of equipment	AC
Voltage rating	220 - 240 V
Type of driver	DALI, ON/OFF
Optional	Emergency module, Motion sensor

Light Data

Luminous Flux	3410 - 11280 lm
Efficacy	79 - 127 lm/W
Correlated Color Temperature	3000K, 4000K
Color Rendering Index	Ra80, Ra90
Lifetime L80B10 @25°C	100.000 h
MacAdam	SDCM 3
IP Rating	IP65
IK Rating	IK07

Optical Data

Louver/ diffuser	MPRM, OPAL, PAR, PAR SH, SH MAT
Louver material	Aluminum
Reflector	High gloss
UGR	16, 18, 19, 22

Information Data

Net weight	6.4 - 17 kg
Colour	White

Dimensions

L (mm)	W (mm)	H (mm)
596	596	85
1196	596	85
596	296	85
1196	296	85

