



# Torino II

Durable surface-mounted LED luminaire designed for cleanrooms and industrial environments. Offers IP65 protection and is available with opal or microprismatic diffuser for optimal light control. Ideal for applications requiring reliability and high hygiene standards.

## Application & Mounting

**Application:** Laboratory, Treatment rooms, Operating theatre, Doctor's office, Infirmary, Technical room, Swimming pool, Production hall  
**Mounting:** Ceiling mounted

## Mechanical Data

Type of installation	300x1200, 600x600 ceiling
Housing material	Steel sheet

## Electrical Data

Light source	LED
Luminaire power	43 - 100 W
Type of equipment	AC
Voltage rating	220 - 240 V
Type of driver	DALI, ON/OFF
Optional	Emergency module, Motion sensor

## Light Data

Luminous Flux	3250 - 9560 lm
Efficacy	76 - 127 lm/W
Correlated Color Temperature	3000K, 4000K
Color Rendering Index	Ra80, Ra90
Lifetime L80B10 @25°C	100.000 h
MacAdam	SDCM 3
IP Rating	IP65
IK Rating	IK07

## Optical Data

Louver/ diffuser	MPRM, OPAL, PAR, PAR SH, SH MAT
Louver material	Aluminum
Reflector	High gloss
UGR	17, 18, 19

## Information Data

Net weight	5.6 - 10.5 kg
Colour	White

## Dimensions

L (mm)	W (mm)	H (mm)
596	596	68
1196	596	68
596	296	68
1196	296	68

