



Roma IP54

Recessed LED luminaire designed for environments requiring enhanced IP protection. Suitable for 600x600 mm modular ceilings with a visible grid, featuring an opal diffuser for uniform light distribution.

Application & Mounting

Application: Bathroom, Corridor and staircase, Cloak room, Technical room, Security, Social room
Mounting: Modular recessed

Mechanical Data

Type of installation	300x1200, 600x600 ceiling
Housing material	Steel sheet

Electrical Data

Light source	LED
Luminaire power	38 - 43 W
Type of equipment	AC
Voltage rating	220 - 240 V
Type of driver	DALI, ON/OFF
Optional	Emergency module, Motion sensor

Light Data

Luminous Flux	3510 - 4870 lm
Efficacy	87 - 128 lm/W
Correlated Color Temperature	3000K, 4000K
Color Rendering Index	Ra80, Ra90
Lifetime L80B10 @25°C	100.000 h
MacAdam	SDCM 3
IP Rating	IP54
IK Rating	IK04

Optical Data

Louver/ diffuser	MPOP, MPRM, OPAL
Reflector	High gloss
UGR	18, 19

Information Data

Net weight	4.6 - 5.4 kg
Colour	Black, Grey, White

Dimensions

L (mm)	W (mm)	H (mm)
595	595	80/118
1195	595	80/118
595	295	80/118
1195	295	80/118