



Torino IP54

Functional surface-mounted LED luminaire with uniform light distribution and quick installation. Offers IP54 protection and reliable performance in technical spaces.

Application & Mounting

Application: Bathroom, Corridor and staircase, Cloak room, Technical room, Security, Social room
Mounting: Ceiling mounted

Mechanical Data

Type of installation	300x1200, 600x600 ceiling
Housing material	Steel sheet

Electrical Data

Light source	LED
Luminaire power	21 - 30 W
Type of equipment	AC
Voltage rating	220 - 240 V
Power factor	0.96
Type of driver	DALI, ON/OFF
Optional	Emergency module, Motion sensor

Light Data

Luminous Flux	2700 - 4340 lm
Efficacy	126 - 148 lm/W
Correlated Color Temperature	3000K, 4000K
Color Rendering Index	Ra80
Lifetime L80B10 @25°C	100.000 h
MacAdam	SDCM 3
IP Rating	IP54
IK Rating	IK04

Optical Data

Louver/ diffuser	MPRM, OPAL
UGR	16, 17, 18, 19

Information Data

Net weight	6.5 kg
Colour	Black, Grey, White

Dimensions

L (mm)	W (mm)	H (mm)	H
595	595	65	
1195	595	65	
595	295	65	
1195	295	65	