

All prices are recommended gross sales prices including VAT. We keep the right to adjust the prices during the validity of the catalogue. You will always find the current prices on our website. Our general terms and conditions apply. Errors and availability reserved. All articles are basically delivered without illuminants, unless the product description specifies otherwise.

THE RIGHT LIGHTING FOR EVERY APPLICATION

Our versatile range for professional building lighting offers you the right solution - whether for refurbishment, modernisation or new build. With well thought-out lighting concepts and innovative products, we create optimum conditions for every application situation.



industrie



hotel and catering industry



living space



retail trade



outdoor area



office



educational institution



healthcare facility

04 product highlights

INTERIOR LIGHTS

- 34 pendant lights
- 58 surface mounted ceiling lights
- 106 built in ceiling lights
- 156 downlights
- 178 insert panels
- 198 surface mounted wall lights
- 208 built in wall lights
- 218 reading lights
- 228 table and floor lights
- 238 showcase lights
- 246 office lights
- 270 hall floodlight
- 280 damp-proof luminaires

SINGLE-PHASE LIGHTS

- 294 single-phase lights

POWER RAILS

- 304 D ONE 1-phase power rail system
- 322 1-phase power rail luminaires
- 338 D Line 3-phase power rail system
- 370 D Line DALI 3-phase power rail system
- 398 power rail luminaires

BATTERY AND SOLAR LIGHTS

- 448 battery lights
- 456 solar lights

OUTDOOR LIGHTS

- 464 bollard lights
- 484 surface mounted wall lights
- 522 ceiling and wall lights
- 526 built in wall lights
- 532 spherical lamps
- 536 energy distributor
- 546 surface mounted / ground spike lights
- 556 wall washer
- 560 ground recessed lights
- 580 floodlight
- 586 display lights

SYSTEM LAUTARO

- 592 pendant lights
- 598 surface mounted ceiling lights

SYSTEM PLANO

- 604 luminaire system
- 622 profile system

SYSTEM COMBO

- 630 concrete profile
- 636 built-in profile
- 640 facade profile
- 644 insulation profile
- 646 click profile

ALUMINIUM PROFILES

- 652 linear light in 5 steps
- 656 assembly
- 658 homogeneous light image
- 660 U-profiles – flat + high – built-in / built-on
- 684 T-profiles – flat + high – built-in
- 702 H- and groove-profiles
- 710 step/plinth/angle/corner-profiles – built-in / built-on
- 734 dry construction profiles
- 754 tile profiles
- 770 profiles for outdoor usw – walkable/trafficable

LED STRIPES

- 786 COB
- 800 12V
- 802 24V
- 840 48V
- 854 230V
- 856 mounting material for LED stripes

POWER SUPPLIES

- 862 DC – CV
- 878 DC – CC
- 892 AC – CV

CONTROLLER


- 898 RF-Smart
- 920 Casambi Bluetooth
- 922 DMX-controller / dimmer
- 926 DALI PWM dimmer

ILLUMINANTS

- 934 MR16 / GU53
- 935 G9 – GU10
- 939 E27
- 943 R7s – GX53

ACCESSOIRES

- 948 indoor
- 951 outdoor
- 959 chemical products
- 960 legend
- 968 lighting solutions
- 972 index



SANOTRUNK UNIVERSAL

LED refurbishment doesn't have to be a major construction project. With the right products, it can be completed quickly, safely and economically. With SANOTRUNK UNIVERSAL, DEKO-LIGHT offers an LED system for the simple retrofit of existing T5/T8 trunking systems, which is compatible with almost all common trunking rails on the market. This allows users to continue using their existing trunking rails without having to forgo the many advantages of modern LED technology.



SANOTRUNK UNIVERSAL is compatible with over 40 brands and systems. You can find the complete list here.


All information on the SANOTRUNK UNIVERSAL can be found from page 290.

SANOTRUNK UNIVERSAL is the ideal solution for refurbishing high-bay warehouses, industrial and storage halls, or DIY and supermarkets, and sets new standards in terms of compatibility. Thanks to quick-mounting clips and tool-free installation, the system can be quickly and easily integrated into existing trunking systems. The retrofit takes place in five simple steps:



REMOVE OLD LUMINAIRE INSERTS

Simply unclip the existing T5/T8 luminaires from the current trunking rail – the wiring remains in the rail and does not need to be replaced.




HOOK IN NEW LED MODULES

The SANOTRUNK LED modules are inserted into the existing trunking rail without tools – no drilling or screwing required.



CONNECT MODULES AND SET OUTPUT

The LED modules can be connected quickly and securely using integrated plug connectors. Optionally, the desired power level can be selected via the power switch.



CLICK IN MODULES

The pre-mounted quick-mounting clips ensure a secure fit in the trunking rail – regardless of the manufacturer.






DONE

The retrofit is complete – the new LED lighting is ready for immediate use.

BENEFITS FOR EVERY APPLICATION

The SANOTRUNK UNIVERSAL refurbishment insert offers a wide range of possible applications and enables sustainable modernisation of your lighting.



Supermarket / Sales Area

Optic: 25° asymmetric, single- or double-sided



Benefit: The asymmetric light distribution illuminates shelf areas precisely, avoids stray light in the aisles, and creates a pleasant, sales-promoting atmosphere.



Industrial and Production Halls

Optic: 90° beam angle

Benefit: Uniform, standard-compliant illumination of work areas. Ideal for precision tasks and safety-relevant activities.



Warehouse / High-Bay Storage

Optics: 30°, 60° or 90°

Benefit: Deep shelving aisles and varying storage heights can be illuminated with pinpoint accuracy. The light reaches the lowest and highest levels – without shadows or isolated light spots.



Workshops / Assembly Areas

Optic: 120° beam angle

Benefit: Broad, low-shadow illumination of entire rooms. Perfect for fine assembly work, inspections, or manual tasks with high lighting requirements.




PRO OFFICE SANO

The PRO OFFICE SANO ceiling luminaires are the ideal solution for converting old grid luminaires to modern LED technology – quickly, efficiently and without complex renovation work. Thanks to their well-designed housing shape, the panels are slightly larger than traditional T5/T8 luminaires and effortlessly cover old drill holes or discoloration on ceilings and walls. This not only eliminates the need for painting, but also ensures a clean, uniform appearance.


Installation is fast and tool-free thanks to safety cables, mounting brackets and plug-in systems – often manageable by a single person. This significantly reduces installation effort without compromising on safety or stability. All panels feature a three-step adjustable colour temperature (3,000 K / 3,500 K / 4,000 K). The TRIAC models also offer four-level power adjustment – ideal for optimising energy consumption and brightness.

The microprismatic surface and a 90° beam angle ensure glare-free, uniform lighting that meets the requirements for computer workstations according to EN 12464-1. With a colour rendering index of $Ra \geq 90$, the panels provide high-quality light for productive work. In addition to their high efficiency (up to 5,500 lumens at just 42 W), the luminaires are also suitable for emergency power operation (176–280 V/DC, EOFI: 95%) – a valuable feature for safety-relevant areas. All models are eligible for BEG funding, making them particularly attractive for sustainable refurbishment projects in existing buildings.


All information on PRO OFFICE SANO can be found from page 98.




old T5/T8 grid luminaire on the ceiling



remove old grid luminaire



hook in new panel – with safety cable and pre-assembled plug connection



slide panel onto mounting bracket – luminaire sits securely

TARVOS

The TARVOS series offers a well-designed LED downlight portfolio for professional indoor lighting solutions. The name of each luminaire directly refers to the cut-out diameter in millimeters – TARVOS 68, 100, 150, or 240. This allows the models to be planned quickly and precisely into existing or new ceiling cut-outs. All TARVOS recessed spotlights are suitable for emergency power operation, feature a round housing, and are available in several variants that differ in housing colour, light colour, beam angle, and control [see list]. This enables precise and individual adaptation of the lighting effect to the respective application – from pinpoint accentuation to wide, diffuse general lighting.



Overview of variants

- housing colour: black, light grey, white
- colour temperature: 2700K, 3000K, 4000K
- beam angle: 15°, 30°, 45°
- control: DALI 2.0, DT6, push dim

The TARVOS series meets the requirements for BEG funding (Federal Funding for Efficient Buildings). Combined with its high energy efficiency and long-lasting LED technology, the recessed spotlights thus present a future-proof solution from both economic and ecological perspectives – especially for refurbishment projects in existing buildings. The range covers offices, corridors and stairwells, retail and gastronomy areas, as well as public facilities.

All information on the TARVOS series can be found from page 130.







ANIK

The ANIK series stands for modern lighting solutions with minimal installation depth and maximum design freedom. With its elegant design language – available as either round or square versions – and three variants [Standard, CCT, RGBW], it offers flexible options for indoor use. The downlights are equipped with high-quality LEDs and feature a wide light distribution of 120° as well as excellent colour rendering ($R_a > 90$). Additionally, low glare [$UGR < 19$] ensures high visual comfort – ideal for computer workstations and longer stays in the room.

Thanks to the particularly slim design [maximum installation depth 36 mm] and its elegant aluminium housing, the ANIK is perfect for demanding applications in ceilings with limited installation depth – for example in hotels, shops, corridors, or bathrooms. The series is splash-proof according to IP44 [downwards when installed] and can be individually combined with suitable power supplies.

All luminaires in the ANIK series are supplied without power supplies and can be combined with various dimmable or switchable drivers. The extensive accessories enable flexible integration into existing or new control systems [e.g., DALI DT6/DT8, Casambi, PWM, or wireless].

All information on the ANIK series can be found from page 158.

OVERVIEW OF VARIANTS



ANIK ROUND

Classic round downlights in four sizes and three colour temperatures [2,700 / 3,000 / 4,000 K]. Ideal for use in residential and commercial areas.

ANIK ROUND CCT

Tunable white variant for dynamic light atmospheres from 2,700 - 6,500 K. Controllable via DALI, RF-Smart, Casambi, or DMX.

ANIK ROUND RGBW

The ANIK for coloured light accents: RGB reproduction plus warm white [3,000 K] for creative applications.



ANIK SQUARE

Square version in four sizes and three colour temperatures [2,700 / 3,000 / 4,000 K] – for modern, clean architectures.

ANIK SQUARE CCT

Tunable white variant in square format – individually controllable, e.g., for modern offices, hotels, or retail spaces.

ANIK SQUARE RGBW

RGBW solutions in square format for impressive accents and individual light design.



ACRUX PRO

The ACRUX PRO series combines compact design with maximum functionality. Whether for living spaces, corridors, or commercial areas, the recessed downlights impress with their high light quality [Ra > 90], flexible adjustment options, and easy installation.

Thanks to the integrated power supply, a 230V direct connection is possible without additional accessories. The integrated CCT switch allows the colour temperature to be set before installation to 2,700 K, 3,000 K, or 4,000 K – ideal for different room requirements. For models from Ø 145 mm upwards, an additional power switch is used to adjust the output in three stages. This enables precise control of the light output – all without external control.

With a high efficiency of over 120 lm/W, IP54 protection rating [downwards], and the possibility for through-wiring, the ACRUX PRO is also well suited for larger installation projects. Additionally, it is BEG eligible and thus meets all requirements for energy-efficient construction and renovation.

All information on the new ACRUX PRO can be found on page 157.





ALWAID PRO

The new ALWAID PRO series combines functional wall-mounted recessed luminaires with a compact design, elegant appearance, and practical features. With a mounting depth of only 39 mm, the luminaires fit into all common 68 mm switch boxes – whether standard or deep versions. This makes the ALWAID PRO ideal for renovations and new constructions with limited space.

The ALWAID PRO series offers maximum design freedom: all luminaires are available with both round and square covers. Two colour options are available for the housing – white and black – as well as two high-quality material finishes: aluminium and glass/polycarbonate. Additionally, a selection of geometric light exit openings provides individual lighting moods depending on the application and architectural requirements. Furthermore, the recessed spots [2,700 K or 3,000 K] are available as dimmable versions or as ALWAID PRO MOTION with integrated motion sensor. The latter additionally offers a two-stage power switch [2 W / 4 W] for individual adjustment of light output.

All variants are equipped with an integrated power supply for 230V direct connection and can be easily through-wired – ideal for series installations in corridors or staircases.

All information on the new ALWAID PRO can be found from page 208.





CAN MIX'N MATCH

The new CAN series is the all-round solution for both private and commercial use – more extensive than ever before! Whether pendant light, ceiling light, wall light, reading light, track light, table and floor lamp, or outdoor luminaire – CAN is available in numerous variants and feels at home almost anywhere: living rooms, hotel rooms, restaurants, or garden areas.

With the new Mix'n Match variant – available for almost every type of luminaire – CAN can now be designed even more individually and adapted to different environments. The modular principle includes base, cylinder housing, and reflector ring as well as individual accessories, which, however, do not affect the look of the luminaire itself.

All information on the CAN MIX'N MATCH series can be found from page 94.

1

choose BASE

Define the CAN luminaire type:
ceiling light, wall light, floor lamp, etc.

2

select CYLINDER HOUSING

The cylinder housing is available in six different colours:
black, white, dark grey, brass, bronze, rose gold.

3

add REFLECTOR RING

Combine the reflector ring colour-matched to the cylinder housing
or create a deliberate contrast.

4

ACCESSORIES [optional]

If desired, the CAN can be complemented with a honeycomb filter
or a special lens.





HIGHBAY BASIC

The HIGHBAY BASIC series combines high luminous output, robust industrial quality, and maximum energy efficiency – ideal for workshops, production areas, warehouses, or sales areas with high ceilings. Both variants – HIGHBAY BASIC and HIGHBAY BASIC DALI – impress with a compact IP65 housing featuring integrated power and CCT control, allowing flexible adjustment of power [110W / 160W / 210W] and colour temperature [4,000K / 4,500K / 5,700K] to suit the specific usage and environment.

With a luminous flux of up to 34,500 lumens and a wide beam angle of 90°, the HIGHBAY BASIC is perfect for large-area lighting. Optional lenses [60° / 120°] enable targeted light control, for example in aisles, production floors, or sales areas. The DALI version is also equipped with a modern DALI-2 / DT6 D4i driver and supports Intelli-Data for monitoring energy, maintenance, and luminaire data according to DALI Parts 251, 252, and 253 – a real advantage for smart lighting networks in industrial settings.

HIGHBAY BASIC AT A GLANCE


- high luminous flux up to 34,500 lm
- selectable power: 110W / 160W / 210W
- switchable color temperature: 4,000K / 4,500K / 5,700K
- protection rating IP65 – ideal for industrial and commercial use
- robust IK08 housing made of aluminum and steel
- beam angle: 90° [optional: 60° / 120°]
- DALI 2 DT6 D4i [for DALI version] including Intelli-Data

FOR INDUSTRY, TRADE, AND COMMERCIAL USE

The HIGHBAY BASIC series is ideal for all applications requiring high light output, long operating hours, and economical operation, such as industrial halls, supermarkets, hardware stores, car dealerships, or storage areas. The simple installation with chain suspension or wall bracket, flexible control options, and robust materials make this series the perfect solution for energy-efficient lighting concepts with high operational reliability.

All information on the HIGHBAY BASIC can be found from page 270.





LUCEA DALI

The LUCEA DALI track luminaires combine minimalist design with state-of-the-art control technology – ideal for projects where aesthetics, flexibility, and precise lighting control are equally important. Whether in retail, office, or public spaces, LUCEA blends seamlessly into any interior and can be controlled via DALI 2 / DT6 or Push-Dim with high precision.

The LUCEA DALI series is available in two versions: a classic spotlight and an elegant pendant luminaire. Both are fully compatible with the exclusive D LINE DALI track system available from DE-KO-LIGHT. All models in the series are emergency power-capable [176–280 V/DC, EOFI: 100%] and come in various output levels [10 to 40 W], with fixed or switchable colour temperatures [CCT: 3,000 K / 4,000 K], and selectable luminous flux [up to 4,480 lm] – ideal for zoned lighting, accent lighting, or general illumination.

LUCEA DALI luminaires are perfect for high-end lighting concepts in retail environments, gastronomy, offices, hotels, galleries, or residential spaces. With their clean cylindrical design in black or white and tool-free mounting onto track systems, they offer both technical and visual flexibility. A wide range of accessories – including barn doors, interchangeable lenses [24° / 60°], and decorative black reflector rings – allows for custom lighting effects that can be adapted at any time.

All information on LUCEA DALI can be found from page 426.





1,080 GOOD REASONS

The LAUTARO surface-mounted and pendant light offers so many variants. But don't worry: the configuration is very simple! LAUTARO is a new luminaire series which, despite its enormous configuration options, has one thing in common: it is round or ring-shaped and has a uniform, all-round light emission. But that's where the similarities end. All other product features can be selected, making LAUTARO ideal for a wide range of commercial [and private] applications, including reception areas, restaurants, atriums, open-plan offices and much more.

DALI for all

All LAUTARO variants are equipped with an integrated DALI power supply unit and are dimmable. The power supply units are suitable for emergency power and facilitate installation thanks to integrated loop-in/loop-out technology.

All information on the LAUTARO series can be found from page 588.



Is your desired variant not included in the standard range? Then simply configure your customised LAUTARO using our online configurator.



6 STEPS TO A CUSTOMISED LAUTARO

1. SELECT THE PRODUCT VARIANT

The LAUTARO is available as a surface-mounted or pendant luminaire - the latter with two types of suspension and direct or direct/indirect lighting.

2. SELECT THE PROFILE

There is a choice of three different profiles [height x width in mm]: 60x40, 80x55 and 100x80.

3. SELECT THE DIAMETER

In order to use the LAUTARO in different room sizes and applications, it is available in four diameters: 600, 900, 1,200 and 1,500 mm.

4. SELECT THE HOUSING COLOUR

Black, grey, white - each in matt with a powder-coated surface. Individual RAL colours are available on special request.

5. SELECT THE DIFFUSER

In addition to the opal diffuser, a microprismatic version is also available for use in workplaces with particularly low glare [UGR<19].

6. SELECT THE COLOUR TEMPERATURE

2,700K, 3,000K or 4,000K - incandescent lamp, warm white or neutral white. With these three colour temperatures, you can cover most lighting requirements.





SHORELINE

The SHORELINE PRO series features premium surface-mounted wall luminaires for outdoor use, offering maximum design freedom for modern façade and architectural lighting. With more than a dozen models in round or square designs – available as downlights or up-and-down variants – the series covers a wide range of applications, from residential and commercial buildings to hotel and hospitality environments.

All luminaires are made from durable die-cast aluminum, are seawater-resistant, and offer IP65 protection and IK08 impact resistance. The integrated technology allows for two-stage color temperature switching [3,000K / 4,000K] directly on the unit, while the high-quality optics ensure targeted, uniform light distribution.



These lights have been developed for use in coastal regions and can withstand the increased salt and moisture in the environment - ideal for outdoor areas near the sea.

EASY INSTALLATION

The SHORELINE PRO series has been specifically designed for fast and secure installation, featuring several well-thought-out mounting details:

- detachable mounting plate with plug-in connector for easy pre-installation
- angled locking screws for improved accessibility during fastening
- through-wiring capability for continuous row installation
- optional spacers available for a clean and elegant surface-mount – even on uneven walls

ACCESSORIES FOR SHORELINE PRO

- reflector inserts: 24°, 30°, 36°, 60° [depending on the model]
- covers: with slot or triangle openings [for directional light emission]
- spacers: for clean surface mounting on uneven backgrounds

Note: All accessories are available in colors matching the housing finish [white, black, grey].

All information on the SHORELINE series can be found from page 484.



FACADO II

FACADO II is our flexible solution for outdoor lighting - either as a bollard light or as a wall light. In both versions, the IP65 luminaires made of robust die-cast aluminium offer a wide range of optical options: angular or round shape, with opal or transparent diffuser in smoked glass look, in dark grey or rust housing colours. diffuser in smoked glass look, in the housing colours dark grey or rust. The FACADO II bollard luminaires are also available in two different sizes [650 mm / 1,000 mm]. For even more flexibility, the FACADO II has an E27 socket for interchangeable light sources. Both FACADO II versions enable quick and easy installation: the wall luminaires have a removable mounting plate with plug-in connection and screwless connection terminals. The bollard luminaires are supplied with an IP67 connection box with double M20 cable gland which is suitable for underground cables with 3x 1.5 mm², 5x 1.5 mm² or 3x 2.5 mm², among others. All FACADO II luminaires can also be through-wired.


All information on the FACADO II series can be found from page 466.



ROLLABLE COVER

The new rollable cover for LED profiles opens up entirely new possibilities in lighting design. Supplied as a 20-meter roll, the flexible cover can be cut with millimeter precision—ideal for seamless light lines without visible joints, gaps, or interruptions. Especially in longer lighting runs, angled rooms, or complex ceiling shapes, this solution offers significant advantages over rigid diffuser profiles.

Thanks to its frameless design, the visible profile edge disappears completely—leaving behind a smooth, continuous light surface that integrates perfectly into architectural elements, furniture, or ceiling and wall structures. Whether used as general lighting, for accent lines, or as a decorative feature, the rollable cover is an innovative, professional solution for electricians, lighting designers, and architects alike.



3 VARIANTS

The rollable covers are available in three variants:

- frosted – for soft, diffused light without visible light spots
- clear – for maximum efficiency and direct lighting
- black – for particularly discreet applications with full light output and architectural effect

COMPATIBILITY

The rollable LED profile covers are compatible with the following DEKO-LIGHT profile types: AU-10-12, EL-04-12, EU-10-12, EV-11-12, EV-12-12

The matching profiles can be found from page 708.



FACADE LONG RUN 48V

The FACADE LONG RUN 48V series is specially designed for use on exposed façades and outdoor areas with direct sunlight. Featuring a UV-resistant casing, an operating temperature range from -40 to +95 °C, and an IP67 rating, it is the perfect solution for all environmental conditions – including sauna applications. Available in lengths of 5 or 15 meters, the flexible COB LED strips deliver homogeneous light runs without visible breaks – ideal for large-scale illumination of buildings, walls, pathways, or architectural lines. Thanks to the 48V operation, long power feed lines can be efficiently implemented without visible brightness loss.

Whether warm white for atmospheric light lines or RGB for colorful accents – the FACADE LONG RUN series offers the right solution for every application. Particularly practical are the combination models with RGB plus warm or neutral white [3,000K or 4,000K], which combine atmospheric color effects with functional lighting – without the need for additional light sources. Switchable versions with CCT [2,700K-6,500K] also allow variable lighting design depending on time of day, architecture, or use. All variants are dimmable via suitable controllers and can be quickly and securely installed using a wide range of accessories such as silicone end caps, clamps, plastic profiles, or power feed cables.

All information on the LED Stripes can be found from page 792.





INTERIOR LIGHTS

- 34 pendant lights
- 58 surface mounted ceiling lights
- 106 built in ceiling lights
- 156 downlights
- 178 insert panels
- 198 surface mounted wall lights
- 208 built in wall lights
- 218 reading lights
- 228 table and floor lights
- 238 showcase lights
- 246 office lights
- 270 hall floodlight
- 280 damp-proof luminaires

pendant lights



□ ■ □ ■
page 34



□ ■ □ ■
page 36



■ □
page 39



■ □
page 40



□ ■
page 42



□ ■
page 44



□ ■
page 45



□ ■
page 46



■
page 48



■
page 50



■ ■
page 51



■ ■
page 52



■ ■
page 53



□ ■
page 54



MENKAR

The pendant lights in the MENKAR series impress with clever lighting functions and high-quality aluminium accents. The separate rear light (approx. 15 - 20 % indirect light component) enables permanent indirect lighting. The light colour can be adjusted in 2 stages [3000/4000K] via a CCT switch.






MENKAR

- Indirect and direct lighting
- High light intensity
- Light colour adjustable in two stages
- Can be suspended by up to 1,800/3,000 mm [depending on model]
- Optional diffuser lens for UGR<19

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000/4000 K	Control	Leading-edge dimmer, Trailing-edge dimmer
Rated Input Voltage	220-240 V/AC	CRI (Ra)	80
Height	90 mm	IK Protection Class	IK04
Base Height	30 mm		



342201

Article	Housing Color		Luminous Flux	Power	Ø	Pendulum Length	Base Ø	Price
342201	White	WW NW	3300/3500 lm	45.0 W	400 mm	1800 mm	100 mm	€ 239.95
342202	Black	WW NW	3300/3500 lm	45.0 W	400 mm	1800 mm	100 mm	€ 239.95
342203	Silver	WW NW	3300/3500 lm	45.0 W	400 mm	1800 mm	100 mm	€ 239.95
342204	Coffee	WW NW	3300/3500 lm	45.0 W	400 mm	1800 mm	100 mm	€ 239.95
342205	White	WW NW	5600/6000 lm	65.0 W	600 mm	1800 mm	120 mm	€ 399.95
342206	Black	WW NW	5600/6000 lm	65.0 W	600 mm	1800 mm	120 mm	€ 399.95
342207	Silver	WW NW	5600/6000 lm	65.0 W	600 mm	1800 mm	120 mm	€ 399.95
342208	Coffee	WW NW	5600/6000 lm	65.0 W	600 mm	1800 mm	120 mm	€ 399.95
342209	White	WW NW	8400/8700 lm	90.0 W	800 mm	3000 mm	150 mm	€ 559.95
342210	Black	WW NW	8400/8700 lm	90.0 W	800 mm	3000 mm	150 mm	€ 559.95
342211	Silver	WW NW	8400/8700 lm	90.0 W	800 mm	3000 mm	150 mm	€ 559.95
342212	Coffee	WW NW	8400/8700 lm	90.0 W	800 mm	3000 mm	150 mm	€ 559.95



Accessories for **342201, 342202, 342203, 342204**

930709 Diffusing lenses UGR 19 for Menkar 400 lamp

€ 14.95

Accessories for **342205, 342206, 342207, 342208**

930710 Diffusing lenses UGR 19 for Menkar 600 lamp

€ 24.95

Accessories for **342209, 342210, 342211, 342212**


930711 Diffusing lenses UGR 19 for Menkar 800 lamp

€ 39.95



MEROPE

The pendant lamps of the MEROPE series combine timeless elegance and subdued modernity. Available in the diameters 380, 580 and 780 mm, the light colour [3,000/4,000 K] can be selected before installation using a CCT switch. The exterior finish is brushed aluminium in the colours coffee and silver or matt powder-coated in black and white.






MEROPE

- Light colour adjustable in two stages
- Can be suspended by up to 1,800/3,000 mm [depending on model]

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000/4000 K	Control	Leading-edge dimmer, Trailing-edge dimmer
Rated Input Voltage	220-240 V/AC	CRI (Ra)	80
Height	35 mm	IK Protection Class	IK04
Base Height	65 mm		




342189

Article	Housing Color		Luminous Flux	Power	Ø	Pendulum Length	Base Ø	Price
342189	White	WW NW	2100/2200 lm	30.0 W	380 mm	1800 mm	220 mm	€ 209.95
342190	Black	WW NW	2100/2200 lm	30.0 W	380 mm	1800 mm	220 mm	€ 209.95
342191	Silver	WW NW	2100/2200 lm	30.0 W	380 mm	1800 mm	220 mm	€ 209.95
342192	Coffee	WW NW	2100/2200 lm	30.0 W	380 mm	1800 mm	220 mm	€ 209.95
342193	White	WW NW	3100/3200 lm	42.0 W	580 mm	1800 mm	220 mm	€ 279.95
342194	Black	WW NW	3100/3200 lm	42.0 W	580 mm	1800 mm	220 mm	€ 279.95
342195	Silver	WW NW	3100/3200 lm	42.0 W	580 mm	1800 mm	220 mm	€ 279.95
342196	Coffee	WW NW	3100/3200 lm	42.0 W	580 mm	1800 mm	220 mm	€ 279.95
342197	White	WW NW	4800/4900 lm	60.0 W	780 mm	3000 mm	275 mm	€ 469.95
342198	Black	WW NW	4800/4900 lm	60.0 W	780 mm	3000 mm	275 mm	€ 469.95
342199	Silver	WW NW	4800/4900 lm	60.0 W	780 mm	3000 mm	275 mm	€ 469.95
342200	Coffee	WW NW	4800/4900 lm	60.0 W	780 mm	3000 mm	275 mm	€ 469.95








SLIM ANGULAR

- Extra-soft fabric cable
- Glare-free, due to low UGR value [<19]
- Slim design at just 39 mm in diameter
- Incl. silver-coloured reflector ring

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Base Length	370 mm
Colour Temperature	2700 K	Base Width	80 mm
Luminous Flux	1500 lm	Base Height	26 mm
Power	15 W	Power Supply Unit incl.	Yes
Rated Input Voltage	220-240 V/AC	Light Beam Angle	24 Degree
Height	300 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Ø	39 mm	CRI (Ra)	90
Pendulum Length	1800 mm		



342239


Article	Housing Color		Price
342239	Black	WW	€ 209.95
342240	White	WW	€ 209.95



Accessories

930744	Reflector ring white for Slim series		€ 4.95
930745	Reflector ring black for Slim series		€ 4.95
930746	Reflector ring gold-coloured for Slim series		€ 5.95
930748	36° lens for Slim series		€ 4.95
930749	60° lens for Slim series		€ 4.95






SLIM ROUND

SLIM series lights include single-luminaire and triple-luminaire pendant lamps, recessed ceiling lights and matching pendant lamps for the DEKO-LIGHT current track system. The die-cast aluminium light body is the same size for all variants [300 × 39 mm]. Several SLIM models therefore can also be combined with each other in larger spaces. The pendant lamps for ceiling installation with max. 180 cm suspended mounting are available in a one or three-luminaire variant; three-luminaire variant both with long or round base depending on the arrangement of the lights.

While the fixed SLIM models create a pleasant warm white light in dining rooms, reading nooks and more, the single-luminaire SLIM current track light is ideal for gastronomy and retail projects with changing room layouts. The premium SLIM series is rounded off with the opportunity for customisation using interchangeable reflector rings and lenses.




SLIM ROUND

- Extra-soft fabric cable
- Glare-free, due to low UGR value [<19]
- Slim design at just 39 mm in diameter
- Incl. silver-coloured reflector ring

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Base Height	25 mm
Colour Temperature	2700 K	Power Supply Unit incl.	Yes
Rated Input Voltage	220-240 V/AC	Light Beam Angle	24 Degree
Height	300 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Ø	39 mm	CRI (Ra)	90
Pendulum Length	1800 mm		



342237

Article	Housing Color	Luminous Flux	Power	Base Ø	Price
342237	Black	500 lm	5.0 W	100 mm	€ 84.95
342238	White	500 lm	5.0 W	100 mm	€ 84.95
342241	Black	1500 lm	15.0 W	240 mm	€ 209.95
342242	White	1500 lm	15.0 W	240 mm	€ 209.95



Accessories

930744	Reflector ring white for Slim series		€ 4.95
930745	Reflector ring black for Slim series		€ 4.95
930746	Reflector ring gold-coloured for Slim series		€ 5.95
930748	36° lens for Slim series		€ 4.95
930749	60° lens for Slim series		€ 4.95

Accessories for **342237**

930914	68 mm Recessed Ceiling Adapter for Pendant Luminaires, black		€ 29.95
---------------	--	--	---------

Accessories for **342238**

930913	68 mm Recessed Ceiling Adapter for Pendant Luminaires, white		€ 29.95
---------------	--	--	---------





LUCEA CCT

LUCEA series pendant lights with CCT are available in 10, 15 and 20 W versions and offer up to 2,000 lumens of light output. The maximum suspended mounting is 1,800 mm. Optional lenses can be used to narrow or expand the light emission angle of the individual models. LUCEA lights feature a die-cast aluminium housing.



page 80

page 82

page 432

page 436




LUCEA CCT

- Light colour adjustable in two stages
- Incl. black reflector ring

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Trade fair construction / shop fitting

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000/4000 K	Light Beam Angle	36 Degree
Rated Input Voltage	220-240 V/AC	Control	Leading-edge dimmer, Trailing-edge dimmer
Pendulum Length	1800 mm	CRI (Ra)	90
Base Height	29 mm	IK Protection Class	IK03
Base Ø	104.5 mm		



342177

Article	Housing Color		Luminous Flux	Power	Height	Ø	Price
342177	☐ White		930/1000 lm	10.0 W	157 mm	65 mm	€ 139.95
342178	☒ Black		930/1000 lm	10.0 W	157 mm	65 mm	€ 139.95
342179	☐ White		1460/1500 lm	15.0 W	178 mm	85 mm	€ 159.95
342180	☒ Black		1460/1500 lm	15.0 W	178 mm	85 mm	€ 159.95
342181	☐ White		1930/2000 lm	20.0 W	178 mm	85 mm	€ 179.95
342182	☒ Black		1930/2000 lm	20.0 W	178 mm	85 mm	€ 179.95



Accessories for **342177, 342178**

930679	Lens 24° for Lucea 6/10		€ 9.95
930756	Reflector ring for Lucea 6/10 white		€ 4.95
930757	Reflector ring for Lucea 6/10 black		€ 4.95
930758	Reflector ring for Lucea 6/10 gold		€ 4.95

Accessories for **342177, 342179, 342181**

930913	68 mm Recessed Ceiling Adapter for Pendant Luminaires, white		€ 29.95
---------------	--	--	---------

Accessories for **342178, 342180, 342182**

930914	68 mm Recessed Ceiling Adapter for Pendant Luminaires, black		€ 29.95
---------------	--	--	---------

Accessories for **342179, 342180, 342181, 342182**

930680	Lens 24° for Lucea 15/20		€ 12.95
930681	Lens 60° for Lucea 15/20		€ 12.95
930759	Reflector ring for Lucea 15/20 white		€ 5.95
930760	Reflector ring for Lucea 15/20 black		€ 5.95
930761	Reflector ring for Lucea 15/20 gold		€ 5.95



LUCEA

- Extra-soft fabric cable
- Incl. black reflector ring

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Base Ø	104.5 mm
Colour Temperature	2700 K	Power Supply Unit incl.	Yes
Rated Input Voltage	200-240 V/AC	Light Beam Angle	36 Degree
Height	157 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Ø	65 mm	CRI (Ra)	90
Pendulum Length	1800 mm	IK Protection Class	IK03
Base Height	29 mm		


Article	Housing Color	Luminous Flux	Power	Price
342243	White	800 lm	6.0 W	€ 129.95
342244	Black	800 lm	6.0 W	€ 129.95
342245	White	1300 lm	10.0 W	€ 139.95
342246	Black	1300 lm	10.0 W	€ 139.95



Accessories


930679	Lens 24° for Lucea 6/10		€ 9.95
930756	Reflector ring for Lucea 6/10 white		€ 4.95
930757	Reflector ring for Lucea 6/10 black		€ 4.95
930758	Reflector ring for Lucea 6/10 gold		€ 4.95

Accessories for **342243, 342245**
930913 68 mm Recessed Ceiling Adapter for Pendant Luminaires, white



€ 29.95

Accessories for **342244, 342246**
930914 68 mm Recessed Ceiling Adapter for Pendant Luminaires, black



€ 29.95





LUCEA DTW

- Extra-soft fabric cable
- Dim-to-warm 1,800 K-2,700 K
- Incl. black reflector ring

Application Area

Home / Living, Reception / Communication, Hotel / catering

Housing	Aluminium	Pendulum Length	1800 mm
Colour Temperature	1800-2700 K	Power Supply Unit incl.	Yes
Luminous Flux	750 lm	Light Beam Angle	36 Degree
Power	10 W	Control	Leading-edge dimmer, Trailing-edge dimmer
Rated Input Voltage	200-240 V/AC	CRI (Ra)	90
Height	157 mm	IK Protection Class	IK03
Ø	65 mm		

Article	Housing Color		Price
342247	White		€ 149.95
342248	Black		€ 149.95



Accessories

930756	Reflector ring for Lucea 6/10 white		€ 4.95
930757	Reflector ring for Lucea 6/10 black		€ 4.95
930758	Reflector ring for Lucea 6/10 gold		€ 4.95

Accessories for **342247**

930913	68 mm Recessed Ceiling Adapter for Pendant Luminaires, white		€ 29.95
---------------	--	--	----------------

Accessories for **342248**

930914	68 mm Recessed Ceiling Adapter for Pendant Luminaires, black		€ 29.95
---------------	--	--	----------------



page 80

page 82


page 432

page 436



CAN

The CAN pendant light in lengths 150 mm and 350 mm combines modern design with practical functionality. The GU10 base enables quick and simple replacement of the lamp. The screw-on cylinder enables tool-free maintenance and optional decorative rings allow colourful accents to be created. The pendant light is part of the CAN series, which also contains ceiling, wall, reading and outdoor lights and therefore provides versatile application options for private and commercial spaces.





CAN

- Flat and discreet lamp base
- Can be customised with a wide range of accessories
- Replaceable lamp to offer an individual lighting solution
- Can be combined with the comprehensive CAN series product family

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Sockets	1 PCS
Ø	60 mm	Max. Power	1x max. 7.5 W
Pendulum Length	1700 mm	Rated Input Voltage	220-240 V/AC
Base Height	27 mm	Control	Dimmable via optional light source
Base Ø	60 mm		

Article	Housing Color	Height	Price
342254	White	150 mm	€ 64.95
342255	Black	150 mm	€ 64.95
342256	White	350 mm	€ 74.95
342257	Black	350 mm	€ 74.95



Accessories

930301	Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930302	Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930303	Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930366	Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
931065	Acrylic attachment for Can		€ 4.95

Accessories for **342254, 342256**

930913	68 mm Recessed Ceiling Adapter for Pendant Luminaires, white		€ 29.95
---------------	--	--	----------------

Accessories for **342255, 342257**

930914	68 mm Recessed Ceiling Adapter for Pendant Luminaires, black		€ 29.95
---------------	--	--	----------------





APOLLON

The APOLLON narrow, puristic pendant lamp fits into almost any environment seamlessly and in addition to the elegant visual design also delivers a rich warm white light. The APOLLON is available in two different sizes with a matte surface in black.



APOLLON


- Especially narrow design
- High colour rendering
- Suspended mounting up to max. 3,000 mm
- Dimmable

Application Area

Home / Living, Reception / Communication

Housing	Aluminium
Colour Temperature	2700 K
Rated Input Voltage	200-250 V/AC
Width	8 mm
Height	80 mm
Pendulum Length	3000 mm
Base Width	35 mm

Base Height	48 mm
Power Supply Unit incl.	Yes
Light Beam Angle	110 Degree
Control	Leading-edge dimmer, Trailing-edge dimmer
CRI (Ra)	90



342148

Article	Housing Color		Luminous Flux	Power	Length	Base Length	EEL	Price
342148	Black	WW	1755 lm	28.0 W	1004 mm	650 mm	G	€ 344.95
342150	Black	WW	2475 lm	42.0 W	1464 mm	850 mm	F	€ 459.95





SOCKET SEGULA DESIGN BULBS

The pendant lights are fitted with textile cables. This generous cable length enables flexible installation even in high rooms and allows individual height adjustment depending on the installation situation. The housing is characterised by a reduced, clear design language and is therefore ideal for modern architectural and lighting concepts in interiors. The E27 sockets used are deliberately oversized. The enlarged sleeve creates a visually harmonious unit between the socket and light source - without visible transitions or technical breaks. Compatible with our DESIGN-BULB light sources, this pendant luminaire is particularly suitable for project-oriented applications in the interior design, shop fitting or catering sectors. It provides an ideal basis for decorative lighting solutions with design requirements.




SOCKET SEGULA DESIGN BULBS

- Sliding E27 socket sleeve(s) for adapting to lamps with special dimensions
- Ideal for use in conjunction with our designer bulb series
- Soft textile cable
- High-quality surface finish

Housing	Metal, Plastic	Rated Input Voltage	220-240 V/AC
Height	80 mm	Connection Type	Connectionbox IP20
Ø	50 mm		


Article	Housing Color	Max. Power	Pendulum Length	Base Length	Base Width	Base Height	Base Ø	Price
930908	Black	1x max. 60.0 W	2.000 mm			20 mm	100 mm	€ 59.95
930909	Black	1x max. 60.0 W	5.000 mm			20 mm	100 mm	€ 69.95
930965	Black	3x max. 57.0 W	3.000 mm			25 mm	125 mm	€ 194.95
930966	Black	3x max. 57.0 W	1.500 mm	990 mm	150 mm	25 mm		€ 329.95



DEKO-LIGHT LED DESIGN-BULB ORBIT E27 DIMMABLE

Housing	Glass	Rated Input Voltage	220-240 V/AC
Light Beam Angle	330 Degree	Life Time	20000 h
Height	120 mm	Control	Trailing-edge dimmer
Ø	220 mm	Channels	1

Article	Housing Color	Colour Temperature	Luminous Flux	Power	CRI (Ra)	EEL	Price
180731	Smoky	1900 K	185 lm	4.5 W	85		€ 129.95
180730	Gold	2200 K	240 lm	4.0 W	90		€ 129.95





DEKO-LIGHT LED DESIGN BULB SHINE E27 DIMMABLE

Let our new designer light series ORBIT, SHINE and MOON take you into the world of style. The sophisticated luminous elements and the reflections generated in the glass create the impression of floating light. Whether light and airy in your living room at home or opulent and spacious in the hotel lobby - the dimmable LED lamps from the designer bulb series are perfect for open lights without shades or lampholders with E27 sockets and are a real eye-catcher wherever they are used.



DEKO-LIGHT LED DESIGN BULB SHINE E27 DIMMABLE

Housing	Glass	Rated Input Voltage	220-240 V/AC
Light Beam Angle	330 Degree	Life Time	20000 h
Height	190 mm	Control	Trailing-edge dimmer
Ø	200 mm	Channels	1
Power Consumption	5 kWh/1000h		

Article	Housing Color	Colour Temperature	Luminous Flux	Power	CRI (Ra)	EEI	Price
180733	Smoky	1900 K	210 lm	5 W	85		€ 114.95
180732	Gold	2200 K	300 lm	4.5 W	90		€ 114.95



DEKO-LIGHT LED DESIGN BULB MOON E27 DIMMABLE

- Glass body is manufactured by hand
- Filigree lamp
- Reflections create the impression of floating light
- Patented soft filament technology
- Suitable for decorative and creative lights with and without lampshade
- Ideal for use in combination with our sockets with sliding socket sleeve

Housing	Glass	Control	Trailing-edge dimmer
Light Beam Angle	330 Degree	Channels	1
Rated Input Voltage	220-240 V/AC		

Article	Housing Color	Colour Temperature	Luminous Flux	Power	Height	Ø	EEI	Price
180734	Smoky	1900 K	220 lm	6.0 W	165 mm	125 mm		€ 69.95
180735	Smoky	1900 K	260 lm	6.0 W	185 mm	150 mm		€ 79.95
180736	Smoky	1900 K	300 lm	6.0 W	230 mm	200 mm		€ 109.95
180737	Smoky	1900 K	350 lm	8.0 W	320 mm	300 mm		€ 249.95
180741	Black	2200 K	240 lm	4.0 W	165 mm	125 mm		€ 89.95
180742	Black	2200 K	240 lm	4.0 W	200 mm	150 mm		€ 114.95
180743	Black	2200 K	240 lm	4.0 W	230 mm	200 mm		€ 149.95





68 MM CEILING MOUNT ADAPTER FOR PENDANT LAMPS

The recessed ceiling adapter is the ideal solution for discreetly and securely installing pendant lights weighing up to 2.5 kg. Thanks to the integrated three-pin connection box with strain relief and feed-through wiring, the adapter can be connected to the power supply quickly and reliably. Suitable for cable diameters of 5-7 mm and ceiling thicknesses of 2-15 mm, the adapter ensures that the light is seamlessly integrated into the ceiling. The result: A simple, high-quality look that discreetly conceals all electrical components and meets the highest aesthetic demands.





68 MM CEILING MOUNT ADAPTER FOR PENDANT LAMPS

- Secure installation of pendant lamps in 68 mm ceiling recesses
- Includes three-pin connection box with strain relief and feed-through wiring
- Suitable for cable diameters of 5-7 mm
- Suitable for ceiling thicknesses of 2-15 mm

Housing	Polycarbonate, Steel	Installation Depth	27 mm
Height	32 mm	Cut Out Ø	65-75 mm
Ø	90 mm		

Article	Housing Color	Price
930913	☐ White	€ 29.95
930914	☒ Black	€ 29.95

IP20

Accessories for **930914**

930908	Segula E27 socket for designer bulb, black, with 2 m fabric cable and canopy		€ 59.95
930909	Segula E27 socket for designer bulb, black, with 5 m fabric cable and canopy		€ 69.95



Lighting design

Interested in our lighting design service?

Your contact person will be happy to answer any questions you may have.

surface mounted ceiling lights



page 58




page 60




page 62



page 64




page 66



page 68



page 69



page 70




page 74



page 75



page 76



page 77



□ ■ □ ■
page 78



□ ■
page 79



□ ■
page 80



□ ■
page 82



□ ■
page 84



□ ■
page 85



□ ■
page 86



□ ■
page 87



□ ■
page 88



□ ■
page 89



□ ■
page 90



□ ■
page 92



□ ■
page 94



□ ■
page 94



□ ■ □
page 96



□ ■
page 97



□
page 98



□
page 101



□ □
page 102



MENKAR

MENKAR series ceiling and wall lights feature clever lighting functions and high-quality aluminium accents. The rear light (approx. 15-20 % indirect light) also allows additional indirect lighting.






MENKAR

- Direct and indirect lighting (light proportion approx. 15-20 %)
- Light colour adjustable in two steps
- Optional diffuser lens for UGR<19
- Can be used as a wall or ceiling light (depending on model)

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium, Polycarbonate, Steel	Power Supply Unit incl. Control	Yes Leading-edge dimmer, Trailing-edge dimmer
Colour Temperature	3000/4000 K	CRI (Ra)	80
Height	90 mm	IK Protection Class	IK04
Rated Input Voltage	220-240 V/AC		



348198

Article	Housing Color		Luminous Flux Surface	Ø	Power	Price
348200	Silver		3300/3500 lm Brushed	400 mm	45.0 W	€ 219.95
348201	Coffee		3300/3500 lm Brushed	400 mm	45.0 W	€ 219.95
348198	White		3300/3500 lm Matt	400 mm	45.0 W	€ 219.95
348199	Black		3300/3500 lm Matt	400 mm	45.0 W	€ 219.95
348204	Silver		5600/6000 lm Brushed	600 mm	65.0 W	€ 379.95
348205	Coffee		5600/6000 lm Brushed	600 mm	65.0 W	€ 379.95
348202	White		5600/6000 lm Matt	600 mm	65.0 W	€ 379.95
348203	Black		5600/6000 lm Matt	600 mm	65.0 W	€ 379.95
348208	Silver		8400/8700 lm Brushed	800 mm	90.0 W	€ 539.95
348209	Coffee		8400/8700 lm Brushed	800 mm	90.0 W	€ 539.95
348206	White		8400/8700 lm Matt	800 mm	90.0 W	€ 539.95
348207	Black		8400/8700 lm Matt	800 mm	90.0 W	€ 539.95



Accessories for **348198, 348199, 348200, 348201**

930709 Diffusing lenses UGR 19 for Menkar 400 lamp

€ 14.95

Accessories for **348202, 348203, 348204, 348205**

930710 Diffusing lenses UGR 19 for Menkar 600 lamp

€ 24.95

Accessories for **348206, 348207, 348208, 348209**

930711 Diffusing lenses UGR 19 for Menkar 800 lamp

€ 39.95



MEROPE

The timeless MEROPE demonstrates not only impressively high luminous flux and a low assembly height, it is also highly visually appealing thanks to its elegant outer aluminium ring – available in sand-blasted white or black, brushed in silver or on-trend coffee. Available in the diameters 380 mm, 580 mm and 780 mm, the MEROPE can be integrated into very different environments even more flexibly.

In addition, the light colour can be adjusted in 2 stages, 3,000 K or 4,000 K.





MEROPE

- High luminous flux
- Light colour adjustable in 2 stages
- Low assembly height


Application Area

Home / Living

Housing Aluminium
 Colour Temperature 3000/4000 K
 Height 60 mm
 Rated Input Voltage 220-240 V/AC
 Power Supply Unit incl. Yes

Control
 CRI (Ra)
 IK Protection Class

Leading-edge dimmer,
 Trailing-edge dimmer
 80
 IK04



348186

Article	Housing Color		Luminous Flux Surface	Ø	Power	Price
348188	Silver	WW NW	2100/2200 lm Brushed	380 mm	30.0 W	€ 189.95
348189	Coffee	WW NW	2100/2200 lm Brushed	380 mm	30.0 W	€ 189.95
348186	White	WW NW	2100/2200 lm Matt	380 mm	30.0 W	€ 189.95
348187	Black	WW NW	2100/2200 lm Matt	380 mm	30.0 W	€ 189.95
348192	Silver	WW NW	3100/3200 lm Brushed	580 mm	42.0 W	€ 269.95
348193	Coffee	WW NW	3100/3200 lm Brushed	580 mm	42.0 W	€ 269.95
348190	White	WW NW	3100/3200 lm Matt	580 mm	42.0 W	€ 269.95
348191	Black	WW NW	3100/3200 lm Matt	580 mm	42.0 W	€ 269.95
348196	Silver	WW NW	4800/4900 lm Brushed	780 mm	60.0 W	€ 449.95
348197	Coffee	WW NW	4800/4900 lm Brushed	780 mm	60.0 W	€ 449.95
348194	White	WW NW	4800/4900 lm Matt	780 mm	60.0 W	€ 449.95
348195	Black	WW NW	4800/4900 lm Matt	780 mm	60.0 W	€ 449.95





SCULPTORIS

Modern elegance for ceilings; the ceiling lights from the SCULPTORIS series can be used in a number of ways indoors thanks to different outputs, sizes and colour temperatures. The surface-mounted ceiling lights provide extensive illumination for rooms and also look great as wall lights.

The light is softly and extensively diffused through the large, circumferential diffuser with matt aluminium design and illuminates rooms pleasantly and evenly.

The light colours warm white (3,000 K) or neutral white (4,000 K) can be set for each variant.





SCULPTORIS

- Light colour adjustable in 2 stages
- Uniform illumination
- Circumferential diffuser

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Light Beam Angle	150 Degree
Colour Temperature	3000/4000 K	Control	Leading-edge dimmer, Trailing-edge dimmer
Surface	Matt	CRI (Ra)	80
Rated Input Voltage	220-240 V/AC	IK Protection Class	IK04
Power Supply Unit incl.	Yes		

Article	Housing Color		Luminous Flux	Height	Ø	Power	Price
348180	White		2000/2100 lm	100 mm	400 mm	30.0 W	€ 269.95
348181	Black		2000/2100 lm	100 mm	400 mm	30.0 W	€ 269.95
348182	White		3000/3100 lm	130 mm	600 mm	42.0 W	€ 349.95
348183	Black		3000/3100 lm	130 mm	600 mm	42.0 W	€ 349.95
348184	White		4100/4200 lm	130 mm	800 mm	60.0 W	€ 579.95
348185	Black		4100/4200 lm	130 mm	800 mm	60.0 W	€ 579.95




Technical data sheet

New in the onlineshop: The technical data sheets offer even more information: Light and energy data, light distribution curves, dimensional drawings and more.



ZANIAH

Whilst flat surfaces and covers are the go-to for most surface-mounted ceiling lights, the ZANIAH places special emphasis on its 360° lamp [either a 12 W, 18 W or 24 W variant]. Replaceable covers allow the visual appearance of ZANIAH to be changed even after installation. The covers are available in eight colour variants, allowing plenty of scope for customisation.





ZANIAH

- Can be customised using coloured covers
- 360° light emission angle
- Can be used as a wall or ceiling light

Application Area

Reception / Communication, Corridor / stairwell, Home / Living, Hotel / catering

Housing	Aluminium	Control	Leading-edge dimmer, Trailing-edge dimmer
Colour Temperature	3000 K	CRI (Ra)	80
Rated Input Voltage	220-240 V/AC	IK Protection Class	IK05
Power Supply Unit incl.	Yes		
Light Beam Angle	120 Degree		

Article	Housing Color		Luminous Flux	Height	Ø	Power	EEI	Price
620033	Silver		1510 lm	42 mm	290 mm	12.0 W		€ 99.95
620034	Blue		1510 lm	42 mm	290 mm	12.0 W		€ 99.95
620035	Green		1510 lm	42 mm	290 mm	12.0 W		€ 99.95
620036	Red		1510 lm	42 mm	290 mm	12.0 W		€ 99.95
620037	Yellow		1510 lm	42 mm	290 mm	12.0 W		€ 99.95
620038	Grey		1510 lm	42 mm	290 mm	12.0 W		€ 99.95
620039	Black		1510 lm	42 mm	290 mm	12.0 W		€ 99.95
620040	White		1510 lm	42 mm	290 mm	12.0 W		€ 99.95
620041	Silver		2020 lm	46 mm	370 mm	18.0 W		€ 109.95
620042	Blue		2020 lm	46 mm	370 mm	18.0 W		€ 109.95
620043	Green		2020 lm	46 mm	370 mm	18.0 W		€ 109.95
620044	Red		2020 lm	46 mm	370 mm	18.0 W		€ 109.95
620045	Yellow		2020 lm	46 mm	370 mm	18.0 W		€ 109.95
620046	Grey		2020 lm	46 mm	370 mm	18.0 W		€ 109.95
620047	Black		2020 lm	46 mm	370 mm	18.0 W		€ 109.95
620048	White		2020 lm	46 mm	370 mm	18.0 W		€ 109.95
620049	Silver		2565 lm	46 mm	420 mm	24.0 W		€ 119.95
620050	Blue		2565 lm	46 mm	420 mm	24.0 W		€ 119.95
620051	Green		2565 lm	46 mm	420 mm	24.0 W		€ 119.95
620052	Red		2565 lm	46 mm	420 mm	24.0 W		€ 119.95
620053	Yellow		2565 lm	46 mm	420 mm	24.0 W		€ 119.95
620054	Grey		2565 lm	46 mm	420 mm	24.0 W		€ 119.95
620055	Black		2565 lm	46 mm	420 mm	24.0 W		€ 119.95
620056	White		2565 lm	46 mm	420 mm	24.0 W		€ 119.95





ALTAIS 2 ROUND

The ALTAIS 2 Round is a modern ceiling and wall luminaire that is ideal for lighting solutions in commercial, public and private areas. Its clear, round design blends into a wide variety of architectural settings - from technical rooms, corridors and stairwells to modern residential and commercial areas. Thanks to the integrated CCT switch, the light colour can be adjusted in three stages (2700K / 3000K / 4000K). The output can also be adjusted in two stages to optimise energy efficiency and luminous efficacy depending on the room requirements. With through-wiring and surface-mounted cable entries, the installation options are very flexible. Installation is convenient thanks to a practical and time-saving click system.

As an eligible product in accordance with the requirements of the Federal Subsidy for Efficient Buildings (BEG), the ALTAIS 2 Round also contributes to energy-efficient refurbishment - a plus point for sustainable projects.





ALTAIS 2 ROUND

- Light colour adjustable in 3 stages
- Power adjustable in 2 steps
- through-wiring possible
- Easy installation thanks to click system
- Optional surface-mounted cable entry
- BEG eligible

Application Area

Bathroom / WC, Corridor / stairwell, Wellness / Spa / Gym, Workshop / Craft / Warehouse, Home / Living

Housing	Polycarbonate	Rated Input Voltage	100-240 V/AC
Colour Temperature	2700/3000/4000 K	Light Beam Angle	120 Degree
Height	52 mm	CRI (Ra)	85
Base Height	20.5 mm	IK Protection Class	IK10

Article	Housing Color		Luminous Flux	Ø	Base Ø	Power Selectable	Price
348276	☐ White	☒ WW ☐ NW	1650/1800/1800 lm	220 mm	180 mm	10.0 W / 15.0 W	€ 69.95
348277	☐ White	☒ WW ☐ NW	1980/2160/2160 lm	280 mm	240 mm	13.0 W / 18.0 W	€ 84.95
348278	☐ White	☒ WW ☐ NW	2750/3000/3000 lm	330 mm	280 mm	18.0 W / 25.0 W	€ 99.95



Onlineshop

You can find more information about the products in the onlineshop:
Detailed images, videos, project reports, LDT files, EPREL data sheets and more.




ALTAIS 2 ROUND MOTION

- Light colour adjustable in 3 stages
- Power adjustable in 2 levels
- Adjustable motion detector with corridor function
- through-wiring possible
- Easy installation thanks to click system
- Optional surface-mounted cable entry
- BEG eligible

Application Area
Bathroom / WC, Corridor / stairwell, Wellness / Spa / Gym, Workshop / Craft / Warehouse, Home / Living

Housing	Polycarbonate	Light Beam Angle	120 Degree
Colour Temperature	2700/3000/4000 K	CRI (Ra)	85
Height	52 mm	Motion Detector	Yes
Base Height	20.5 mm	IK Protection Class	IK10
Rated Input Voltage	100-240 V/AC		

Article	Housing Color		Luminous Flux	Ø	Base Ø	Power Selectable	Price
348279	☐ White	 	1650/1800/1800 lm	220 mm	180 mm	10.0 W / 15.0 W	€ 99.95
348280	☐ White	 	1980/2160/2160 lm	280 mm	240 mm	13.0 W / 18.0 W	€ 114.95
348281	☐ White	 	2750/3000/3000 lm	330 mm	280 mm	18.0 W / 25.0 W	€ 129.95



Lighting design
Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.



ALTAIS 2 ROUND MOTION MS


- Light colour adjustable in 3 stages
- Power adjustable in 2 levels
- Adjustable motion detector with corridor function
- Multi-master-slave configuration with up to 8 groups
- through-wiring possible
- Easy installation thanks to click system
- Optional surface-mounted cable entry
- BEG eligible

Application Area

Bathroom / WC, Corridor / stairwell, Wellness / Spa / Gym, Workshop / Craft / Warehouse, Home / Living

Housing	Polycarbonate	Light Beam Angle	120 Degree
Colour Temperature	2700/3000/4000 K	CRI (Ra)	85
Height	52 mm	Motion Detector	Yes
Base Height	20.5 mm	IK Protection Class	IK10
Rated Input Voltage	100-240 V/AC		

Article	Housing Color		Luminous Flux	Ø	Base Ø	Power Selectable	Price
348285	☐ White	WW NW	1980/2160/2160 lm	280 mm	240 mm	13.0 W / 18.0 W	€ 134.95
348286	☐ White	WW NW	2750/3000/3000 lm	330 mm	280 mm	18.0 W / 25.0 W	€ 149.95




Accessories
931075

 € 24.95



Technical data sheet
New in the onlineshop: The technical data sheets offer even more information:
Light and energy data, light distribution curves, dimensional drawings and more.






HELEN

- Light colour adjustable in 3 stages
- Splash water protected

Application Area


Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, Bathroom / WC, Hotel bathrooms / commercial wet areas

Housing	Plastic	Rated Input Voltage	220-240 V/AC
Colour Temperature	3000/4000/5500 K	Power Supply Unit incl.	Yes
Surface	Brushed	Light Beam Angle	115 Degree
Base Height	20 mm	CRI (Ra)	80



348052

Article	Housing Color		Luminous Flux	Height	Ø	Power	Base Ø	Price
348051	Silver	WW NW CW	1400 lm	83 mm	276 mm	16.3 W	251 mm	€ 79.95
348052	Silver	WW NW CW	1800 lm	89 mm	351 mm	20.0 W	326 mm	€ 119.95



Lighting design
Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.

UNI II

The UNI II series comprises high-quality surface-mounted luminaires and track-mounted spotlights for use on walls and ceilings in commercial and private premises.

The rotating and swivelling luminaire heads of the UNI II series – available in white and black aluminium housing versions – are equipped with warm white COB LEDs and can be folded flush onto the base if required to shine vertically downwards like a ceiling spotlight. In addition to the single, double and triple versions, both a MINI version [with smaller luminaire head and base] and a MAX version are available.

THE SERIES AT A GLANCE



UNI II

The standard version [TILT] with 3,000 K is also available with two [DOUBLE] and three [TRIPLE] luminaire heads on a base and as a wall-mounted version.



UNI II MINI

The MINI version [optionally 2,700 K or 3,000 K] is available with one [MINI II TILT] or two [MINI II DOUBLE] luminaire heads and is suitable for particularly discreet use in small rooms.



UNI II MAX

THE MAX version [3,000 K] with its 2,410 lumens also makes a big impression on its own.



UNI II TRACK SPOT

Whether private [1-phase] or commercial [3-phase]: As a track spotlight, the UNI II can be aligned even more flexibly in the room. Available as a standard version [UNI II TILT] and as a MINI version [MINI II TILT].



UNI II RECESSED LIGHT

The rotatable and swivelling luminaire head of the UNI II recessed luminaire [also available as a MINI and MAX version] can be folded flush onto the base if required in order to shine vertically downwards like a ceiling spotlight.

VERSATILE ACCESSORIES

THE UNI II series offers numerous options to further individualise the light and appearance of the luminaires:



Reflectors

Interchangeable reflectors for narrower [24°] or wider [48°] light emission.

Lenses

Interchangeable lenses in clear/satin finish for a broader and/or softer light.

Honeycomb filter

Optional honeycomb filter to reduce glare.

Reflector rings

Interchangeable reflector rings [black, glossy black, gold, chrome] for customising the lighting effect.

Covers

Covers [white, black] as replacement or deliberate colour contrast when UNI II is opened.




UNI 2

- „Glow“ effect on reflector ring
- Can be rotated and swivelled
- Can be customised with a comprehensive range of accessories

Application Area
 Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000 K	Light Beam Angle	36 Degree
Height	103 mm	Rotation Angle	350 Degree
Ø	100 mm	Swivelling Angle	90 Degree
Power	12 W	Control	Leading-edge dimmer, Trailing-edge dimmer
Base Height	14.5 mm	CRI (Ra)	90
Base Ø	96 mm		
Rated Input Voltage	220-240 V/AC		



348124

Article	Housing Color	Luminous Flux	Price
348179	Black	780 lm	€ 144.95
348124	White	835 lm	€ 144.95



Accessories

930305	36° reflector for Klara/Nihal Mini/Rigel Mini/Uni II series	€ 3.60
930306	48° reflector for Klara/Nihal Mini/Rigel Mini/Uni II series	€ 8.95
930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series	€ 8.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series	€ 8.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series	€ 8.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series	€ 8.95
930334	Rear white cover for Uni II series	€ 3.55
930335	Rear black cover for Uni II series	€ 2.95
930336	White heat sink cover for Uni II series	€ 3.55
930337	Black heat sink cover for Uni II series	€ 7.95
930338	Reflector ring white for Uni II series	€ 11.95
930339	Reflector ring black for Uni II series	€ 10.95
930340	Reflector ring gold for Uni II series	€ 10.95
930341	Reflector ring chrome for Uni II series	€ 10.95





UNI 2 DOUBLE

- „Glow“ effect on reflector ring
- Can be rotated and swivelled
- Can be customised with a comprehensive range of accessories

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Colour Temperature	3000 K	Power Supply Unit incl.	Yes
Length	212 mm	Light Beam Angle	36 Degree
Width	100 mm	Rotation Angle	350 Degree
Height	103 mm	Swivelling Angle	90 Degree
Power	20 W	Control	Leading-edge dimmer, Trailing-edge dimmer
Base Length	212 mm	CRI (Ra)	90
Base Width	20 mm		
Base Height	14 mm		

348125

Article	Housing Color	Luminous Flux	Price
348175	Black	1440 lm	€ 259.95
348125	White	1730 lm	€ 259.95



Accessories

930305	36° reflector for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 3.60
930306	48° reflector for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930334	Rear white cover for Uni II series		€ 3.55
930335	Rear black cover for Uni II series		€ 2.95
930336	White heat sink cover for Uni II series		€ 3.55
930337	Black heat sink cover for Uni II series		€ 7.95
930338	Reflector ring white for Uni II series		€ 11.95
930339	Reflector ring black for Uni II series		€ 10.95
930340	Reflector ring gold for Uni II series		€ 10.95
930341	Reflector ring chrome for Uni II series		€ 10.95





UNI 2 TRIPLE


- „Glow“ effect on reflector ring
- Can be rotated and swivelled
- Can be customised with a comprehensive range of accessories

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Base Height	14.5 mm
Colour Temperature	3000 K	Rated Input Voltage	220-240 V/AC
Length	324 mm	Power Supply Unit incl.	Yes
Width	100 mm	Light Beam Angle	36 Degree
Height	103 mm	Rotation Angle	350 Degree
Ø	100 mm	Swivelling Angle	90 Degree
Power	30 W	Control	Leading-edge dimmer, Trailing-edge dimmer
Base Length	315 mm	CRI (Ra)	90
Base Width	25 mm		

Article	Housing Color		Luminous Flux	Price
348210	 Black		2150 lm	€ 369.95
348107	 White		2420 lm	€ 369.95



Accessories

930305	36° reflector for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 3.60
930306	48° reflector for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930334	Rear white cover for Uni II series		€ 3.55
930335	Rear black cover for Uni II series		€ 2.95
930336	White heat sink cover for Uni II series		€ 3.55
930337	Black heat sink cover for Uni II series		€ 7.95
930338	Reflector ring white for Uni II series		€ 11.95
930339	Reflector ring black for Uni II series		€ 10.95
930340	Reflector ring gold for Uni II series		€ 10.95
930341	Reflector ring chrome for Uni II series		€ 10.95






UNI 2 MINI

- „Glow“ effect on reflector ring
- Can be rotated and swivelled
- Can be customised with a comprehensive range of accessories

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Light Beam Angle	36 Degree
Height	75 mm	Rotation Angle	350 Degree
Ø	91 mm	Swivelling Angle	90 Degree
Base Height	44 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Base Ø	75 mm	CRI (Ra)	90
Rated Input Voltage	220-240 V/AC		
Power Supply Unit incl.	Yes		



348122

Article	Housing Color	Colour Temperature	Luminous Flux	Power	EEI	Price
348234	Black	2700 K	700 lm	11.3 W		€ 129.95
348233	White	2700 K	730 lm	11.3 W		€ 129.95
348178	Black	3000 K	540 lm	8.0 W		€ 119.95
348122	White	3000 K	630 lm	8.0 W		€ 119.95



Accessories

930327	Rear black cover for Uni II Mini series		€ 3.45
930328	White heat sink cover for Uni II Mini series		€ 3.55
930329	Black heat sink cover for Uni II Mini series		€ 2.95
930330	Reflector ring white for Uni II Mini series		€ 10.95
930331	Reflector ring black for Uni II Mini series		€ 10.95
930332	Reflector ring gold for Uni II Mini series		€ 10.95
930333	Reflector ring chrome for Uni II Mini series		€ 10.95
930770	Reflector 24° for Uni II Mini series		€ 10.95
930771	Reflector 48° for Uni II Mini series		€ 10.95



Technical data sheet

New in the onlineshop: The technical data sheets offer even more information: Light and energy data, light distribution curves, dimensional drawings and more.




UNI 2 MINI DOUBLE

- „Glow“ effect on reflector ring
- Can be rotated and swivelled
- Can be customised with a comprehensive range of accessories

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Power Supply Unit incl.	Yes
Length	160 mm	Light Beam Angle	36 Degree
Width	75 mm	Rotation Angle	350 Degree
Height	91 mm	Swivelling Angle	90 Degree
Base Length	160 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Base Width	75 mm	CRI (Ra)	90
Base Height	44 mm		
Rated Input Voltage	220-240 V/AC		



Article	Housing Color	Colour Temperature	Luminous Flux	Power	EEL	Price
348236	Black	2700 K	1300 lm	21.0 W		€ 209.95
348235	White	2700 K	1400 lm	21.0 W		€ 209.95
348177	Black	3000 K	1020 lm	15.0 W		€ 199.95
348123	White	3000 K	1210 lm	15.0 W		€ 199.95



Accessories

930327	Rear black cover for Uni II Mini series		€ 3.45
930328	White heat sink cover for Uni II Mini series		€ 3.55
930329	Black heat sink cover for Uni II Mini series		€ 2.95
930330	Reflector ring white for Uni II Mini series		€ 10.95
930331	Reflector ring black for Uni II Mini series		€ 10.95
930332	Reflector ring gold for Uni II Mini series		€ 10.95
930333	Reflector ring chrome for Uni II Mini series		€ 10.95
930770	Reflector 24° for Uni II Mini series		€ 10.95
930771	Reflector 48° for Uni II Mini series		€ 10.95




UNI 2 MAX

- „Glow“ effect on reflector ring
- Can be rotated and swivelled
- Can be customised with a comprehensive range of accessories

Application Area


Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000 K	Light Beam Angle	36 Degree
Height	128 mm	Rotation Angle	350 Degree
Ø	125 mm	Swivelling Angle	90 Degree
Power	32 W	Control	Leading-edge dimmer, Trailing-edge dimmer
Base Height	62 mm	CRI (Ra)	90
Base Ø	125 mm		
Rated Input Voltage	220-240 V/AC		



348127

Article	Housing Color	Luminous Flux	Price
348176	Black	2730 lm	€ 249.95
348127	White	2830 lm	€ 249.95



Accessories

930390	24° reflector for Uni II Max	€ 10.95
930391	36° reflector for Uni II Max	€ 12.95
930392	48° reflector for Uni II Max	€ 10.95
930393	Rear white cover for Uni II Max series	€ 10.95
930394	Rear black cover for Uni II Max series	€ 10.95
930395	White heat sink cover for Uni II Max series	€ 10.95
930396	Black heat sink cover for Uni II Max series	€ 10.95
930397	Reflector ring white for Uni II Max series	€ 12.95
930398	Reflector ring black for Uni II Max series	€ 10.95
930399	Reflector ring gold for Uni II Max series	€ 14.95






LUCEA CCT

- Incl. black reflector ring
- Comprehensive range of accessories for customisation
- Light colour adjustable in two steps

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Trade fair construction / shop fitting

Housing	Aluminium	Control	Leading-edge dimmer, Trailing-edge dimmer
Colour Temperature	3000/4000 K	CRI (Ra)	90
Rated Input Voltage	220-240 V/AC	IK Protection Class	IK03
Power Supply Unit incl.	Yes		
Light Beam Angle	36 Degree		



348153

Article	Housing Color		Luminous Flux	Height	Ø	Power	Price
348153	 White	 	930/1000 lm	157 mm	65 mm	10.0 W	€ 119.95
348154	 Black	 	930/1000 lm	157 mm	65 mm	10.0 W	€ 119.95
348155	 White	 	1460/1500 lm	178 mm	85 mm	15.0 W	€ 139.95
348156	 Black	 	1460/1500 lm	178 mm	85 mm	15.0 W	€ 139.95
348157	 White	 	1930/2000 lm	178 mm	85 mm	20.0 W	€ 159.95
348158	 Black	 	1930/2000 lm	178 mm	85 mm	20.0 W	€ 159.95
348159	 White	 	2700/2900 lm	211 mm	100 mm	30.0 W	€ 179.95
348160	 Black	 	2700/2900 lm	211 mm	100 mm	30.0 W	€ 179.95



Accessories for 348153, 348154

930679	Lens 24° for Lucea 6/10		€ 9.95
930756	Reflector ring for Lucea 6/10 white		€ 4.95
930757	Reflector ring for Lucea 6/10 black		€ 4.95
930758	Reflector ring for Lucea 6/10 gold		€ 4.95

Accessories for 348155, 348156, 348157, 348158


930680	Lens 24° for Lucea 15/20		€ 12.95
930681	Lens 60° for Lucea 15/20		€ 12.95
930759	Reflector ring for Lucea 15/20 white		€ 5.95
930760	Reflector ring for Lucea 15/20 black		€ 5.95
930761	Reflector ring for Lucea 15/20 gold		€ 5.95

Accessories for 348159

930677	Door panel for Lucea 30/40 white		€ 24.95
---------------	----------------------------------	---	----------------

Accessories for 348159, 348160

930682	Lens 24° for Lucea 30		€ 15.95
930684	Lens 60° for Lucea 30		€ 15.95
930762	Reflector ring for Lucea 30/40 white		€ 6.95
930763	Reflector ring for Lucea 30/40 black		€ 6.95
930764	Reflector ring for Lucea 30/40 gold		€ 6.95






LUCEA TILT CCT

- Incl. black reflector ring
- Comprehensive range of accessories for customisation
- Light colour adjustable in two steps

Application Area
 Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Swivelling Angle	90 Degree
Colour Temperature	3000/4000 K	Control	Leading-edge dimmer, Trailing-edge dimmer
Rated Input Voltage	220-240 V/AC	CRI (Ra)	90
Power Supply Unit incl.	Yes	IK Protection Class	IK03
Light Beam Angle	36 Degree		
Rotation Angle	350 Degree		



348161

Article	Housing Color		Luminous Flux	Height	Ø	Power	Price
348161	☐ White	 	930/1000 lm	218 mm	65 mm	10.0 W	€ 129.95
348162	☒ Black	 	930/1000 lm	218 mm	65 mm	10.0 W	€ 129.95
348163	☐ White	 	1460/1500 lm	241 mm	85 mm	15.0 W	€ 149.95
348164	☒ Black	 	1460/1500 lm	241 mm	85 mm	15.0 W	€ 149.95
348165	☐ White	 	1930/2000 lm	241 mm	85 mm	20.0 W	€ 169.95
348166	☒ Black	 	1930/2000 lm	241 mm	85 mm	20.0 W	€ 169.95
348167	☐ White	 	2700/2900 lm	274 mm	100 mm	30.0 W	€ 189.95
348168	☒ Black	 	2700/2900 lm	274 mm	100 mm	30.0 W	€ 189.95



Accessories for **348161, 348162**

930679	Lens 24° for Lucea 6/10		€ 9.95
930752	Door panel for Lucea 6/10 white		€ 22.95
930753	Door panel for Lucea 6/10 black		€ 22.95
930756	Reflector ring for Lucea 6/10 white		€ 4.95
930757	Reflector ring for Lucea 6/10 black		€ 4.95
930758	Reflector ring for Lucea 6/10 gold		€ 4.95

Accessories for **348163, 348164, 348165, 348166**

930680	Lens 24° for Lucea 15/20		€ 12.95
930681	Lens 60° for Lucea 15/20		€ 12.95
930754	Door panel for Lucea 15/20 white		€ 23.95
930755	Door panel for Lucea 15/20 black		€ 23.95
930759	Reflector ring for Lucea 15/20 white		€ 5.95
930760	Reflector ring for Lucea 15/20 black		€ 5.95
930761	Reflector ring for Lucea 15/20 gold		€ 5.95

Accessories for **348167, 348168**

- 930677** Door panel for Lucea 30/40 white
- 930678** Door panel for Lucea 30/40 black
- 930682** Lens 24° for Lucea 30
- 930684** Lens 60° for Lucea 30
- 930762** Reflector ring for Lucea 30/40 white
- 930763** Reflector ring for Lucea 30/40 black
- 930764** Reflector ring for Lucea 30/40 gold

	€ 24.95
	€ 24.95
	€ 15.95
	€ 15.95
	€ 6.95
	€ 6.95
	€ 6.95



page 42



page 432



page 436



Lighting design
Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.



LUCEA

- High colour rendering
- Light colour adjustable in 2 stages
- Housing made from die-cast aluminium
- Dimmable

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Light Beam Angle	36 Degree
Colour Temperature	2700 K	Control	Leading-edge dimmer, Trailing-edge dimmer
Height	157 mm	CRI (Ra)	90
Ø	65 mm	IK Protection Class	IK03
Rated Input Voltage	200-240 V/AC		
Power Supply Unit incl.	Yes		

Article	Housing Color		Luminous Flux	Power	Price
348213	 White		800 lm	6.0 W	€ 119.95
348214	 Black		800 lm	6.0 W	€ 119.95
348215	 White		1300 lm	10.0 W	€ 129.95
348216	 Black		1300 lm	10.0 W	€ 129.95



Accessories

930679	Lens 24° for Lucea 6/10		€ 9.95
930756	Reflector ring for Lucea 6/10 white		€ 4.95
930757	Reflector ring for Lucea 6/10 black		€ 4.95
930758	Reflector ring for Lucea 6/10 gold		€ 4.95





LUCEA TILT

- Incl. black reflector ring
- Can be customised with a comprehensive range of accessories

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Light Beam Angle	36 Degree
Colour Temperature	2700 K	Rotation Angle	350 Degree
Height	157 mm	Swivelling Angle	90 Degree
Ø	65 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Base Height	29 mm	CRI (Ra)	90
Base Ø	103.5 mm	IK Protection Class	IK03
Rated Input Voltage	200-240 V/AC		
Power Supply Unit incl.	Yes		

Article	Housing Color		Luminous Flux	Power	Price
348223	 White		800 lm	6.0 W	€ 119.95
348224	 Black		800 lm	6.0 W	€ 119.95
348225	 White		1300 lm	10.0 W	€ 129.95
348226	 Black		1300 lm	10.0 W	€ 129.95



Accessories

930679	Lens 24° for Lucea 6/10		€ 9.95
930752	Door panel for Lucea 6/10 white		€ 22.95
930753	Door panel for Lucea 6/10 black		€ 22.95
930756	Reflector ring for Lucea 6/10 white		€ 4.95
930757	Reflector ring for Lucea 6/10 black		€ 4.95
930758	Reflector ring for Lucea 6/10 gold		€ 4.95





LUCEA DTW

- Dim-to-warm 1,800K-2,700K
- Incl. black reflector ring
- Comprehensive range of accessories for customisation

Application Area

Home / Living, Reception / Communication, Hotel / catering

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	1800-2700 K	Light Beam Angle	36 Degree
Luminous Flux	750 lm	Control	Leading-edge dimmer, Trailing-edge dimmer
Height	157 mm	CRI (Ra)	90
Ø	65 mm	IK Protection Class	IK03
Power	10 W		
Rated Input Voltage	200-240 V/AC		

Article	Housing Color		Price
348237	White		€ 129.95
348238	Black		€ 129.95



Accessories

930752	Door panel for Lucea 6/10 white		€ 22.95
930753	Door panel for Lucea 6/10 black		€ 22.95
930756	Reflector ring for Lucea 6/10 white		€ 4.95
930757	Reflector ring for Lucea 6/10 black		€ 4.95
930758	Reflector ring for Lucea 6/10 gold		€ 4.95





LUCEA DTWTILT

- Dim-to-warm 1,800K-2,700K
- Incl. black reflector ring
- Comprehensive range of accessories for customisation

Application Area

Home / Living, Reception / Communication, Hotel / catering

Housing	Aluminium	Light Beam Angle	36 Degree
Colour Temperature	1800-2700 K	Rotation Angle	350 Degree
Luminous Flux	750 lm	Swivelling Angle	90 Degree
Height	218 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Ø	65 mm	CRI (Ra)	90
Power	10 W	IK Protection Class	IK03
Rated Input Voltage	200-240 V/AC		
Power Supply Unit incl.	Yes		

Article	Housing Color		Price
348239	White		€ 129.95
348240	Black		€ 129.95



Accessories

930752	Door panel for Lucea 6/10 white		€ 22.95
930753	Door panel for Lucea 6/10 black		€ 22.95
930756	Reflector ring for Lucea 6/10 white		€ 4.95
930757	Reflector ring for Lucea 6/10 black		€ 4.95
930758	Reflector ring for Lucea 6/10 gold		€ 4.95



page 42



page 432



page 436



CAN IP20

- Can be customised with a wide range of accessories
- Replaceable light source to offer an individual lighting solution
- Can be combined with the comprehensive CAN series product family

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Height	105 mm	Control	Dimmable via optional light source
Ø	60 mm		
Max. Power	1x max. 7.5 W		

Article	Housing Color	Price
348241	 White	€ 29.95
348242	 Black	€ 29.95



Accessories

- 930301** Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series
- 930302** Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series
- 930303** Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series
- 930307** Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series
- 930308** Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series
- 930309** Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series
- 930310** Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series
- 930366** Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series
- 931065** Acrylic attachment for Can





CAN IP44

- Customised lighting solution thanks to replaceable light source
- Can be combined with the extensive product family of the CAN series
- Suitable for damp rooms

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, Bathroom / WC, Hotel bathrooms / commercial wet areas

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Height	105 mm	Control	Dimmable via optional light source
Ø	60 mm		
Max. Power	1x max. 7.5 W		

Article	Housing Color	Price
348243	 White	€ 34.95
348244	 Black	€ 34.95



Accessories

930301	Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930302	Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930366	Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930303	Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95



page 46 page 202 page 222 page 223 page 414 page 507





CANTILT SQUARE

The square CAN surface-mounted ceiling light provides a flexible lighting solution for commercial and private spaces. Available as a one-, two- and three-luminaire variant in the colours black and white, it enables precise alignment of the light using rotating and swivelling luminous elements. The widely used GU10 base enables quick and simple replacement of the lamp, while the screw-on cylinder housing enables tool-free access. Installation for rigid and flexible conductors is easy and efficient due to the integrated push terminals. The CAN surface-mounted ceiling light is part of a versatile series, which also contains pendant, wall, reading and outdoor lights.





CAN TILT SQUARE

- Flat and discreet lamp base
- Can be customised with a wide range of accessories
- Replaceable lamp to offer an individual lighting solution
- Can be combined with the comprehensive CAN series product family

Application Area
Home / Living, Hotel / catering

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Height	125 mm	Control	Dimmable via optional light source
Ø	60 mm	Rotation Angle	350 Degree
Base Width	90 mm	Swivelling Angle	90 Degree
Base Height	15 mm		

Article	Housing Color	Base Length	Max. Power	Price
348245	White	110 mm	1x max. 7.5 W	€ 44.95
348246	Black	110 mm	1x max. 7.5 W	€ 44.95
348247	White	305 mm	2x max. 7.5 W	€ 84.95
348248	Black	305 mm	2x max. 7.5 W	€ 84.95
348249	White	480 mm	3x max. 7.5 W	€ 119.95
348250	Black	480 mm	3x max. 7.5 W	€ 119.95



Accessories


930301	Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930302	Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930303	Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930366	Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
931065	Acrylic attachment for Can		€ 4.95





CAN TILT ROUND

The round CAN surface-mounted ceiling light provides a flexible lighting solution for commercial and private spaces. Available as a one-, two- and three-luminaire variant in the colours black and white, it enables precise alignment of the light using rotating and swivelling luminous elements. The widely used GU10 base enables quick and simple replacement of the lamp, while the screw-on cylinder housing enables tool-free access. Installation for rigid and flexible conductors is easy and efficient due to the integrated push terminals. The CAN surface-mounted ceiling light is part of a versatile series, which also contains pendant, wall, reading and outdoor lights.





CAN TILT ROUND

- Flat and discreet lamp base
- Replaceable lamp to offer an individual lighting solution
- Can be customised with a wide range of accessories
- Can be combined with the comprehensive CAN series product family

Application Area

Home / Living, Hotel / catering

Housing	Aluminium	Control	Dimmable via optional light source
Height	125 mm	Rotation Angle	350 Degree
Ø	60 mm	Swivelling Angle	90 Degree
Base Height	15 mm		
Rated Input Voltage	220-240 V/AC		

Article	Housing Color	Base Ø	Max. Power	Price
348251	White	80 mm	1x max. 7.5 W	€ 44.95
348252	Black	80 mm	1x max. 7.5 W	€ 44.95
348253	White	200 mm	2x max. 7.5 W	€ 84.95
348254	Black	200 mm	2x max. 7.5 W	€ 84.95
348255	White	250 mm	3x max. 7.5 W	€ 119.95
348256	Black	250 mm	3x max. 7.5 W	€ 119.95



Accessories

930301	Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930302	Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930303	Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930366	Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
931065	Acrylic attachment for Can		€ 4.95





CAN TILT SQUARE BASE MIX'N MATCH 1/3

- flat and discreet luminaire base
- can be customised with cylinder housing in 6 different colours

Housing	Aluminium	Control	Dimmable via optional light source
Height	58 mm	Rotation Angle	350 Degree
Base Width	90 mm	Swivelling Angle	90 Degree
Base Height	15 mm		
Rated Input Voltage	220-240 V/AC		

Article	Housing Color	Base Length	Max. Power	Price
348264	White	110 mm	1x max. 7.5 W	€ 36.95
348265	Black	110 mm	1x max. 7.5 W	€ 36.95
348266	White	305 mm	2x max. 7.5 W	€ 69.95
348267	Black	305 mm	2x max. 7.5 W	€ 69.95
348268	White	480 mm	3x max. 7.5 W	€ 99.95
348269	Black	480 mm	3x max. 7.5 W	€ 99.95



CAN TILT ROUND BASE MIX'N MATCH 1/3

Housing	Aluminium	Control	Dimmable via optional light source
Height	58 mm	Rotation Angle	350 Degree
Base Height	15 mm	Swivelling Angle	90 Degree
Rated Input Voltage	220-240 V/AC		

Article	Housing Color	Base Ø	Max. Power	Price
348272	White	20 mm	2x max. 7.5 W	€ 68.95
348273	Black	20 mm	2x max. 7.5 W	€ 68.95
348274	White	25 mm	3x max. 7.5 W	€ 99.95
348275	Black	25 mm	3x max. 7.5 W	€ 99.95
348270	White	80 mm	1x max. 7.5 W	€ 36.95
348271	Black	80 mm	1x max. 7.5 W	€ 36.95





CYLINDER HOUSING FOR CAN MIX'N MATCH 2/3

Housing Aluminium Ø 60 mm
Height 98 mm

Article	Housing Color	Price
931053	White	€ 7.95
931054	Black	€ 7.95
931055	Bronze	€ 18.95
931056	Brass	€ 18.95
931057	Black gray	€ 18.95
931058	Rosé	€ 18.95

IP20



REFLECTOR RING CAN SERIES MIX'N MATCH 3/3

Housing Plastic Ø 57 mm
Height 28 mm

Article	Housing Color	Price
930301	 White	€ 4.95
930302	 Black	€ 4.95
930303	 Gold	€ 4.95
930366	 Silver	€ 4.95

IP20




BENGALA

- Exchangeable lamp
- Can be rotated and swivelled

Application Area
Garden / Terrace / Balcony / Walkways, Garage / carport / car park, House wall / facade / front door, Home / Living

Housing	Aluminium	Control	Dimmable via optional light source
Height	120 mm	Swivelling Angle	30 Degree
Max. Power	1x max. 50 W		
Rated Input Voltage	220-240 V/AC		

Article	Housing Color	Length	Width	Ø	Base Length	Base Width	Price
122416	 Silver			96 mm			€ 44.95
348022	 Black			96 mm			€ 44.95
348023	 White			96 mm			€ 44.95
122417	 Silver	96 mm	96 mm		96 mm	96 mm	€ 44.95
348024	 Black	96 mm	96 mm		96 mm	96 mm	€ 44.95
348025	 White	96 mm	96 mm		96 mm	96 mm	€ 44.95





MONA

- Exchangeable lamp
- Can be rotated and swivelled

Housing	Aluminium	Control	Dimmable via optional light source
Width	93 mm	Swivelling Angle	45 Degree
Height	120 mm		
Rated Input Voltage	220-240 V/AC		

Article	Housing Color	Length	Max. Power	Price
348001	 White	93 mm	1x max. 50.0 W	€ 61.95
348002	 Black	93 mm	1x max. 50.0 W	€ 61.95
348004	 White	186 mm	2x max. 50.0 W	€ 114.95
348005	 Black	186 mm	2x max. 50.0 W	€ 114.95






PRO OFFICE SANO

PRO OFFICE SANO series ceiling lights are an efficient solution for renovating and modernising old T5/T8 louver lights. Due to slightly larger dimensions, the lights cover the old installations and so do not require the ceiling to be repainted.

Arrestor cables, plug connectors and mounting brackets make installation so easy that it can be performed by one person. In addition to ease of installation, the series offers impressive technical highlights: It provides flexible light control via CCT switch (3,000 K / 3,500 K / 4,000 K), dimmable variants (leading-edge/trailing-edge or DALI) and output adjustment in four stages (TRIAC variants only). They are also eligible for BEG German federal funding for energy-efficient buildings and emergency power capable (176-280 V/DC EOFI: 95 %).






PRO OFFICE SANO

- Renovation solution for T5/T8 louver lights
- Uniform illumination
- Covers the old installation, therefore no repainting necessary
- Easy to install due to plug connector, arrestor cables and mounting bracket
- Light colour adjustable in three levels
- Output adjustable in four levels [TRIAC variants only]
- Microprismatic surface structure
- Eligible for BEG German federal funding for energy-efficient buildings
- Emergency power capable [176-280 V/DC EOfI: 95 %]
- Suitable for workplaces with screens in accordance with EN 12464-1 BAP65 [$L_{65} \leq 3,000 \text{ cd/m}^2$]

Application Area

Office / conference, Health / care / hospital / practice, Education / school / lecture theatre, Refurbishment

Housing	Aluminium, Stainless steel	Power Supply Unit incl.	Yes
Colour Temperature	3000/3500/4000 K	Light Beam Angle	90 Degree
Height	48 mm	Control	Trailing-edge dimmer, Leading-edge dimmer
Rated Input Voltage	198-264 V/AC	CRI (Ra)	90



348258

Article	Housing Color		Luminous Flux	Length	Width	Power Selectable	EEI	Price
348258	☐ White	WW NW	4200/4500/4400 lm	625 mm	625 mm	27,0 / 30,0 / 33,0 / 35,0 W		€ 189.95
348259	☐ White	WW NW	4350/4600/4500 lm	1225 mm	325 mm	27,0 / 30,0 / 32,0 / 35,0 W		€ 209.95
348260	☐ White	WW NW	5200/5500/5400 lm	1525 mm	325 mm	32,0 / 35,5 / 38,0 / 42,0 W		€ 229.95








PRO OFFICE SANO DALI

- Renovation solution for T5/T8 louver lights
- uniform illumination
- Covers the old installation, therefore no repainting necessary
- Easy to install due to plug connector, arrestor cables and mounting bracket
- Light colour adjustable in three levels
- Output adjustable in four levels [TRIAC variants only]
- Microprismatic surface structure
- Eligible for BEG German federal funding for energy-efficient buildings
- Emergency power capable [176-280 V/DC EOFI: 95 %]
- Suitable for workplaces with screens in accordance with EN 12464-1 BAP65 [$L65 \leq 3,000 \text{ cd/m}^2$]

Application Area

Office / conference, Health / care / hospital / practice, Education / school / lecture theatre, Refurbishment

Housing	Aluminium, Stainless steel	Power Supply Unit incl.	Yes
Colour Temperature	3000/3500/4000 K	Light Beam Angle	90 Degree
Height	48 mm	Control	DALI 2 / DT6, Intelli Push-Dim
Rated Input Voltage	198-264 V/AC	CRI (Ra)	90



348261

Article	Housing Color		Luminous Flux	Length	Width	Power	Price
348262	☐ White	WW NW	4200/4500/4400 lm	1225 mm	325 mm	34.0 W	€ 239.95
348261	☐ White	WW NW	4400/4700/4600 lm	625 mm	625 mm	35.0 W	€ 219.95
348263	☐ White	WW NW	5300/5600/5500 lm	1525 mm	325 mm	42.0 W	€ 259.95





DRACONIS

The DRACONIS series from DEKO-LIGHT allows flexible ceiling lighting for a variety of applications in the areas of industry, trade and logistics. With the DRACONIS light for optional use as a surface-mounted ceiling light or in a 3-phase track system, the power [45, 55 or 72 W] and light colour [2,700, 3,500 or 4,000 K] can be flexibly adjusted using a switch on the back of the housing. To be able to integrate the DRACONIS into almost any environment, we offer several lenses for asymmetrical or symmetrical lighting in different light emission angles. The maximum luminous flux is 8,215 lumens.



luminous flux at 2700 K: 72 W = 7330 lm / 55 W = 6000 lm / 45 W = 5030 lm

luminous flux at 3500 K: 72 W = 8210 lm / 55 W = 6590 lm / 45 W = 5560 lm

luminous flux at 4000 K: 72 W = 8250 lm / 55 W = 6950 lm / 45 W = 5700 lm





DRACONIS


- Output adjustable in three stages
- Light colour adjustable in three stages
- High luminous flux
- Replaceable lenses

Application Area

Office / conference, Home / Living

Housing	Aluminium	Base Length	102 mm
Colour Temperature	2700/3500/4000 K	Base Width	88 mm
Luminous Flux	7330/8210/8250 lm	Base Height	25 mm
Length	577.6 mm	Rated Input Voltage	220-240 V/AC
Width	188.6 mm	Power Supply Unit incl.	Yes
Height	71 mm	Light Beam Angle	60 Degree
Power Selectable	45 W, 55 W, 72 W	CRI (Ra)	80

Article	Housing Color		Price
348099	Light gray	WW NW	€ 279.95
348128	White	WW NW	€ 279.95



Accessories

930544	20° lens for surface-mounted ceiling lamp Draconis, symmetrical		€ 9.95
930545	30° lens for surface-mounted ceiling lamp Draconis, symmetrical		€ 9.95
930546	90° lens for surface-mounted ceiling lamp Draconis, symmetrical		€ 9.95
930577	15° lens for surface-mounted ceiling lamp Draconis, asymmetrical		€ 9.95



Lighting design

Interested in our lighting design service?

Your contact person will be happy to answer any questions you may have.


built in ceiling lights



page 106



page 107



page 108



page 109



page 111



page 116



page 122



page 123



page 124



page 126



page 129



page 131



☐ ☒
page 146



☐ ☒
page 148



☐ ☐
page 152



SAMSOLA ROUND

- Suitable for GU10/GU5.3 sockets [sold separately]
- Lamps are easy to install due to click lock

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Metal	Control	Dimmable via optional light source
Height	23 mm	Swivelling Angle	30 Degree
Installation Depth	100 mm		
Cut Out Ø	68 mm		

Article	Housing Color	Surface	Ø	Price
110040	 Silver	Brushed	82 mm	€ 9.95
110038	 Copper	Brushed	95 mm	€ 9.95
110039	 White	Matt	82 mm	€ 9.95
110042	 Aluminium	Matt	82 mm	€ 9.95
110043	 Black	Matt	82 mm	€ 9.95
110041	 Silver	Shiny	82 mm	€ 9.95




Accessories

100204	Socket GU10 with spacer		€ 3.95
100200	Socket GU5.3 with 15 cm cable		€ 0.95
829063	Safety spacer		€ 3.95
930967	Reducing ring round 130/70 mm, Traffic white		€ 9.95
931043	Reducing ring round 130/70 mm, Signal white		€ 9.95



Light sources
For all lights and bases:
You can find the right light sources in the »Light sources« section.



SAMSOLA SQUARE

- Suitable for GU10/GU5.3 sockets [sold separately]
- Lamps are easy to install due to click lock

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Metal	Cut Out Ø	68 mm
Length	85 mm	Control	Dimmable via optional light source
Width	85 mm		
Height	23 mm	Swivelling Angle	30 Degree
Installation Depth	100 mm		

Article	Housing Color	Surface	Price
110044	Copper	Brushed	€ 9.95
110046	Silver	Brushed	€ 9.95
110045	White	Matt	€ 9.95
110048	Aluminium	Matt	€ 9.95
110049	Black	Matt	€ 9.95
110047	Silver	Shiny	€ 9.95



Accessories

100204	Socket GU10 with spacer	€ 3.95
100200	Socket GU5.3 with 15 cm cable	€ 0.95
829063	Safety spacer	€ 3.95
930972	Reducing ring square 130/70 mm, Traffic white	€ 9.95
931048	Reducing ring square 130/70 mm, Signal white	€ 9.95



Onlineshop
You can find more information about the products in the onlineshop:
Detailed images, videos, project reports, LDT files, EPREL data sheets and more.



SAMSOLA MAX ROUND

- Suitable for GU10 / GU5.3 sockets [sold separately]
- Easy installation of the light sources thanks to click lock

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Cut Out Ø	68-80 mm
Height	23 mm	Control	Dimmable via optional light source
Ø	95 mm	Swivelling Angle	30 Degree
Installation Depth	100 mm		

Article	Housing Color	Surface	Price
110050	Copper	Brushed	€ 11.95
110051	White	Brushed	€ 11.95
110052	Silver	Brushed	€ 11.95
110054	Aluminium	Matt	€ 11.95
110055	Black	Matt	€ 11.95
110053	Silver	Shiny	€ 11.95




Accessories

100204	Socket GU10 with spacer		€ 3.95
100200	Socket GU5.3 with 15 cm cable		€ .95
829063	Safety spacer		€ 3.95
930967	Reducing ring round 130/70 mm, Traffic white		€ 9.95
931043	Reducing ring round 130/70 mm, Signal white		€ 9.95



Light sources
For all lights and bases:
You can find the right light sources in the »Light sources« section.



SAMSOLA MAX SQUARE

- Suitable for GU10 / GU5.3 sockets [sold separately]
- Easy installation of the light sources thanks to click lock

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Cut Out Ø	68-80 mm
Length	95 mm	Control	Dimmable via optional light source
Width	95 mm	Swivelling Angle	30 Degree
Height	23 mm		
Installation Depth	100 mm		

Article	Housing Color	Surface	Price
110056	Copper	Brushed	€ 11.95
110058	Silver	Brushed	€ 11.95
110057	White	Matt	€ 11.95
110060	Aluminium	Matt	€ 11.95
110061	Black	Matt	€ 11.95
110059	Silver	Shiny	€ 11.95



Accessories

100204	Socket GU10 with spacer		€ 3.95
100200	Socket GU5.3 with 15 cm cable		€ .95
829063	Safety spacer		€ 3.95
930972	Reducing ring square 130/70 mm, Traffic white		€ 9.95
931048	Reducing ring square 130/70 mm, Signal white		€ 9.95




5-year guarantee
Benefit from the maximum quality promise:
All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.

CAN

The CAN series is available in numerous versions: as a pendant, ceiling, wall, reading, track, outdoor or - as shown here - recessed ceiling light. This means that the CAN feels at home almost anywhere: in living rooms, hotel rooms, restaurants and many other areas of application.

A wide range of accessory components means that each luminaire can be individually adapted. Discover the diversity of the CAN series with us - also for your next project.





CAN ROUND

- customised lighting solution thanks to replaceable light source
- can be customised with cylinder housing in 5 different colours
- can be combined with the extensive product family of the CAN series



Application Area

Home / Living, Hotel / catering

Housing	Aluminium	Cut Out Ø	51 mm
Height	98 mm	Control	Dimmable via optional light source
Ø	60 mm	Rotation Angle	350 Degree
Installation Depth	40 mm	Swivelling Angle	90 Degree
Rated Input Voltage	220-240 V/AC		

Article	Housing Color	Length	Sockets	Max. Power	Cut Out Length	Price
565755	White		1 PCS	1x max. 7.5 W		€ 33.95
565756	Black		1 PCS	1x max. 7.5 W		€ 33.95
565757	White	160 mm	2 PCS	2x max. 7.5 W	100 mm	€ 69.95
565758	Black	160 mm	2 PCS	2x max. 7.5 W	100 mm	€ 69.95



Accessories

- 930301 Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series
- 930302 Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series
- 930303 Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series
- 930307 Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series
- 930308 Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series
- 930309 Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series
- 930310 Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series
- 930366 Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series
- 931065 Acrylic attachment for Can







REDUCING RINGS FOR RECESSED LIGHTS

- Renovation solution for excessively large ceiling cut-outs
- Flexible adaptation to ceiling cut-outs
- suitable for 3-30 mm thick hollow ceilings
- toolless installation possible

Housing		Metal		Height		1.5 mm	
Article	Housing Color	Length	Width	Ø	Cut Out Ø	Inner diameter	Price
930967	☐ White			130 mm	95 mm	70 mm	€ 9.95
931043	☐ White			130 mm	95 mm	70 mm	€ 9.95
930968	☐ White			155 mm	120 mm	95 mm	€ 11.95
931044	☐ White			155 mm	120 mm	95 mm	€ 11.95
930969	☐ White			210 mm	175 mm	135 mm	€ 13.95
931045	☐ White			210 mm	175 mm	135 mm	€ 13.95
930970	☐ White			240 mm	205 mm	180 mm	€ 17.95
931046	☐ White			240 mm	205 mm	180 mm	€ 17.95
930971	☐ White			280 mm	245 mm	210 mm	€ 23.95
931047	☐ White			280 mm	245 mm	210 mm	€ 23.95
930972	☐ White	130 mm	130 mm		95 mm	70 mm	€ 9.95
931048	☐ White	130 mm	130 mm		95 mm	70 mm	€ 9.95
930973	☐ White	155 mm	155 mm		120 mm	95 mm	€ 11.95
931049	☐ White	155 mm	155 mm		120 mm	95 mm	€ 11.95
930974	☐ White	210 mm	210 mm		175 mm	135 mm	€ 13.95
931050	☐ White	210 mm	210 mm		175 mm	135 mm	€ 13.95
930975	☐ White	240 mm	240 mm		205 mm	180 mm	€ 17.95
931051	☐ White	240 mm	240 mm		205 mm	180 mm	€ 17.95
930976	☐ White	280 mm	280 mm		245 mm	210 mm	€ 23.95
931052	☐ White	280 mm	280 mm		245 mm	210 mm	€ 23.95



Lighting design
Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.

DIONE

The DIONE series comprises elegant recessed spotlights in aluminium housing with particularly shallow mounting depth - a real problem solver in the refurbishment sector.

The popular DIONE recessed ceiling luminaires with high-quality COB LED including reflector are housed in an aluminium casing and have a cut-out dimension of 68 mm. While the available colours white, silver, black, chrome and nickel harmonise with almost any type of ceiling, the actual special feature of the DIONE is not visible when installed: The recessed spotlights are extremely space-saving when installed and require only 25 or 27 mm of ceiling cavity. This is where the power supply unit and the Quick connection box are located, which allows 3-pole through-wiring of several DIONE models as well as retrofitting as part of renovations.

The plug-in connector between the spotlight and the power supply unit allows installers to conveniently install the lighting equipment and connect the spotlight once the ceiling work has been completed.

The DIONE recessed spotlights are available in the light colours 2,700K, 3,000 K, 4,000 K and as a dim-to-warm version [1,800-3,000K]. In addition to the IP20 version, an IP44 version is also available, making the DIONE suitable for bathrooms and other damp areas indoors.

With this variety, the DIONE series offers recessed spotlights for a wide range of applications - from private homes and exhibition areas to guest areas in hotels and restaurants. Thanks to the wide selection of light colours and IP classes, the DIONE can be flexibly integrated into any environment and covers all design requirements, from a feel-good character to functional lighting.



only 25 or 27 mm ceiling cavity required

H x Ø: 41 x 82 mm [cut-out dimension 68 mm]

aluminium housing in white, silver, black, chrome and brushed nickel

reflector with 36° beam angle

high-quality COB technology with up to 800 lm

new connector between spot and power supply unit for even more convenient mounting

dimmable power supply unit

Quick connection box with quick-release fastener [optionally fixable with screw] for quick installation and through-wiring for flexible and rigid cables up to 1.5 mm² NYM

THAT'S HOW EASY IT IS



1 - Quick wiring / through-wiring on the Quick connection box due to screwless plug-in terminals



2 - quick connection box is placed over the 68 mm cut-out in the cavity




3 - compact power supply unit is inserted into the cavity



4 - connect the power supply unit to the spot using the connector



5 - inserting the spot into the ceiling cut-out



6 - The result: a compact installation with a swivelling spot, a dimmable power supply unit and the option of through-wiring in the ceiling cavity - ideal in refurbishment areas.




DIONE IP20

- Low installation depth
- Incl. dimmable power supply unit and connection box
- Feed-through wiring possible
- Ideal renovation solution
- Light and power supply unit with intermediate connector

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Required Installation Depth	25 mm
Height	41 mm	Light Beam Angle	36 Degree
Ø	82 mm	Swivelling Angle	30 Degree
Power	8.5 W	Cut Out Ø	68 mm
Rated Input Voltage	220-240 V/AC	Control	Leading-edge dimmer, Trailing-edge dimmer
Power Supply Unit incl.	Yes		
Installation Depth	38 mm		



565355

Article	Housing Color	Colour Temperature	Luminous Flux	CRI (Ra)	Price
565375	White	2700 K	750 lm	81	€ 59.95
565376	Silver	2700 K	750 lm	81	€ 59.95
565377	Black	2700 K	750 lm	81	€ 59.95
565378	Nickel	2700 K	750 lm	81	€ 59.95
565379	Chrome	2700 K	750 lm	81	€ 59.95
565355	White	3000 K	800 lm	81	€ 59.95
565356	Silver	3000 K	800 lm	81	€ 59.95
565357	Black	3000 K	800 lm	81	€ 59.95
565371	Nickel	3000 K	800 lm	81	€ 59.95
565372	Chrome	3000 K	800 lm	81	€ 59.95
565358	White	4000 K	800 lm	84	€ 59.95
565359	Silver	4000 K	800 lm	84	€ 59.95
565360	Black	4000 K	800 lm	84	€ 59.95
565373	Nickel	4000 K	800 lm	84	€ 59.95
565374	Chrome	4000 K	800 lm	84	€ 59.95



Accessories

- 930863** 60° reflector for Dione
- 930864** Frosted diffusing lens for Dione
- 829063** Safety spacer
- 930967** Reducing ring round 130/70 mm, Traffic white
- 931043** Reducing ring round 130/70 mm, Signal white

	€ 5.95
	€ 2.95
	€ 3.95
	€ 9.95
	€ 9.95




DIONE IP20 DTW

- Low installation depth
- Incl. dimmable power supply unit and connection box
- Feed-through wiring possible
- Ideal renovation solution
- Light and power supply unit with intermediate connector

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Installation Depth	38 mm
Colour Temperature	1800-3000 K	Required Installation Depth	25 mm
Luminous Flux	480 lm	Light Beam Angle	36 Degree
Height	41 mm	Swivelling Angle	30 Degree
Ø	82 mm	Cut Out Ø	68 mm
Power	8.5 W	Control	Leading-edge dimmer, Trailing-edge dimmer
Rated Input Voltage	220-240 V/AC	CRI (Ra)	95
Power Supply Unit incl.	Yes		




Article	Housing Color	Price
565380	White	€ 69.95
565381	Silver	€ 69.95
565382	Black	€ 69.95
565383	Chrome	€ 69.95
565384	Nickel	€ 69.95



Accessories

930863	60° reflector for Dione
930864	Frosted diffusing lens for Dione
829063	Safety spacer
930967	Reducing ring round 130/70 mm, Traffic white
931043	Reducing ring round 130/70 mm, Signal white

	€ 5.95
	€ 2.95
	€ 3.95
	€ 9.95
	€ 9.95






DIONE IP44

- Low installation depth
- Splash-proof [downwards after installation]
- Incl. dimmable power supply unit and connection box
- Feed-through wiring possible
- Ideal renovation solution
- Light and power supply unit with intermediate connector

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, Bathroom / WC

Housing	Aluminium	Required Installation Depth	27 mm
Height	44 m	Light Beam Angle	36 Degree
Ø	82 mm	Swivelling Angle	30 Degree
Power	8.5 W	Cut Out Ø	68 mm
Rated Input Voltage	220-240 V/AC	Control	Leading-edge dimmer, Trailing-edge dimmer
Power Supply Unit incl.	Yes		
Installation Depth	41 mm		




Article	Housing Color	Colour Temperature	Luminous Flux	CRI (Ra)	Price
565388	White	2700 K	750 lm	81	€ 64.95
565389	Silver	2700 K	750 lm	81	€ 64.95
565390	Black	2700 K	750 lm	81	€ 64.95
565391	Chrome	2700 K	750 lm	81	€ 64.95
565392	Nickel	2700 K	750 lm	81	€ 64.95
565393	White	3000 K	800 lm	81	€ 64.95
565394	Silver	3000 K	800 lm	81	€ 64.95
565395	Black	3000 K	800 lm	81	€ 64.95
565396	Chrome	3000 K	800 lm	81	€ 64.95
565397	Nickel	3000 K	800 lm	81	€ 64.95
565398	White	4000 K	800 lm	84	€ 64.95
565399	Silver	4000 K	800 lm	84	€ 64.95
565400	Black	4000 K	800 lm	84	€ 64.95
565401	Chrome	4000 K	800 lm	84	€ 64.95
565402	Nickel	4000 K	800 lm	84	€ 64.95



Accessories

930863	60° reflector for Dione
930864	Frosted diffusing lens for Dione
829063	Safety spacer
930967	Reducing ring round 130/70 mm, Traffic white
931043	Reducing ring round 130/70 mm, Signal white

	€ 5.95
	€ 2.95
	€ 3.95
	€ 9.95
	€ 9.95




DIONE IP44 DTW

- Low installation depth
- Splash-proof [downwards after installation]
- Incl. dimmable power supply unit and connection box
- Feed-through wiring possible
- Ideal renovation solution
- Light and power supply unit with intermediate connector




Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, Bathroom / WC

Housing	Aluminium	Installation Depth	41 mm
Colour Temperature	1800-3000 K	Required Installation Depth	27 mm
Luminous Flux	480 lm	Light Beam Angle	36 Degree
Height	44 mm	Swivelling Angle	30 Degree
Ø	82 mm	Cut Out Ø	68 mm
Power	8.5 W	Control	Leading-edge dimmer, Trailing-edge dimmer
Rated Input Voltage	220-240 V/AC	CRI (Ra)	95
Power Supply Unit incl.	Yes		




Article	Housing Color	Price
565403	White	€ 74.95
565404	Silver	€ 74.95
565405	Black	€ 74.95
565406	Chrome	€ 74.95
565407	Nickel	€ 74.95




Accessories

- 930863 60° reflector for Dione
- 930864 Frosted diffusing lens for Dione
- 829063 Safety spacer
- 930967 Reducing ring round 130/70 mm, Traffic white
- 931043 Reducing ring round 130/70 mm, Signal white

- € 5.95
- € 2.95
- € 3.95
- € 9.95
- € 9.95







DIONE, IP44, RGBW

- Low installation depth
- splash-proof [downwards when installed]
- suitable for 24V CV colour controls (e.g. RF-smart, Dali, DMX, Casambi, etc.)
- can be combined with all Dione recessed spotlights
- high-quality RGBW COB technology
- RGB 3x 3W, WW 1x 6W, max. possible total output 9W
- homogeneous colour mixing

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, Bathroom / WC

Housing	Aluminium	Installation Depth	41 mm
Colour Temperature	3000 K	Required Installation Depth	27 mm
Luminous Flux	540 lm	Light Beam Angle	36 Degree
Height	41 mm	Swivelling Angle	30 Degree
Ø	82 mm	Cut Out Ø	68 mm
Power	9 W	Control	Dimmable via optional controller
Rated Input Voltage	24 V/DC	CRI (Ra)	90
Power Supply Unit incl.	No		

Article	Housing Color	Price
565450	White	€ 74.95
565451	Light gray	€ 74.95
565452	Black	€ 74.95
565453	Chrome	€ 74.95
565454	Nickel	€ 74.95



Accessories

843502	RF-smart, starter set RGB/W/CCT, 12-48 V, 20 A incl. remote, IP20
843343	DALI 2 PWM dimmer CV 4CH 12-48V, 4A/CH, DT6
843344	DALI 2 PWM dimmer CV 4CH 12-48V, 4A/CH, DT8
843279	MULTI-LED dimmer 1-4 channels, DMX/auto/manual, 12-48 V, 20 A, flicker-free
862234	FLAT, CV, UT 24 V/20 W
862122	FLAT, CV, UT 24 V/50 W
862126	LONG-FLAT, CV, LT-100-24
930967	Reducing ring round 130/70 mm, Traffic white
931043	Reducing ring round 130/70 mm, Signal white

	€ 99.95
	€ 94.95
	€ 94.95
	€ 114.95
	€ 25.95
	€ 52.95
	€ 96.95
	€ 9.95
	€ 9.95



SURTUR

- Integrated power supply unit
- through-wiring possible
- Light colour adjustable in 3 steps
- Very high colour rendering

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Colour Temperature	2700/3000/4000 K	Control	Trailing-edge dimmer, Leading-edge dimmer
Rated Input Voltage	220-240 V/AC		
Power Supply Unit incl.	Yes	CRI (Ra)	90
Light Beam Angle	40 Degree	Accumulator/Battery Operated	No
Swivelling Angle	30 Degree		
Cut Out Ø	68-75 mm	IK Protection Class	IK06

Article	Housing Color	Luminous Flux	Housing	Height	Ø	Power	Price
565455	White		520/600/510 lm Polycarbonate	44 mm	85 mm	6.0 W	€ 24.95
565456	Black		520/600/510 lm Polycarbonate	44 mm	85 mm	6.0 W	€ 24.95
565457	White		880/950/810 lm Polycarbonate / PA - Polyamide	72 mm	105 mm	10.0 W	€ 32.95
565458	Black		880/950/810 lm Polycarbonate / PA - Polyamide	72 mm	105 mm	10.0 W	€ 32.95



Accessories for 565455, 565456		
930967	Reducing ring round 130/70 mm, Traffic white	€ 9.95
931043	Reducing ring round 130/70 mm, Signal white	€ 9.95
Accessories for 565457, 565458		
930968	Reducing ring round 155/95 mm, Traffic white	€ 11.95
931044	Reducing ring round 155/95 mm, Signal white	€ 11.95



Onlineshop
You can find more information about the products in the onlineshop:
Detailed images, videos, project reports, LDT files, EPREL data sheets and more.



SURTUR DTW

- Integrated power supply unit
- Feed-through wiring possible
- Adjustable light colour - dim to warm
- Very high colour rendering

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Colour Temperature	1800-2700 K	Control	Trailing-edge dimmer, Leading-edge dimmer
Rated Input Voltage	220-240 V/AC	CRI (Ra)	90
Power Supply Unit incl.	Yes	Accumulator/Battery Operated	No
Light Beam Angle	40 Degree	IK Protection Class	IK06
Swivelling Angle	30 Degree		
Cut Out Ø	68-75 mm		

Article	Housing Color	Luminous Flux	Housing	Height	Ø	Power	Price
565459	White		230/430 lm Polycarbonate	44 mm	85 mm	6.0 W	€ 28.95
565460	Black		230/430 lm Polycarbonate	44 mm	85 mm	6.0 W	€ 28.95
565461	White		360/720 lm Polycarbonate / PA - Polyamide	72 mm	105 mm	10.0 W	€ 36.95
565462	Black		360/720 lm Polycarbonate / PA - Polyamide	72 mm	105 mm	10.0 W	€ 36.95



Accessories for 565459, 565460

930967	Reducing ring round 130/70 mm, Traffic white		€ 9.95
931043	Reducing ring round 130/70 mm, Signal white		€ 9.95


Accessories for 565461, 565462

930968	Reducing ring round 155/95 mm, Traffic white		€ 11.95
931044	Reducing ring round 155/95 mm, Signal white		€ 11.95



Technical data sheet

New in the onlineshop: The technical data sheets offer even more information:
Light and energy data, light distribution curves, dimensional drawings and more.



SMD-68-230V-ROUND

Plenty of power for less! SMD-68 series recessed lights deliver up to 550 lm and also have an integrated, dimmable power supply (230 V direct connection), which makes the use of GU10 holders and retrofitted equipment redundant.






SMD-68-230V-ROUND

- Integrated power supply unit
- Swivel-mounted
- Low installation depth

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Plastic	Light Beam Angle	45 Degree
Height	43.8 mm	Swivelling Angle	36 Degree
Ø	85 mm	Cut Out Ø	68 mm
Power	6.5 W	Control	Leading-edge dimmer, Trailing-edge dimmer
Rated Input Voltage	220-240 V/AC	CRI (Ra)	80
Power Supply Unit incl.	Yes		
Installation Depth	41.3 mm		



565337

Article	Housing Color	Colour Temperature	Luminous Flux	EEL	Price
565337	White	2700 K	510 lm		€ 19.95
565385	Black	2700 K	510 lm		€ 19.95
565338	White	3000 K	540 lm		€ 19.95
565386	Black	3000 K	540 lm		€ 19.95
565339	White	4000 K	550 lm		€ 19.95
565387	Black	4000 K	550 lm		€ 19.95




Accessories

930967	Reducing ring round 130/70 mm, Traffic white		€ 9.95
931043	Reducing ring round 130/70 mm, Signal white		€ 9.95



5-year guarantee
Benefit from the maximum quality promise:
All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.




COB 68 HCL

- Suitable for 24 V HCL controllers
- Swivel-mounted

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Installation Depth	60 mm
Colour Temperature	2500-6500 K	Light Beam Angle	65 Degree
Luminous Flux	534 lm	Swivelling Angle	25 Degree
Height	46 mm	Cut Out Ø	68 mm
Ø	78 mm	Control	Dimmable via optional controller
Power	8 W	CRI (Ra)	80
Rated Input Voltage	24 V/DC		
Power Supply Unit incl.	No		

Article	Housing Color	Colour Temperature	Price
565193	☐ White	☒ WW ☐ CW 2500-6500 K	€ 65.95



Accessories	
829063	Safety spacer
862234	FLAT, CV, UT 24 V/20 W
862168	BASIC, CV, Q8H-24-150 W
843501	RF-smart, starter set LED single/CCT, 12-48 V, 20 A incl. remote control
930967	Reducing ring round 130/70 mm, Traffic white
931043	Reducing ring round 130/70 mm, Signal white

	€ 3.95
	€ 25.95
	€ 129.95
	€ 99.95
	€ 9.95
	€ 9.95



COB 95 HCL

- suitable for 24V HCL control
- swivelling

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Installation Depth	70 mm
Colour Temperature	2500-6500 K	Light Beam Angle	65 Degree
Luminous Flux	1118 lm	Swivelling Angle	25 Degree
Height	65 mm	Cut Out Ø	95 mm
Ø	108 mm	Control	Dimmable via optional controller
Power	16 W	CRI (Ra)	80
Rated Input Voltage	24 V/DC		
Power Supply Unit incl.	No		

Article	Housing Color	Colour Temperature	Price
565194	☐ White	☒ WW ☐ CW 2500-6500 K	€ 109.95



Accessories	
829063	Safety spacer
862233	FLAT, CV, UT 24 V/12 W
862166	BASIC, CV, Q8H-24-100 W
843501	RF-smart, starter set LED single/CCT, 12-48 V, 20 A incl. remote control
930968	Reducing ring round 155/95 mm, Traffic white
931044	Reducing ring round 155/95 mm, Signal white


	€ 3.95
	€ 21.95
	€ 96.95
	€ 99.95
	€ 11.95
	€ 11.95



COB-68-350MA-2700K-SQUARE

Application Area
 Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Light Beam Angle	45 Degree
Length	78 mm	Swivelling Angle	25 Degree
Width	78 mm	Cut Out Ø	68 mm
Height	46 mm	Control	Dimmable via optional power supply unit
Power	6 W	CRI (Ra)	90
Rated Input Voltage	16-17 V/DC	Rated Current	350 mA
Power Supply Unit incl.	No		
Installation Depth	50 mm		



565282

Article	Housing Color	Colour Temperature	Luminous Flux	EEL	Price
565282	Silver	2700 K	580 lm		€ 59.95
565283	White	2700 K	580 lm		€ 59.95
565284	Silver	4000 K	660 lm		€ 59.95
565285	White	4000 K	660 lm		€ 59.95



Accessories

829063	Safety spacer	
180512	BASIC, CC, CC35018/18 W	
862202	BASIC, DIM, CC, D35009UF/9 W	
930972	Reducing ring square 130/70 mm, Traffic white	
931048	Reducing ring square 130/70 mm, Signal white	



€ 3.95
 € 23.95
 € 28.95
 € 9.95
 € 9.95



COB 95 RGBW

- Suitable for 24 V colour controller
- Swivel-mounted

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment


Housing	Aluminium	Installation Depth	68 mm
Colour Temperature	3000 K	Light Beam Angle	60 Degree
Luminous Flux	710 lm	Swivelling Angle	25 Degree
Height	70 mm	Cut Out Ø	95 mm
Ø	110 mm	Control	Dimmable via optional controller
Power	16 W	CRI (Ra)	80
Rated Input Voltage	24 V/DC		
Power Supply Unit incl.	No		

Article	Housing Color		Price
565245	White		€ 129.95
565246	Silver		€ 129.95



Accessories	
862234	FLAT, CV, UT 24 V/20 W
862166	BASIC, CV, Q8H-24-100 W
843502	RF-smart, starter set RGB/W/CCT, 12-48 V, 20 A incl. remote, IP20
930968	Reducing ring round 155/95 mm, Traffic white
931044	Reducing ring round 155/95 mm, Signal white

	€ 25.95
	€ 96.95
	€ 99.95
	€ 11.95
	€ 11.95



TARVOS

The TARVOS series offers a well-designed LED downlight portfolio for professional indoor lighting solutions. The name of each luminaire directly refers to the cut-out diameter in millimeters – TARVOS 68, 100, 150, or 240. This allows the models to be planned quickly and precisely into existing or new ceiling cut-outs. All TARVOS recessed spotlights are suitable for emergency power operation, feature a round housing, and are available in several variants that differ in housing colour, light colour, beam angle, and control (see list). This enables precise and individual adaptation of the lighting effect to the respective application – from pinpoint accentuation to wide, diffuse general lighting.



Note: Please note that the TARVOS series are project items that are not available from stock. The delivery time is approx. 6 weeks.



TARVOS 68 2700 K

- Through-wiring possible
- very high color rendering
- BEG eligible
- capable of emergency power supply
- incl. power supply unit and 230V direct connection

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Power	7.2 W
Colour Temperature	2700 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	860 lm	Cut Out Ø	68 mm
Length	85 mm	CRI (Ra)	90
Width	85 mm	Accumulator/Battery Operated	No
Height	54 mm	IK Protection Class	IK05
Ø	85 mm		

Article	Housing Color	Light Beam Angle	Dimmable	Control	Price
565463	Black	15 Degree	No		€ 144.95
565466	Light gray	15 Degree	No		€ 144.95
565469	White	15 Degree	No		€ 144.95
565472	Black	15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 199.95
565475	Light gray	15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 199.95
565478	White	15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 199.95
565464	Black	30 Degree	No		€ 144.95
565467	Light gray	30 Degree	No		€ 144.95
565470	White	30 Degree	No		€ 144.95
565473	Black	30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 199.95
565476	Light gray	30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 199.95
565479	White	30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 199.95
565465	Black	45 Degree	No		€ 144.95
565468	Light gray	45 Degree	No		€ 144.95
565471	White	45 Degree	No		€ 144.95
565474	Black	45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 199.95
565477	Light gray	45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 199.95
565480	White	45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 199.95



IP20



Accessories

930967 Reducing ring round 130/70 mm, Traffic white



€ 9.95

931043 Reducing ring round 130/70 mm, Signal white



€ 9.95



TARVOS 68 3000 K

- Through-wiring possible
- very high color rendering
- BEG eligible
- capable of emergency power supply
- incl. power supply unit and 230V direct connection

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Power	7.2 W
Colour Temperature	3000 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	870 lm	Cut Out Ø	68 mm
Length	85 mm	CRI (Ra)	90
Width	85 mm	Accumulator/Battery Operated	No
Height	54 mm	IK Protection Class	IK05
Ø	85 mm		

Article	Housing Color		Light Beam Angle	Dimmable	Control	Price
565481		Black		15 Degree	No	€ 144.95
565484		Light gray		15 Degree	No	€ 144.95
565487		White		15 Degree	No	€ 144.95
565490		Black		15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim € 199.95
565493		Light gray		15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim € 199.95
565496		White		15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim € 199.95
565482		Black		30 Degree	No	€ 144.95
565485		Light gray		30 Degree	No	€ 144.95
565488		White		30 Degree	No	€ 144.95
565491		Black		30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim € 199.95
565494		Light gray		30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim € 199.95
565497		White		30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim € 199.95
565483		Black		45 Degree	No	€ 144.95
565486		Light gray		45 Degree	No	€ 144.95
565489		White		45 Degree	No	€ 144.95
565492		Black		45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim € 199.95
565495		Light gray		45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim € 199.95
565498		White		45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim € 199.95



Accessories

930967	Reducing ring round 130/70 mm, Traffic white		€ 9.95
931043	Reducing ring round 130/70 mm, Signal white		€ 9.95



TARVOS 68 3000 K

- Through-wiring possible
- very high color rendering
- BEG eligible
- capable of emergency power supply
- incl. power supply unit and 230V direct connection

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Power	7.2 W
Colour Temperature	4000 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	905 lm	Cut Out Ø	68 mm
Length	85 mm	CRI (Ra)	90
Width	85 mm	Accumulator/Battery Operated	No
Height	54 mm	IK Protection Class	IK05
Ø	85 mm		

Article	Housing Color		Light Beam Angle	Dimmable	Control	Price
565499	Black	NW	15 Degree	No		€ 144.95
565502	Light gray	NW	15 Degree	No		€ 144.95
565505	White	NW	15 Degree	No		€ 144.95
565508	Black	NW	15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 199.95
565511	Light gray	NW	15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 199.95
565514	White	NW	15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 199.95
565500	Black	NW	30 Degree	No		€ 144.95
565503	Light gray	NW	30 Degree	No		€ 144.95
565506	White	NW	30 Degree	No		€ 144.95
565509	Black	NW	30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 199.95
565512	Light gray	NW	30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 199.95
565515	White	NW	30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 199.95
565501	Black	NW	45 Degree	No		€ 144.95
565504	Light gray	NW	45 Degree	No		€ 144.95
565507	White	NW	45 Degree	No		€ 144.95
565510	Black	NW	45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 199.95
565513	Light gray	NW	45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 199.95
565516	White	NW	45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 199.95



Accessories

- 930967** Reducing ring round 130/70 mm, Traffic white
- 931043** Reducing ring round 130/70 mm, Signal white



€ 9.95



€ 9.95



TARVOS 100 2700 K

- through-wiring possible
- very high color rendering
- BEG eligible
- emergency power supply capable
- incl. power supply unit and 230V direct connection

Application Area
 Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Power	10.8 W
Colour Temperature	2700 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	1290 lm	Cut Out Ø	100 mm
Length	115 mm	CRI (Ra)	90
Width	115 mm	Accumulator/Battery	No
Height	68 mm	Operated	
Ø	115 mm	IK Protection Class	IK05

Article	Housing Color		Light Beam Angle	Dimmable	Control	Price
565517		Black		15 Degree	No	€ 159.95
565520		Light gray		15 Degree	No	€ 159.95
565523		White		15 Degree	No	€ 159.95
565526		Black		15 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 214.95
565529		Light gray		15 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 214.95
565532		White		15 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 214.95
565518		Black		30 Degree	No	€ 159.95
565521		Light gray		30 Degree	No	€ 159.95
565524		White		30 Degree	No	€ 159.95
565527		Black		30 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 214.95
565530		Light gray		30 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 214.95
565533		White		30 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 214.95
565519		Black		45 Degree	No	€ 159.95
565522		Light gray		45 Degree	No	€ 159.95
565525		White		45 Degree	No	€ 159.95
565528		Black		45 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 214.95
565531		Light gray		45 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 214.95
565534		White		45 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 214.95





TARVOS 100 3000 K

- through-wiring possible
- very high color rendering
- BEG eligible
- emergency power supply capable
- incl. power supply unit and 230V direct connection

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Power	10.8 W
Colour Temperature	3000 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	1310 lm	Cut Out Ø	100 mm
Length	115 mm	CRI (Ra)	90
Width	115 mm	Accumulator/Battery	No
Height	68 mm	Operated	
Ø	115 mm	IK Protection Class	IK05

Article	Housing Color		Light Beam Angle	Dimmable	Control	Price
565535		Black		15 Degree	No	€ 159.95
565538		Light gray		15 Degree	No	€ 159.95
565541		White		15 Degree	No	€ 159.95
565544		Black		15 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 214.95
565547		Light gray		15 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 214.95
565550		White		15 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 214.95
565536		Black		30 Degree	No	€ 159.95
565539		Light gray		30 Degree	No	€ 159.95
565542		White		30 Degree	No	€ 159.95
565545		Black		30 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 214.95
565548		Light gray		30 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 214.95
565551		White		30 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 214.95
565537		Black		45 Degree	No	€ 159.95
565540		Light gray		45 Degree	No	€ 159.95
565543		White		45 Degree	No	€ 159.95
565546		Black		45 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 214.95
565549		Light gray		45 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 214.95
565552		White		45 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 214.95





TARVOS 100 4000 K

- through-wiring possible
- very high color rendering
- BEG eligible
- emergency power supply capable
- incl. power supply unit and 230V direct connection

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Power	10.8 W
Colour Temperature	4000 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	1360 lm	Cut Out Ø	100 mm
Length	115 mm	CRI (Ra)	90
Width	115 mm	Accumulator/Battery	No
Height	68 mm	Operated	
Ø	115 mm	IK Protection Class	IK05

Article	Housing Color		Light Beam Angle	Dimmable	Control	Price
565553		Black		15 Degree	No	€ 159.95
565556		Light gray		15 Degree	No	€ 159.95
565559		White		15 Degree	No	€ 159.95
565562		Black		15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim € 214.95
565565		Light gray		15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim € 214.95
565568		White		15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim € 214.95
565554		Black		30 Degree	No	€ 159.95
565557		Light gray		30 Degree	No	€ 159.95
565560		White		30 Degree	No	€ 159.95
565563		Black		30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim € 214.95
565566		Light gray		30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim € 214.95
565569		White		30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim € 214.95
565555		Black		45 Degree	No	€ 159.95
565558		Light gray		45 Degree	No	€ 159.95
565561		White		45 Degree	No	€ 159.95
565564		Black		45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim € 214.95
565567		Light gray		45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim € 214.95
565570		White		45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim € 214.95





TARVOS 150 2700 K

- Through-wiring possible
- very high color rendering
- BEG eligible
- capable of emergency power supply
- incl. power supply unit and 230V direct connection

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Power	14.4 W
Colour Temperature	2700 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	1720 lm	Cut Out Ø	150 mm
Length	165 mm	CRI (Ra)	90
Width	165 mm	Accumulator/Battery	No
Height	106 mm	Operated	
Ø	165 mm	IK Protection Class	IK05

Article	Housing Color		Light Beam Angle	Dimmable	Control	Price
565571	Black	ww	15 Degree	No		€ 189.95
565574	Light gray	ww	15 Degree	No		€ 189.95
565577	White	ww	15 Degree	No		€ 189.95
565580	Black	ww	15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 244.95
565583	Light gray	ww	15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 244.95
565586	White	ww	15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 244.95
565572	Black	ww	30 Degree	No		€ 189.95
565575	Light gray	ww	30 Degree	No		€ 189.95
565578	White	ww	30 Degree	No		€ 189.95
565581	Black	ww	30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 244.95
565584	Light gray	ww	30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 244.95
565587	White	ww	30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 244.95
565573	Black	ww	45 Degree	No		€ 189.95
565576	Light gray	ww	45 Degree	No		€ 189.95
565579	White	ww	45 Degree	No		€ 189.95
565582	Black	ww	45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 244.95
565585	Light gray	ww	45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 244.95
565588	White	ww	45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 244.95





TARVOS 150 3000 K

- Through-wiring possible
- very high color rendering
- BEG eligible
- capable of emergency power supply
- incl. power supply unit and 230V direct connection

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Power	14.4 W
Colour Temperature	3000 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	1750 lm	Cut Out Ø	150 mm
Length	165 mm	CRI (Ra)	90
Width	165 mm	Accumulator/Battery	No
Height	106 mm	Operated	
Ø	165 mm	IK Protection Class	IK05

Article	Housing Color		Light Beam Angle	Dimmable	Control	Price
565589	 Black		15 Degree	No		€ 189.95
565592	 Light gray		15 Degree	No		€ 189.95
565595	 White		15 Degree	No		€ 189.95
565598	 Black		15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 244.95
565601	 Light gray		15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 244.95
565604	 White		15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 244.95
565590	 Black		30 Degree	No		€ 189.95
565593	 Light gray		30 Degree	No		€ 189.95
565596	 White		30 Degree	No		€ 189.95
565599	 Black		30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 244.95
565602	 Light gray		30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 244.95
565605	 White		30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 244.95
565591	 Black		45 Degree	No		€ 189.95
565594	 Light gray		45 Degree	No		€ 189.95
565597	 White		45 Degree	No		€ 189.95
565600	 Black		45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 244.95
565603	 Light gray		45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 244.95
565606	 White		45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 244.95





TARVOS 150 4000 K

- Through-wiring possible
- very high color rendering
- BEG eligible
- capable of emergency power supply
- incl. power supply unit and 230V direct connection

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Power	14.4 W
Colour Temperature	4000 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	1810 lm	Cut Out Ø	150 mm
Length	165 mm	CRI (Ra)	90
Width	165 mm	Accumulator/Battery	No
Height	106 mm	Operated	
Ø	165 mm	IK Protection Class	IK05

Article	Housing Color		Light Beam Angle	Dimmable	Control	Price
565607	Black	NW	15 Degree	No		€ 189.95
565610	Light gray	NW	15 Degree	No		€ 189.95
565613	White	NW	15 Degree	No		€ 189.95
565616	Black	NW	15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 244.95
565619	Light gray	NW	15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 244.95
565622	White	NW	15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 244.95
565608	Black	NW	30 Degree	No		€ 189.95
565611	Light gray	NW	30 Degree	No		€ 189.95
565614	White	NW	30 Degree	No		€ 189.95
565617	Black	NW	30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 244.95
565620	Light gray	NW	30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 244.95
565623	White	NW	30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 244.95
565609	Black	NW	45 Degree	No		€ 189.95
565612	Light gray	NW	45 Degree	No		€ 189.95
565615	White	NW	45 Degree	No		€ 189.95
565618	Black	NW	45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 244.95
565621	Light gray	NW	45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 244.95
565624	White	NW	45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 244.95





TARVOS 190 2700 K

- Through-wiring possible
- very high color rendering
- BEG eligible
- capable of emergency power supply
- incl. power supply unit and 230V direct connection

Application Area
 Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Power	21.6 W
Colour Temperature	2700 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	1590 lm	Cut Out Ø	190 mm
Length	205 mm	CRI (Ra)	90
Width	205 mm	Accumulator/Battery	No
Height	124 mm	Operated	
Ø	205 mm	IK Protection Class	IK05

Article	Housing Color		Light Beam Angle	Dimmable	Control	Price
565625		Black		15 Degree	No	€ 204.95
565628		Light gray		15 Degree	No	€ 204.95
565631		White		15 Degree	No	€ 204.95
565634		Black		15 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 259.95
565637		Light gray		15 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 259.95
565640		White		15 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 259.95
565626		Black		30 Degree	No	€ 204.95
565629		Light gray		30 Degree	No	€ 204.95
565632		White		30 Degree	No	€ 204.95
565635		Black		30 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 259.95
565638		Light gray		30 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 259.95
565641		White		30 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 259.95
565627		Black		45 Degree	No	€ 204.95
565630		Light gray		45 Degree	No	€ 204.95
565633		White		45 Degree	No	€ 204.95
565636		Black		45 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 259.95
565639		Light gray		45 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 259.95
565642		White		45 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 259.95





TARVOS 190 3000 K

- Through-wiring possible
- very high color rendering
- BEG eligible
- capable of emergency power supply
- incl. power supply unit and 230V direct connection

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Power	21.6 W
Colour Temperature	3000 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	2630 lm	Cut Out Ø	190 mm
Length	205 mm	CRI (Ra)	90
Width	205 mm	Accumulator/Battery	No
Height	124 mm	Operated	
Ø	205 mm	IK Protection Class	IK05

Article	Housing Color		Light Beam Angle	Dimmable	Control	Price
565643	 Black		15 Degree	No		€ 204.95
565646	 Light gray		15 Degree	No		€ 204.95
565649	 White		15 Degree	No		€ 204.95
565652	 Black		15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 259.95
565655	 Light gray		15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 259.95
565658	 White		15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 259.95
565644	 Black		30 Degree	No		€ 204.95
565647	 Light gray		30 Degree	No		€ 204.95
565650	 White		30 Degree	No		€ 204.95
565653	 Black		30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 259.95
565656	 Light gray		30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 259.95
565659	 White		30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 259.95
565645	 Black		45 Degree	No		€ 204.95
565648	 Light gray		45 Degree	No		€ 204.95
565651	 White		45 Degree	No		€ 204.95
565654	 Black		45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 259.95
565657	 Light gray		45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 259.95
565660	 White		45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 259.95





TARVOS 190 4000 K

- Through-wiring possible
- very high color rendering
- BEG eligible
- capable of emergency power supply
- incl. power supply unit and 230V direct connection

Application Area
 Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Power	21.6 W
Colour Temperature	4000 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	2720 lm	Cut Out Ø	190 mm
Length	205 mm	CRI (Ra)	90
Width	205 mm	Accumulator/Battery	No
Height	124 mm	Operated	
Ø	205 mm	IK Protection Class	IK05

Article	Housing Color		Light Beam Angle	Dimmable	Control	Price
565661		Black		15 Degree	No	€ 204.95
565664		Light gray		15 Degree	No	€ 204.95
565667		White		15 Degree	No	€ 204.95
565670		Black		15 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 259.95
565673		Light gray		15 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 259.95
565676		White		15 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 259.95
565662		Black		30 Degree	No	€ 204.95
565665		Light gray		30 Degree	No	€ 204.95
565668		White		30 Degree	No	€ 204.95
565671		Black		30 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 259.95
565674		Light gray		30 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 259.95
565677		White		30 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 259.95
565663		Black		45 Degree	No	€ 204.95
565666		Light gray		45 Degree	No	€ 204.95
565669		White		45 Degree	No	€ 204.95
565672		Black		45 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 259.95
565675		Light gray		45 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 259.95
565678		White		45 Degree	Yes DALI 2.0 / DT6 / Push-Dim	€ 259.95





TARVOS 240 2700 K

- Through-wiring possible
- very high color rendering
- BEG eligible
- capable of emergency power supply
- incl. power supply unit and 230V direct connection

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Colour Temperature	2700 K	Cut Out Ø	240 mm
Luminous Flux	3020 lm	CRI (Ra)	90
Length	255 mm	Accumulator/Battery	No
Width	255 mm	Operated	
Height	141 mm	IK Protection Class	IK05
Power	25.2 W		

Article	Housing Color		Light Beam Angle	Dimmable	Control	Price
565679	Black	WW	15 Degree	No		€ 239.95
565682	Light gray	WW	15 Degree	No		€ 239.95
565685	White	WW	15 Degree	No		€ 239.95
565688	Black	WW	15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 309.95
565691	Light gray	WW	15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 309.95
565694	White	WW	15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 309.95
565680	Black	WW	30 Degree	No		€ 239.95
565683	Light gray	WW	30 Degree	No		€ 239.95
565686	White	WW	30 Degree	No		€ 239.95
565689	Black	WW	30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 309.95
565692	Light gray	WW	30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 309.95
565695	White	WW	30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 309.95
565681	Black	WW	45 Degree	No		€ 239.95
565684	Light gray	WW	45 Degree	No		€ 239.95
565687	White	WW	45 Degree	No		€ 239.95
565690	Black	WW	45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 309.95
565693	Light gray	WW	45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 309.95
565696	White	WW	45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 309.95





TARVOS 240 3000 K

- Through-wiring possible
- very high color rendering
- BEG eligible
- capable of emergency power supply
- incl. power supply unit and 230V direct connection

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Colour Temperature	3000 K	Cut Out Ø	240 mm
Luminous Flux	3070 lm	CRI (Ra)	90
Length	255 mm	Accumulator/Battery Operated	No
Width	255 mm	IK Protection Class	IK05
Height	141 mm		
Power	25.2 W		

Article	Housing Color		Light Beam Angle	Dimmable	Control	Price
565697	 Black		15 Degree	No		€ 239.95
565700	 Light gray		15 Degree	No		€ 239.95
565703	 White		15 Degree	No		€ 239.95
565706	 Black		15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 309.95
565709	 Light gray		15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 309.95
565712	 White		15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 309.95
565698	 Black		30 Degree	No		€ 239.95
565701	 Light gray		30 Degree	No		€ 239.95
565704	 White		30 Degree	No		€ 239.95
565707	 Black		30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 309.95
565710	 Light gray		30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 309.95
565713	 White		30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 309.95
565699	 Black		45 Degree	No		€ 239.95
565702	 Light gray		45 Degree	No		€ 239.95
565705	 White		45 Degree	No		€ 239.95
565708	 Black		45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 309.95
565711	 Light gray		45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 309.95
565714	 White		45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 309.95





TARVOS 240 4000 K

- Through-wiring possible
- very high color rendering
- BEG eligible
- capable of emergency power supply
- incl. power supply unit and 230V direct connection

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Colour Temperature	4000 K	Cut Out Ø	240 mm
Luminous Flux	3170 lm	CRI (Ra)	90
Length	255 mm	Accumulator/Battery	No
Width	255 mm	Operated	
Height	141 mm	IK Protection Class	IK05
Power	25.2 W		

Article	Housing Color		Light Beam Angle	Dimmable	Control	Price
565715	Black		15 Degree	No		€ 239.95
565718	Light gray		15 Degree	No		€ 239.95
565721	White		15 Degree	No		€ 239.95
565724	Black		15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 309.95
565727	Light gray		15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 309.95
565730	White		15 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 309.95
565716	Black		30 Degree	No		€ 239.95
565719	Light gray		30 Degree	No		€ 239.95
565722	White		30 Degree	No		€ 239.95
565725	Black		30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 309.95
565728	Light gray		30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 309.95
565731	White		30 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 309.95
565717	Black		45 Degree	No		€ 239.95
565720	Light gray		45 Degree	No		€ 239.95
565723	White		45 Degree	No		€ 239.95
565726	Black		45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 309.95
565729	Light gray		45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 309.95
565732	White		45 Degree	Yes	DALI 2.0 / DT6 / Push-Dim	€ 309.95





SLIM

Matching recessed spotlights are available for our SLIM luminaire series. The die-cast aluminium luminaire body is always the same size [300 x 39 mm]. The SLIM recessed spotlights have the standard installation dimension of 68 mm. This makes the single-flame recessed spotlights particularly suitable for sales areas, reception areas or even hotels and restaurants.





SLIM

- Glare-free, due to low UGR value (<19)
- Slim design with only 39 mm diameter
- Incl. silver-coloured reflector ring
- Installation diameter 68 mm

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Installation Depth	25 mm
Colour Temperature	2700 K	Light Beam Angle	36 Degree
Luminous Flux	500 lm	Rotation Angle	300 Degree
Length	194 mm	Swivelling Angle	60 Degree
Ø	80 mm	Cut Out Ø	68 mm
Power	5 W	Control	Leading-edge dimmer, Trailing-edge dimmer
Rated Input Voltage	220-240 V/AC	CRI (Ra)	90
Power Supply Unit incl.	Yes		

Article	Housing Color		Price
565408	 White		€ 59.95
565409	 Black		€ 59.95



Accessories

930744	Reflector ring white for Slim series		€ 4.95
930745	Reflector ring black for Slim series		€ 4.95
930746	Reflector ring gold-coloured for Slim series		€ 5.95
930748	36° lens for Slim series		€ 4.95
930749	60° lens for Slim series		€ 4.95




UNI 2

- „Glow“ effect on reflector ring
- Can be rotated and swivelled
- Can be combined with a power supply unit as desired [excl.]

Application Area
 Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Light Beam Angle	36 Degree
Colour Temperature	3000 K	Swivelling Angle	85 Degree
Height	84 mm	Cut Out Ø	125 mm
Ø	139 mm	Control	Dimmable via optional power supply unit
Power	12 W	CRI (Ra)	90
Rated Input Voltage	33-34 V/DC	Rated Current	350 mA
Power Supply Unit incl.	No		
Installation Depth	90 mm		



565361

Article	Housing Color	Luminous Flux	Price
565343	White	760 lm	€ 119.95
565361	Black	1010 lm	€ 119.95



Accessories

930305	36° reflector for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 3.60
930306	48° reflector for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930334	Rear white cover for Uni II series		€ 3.55
930335	Rear black cover for Uni II series		€ 2.95
930336	White heat sink cover for Uni II series		€ 3.55
930337	Black heat sink cover for Uni II series		€ 7.95
930338	Reflector ring white for Uni II series		€ 11.95
930339	Reflector ring black for Uni II series		€ 10.95
930340	Reflector ring gold for Uni II series		€ 10.95
930341	Reflector ring chrome for Uni II series		€ 10.95
180512	BASIC, CC, CC35018/18 W		€ 23.95
862191	BASIC, DIM, Multi CC, IE-25D		€ 64.95
862204	BASIC, DIM, CC, D35020UF/20 W		€ 39.95
930969	Reducing ring round 210/135 mm, Traffic white		€ 13.95
931045	Reducing ring round 210/135 mm, Signal white		€ 13.95



page 74



page 420






UNI 2 MINI

- „Glow“ effect on reflector ring
- Can be rotated and swivelled
- Can be combined with a power supply unit as desired [excl.]

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Light Beam Angle	36 Degree
Colour Temperature	3000 K	Swivelling Angle	75 Degree
Height	80 mm	Cut Out Ø	95 mm
Ø	103 mm	Control	Dimmable via optional power supply unit
Power	9 W	CRI (Ra)	90
Rated Input Voltage	18-19 V/DC	Rated Current	500 mA
Power Supply Unit incl.	No		
Installation Depth	85 mm		



565342

Article	Housing Color	Luminous Flux	Price
565342	White www	765 lm	€ 99.95
565354	Black www	825 lm	€ 99.95



Accessories

930328	White heat sink cover for Uni II Mini series
930329	Black heat sink cover for Uni II Mini series
930330	Reflector ring white for Uni II Mini series
930331	Reflector ring black for Uni II Mini series
930332	Reflector ring gold for Uni II Mini series
930333	Reflector ring chrome for Uni II Mini series
930770	Reflector 24° for Uni II Mini series
930771	Reflector 48° for Uni II Mini series
180513	BASIC, CC, CC50018/18 W
862190	BASIC, DIM, Multi CC, IE-12D
862236	OCTO, DIM, CC, RSM-12-500T/12 W
930968	Reducing ring round 155/95 mm, Traffic white
931044	Reducing ring round 155/95 mm, Signal white

	€ 3.55
	€ 2.95
	€ 10.95
	€ 10.95
	€ 10.95
	€ 10.95
	€ 10.95
	€ 10.95
	€ 23.95
	€ 59.95
	€ 29.95
	€ 11.95
	€ 11.95




UNI 2 MAX

- „Glow“ effect on reflector ring
- Can be rotated and swivelled
- Can be combined with a power supply unit as desired [excl.]

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Light Beam Angle	36 Degree
Colour Temperature	3000 K	Swivelling Angle	85 Degree
Height	97 mm	Cut Out Ø	155 mm
Ø	165 mm	Control	Dimmable via optional power supply unit
Power	24 W	CRI (Ra)	90
Rated Input Voltage	34-35 V/DC	Rated Current	700 mA
Power Supply Unit incl.	No		
Installation Depth	100 mm		



565344

Article	Housing Color	Luminous Flux	Price
565351	Black	2260 lm	€ 149.95
565344	White	2380 lm	€ 149.95



Accessories

930390	24° reflector for Uni II Max	€ 10.95
930391	36° reflector for Uni II Max	€ 12.95
930392	48° reflector for Uni II Max	€ 10.95
930395	White heat sink cover for Uni II Max series	€ 10.95
930396	Black heat sink cover for Uni II Max series	€ 10.95
930397	Reflector ring white for Uni II Max series	€ 12.95
930398	Reflector ring black for Uni II Max series	€ 10.95
930399	Reflector ring gold for Uni II Max series	€ 14.95
862198	BASIC, CC, V8-30-700 mA/30 W	€ 26.95
862208	BASIC, DIM, CC, D70040NTF/40 W	€ 46.95
862192	BASIC, DIM, Multi CC, IE-45D	€ 69.95





CETI

The CETI recessed ceiling light with its LED light sources produces a glare-free, warm white light (3,000 K). The recessed reflectors of the luminaire make a major contribution to this. The interchangeable coloured reflector inserts in silver and gold offer additional design options. The CETI can be individually combined with a power supply unit and dimmed.






CETI

- Very low glare light
- Recessed reflectors
- Replaceable coloured reflector inserts
- Can be combined with a power supply unit as desired [excl.]

Application Area


Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Light Beam Angle	45 Degree
Colour Temperature	3000 K	Cut Out Width	36 mm
Width	52 mm	Control	Dimmable via optional power supply unit
Height	44 mm	CRI (Ra)	90
Power Supply Unit incl.	No	Rated Current	700 mA
Installation Depth	50 mm		



565250

Article	Housing Color	Luminous Flux	Length	Power	Rated Input Voltage	Cut Out Length	Price
565250	☐ White	800 lm	137 mm	10.5 W	14-15 V/DC	130 mm	€ 109.95
565251	☐ White	1600 lm	257 mm	20.2 W	28-29 V/DC	250 mm	€ 179.95
565252	☐ White	2400 lm	376 mm	30.8 W	44-45 V/DC	369 mm	€ 249.95



Accessories for 565250

930215	Ceti 5 reflector gold		€ 9.95
930218	Ceti 5 reflector silver		€ 9.95
862227	FLAT, CC, UT700 mA/12 W		€ 24.95
862237	OCTO, DIM, CC, RSM-12-700T/12 W		€ 29.95

Accessories for 565251

930216	Ceti 10 reflector gold		€ 10.95
930219	Ceti 10 reflector silver		€ 10.95
862191	BASIC, DIM, Multi CC, IE-25D		€ 64.95
862198	BASIC, CC, V8-30-700 mA/30 W		€ 26.95
862207	BASIC, DIM, CC, D70020UF/20 W		€ 39.95

Accessories for 565252

930217	Ceti 15 reflector gold		€ 14.95
930220	Ceti 15 reflector silver		€ 14.95
862192	BASIC, DIM, Multi CC, IE-45D		€ 69.95
862199	BASIC, CC, V8-40-700 mA/40 W		€ 29.95
862208	BASIC, DIM, CC, D70040NTF/40 W		€ 46.95

Downlights



  
page 156



 
page 157




page 158




page 160




page 161




page 162




page 163




page 164




page 166




page 170




page 172



 
page 174






ACRUX

- Integrated power supply unit
- Light colour adjustable in three stages
- Incl. removable ring in silver/black [model-dependent]
- White basic housing, can also be used without colour ring

Application Area
 Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Plastic	Light Beam Angle	90 Degree
Colour Temperature	3000/4000/6000 K	Control	Leading-edge dimmer, Trailing-edge dimmer
Rated Input Voltage	220-240 V/AC	CRI (Ra)	80
Power Supply Unit incl.	Yes		



565317

Article	Housing Color		Luminous Flux	Surface	Ø cut out	Inst. Depth	Height	Ø	Power	Price
565315	White, Silver		630 lm	Matt	68 mm	55 mm	57.5 mm	95 mm	7.0 W	€ 19.95
565362	White, Black		630 lm	Shiny	68 mm	55 mm	57.5 mm	95 mm	7.0 W	€ 19.95
565316	White, Silver		760 lm	Matt	90 mm	55 mm	58 mm	113 mm	8.0 W	€ 24.95
565363	White, Black		760 lm	Shiny	90 mm	55 mm	58 mm	113 mm	8.0 W	€ 24.95
565317	White, Silver		1370 lm	Matt	120 mm	63 mm	65.8 mm	145 mm	14.5 W	€ 29.95
565364	White, Black		1370 lm	Shiny	120 mm	63 mm	65.8 mm	145 mm	14.5 W	€ 29.95
565318	White, Silver		1570 lm	Matt	145 mm	63 mm	68.5 mm	174 mm	16.0 W	€ 34.95
565365	White, Black		1570 lm	Shiny	145 mm	63 mm	68.5 mm	174 mm	16.0 W	€ 34.95
565332	White, Silver		2670 lm	Matt	195 mm	82 mm	84 mm	244 mm	26.0 W	€ 49.95
565366	White, Black		2670 lm	Shiny	195 mm	82 mm	84 mm	244 mm	26.0 W	€ 49.95



Accessories for 565315, 565317, 565318, 565362, 565363, 565364

930967	Reducing ring round 130/70 mm, Traffic white		€ 9.95
931043	Reducing ring round 130/70 mm, Signal white		€ 9.95

Accessories for 565332

930971	Reducing ring round 280/210 mm, Traffic white		€ 23.95
931047	Reducing ring round 280/210 mm, Signal white		€ 23.95




ACRUX PRO CCT

- through-wiring possible
- Integrated power supply unit for 230V direct connection
- splash-proof [downwards when installed]
- light colour adjustable in three stages
- power adjustable in 3 stages (only Ø 120 / 145 / 190)
- BEG eligible

Housing	Aluminium, PA - Polyamide	Control	Trailing-edge dimmer, Leading-edge dimmer
Surface	Shiny	CRI (Ra)	90
Colour Temperature	2700/3000/4000 K	Accumulator/Battery Operated	No
Rated Input Voltage	220-240 V/AC	IK Protection Class	IK05
Light Beam Angle	100 Degree		

Article	Housing Color		Luminous Flux	Height	Ø	Power	Ø cut out	Inst. Depth	Price
565745	White		800/840/840 lm	50 mm	90 mm	7 W	68-75 mm	50 mm	€ 24.95
565746	Black		800/840/840 lm	50 mm	90 mm	7 W	68-75 mm	50 mm	€ 24.95
565747	White		1080/1130/1180 lm	55 mm	110 mm	9 W	82-95 mm	55 mm	€ 29.95
565748	Black		1080/1130/1180 lm	55 mm	110 mm	9 W	82-95 mm	55 mm	€ 29.95
565749	White		1800/1950/1880 lm	60 mm	145 mm	9/12/15 W	120-130 mm	60 mm	€ 34.95
565750	Black		1800/1950/1880 lm	60 mm	145 mm	9/12/15 W	120-130 mm	60 mm	€ 34.95
565751	White		2400/2600/2500 lm	72 mm	180 mm	12/16/20 W	145-155 mm	72 mm	€ 39.95
565752	Black		2400/2600/2500 lm	72 mm	180 mm	12/16/20 W	145-155 mm	72 mm	€ 39.95
565753	White		3600/3900/3750 lm	85 mm	230 mm	18/24/30 W	190-205 mm	85 mm	€ 54.95
565754	Black		3600/3900/3750 lm	85 mm	230 mm	18/24/30 W	190-205 mm	85 mm	€ 54.95



Accessories for **565745, 565746**

930967	Reducing ring round 130/70 mm, Traffic white		€ 9.95
931043	Reducing ring round 130/70 mm, Signal white		€ 9.95

Accessories for **565747, 565748**


930968	Reducing ring round 155/95 mm, Traffic white		€ 11.95
931044	Reducing ring round 155/95 mm, Signal white		€ 11.95

Accessories for **565749, 565750**

930969	Reducing ring round 210/135 mm, Traffic white		€ 13.95
931045	Reducing ring round 210/135 mm, Signal white		€ 13.95

Accessories for **565753, 565754**

930971	Reducing ring round 280/210 mm, Traffic white		€ 23.95
931047	Reducing ring round 280/210 mm, Signal white		€ 23.95



ANIK ROUND

The ANIK ROUND LED downlight is a high-quality lighting solution for a wide range of applications - for example in reception areas, offices, conference rooms, shops, sales areas, hotels, the catering trade and in bathrooms and WCs. It impresses with its uniform, wide light distribution with a beam angle of 120° and very high colour rendering ($R_a \geq 90$). Thanks to its IP44 downward protection rating when installed, it is also suitable for damp environments. The luminaire can be combined with external power supply units and is therefore dimmable. The ANIK ROUND series covers a wide power spectrum from 9 W to 30 W and is available in the colour temperatures 2700 K, 3000 K and 4000 K. With its flat design (19-22 mm high) and various diameters (144-398 mm), it is suitable for both new buildings and refurbishment projects.



ANIK ROUND

- splash-proof [downwards when installed]
- very low installation depth [max. 36mm]
- uniform and wide light distribution
- very high colour rendering

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, Bathroom / WC

Housing	Aluminium, Steel, PMMA - Polymethyl methacrylate	Light Beam Angle	120 Degree
		Control	Dimmable via optional power supply unit
Surface	Powder-coated, Fine structure, Matt	CRI (Ra)	90
Rated Input Voltage	32-37 V/DC	Accumulator/Battery Operated	No
Power Supply Unit incl.	No	IK Protection Class	IK05

Article	Housing Color	Colour Temp.	Luminous Flux	Ø cut out	Height	Ø	Rated Current	Power	Price
565410	White	2700 K	1070 lm	130 mm	19 mm	144 mm	260 mA	9.0 W	€ 33.95
565413	White	2700 K	1540 lm	165 mm	22 mm	173 mm	350 mA	12.0 W	€ 47.95
565416	White	2700 K	2050 lm	220 mm	20 mm	234 mm	500 mA	17.0 W	€ 68.95
565419	White	2700 K	4130 lm	380 mm	20 mm	398 mm	900 mA	30.0 W	€ 98.95
565411	White	3000 K	1100 lm	130 mm	19 mm	144 mm	260 mA	9.0 W	€ 33.95
565414	White	3000 K	1580 lm	165 mm	22 mm	173 mm	350 mA	12.0 W	€ 47.95
565417	White	3000 K	2080 lm	220 mm	20 mm	234 mm	500 mA	17.0 W	€ 68.95
565420	White	3000 K	4180 lm	380 mm	20 mm	398 mm	900 mA	30.0 W	€ 98.95
565412	White	4000 K	1150 lm	130 mm	19 mm	144 mm	260 mA	9.0 W	€ 33.95
565415	White	4000 K	1620 lm	165 mm	22 mm	173 mm	350 mA	12.0 W	€ 47.95
565418	White	4000 K	2130 lm	220 mm	20 mm	234 mm	500 mA	17.0 W	€ 68.95
565421	White	4000 K	4230 lm	380 mm	20 mm	398 mm	900 mA	30.0 W	€ 98.95



Accessories for **565410, 565411, 565412**

862285 BASIC, DIM, CC, D350012UF/12 W

€ 32.95

Accessories for **565410, 565411, 565412, 565413, 565414, 565415**

862190 BASIC, DIM, Multi CC, IE-12D

€ 59.95

Accessories for **565413, 565414, 565415**

180512 BASIC, CC, CC35018/18 W

€ 23.95

862203 BASIC, DIM, CC, D350012UF/12 W

€ 36.95

Accessories for **565416, 565417, 565418**

862191 BASIC, DIM, Multi CC, IE-25D

€ 64.95

862205 BASIC, DIM, CC, D50020UF/20 W

€ 39.95

862226 FLAT, CC, UT500 mA/20 W

€ 28.95

Accessories for **565419, 565420, 565421**

862157 BASIC, CC, V8-40-900/40 W

€ 29.95

862192 BASIC, DIM, Multi CC, IE-45D

€ 69.95



ANIK ROUND CCT

- splash-proof [downwards when installed]
- very low installation depth [max. 36mm]
- light colour adjustable from 2700-6500 K via opt. controller
- uniform and wide light distribution
- very high colour rendering
- individually combinable and dimmable with power supply

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, Bathroom / WC

Housing	Aluminium, Steel, PMMA - Polymethyl methacrylate	Light Beam Angle	120 Degree
Surface	Powder-coated, Fine structure, Matt	Control	Dimmable via optional controller
Colour Temperature	2700-6500 K	CRI (Ra)	90
Rated Input Voltage	24 V/DC	Accumulator/Battery Operated	No
Power Supply Unit incl.	No	IK Protection Class	IK05

Article	Housing Color	Luminous Flux	Height	Ø	Power	Ø cut out	Installation Depth	Price
565422	☐ White	850 lm	19 mm	144 mm	9.0 W	130 mm	16.5 mm	€ 45.95
565423	☐ White	1310 lm	22 mm	173 mm	12.0 W	165 mm	19.5 mm	€ 58.95
565424	☐ White	1850 lm	20 mm	234 mm	17.0 W	220 mm	17.5 mm	€ 79.95
565425	☐ White	3220 lm	20 mm	398 mm	30.0 W	380 mm	17 mm	€ 109.95



Accessories

843501	RF-smart, starter set LED single/CCT, 12-48 V, 20 A incl. remote control		€ 99.95
862165	BASIC, CV, Q8H-12-100 W		€ 96.95
843341	DALI 2 PWM dimmer CV 2CH 12-48V, 8A/CH, DT6		€ 84.95
843342	DALI 2 PWM dimmer CV 2CH 12-48V, 8A/CH, DT8		€ 84.95
843037	Casambi BT Dimmer CBU-PWM4 (CV, 12-24V, 6A DC)		€ 179.95
843279	MULTI-LED dimmer 1-4 channels, DMX/auto/manual, 12-48 V, 20 A, flicker-free		€ 114.95

Accessories for 565422

930967	Reducing ring round 130/70 mm, Traffic white		€ 9.95
931043	Reducing ring round 130/70 mm, Signal white		€ 9.95

Accessories for 565422, 565423

862234	FLAT, CV, UT 24 V/20 W		€ 25.95
--------	------------------------	--	---------

Accessories for 565424

862163	BASIC, CV, Q8H-24-40 W		€ 46.95
--------	------------------------	--	---------

Accessories for 565425

862122	FLAT, CV, UT 24 V/50 W		€ 52.95
--------	------------------------	--	---------



ANIK ROUND RGBW

- splash-proof [downwards when installed]
- very low installation depth [max. 36mm]
- suitable for 24V colour control
- uniform and wide light distribution
- very high colour rendering
- individually combinable and dimmable with power supply unit

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, Bathroom / WC

Housing	Aluminium, Steel, PMMA - Polymethyl methacrylate	Light Beam Angle	120 Degree
Surface	Powder-coated, Fine structure, Matt	Control	Dimmable via optional controller
Colour Temperature	3000 K	CRI (Ra)	90
Rated Input Voltage	24 V/DC	Accumulator/Battery Operated	No
Power Supply Unit incl.	No	IK Protection Class	IK05

Article	Housing Color		Luminous Flux	Height	Ø	Power	Ø cut out	Installation Depth	Price
565426	☐ White		735 lm	19 mm	144 mm	9.0 W	130 mm	16.5 mm	€ 54.95
565427	☐ White		1110 lm	22 mm	173 mm	12.0 W	165 mm	19.5 mm	€ 68.95
565428	☐ White		1190 lm	20 mm	234 mm	17.0 W	220 mm	17.5 mm	€ 89.95
565429	☐ White		2420 lm	20 mm	398 mm	30.0 W	380 mm	17 mm	€ 119.95



Accessories

843502	RF-smart, starter set RGB/W/CCT, 12-48 V, 20 A incl. remote, IP20		€ 99.95
862165	BASIC, CV, Q8H-12-100 W		€ 96.95
843343	DALI 2 PWM dimmer CV 4CH 12-48V, 4A/CH, DT6		€ 94.95
843344	DALI 2 PWM dimmer CV 4CH 12-48V, 4A/CH, DT8		€ 94.95
843037	Casambi BT Dimmer CBU-PWM4 (CV, 12-24V, 6A DC)		€ 179.95
843279	MULTI-LED dimmer 1-4 channels, DMX/auto/manual, 12-48 V, 20 A, flicker-free		€ 114.95

Accessories for 565426

930967	Reducing ring round 130/70 mm, Traffic white		€ 9.95
931043	Reducing ring round 130/70 mm, Signal white		€ 9.95

Accessories for 565426, 565427

862234	FLAT, CV, UT 24 V/20 W		€ 25.95
---------------	------------------------	--	----------------

Accessories for 565428

862163	BASIC, CV, Q8H-24-40 W		€ 46.95
---------------	------------------------	--	----------------

Accessories for 565429

862122	FLAT, CV, UT 24 V/50 W		€ 52.95
---------------	------------------------	--	----------------



ANIK SQUARE

- splash-proof [downwards when installed]
- very low installation depth [max. 36mm]
- uniform and wide light distribution
- very high colour rendering

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, Bathroom / WC

Housing	Aluminium, Steel, PMMA - Polymethyl methacrylate	Light Beam Angle	120 Degree
Surface	Powder-coated, Fine structure, Matt	Control	Dimmable via optional power supply unit
Rated Input Voltage	32-37 V/DC	CRI (Ra)	90
Power Supply Unit incl.	No	Accumulator/Battery Operated	No
		IK Protection Class	IK05

Article	Housing Color	Colour Temp.	Lum. Flux	Rated Current	Power	L x W x H	L x W cut out	Price
565430	White	2700 K	1020 lm	260 mA	9,0 W	110x110x21 mm	90x90 mm	€ 33.95
565433	White	2700 K	2060 lm	500 mA	17,0 W	180x180x21 mm	155x155 mm	€ 47.95
565436	White	2700 K	2860 lm	700 mA	24,0 W	237x237x21 mm	215x215 mm	€ 68.95
565439	White	2700 K	3850 lm	900 mA	30,0 W	398x398x20 mm	380x380 mm	€ 98.95
565431	White	3000 K	1050 lm	260 mA	9,0 W	110x110x21 mm	90x90 mm	€ 33.95
565434	White	3000 K	2100 lm	500 mA	17,0 W	180x180x21 mm	155x155 mm	€ 47.95
565437	White	3000 K	2910 lm	700 mA	24,0 W	237x237x21 mm	215x215 mm	€ 68.95
565440	White	3000 K	3900 lm	900 mA	30,0 W	398x398x20 mm	380x380 mm	€ 98.95
565432	White	4000 K	1100 lm	260 mA	9,0 W	110x110x21 mm	90x90 mm	€ 33.95
565435	White	4000 K	2150 lm	500 mA	17,0 W	180x180x21 mm	155x155 mm	€ 47.95
565438	White	4000 K	2950 lm	700 mA	24,0 W	237x237x21 mm	215x215 mm	€ 68.95
565441	White	4000 K	4170 lm	900 mA	30,0 W	398x398x20 mm	380x380 mm	€ 98.95



Accessories for 565430, 565431, 565432

- 862190 BASIC, DIM, Multi CC, IE-12D
- 862285 BASIC, DIM, CC, D350012UF/12 W



Accessories for 565433, 565434, 565435

- 862205 BASIC, DIM, CC, D50020UF/20 W
- 862226 FLAT, CC, UT500 mA/20 W



Accessories for 565433, 565434, 565435, 565436, 565437, 565438

- 862191 BASIC, DIM, Multi CC, IE-25D



Accessories for 565436, 565437, 565438

- 862198 BASIC, CC, V8-30-700 mA/30 W
- 862208 BASIC, DIM, CC, D70040NTF/40 W



Accessories for 565439, 565440, 565441

- 862157 BASIC, CC, V8-40-900/40 W
- 862192 BASIC, DIM, Multi CC, IE-45D





ANIK SQUARE CCT

- splash-proof [downwards when installed]
- very low installation depth [max. 36mm]
- light colour adjustable from 2700-6500 K via opt. controller
- uniform and wide light distribution
- very high colour rendering
- individually combinable and dimmable with power supply

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, Bathroom / WC

Housing	Aluminium, Steel, PMMA - Polymethyl methacrylate	Light Beam Angle	120 Degree
Surface	Powder-coated, Fine structure, Matt	Control	Dimmable via optional controller
Colour Temperature	2700-6500 K	CRI (Ra)	90
Rated Input Voltage	24 V/DC	Accumulator/Battery Operated	No
Power Supply Unit incl.	No	IK Protection Class	IK05

Article	Housing Color		Luminous Flux	L x W x H	L x W cut out	Power	Price
565442	White		860 lm	110x110x21 mm	90x90 mm	9.0 W	€ 45.95
565443	White		1860 lm	180x180x21 mm	155x155 mm	17.0 W	€ 58.95
565444	White		2620 lm	237x237x21 mm	215x215 mm	24.0 W	€ 79.95
565445	White		3290 lm	398x398x20 mm	380x380 mm	30.0 W	€ 109.95



Accessories

843501	RF-smart, starter set LED single/CCT, 12-48 V, 20 A incl. remote control		€ 99.95
862165	BASIC, CV, Q8H-12-100 W		€ 96.95
843341	DALI 2 PWM dimmer CV 2CH 12-48V, 8A/CH, DT6		€ 84.95
843342	DALI 2 PWM dimmer CV 2CH 12-48V, 8A/CH, DT8		€ 84.95
843037	Casambi BT Dimmer CBU-PWM4 (CV, 12-24V, 6A DC)		€ 179.95
843279	MULTI-LED dimmer 1-4 channels, DMX/auto/manual, 12-48 V, 20 A, flicker-free		€ 114.95

Accessories for 565442

862234	FLAT, CV, UT 24 V/20 W		€ 25.95
930967	Reducing ring round 130/70 mm, Traffic white		€ 9.95
931043	Reducing ring round 130/70 mm, Signal white		€ 9.95

Accessories for 565443, 565444

862163	BASIC, CV, Q8H-24-40 W		€ 46.95
--------	------------------------	--	---------

Accessories for 565445

862122	FLAT, CV, UT 24 V/50 W		€ 52.95
--------	------------------------	--	---------



ANIK SQUARE RGBW

- splash-proof [downwards when installed]
- suitable for 24V colour control
- uniform and wide light distribution
- very high colour rendering
- can be individually combined and dimmed with power supply unit

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, Bathroom / WC

Housing	Aluminium, Steel, PMMA - Polymethyl methacrylate	Light Beam Angle	120 Degree
Surface	Powder-coated, Fine structure, Matt	Control	Dimmable via optional controller
Colour Temperature	3000 K	CRI (Ra)	90
Rated Input Voltage	24 V/DC	Accumulator/Battery Operated	No
Power Supply Unit incl.	No	IK Protection Class	IK05

Article	Housing Color		Luminous Flux	L x W x H	L x W cut out	Power	Price
565446	☐ White		780 lm	110x110x21 mm	90x90 mm	9.0 W	€ 54.95
565447	☐ White		1230 lm	180x180x21 mm	155x155 mm	17.0 W	€ 68.95
565448	☐ White		1890 lm	237x237x21 mm	215x215 mm	24.0 W	€ 89.95
565449	☐ White		2500 lm	398x398x20 mm	380x380 mm	30.0 W	€ 119.95



Accessories

843502	RF-smart, starter set RGB/W/CCT, 12-48 V, 20 A incl. remote, IP20		€ 99.95
862165	BASIC, CV, Q8H-12-100 W		€ 96.95
843343	DALI 2 PWM dimmer CV 4CH 12-48V, 4A/CH, DT6		€ 94.95
843344	DALI 2 PWM dimmer CV 4CH 12-48V, 4A/CH, DT8		€ 94.95
843037	Casambi BT Dimmer CBU-PWM4 (CV, 12-24V, 6A DC)		€ 179.95
843279	MULTI-LED dimmer 1-4 channels, DMX/auto/manual, 12-48 V, 20 A, flicker-free		€ 114.95

Accessories for 565446

862234	FLAT, CV, UT 24 V/20 W		€ 25.95
930967	Reducing ring round 130/70 mm, Traffic white		€ 9.95
931043	Reducing ring round 130/70 mm, Signal white		€ 9.95

Accessories for 565447, 565448

862163	BASIC, CV, Q8H-24-40 W		€ 46.95
--------	------------------------	--	---------

Accessories for 565449

862122	FLAT, CV, UT 24 V/50 W		€ 52.95
--------	------------------------	--	---------



REDUCING RINGS FOR RECESSED LIGHTS

- Renovation solution for excessively large ceiling cut-outs
- Flexible adaptation to ceiling cut-outs
- suitable for 3-30 mm thick hollow ceilings
- toolless installation possible

Housing		Metal		Height		1.5 mm	
Article	Housing Color	Length	Width	Ø	Cut Out Ø	Inner diameter	Price
930967	☐ White			130 mm	95 mm	70 mm	€ 9.95
931043	☐ White			130 mm	95 mm	70 mm	€ 9.95
930968	☐ White			155 mm	120 mm	95 mm	€ 11.95
931044	☐ White			155 mm	120 mm	95 mm	€ 11.95
930969	☐ White			210 mm	175 mm	135 mm	€ 13.95
931045	☐ White			210 mm	175 mm	135 mm	€ 13.95
930970	☐ White			240 mm	205 mm	180 mm	€ 17.95
931046	☐ White			240 mm	205 mm	180 mm	€ 17.95
930971	☐ White			280 mm	245 mm	210 mm	€ 23.95
931047	☐ White			280 mm	245 mm	210 mm	€ 23.95
930972	☐ White	130 mm	130 mm		95 mm	70 mm	€ 9.95
931048	☐ White	130 mm	130 mm		95 mm	70 mm	€ 9.95
930973	☐ White	155 mm	155 mm		120 mm	95 mm	€ 11.95
931049	☐ White	155 mm	155 mm		120 mm	95 mm	€ 11.95
930974	☐ White	210 mm	210 mm		175 mm	135 mm	€ 13.95
931050	☐ White	210 mm	210 mm		175 mm	135 mm	€ 13.95
930975	☐ White	240 mm	240 mm		205 mm	180 mm	€ 17.95
931051	☐ White	240 mm	240 mm		205 mm	180 mm	€ 17.95
930976	☐ White	280 mm	280 mm		245 mm	210 mm	€ 23.95
931052	☐ White	280 mm	280 mm		245 mm	210 mm	€ 23.95



COB 95 MAX

- Connector on lamp housing
- Incl. two diffusing lenses [transparent, satin-finished]

Application Area
 Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Installation Depth	53 mm
Luminous Flux	1100 lm	Light Beam Angle	60 Degree
Height	53 mm	Cut Out Ø	95 mm
Ø	110 mm	Control	Dimmable via optional power supply unit
Power	13 W	CRI (Ra)	90
Rated Input Voltage	34.8 V/DC	Rated Current	350 mA
Power Supply Unit incl.	No		

Article	Housing Color	Colour Temperature	EEI	Price
565007	☐ White	 3000 K	 F	€ 94.95
565010	☐ White	 4000 K	 G	€ 94.95



Accessories

180512	BASIC, CC, CC35018/18 W		€ 23.95
862204	BASIC, DIM, CC, D35020UF/20 W		€ 39.95
862191	BASIC, DIM, Multi CC, IE-25D		€ 64.95
930968	Reducing ring round 155/95 mm, Traffic white		€ 11.95
931044	Reducing ring round 155/95 mm, Signal white		€ 11.95



Lighting design
 Interested in our lighting design service?
 Your contact person will be happy to answer any questions you may have.



COB 130 MAX

·Connector on lamp housing

·Incl. two diffusing lenses [transparent/satin-finished]

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Light Beam Angle	60 Degree
Height	69 mm	Cut Out Ø	130 mm
Ø	145 mm	Control	Dimmable via optional power supply unit
Power	18.5 W	CRI (Ra)	90
Rated Input Voltage	34.8 V/DC	Rated Current	500 mA
Power Supply Unit incl.	No		
Installation Depth	69 mm		

Article	Housing Color	Colour Temperature	Luminous Flux	Price
565180	☐ White	3000 K	1360 lm	€ 124.95
565181	☐ White	4000 K	1451 lm	€ 124.95



Accessories

862226	FLAT, CC, UT500 mA/20 W		€ 28.95
862205	BASIC, DIM, CC, D50020UF/20 W		€ 39.95
862191	BASIC, DIM, Multi CC, IE-25D		€ 64.95
930969	Reducing ring round 210/135 mm, Traffic white		€ 13.95
931045	Reducing ring round 210/135 mm, Signal white		€ 13.95



Technical data sheet

New in the onlineshop: The technical data sheets offer even more information: Light and energy data, light distribution curves, dimensional drawings and more.




COB 170 MAX

- Connector on lamp housing
- Incl. two diffusing lenses [transparent, satin-finished]

Application Area
 Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Light Beam Angle	60 Degree
Luminous Flux	2100 lm	Cut Out Ø	170 mm
Height	86 mm	Control	Dimmable via optional power supply unit
Ø	190 mm	CRI (Ra)	90
Rated Input Voltage	35 V/DC	Rated Current	700 mA
Power Supply Unit incl.	No		
Installation Depth	86 mm		

Article	Housing Color	Colour Temperature	Power	Price
565182	☐ White	 3000 K	25.0 W	€ 145.95
565183	☐ White	 4000 K	25.6 W	€ 145.95



Accessories

862198	BASIC, CC, V8-30-700 mA/30 W		€ 26.95
862208	BASIC, DIM, CC, D70040NTF/40 W		€ 46.95
862192	BASIC, DIM, Multi CC, IE-45D		€ 69.95
930970	Reducing ring round 240/180 mm, Traffic white		€ 17.95
931046	Reducing ring round 240/180 mm, Signal white		€ 17.95



5-year guarantee
 Benefit from the maximum quality promise:
 All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.



COB 210 MAX

·Connector on lamp housing


·Incl. two diffusing lenses [transparent, satin-finished]

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Light Beam Angle	60 Degree
Height	99 mm	Cut Out Ø	210 mm
Ø	230 mm	Control	Dimmable via optional power supply unit
Power	37 W	CRI (Ra)	90
Rated Input Voltage	35 V/DC	Rated Current	1050 mA
Power Supply Unit incl.	No		
Installation Depth	99 mm		

Article	Housing Color	Colour Temperature	Luminous Flux	Price
565184	☐ White	3000 K	3000 lm	€ 184.95
565185	☐ White	4000 K	3200 lm	€ 184.95



Accessories

862201	BASIC, CC, V8-40-1,050 mA/40 V		€ 29.95
862209	BASIC, DIM, CC, D105040NTF/40 W		€ 46.95
862193	BASIC, DIM, Multi CC, IE-45HD		€ 69.95
930971	Reducing ring round 280/210 mm, Traffic white		€ 23.95
931047	Reducing ring round 280/210 mm, Signal white		€ 23.95



Onlineshop

You can find more information about the products in the onlineshop:
Detailed images, videos, project reports, LDT files, EPREL data sheets and more.



MODULAR SYSTEM COB 31 W

The MODULAR recessed ceiling light range offers a wide range of possible applications. Whether virtually invisible or with a prominent frame - these modules are as flexible as you want them to be. By replacing the reflectors, different light beams can be created and by using filters / diffusers, you can individually select or retrofit your lighting mood. We offer the LED modules in warm and neutral white. This gives you the option of adapting the individual elements to local requirements in order to create your perfect lighting situation.






MODULAR SYSTEM COB 31 W

· Lamp can be customised with comprehensive accessories

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Power Supply Unit incl.	No
Height	103 mm	Light Beam Angle	60 Degree
Ø	85 mm	CRI (Ra)	90
Power	31 W	Rated Current	900 mA
Rated Input Voltage	35-36 V/DC		



565352

Article	Housing Color	Colour Temperature	Luminous Flux	Price
565352	Grey	3000 K	3270 lm	€ 124.95
565353	Grey	4000 K	3350 lm	€ 124.95



Accessories


930084	17° reflector for modular system COB		€ 19.95
930085	40° reflector for modular system COB		€ 19.95
930087	Frosted glass diffuser for modular system COB		€ 1.25
930088	Honeycomb filter for modular system COB		€ 5.95
930089	built-in ring fixed, Ø 170 mm, cut-out Ø 150 mm		€ 22.95
930090	built-in ring fixed, Ø 230 mm, cut-out Ø 220 mm		€ 29.95
930091	built-in ring fixed, Ø 130 mm, cut-out Ø 115 mm		€ 32.95
930092	Cardan frame 1-fold transversable, cut-out size: 130 x 130 mm		€ 36.95
930093	Cardan frame 2-fold transversable, cut-out size: 240 x 130 mm		€ 66.95
930094	Cardan frame 1-fold without frame white, cut-out size: 120 x 120 mm		€ 89.95
930095	Cardan frame 1-fold without frame black, cut-out size: 120 x 120 mm		€ 89.95
930096	Cardan frame 2-fold without frame weiß, cut-out size: 247 x 120 mm		€ 115.95
930097	Cardan frame 2-fold without frame black, cut-out size: 247 x 120 mm		€ 115.95
862157	BASIC, CC, V8-40-900/40 W		€ 29.95
862264	BASIC, DIM, CC, D090040NTF/40 W		€ 46.95
862192	BASIC, DIM, Multi CC, IE-45D		€ 69.95



ZAURAK

Recessed ceiling lights can be subtly integrated into private and commercial spaces, yet when it comes to replacing, the existing ceiling cut-out can present a problem. The ZAURAK series comes with an adjustable mounting clip, which can be used with larger and smaller ceiling cut-outs. In addition, the ZAURAK has a low installation depth for universal use. Two exchangeable cover rings in silver and black are included in the scope of delivery.






ZAURAK

- Light colour adjustable in three stages
- Output adjustable in two stages
- Adjustable recess dimension 65-270 mm [model-dependent]
- Ideal renovation solution for ceiling recesses
- Incl. two colour rings [black/silver]

Application Area


Bathroom / WC, Corridor / stairwell, Home / Living, Refurbishment

Housing	Plastic	Light Beam Angle	110 Degree
Colour Temperature	3000/4000/5700 K	CRI (Ra)	80
Rated Input Voltage	220-240 V/AC	IK Protection Class	IK03
Power Supply Unit incl.	Yes		



565327

Article	Housing Color		Luminous Flux	Height	Ø	Power Selectable	Cut Out Ø	Price
565327	☐ White	WW NW CW	1060 lm	20.5 mm	180 mm	8.0 W / 12.0 W	65-160 mm	€ 46.95
565328	☐ White	WW NW CW	1750 lm	21.5 mm	220 mm	12.0 W / 18.0 W	120-200 mm	€ 56.95
565329	☐ White	WW NW CW	2420 lm	25 mm	300 mm	18.0 W / 25.0 W	150-270 mm	€ 79.95



Lighting design

Interested in our lighting design service?

Your contact person will be happy to answer any questions you may have.



PUNTO LUMI

The PUNTO LUMI is a sophisticated LED recessed ceiling light with warm white light (3,000 K) that is also ideal for integration in furniture due to its small installation diameter (18 mm). The PUNTO LUMI is also protected against splash water with its IP44 certification and is therefore suitable for use in wet areas such as bathrooms. The recessed light is available in a white and silver-coloured housing design.






PUNTO LUMI

- Suitable for wet areas
- Sophisticated light for furniture/ceiling installation
- Small installation diameter

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, Bathroom / WC

Housing	Aluminium	Power Supply Unit incl.	No
Colour Temperature	3000 K	Installation Depth	30 mm
Luminous Flux	40 lm	Light Beam Angle	50 Degree
Height	25 mm	Cut Out Ø	18 mm
Ø	30 mm	CRI (Ra)	80
Power	1 W	Rated Current	350 mA
Rated Input Voltage	3.1-3.9 V/DC		



565172

Article	Housing Color	Surface	Price
565172	☐ White	WW	€ 18.95
565173	☐ Silver	WW Shiny	€ 18.95



Accessories

872628 FLAT, CC, UT350 mA/6 W



€ 17.95



5-year guarantee


Benefit from the maximum quality promise:

All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.


insert panels




☐
page 178



☐
page 182



☐
page 183




☐
page 184




☐
page 185



☐
page 188




☐
page 189



☐
page 190




☐
page 192



☐
page 193



☐
page 194



☐
page 195








LED PANEL SMALL

- Can be installed in surface-mount or flush-mount frames
- For insertion into grid ceilings
- Can be combined with a power supply unit as desired [excl.]

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Power Supply Unit incl.	No
Surface	Matt	Light Beam Angle	120 Degree
Length	295 mm	Control	Dimmable via optional power supply unit
Width	295 mm	CRI (Ra)	80
Height	10 mm	Rated Current	700 mA
Power	25 W		
Rated Input Voltage	36-42 V/DC		



565220

Article	Housing Color	Colour Temperature	Luminous Flux	EEL	Price
565220	☐ White	☒ WW 3000 K	2810 lm	☒ F	€ 78.95
565221	☐ White	☒ NW 4000 K	3070 lm	☒ E	€ 78.95



Accessories

930167	Surface-mounted frame 300x300 for standard panels		€ 29.95
930230	Recessed frame for gypsum 30x30		€ 29.95
862198	BASIC, CC, V8-30-700 mA/30 W		€ 26.95
862208	BASIC, DIM, CC, D70040NTF/40 W		€ 46.95
862192	BASIC, DIM, Multi CC, IE-45D		€ 69.95



Lighting design
Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.

BACKLIGHT PANELS [SERIES: BASIC AND PRO] – TECHNOLOGY AND ADVANTAGES

Not every LED panel is built the same! There are technologies exist to produce homogeneous, flat and glare-free light. Each method has its own advantages and disadvantages and depends on the individual user requirements and budget needs. For example, the LED panels from our BASIC and PRO series rely on backlight technology.

In LED panels with backlight technology, the LEDs - behind the diffuser - are evenly spread over the entire panel surface and shine directly downwards. This design has a decisive advantage: no other components are required to direct the light in the desired direction [downwards], because the LEDs are already in the »right« position. The simpler design results above all in better efficiency and a lower price as well as a longer lifetime. At the same time you do not have to worry about possible yellowing of the light guide plate, which is often used in some cheaper sidelight panels.

The disadvantages: Due to their design, the LED elements require more space, which is why backlight panels are curved towards the backside and therefore have a higher thickness with it. For this [optical] reason, backlight panels are only suitable to a limited extent for suspension from the ceiling. Their smaller beam angle [approx. 90°] results in a smaller illuminated area.

advantages

- better efficiency
- longer lifetime
- lower costs
- much more attractive price/performance ratio

• no light guide plates that are prone to yellowing
disadvantages

- higher thickness
- lower beam angle [approx. 90°]
- less suitable for suspension
- thicker packaging

In the following picture you can see the typical structure of a backlight LED panel.






BASIC

- BEG-eligible
- cost-effective, ready-to-connect solution
- for insertion into grid ceilings
- Mounting in surface-mounted and recessed frames possible
- Refurbishment solution for T5/T8 louvre luminaires
- Incl. power supply unit CC, 900mAh, 33-38V, 36W

Application Area


Reception / Communication, Corridor / stairwell, Shop / Retail / Sales area, Health / care / hospital / practice, Education / school / lecture theatre, Refurbishment

Housing	Aluminium	Light Beam Angle	120 Degree
Height	32 mm	CRI (Ra)	80
Rated Input Voltage	220-240 V/AC	IK Protection Class	IK03
Power Supply Unit incl.	Yes	UGR	22



100140

Article	Housing Color	Colour Temperature	Luminous Flux	Length	Width	Power	Price
100143	☐ White	3000 K	3900 lm	295 mm	1195 mm	30.5 W	€ 79.95
100149	☐ White	3000 K	3900 lm	595 mm	595 mm	30.5 W	€ 69.95
100140	☐ White	3000 K	3900 lm	620 mm	620 mm	30.5 W	€ 74.95
100144	☐ White	4000 K	4320 lm	295 mm	1195 mm	30.5 W	€ 79.95
100150	☐ White	4000 K	4320 lm	595 mm	595 mm	30.5 W	€ 69.95
100141	☐ White	4000 K	4320 lm	620 mm	620 mm	33.0 W	€ 74.95



Accessories

930674	Safety cable		€ 4.95
930676	Mounting brackets for 600x600/300x1,200 mm backlit panel		€ 4.95
862192	BASIC, DIM, Multi CC, IE-45D		€ 69.95

Accessories for 100140, 100141


930665	Surface-mounted frame for 620x620 mm panel		€ 59.95
930668	Recessed frame for 620x620 mm panel		€ 57.95

Accessories for 100143, 100144

930666	Surface-mounted frame for 300x1,200 mm panel		€ 69.95
930669	Recessed frame for 300x1,200 mm panel		€ 67.95

Accessories for 100149, 100150

930664	Surface-mounted frame for 595x595 mm panel		€ 54.95
930667	Recessed frame for 595x595 mm panel		€ 52.95




BASIC FLEX

- Eligible for BEG German federal funding for energy-efficient buildings
- Light colour adjustable in three stages
- For insertion into grid ceilings
- Can be installed in surface-mount or flush-mount frames
- Renovation solution for T5/T8 louver lights
- Incl. CC power supply, 900 mAh, 33-38 V, 36 W

Application Area


Reception / Communication, Corridor / stairwell, Shop / Retail / Sales area, Health / care / hospital / practice, Education / school / lecture theatre, Refurbishment

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000/4000/6000 K	Light Beam Angle	120 Degree
Luminous Flux	3900/4320/4140 lm	CRI (Ra)	80
Height	32 mm	IK Protection Class	IK03
Power	30.5 W	UGR	22
Rated Input Voltage	220-240 V/AC		



100142

Article	Housing Color		Length	Width	Price
100145	☐ White	☒ WW ☒ NW ☒ CW	295 mm	1195 mm	€ 99.95
100142	☐ White	☒ WW ☒ NW ☒ CW	620 mm	620 mm	€ 94.95



Accessories


930674	Safety cable		€ 4.95
930676	Mounting brackets for 600x600/300x1,200 mm backlit panel		€ 4.95
862264	BASIC, DIM, CC, D090040NTF/40 W		€ 46.95
862192	BASIC, DIM, Multi CC, IE-45D		€ 69.95

Accessories for 100142

930665	Surface-mounted frame for 620x620 mm panel		€ 59.95
930668	Recessed frame for 620x620 mm panel		€ 57.95

Accessories for 100145

930666	Surface-mounted frame for 300x1,200 mm panel		€ 69.95
930669	Recessed frame for 300x1,200 mm panel		€ 67.95




BASIC OFFICE

- For insertion into grid ceilings
- Can be installed in surface-mount or flush-mount frames
- Suitable for workplaces with screens in accordance with EN 12464-1 BAP65
- Microprismatic surface structure
- Suitable for office spaces, reception rooms and hallways
- Good value, ready-to-install solution
- Incl. CC power supply, 900 mAh, 33-38 V, 36 W


Application Area
Office / conference, Reception / Communication, Corridor / stairwell, Shop / Retail / Sales area, Health / care / hospital / practice, Education / school / lecture theatre, Refurbishment

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	4000 K	Light Beam Angle	90 Degree
Luminous Flux	4000 lm	CRI (Ra)	80
Height	32 mm	IK Protection Class	IK03
Power	30.5 W	UGR	19
Rated Input Voltage	220-240 V/AC		



100146

Article	Housing Color	Length	Width	Price
100147	White	295 mm	1195 mm	€ 89.95
100151	White	595 mm	595 mm	€ 79.95
100146	White	620 mm	620 mm	€ 84.95



Accessories

930674	Safety cable		€ 4.95
930676	Mounting brackets for 600x600/300x1,200 mm backlit panel		€ 4.95
862264	BASIC, DIM, CC, D090040NTF/40 W		€ 46.95
862192	BASIC, DIM, Multi CC, IE-45D		€ 69.95

Accessories for 100146

930665	Surface-mounted frame for 620x620 mm panel		€ 59.95
930668	Recessed frame for 620x620 mm panel		€ 57.95

Accessories for 100147

930666	Surface-mounted frame for 300x1,200 mm panel		€ 69.95
930669	Recessed frame for 300x1,200 mm panel		€ 67.95

Accessories for 100151

930664	Surface-mounted frame for 595x595 mm panel		€ 54.95
930667	Recessed frame for 595x595 mm panel		€ 52.95




PRO OFFICE

- Eligible for BEG German federal funding for energy-efficient buildings
- For insertion into grid ceilings
- Can be installed in surface-mount or flush-mount frames
- Highly efficient solution
- Renovation solution for T5/T8 louver lights
- Suitable for office spaces/reception rooms/hallways
- Suitable for workplaces with screens in accordance with EN 12464-1 BAP65
- Microprismatic surface structure
- Can be combined with a power supply unit as desired [excl.]

Application Area

Office / conference, Reception / Communication, Corridor / stairwell, Shop / Retail / Sales area, Health / care / hospital / practice, Education / school / lecture theatre, Refurbishment

Housing	Aluminium	Control	Dimmable via optional power supply unit
Height	32 mm	CRI (Ra)	80
Power	17 W	Rated Current	450 mA
Rated Input Voltage	35-40 V/DC	IK Protection Class	IK03
Power Supply Unit incl.	No	UGR	19
Light Beam Angle	90 Degree		



100084

Article	Housing Color	Colour Temperature	Luminous Flux	Length	Width	EEI	Price
100084	☐ White	3000 K	2880 lm	620 mm	620 mm	D	€ 109.95
100089	☐ White	3000 K	2880 lm	1195 mm	295 mm	E	€ 114.95
100122	☐ White	4000 K	3200 lm	295 mm	1195 mm	D	€ 114.95
100148	☐ White	4000 K	3200 lm	595 mm	595 mm	C	€ 104.95
100088	☐ White	4000 K	3200 lm	620 mm	620 mm	D	€ 109.95

CC			IP40		1 CH
----	--	--	------	--	------

Accessories

930674	Safety cable		€ 4.95
930676	Mounting brackets for 600x600/300x1,200 mm backlit panel		€ 4.95
862257	QUICK, CC, 450 mA, 30-40 V, 20 W		€ 36.95
862191	BASIC, DIM, Multi CC, IE-25D		€ 64.95

Accessories for 100084, 100088

930665	Surface-mounted frame for 620x620 mm panel		€ 59.95
930668	Recessed frame for 620x620 mm panel		€ 57.95

Accessories for 100089, 100122

930666	Surface-mounted frame for 300x1,200 mm panel		€ 69.95
930669	Recessed frame for 300x1,200 mm panel		€ 67.95

Accessories for 100148

930664	Surface-mounted frame for 595x595 mm panel		€ 54.95
930667	Recessed frame for 595x595 mm panel		€ 52.95

SIDELIGHT-PANELS [SERIES: STANDARD] – TECHNOLOGY AND ADVANTAGES

Not every LED panel is built the same! There are technologies exist to produce homogeneous, flat light. Each method has its own advantages and disadvantages and depends on the individual user requirements and budget needs. For example LED panels from our standard series use sidelight technology.

Unlike backlight panels, the LEDs are not spread over the entire panel surface, but are located on the side of the aluminum frame of the luminaire. Depending on the model and version, only one, two or all four sides are equipped with LED stripes. What all edgelit or sidelight panels have in common is that the LEDs shine into the center of the panel. The light must therefore still be redirected in order to radiate downwards.

The most important element here is the light guide plate. This is usually made of acrylic glass (also PMMA (polymethyl methacrylate), a transparent thermoplastic material), which distributes the light evenly over the entire surface and deflects it downwards. In addition, acrylic glass does not yellow with age. In addition to the light guide plate, which deflects the light by means of small laser-engraved dots, the additional reflector, similar to the one the backlight panel, and the diffuser also contribute to the significantly more complex structure of a sidelight panel [see picture to the right].

The great advantage is the lower construction thickness, which is why edgelit panels can be integrated more discreetly in rooms and are better suited as pendant variants. At the same time, the panels allow a higher beam angle [approx. 120°] what results in a larger illuminated area.

The disadvantages: Edgelit panels are more expensive and offer less efficiency and lifetime compared to backlight panels.


advantages

- lower thickness
- higher beam angle [approx. 120°]
- more suitable for suspension
- thinner packing

disadvantages

- higher costs
- worse price/performance ratio
- average lifetime
- lower efficiency

In the following picture you can see the typical structure of a sidelight LED panel.






STANDARD FLEX

- Light colour adjustable in three stages
- For insertion into grid ceilings
- Can be installed in surface-mount or flush-mount frames
- Suitable for pendant mounting
- Suitable for reception rooms and hallways
- Can be combined with a power supply unit as desired [excl.]


Application Area
 Reception / Communication, Corridor / stairwell, Shop / Retail / Sales area, Health / care / hospital / practice, Education / school / lecture theatre, Refurbishment

Housing	Aluminium	Control	Dimmable via optional power supply unit
Colour Temperature	3000/4000/6000 K	CRI (Ra)	90
Height	10 mm	IK Protection Class	IK03
Rated Input Voltage	33-38 V/DC	UGR	22
Power Supply Unit incl.	No		
Light Beam Angle	120 Degree		



100123

Article	Housing Color		Luminous Flux	Length	Width	Power	Rated Current	Price
100125	White		3570/3990/3780 lm	1195 mm	295 mm	36.0 W	1050 mA	€ 124.95
100123	White		3780/4200/4000 lm	620 mm	620 mm	36.0 W	1050 mA	€ 119.95
100139	White		5300/6000/5700 lm	1195 mm	595 mm	51.5 W	1500 mA	€ 219.95
100154	White		5300/6000/5700 lm	1240 mm	620 mm	51.5 W	1500 mA	€ 229.95



Accessories

930674	Safety cable		€ 4.95
--------	--------------	--	--------

Accessories for 100123

930665	Surface-mounted frame for 620x620 mm panel		€ 59.95
930670	Recessed frame for 620x620 mm backlit panel		€ 59.95

Accessories for 100123, 100125

930672	Cable suspension for 620x620/300x1,200 mm panel		€ 22.95
862193	BASIC, DIM, Multi CC, IE-45HD		€ 69.95
862258	QUICK, CC, 1,050 mA, 25-40 V, 42 W		€ 46.95

Accessories for 100125

930666	Surface-mounted frame for 300x1,200 mm panel		€ 69.95
930671	Recessed frame for 300x1,200 mm backlit panel		€ 69.95

Accessories for 100139

930675	Surface-mounted frame for 600x1,200 mm panel		€ 69.95
930688	Recessed frame for 600x1,200 mm backlit panel		€ 84.95

Accessories for 100139, 100154

930673	Cable suspension for 600x1,200 mm panel		€ 32.95
862194	BASIC, DIM, Multi CC, IE-75D		€ 84.95
862259	QUICK, CC, 1,500 mA, 27-42 V, 60 W		€ 56.95




STANDARD OFFICE

- For insertion into grid ceilings
- Can be installed in surface-mount or flush-mount frames
- Suitable for pendant mounting
- Suitable for office spaces, reception rooms, hallways
- Suitable for workplaces with screens in accordance with EN 12464-1 BAP65
- Microprismatic surface structure

Application Area

Office / conference, Reception / Communication, Corridor / stairwell, Shop / Retail / Sales area, Health / care / hospital / practice, Education / school / lecture theatre, Refurbishment

Housing	Aluminium	Light Beam Angle	90 Degree
Colour Temperature	4000 K	Control	Dimmable via optional power supply unit
Luminous Flux	4200 lm	CRI (Ra)	90
Height	9 mm	Rated Current	1050 mA
Power	36 W	IK Protection Class	IK03
Rated Input Voltage	33-38 V/DC	UGR	19
Power Supply Unit incl.	No		



100124

Article	Housing Color	Length	Width	EEI	Price
100138	☐ White 	295 mm	1195 mm		€ 129.95
100124	☐ White 	620 mm	620 mm		€ 124.95



Accessories

930672	Cable suspension for 620x620/300x1,200 mm panel		€ 22.95
930674	Safety cable		€ 4.95
862258	QUICK, CC, 1,050 mA, 25-40 V, 42 W		€ 46.95
862193	BASIC, DIM, Multi CC, IE-45HD		€ 69.95

Accessories for 100124

930665	Surface-mounted frame for 620x620 mm panel		€ 59.95
930670	Recessed frame for 620x620 mm backlit panel		€ 59.95

Accessories for 100138

930666	Surface-mounted frame for 300x1,200 mm panel		€ 69.95
930671	Recessed frame for 300x1,200 mm backlit panel		€ 69.95



STANDARD SANO

The SANO LED panel is a simple and cost-effective solution for refurbishing old T5/T8 louvre luminaires. With its slimline design, it can be seamlessly integrated into existing installations without having to make any additional adjustments.

Thanks to its BEG eligibility, this SANO insert panel is not only a sustainable but also an economically attractive solution. It provides uniform illumination with high colour rendering and minimizes glare, which is particularly important in commercial environments.





STANDARD SANO

- Eligible for BEG German federal funding for energy-efficient buildings
- For insertion into grid ceilings
- Can be installed in surface-mount or flush-mount frames
- Suitable for pendant mounting
- Renovation solution for T5/T8 louver lights
- Can be combined with a power supply unit as desired [excl.]

Application Area

Reception / Communication, Corridor / stairwell, Shop / Retail / Sales area, Health / care / hospital / practice, Education / school / lecture theatre, Refurbishment

Housing	Aluminium, Polycarbonate	Rated Input Voltage	35-40 V/DC
Colour Temperature	4000 K	Power Supply Unit incl.	No
Luminous Flux	4900 lm	Light Beam Angle	120 Degree
Length	1495 mm	Control	Dimmable via optional power supply unit
Width	295 mm	CRI (Ra)	90
Height	10 mm	Rated Current	1050 mA
Power	33 W	UGR	22


Article	Housing Color	Price
100158	☐ White ☒ NW	€ 169.95



Accessories

930795	Surface-mounted frame for 1,500x300 mm panel
930796	Recessed frame for 1,500x300 mm panel
930673	Cable suspension for 600x1,200 mm panel
930674	Safety cable
862258	QUICK, CC, 1,050 mA, 25-40 V, 42 W

	€ 79.95
	€ 69.95
	€ 32.95
	€ 4.95
	€ 46.95




OFFICE FLEX

- For insertion into grid ceilings
- Can be installed in surface-mount or flush-mount frames
- Suitable for pendant mounting
- Suitable for office spaces, reception rooms, hallways
- Light colour adjustable in three stages
- Suitable for workplaces with screens in accordance with EN 12464-1 BAP65
- Microprismatic surface structure

Application Area
Office / conference, Reception / Communication, Corridor / stairwell, Shop / Retail / Sales area, Health / care / hospital / practice, Education / school / lecture theatre, Refurbishment

Housing	Aluminium	Light Beam Angle	100 Degree
Colour Temperature	3000/4000/5700 K	Control	Leading-edge dimmer, Trailing-edge dimmer
Height	10 mm	CRI (Ra)	90
Power	40 W	IK Protection Class	IK08
Rated Input Voltage	220-240 V/AC	UGR	19
Power Supply Unit incl.	Yes		

Article	Housing Color			Luminous Flux	Length	Width	Price
100078	☐ White	☒ WW	☐ NW	☐ CW	3300 lm	620 mm	€ 179.95
100079	☐ White	☒ WW	☐ NW	☐ CW	3500 lm	1195 mm	€ 219.95



Accessories

862193 BASIC, DIM, Multi CC, IE-45HD  € 69.95

Accessories for 100078


930665 Surface-mounted frame for 620x620 mm panel  € 59.95

930670 Recessed frame for 620x620 mm backlit panel  € 59.95

Accessories for 100079

930666 Surface-mounted frame for 300x1,200 mm panel  € 69.95

930671 Recessed frame for 300x1,200 mm backlit panel  € 69.95




HCL

- For insertion into grid ceilings
- Can be installed in surface-mount or flush-mount frames
- Suitable for 24 V HCL controllers
- Suitable for event spaces/reception rooms, hallways
- Low housing depth

Application Area


Reception / Communication, Corridor / stairwell, Shop / Retail / Sales area, Health / care / hospital / practice, Education / school / lecture theatre, Refurbishment

Housing	Aluminium	Rated Input Voltage	24 V/DC
Colour Temperature	3000-5500 K	Power Supply Unit incl.	No
Luminous Flux	3551 lm	Light Beam Angle	120 Degree
Length	620 mm	Control	Dimmable via optional controller
Width	620 mm	CRI (Ra)	80
Height	10 mm		
Power	49.5 W		



100032


Article	Housing Color	Colour Temperature	Price
100032	☐ White	☒ WW ☐ CW 3000-5500 K	€ 169.95



Accessories

930665	Surface-mounted frame for 620x620 mm panel
930670	Recessed frame for 620x620 mm backlit panel
862122	FLAT, CV, UT 24 V/50 W
862166	BASIC, CV, Q8H-24-100 W
843501	RF-smart, starter set LED single/CCT, 12-48 V, 20 A incl. remote control

	€ 59.95
	€ 59.95
	€ 52.95
	€ 96.95
	€ 99.95



STANDARD RGB CCT

- For insertion into grid ceilings
- Can be installed in surface-mount or flush-mount frames
- Suitable for event spaces, reception rooms, hallways
- Suitable for 24 V colour and HCL controllers

Application Area
Reception / Communication, Object lighting / architecture, Wellness / Spa / Gym, Advertising lighting, Hotel / catering, Theatre / event, Refurbishment

Housing	Aluminium	Light Beam Angle	110 Degree
Colour Temperature	2700-6500 K	Control	Dimmable via optional controller
Luminous Flux	5000 lm	CRI (Ra)	90
Height	12.5 mm	IK Protection Class	IK05
Power	88 W	UGR	19
Rated Input Voltage	24 V/DC		
Power Supply Unit incl.	No		

Article	Housing Color	Length	Width	Price
100160	☐ White   	595 mm	595 mm	€ 205.95
100159	☐ White   	620 mm	620 mm	€ 209.95




- Accessories for **100159**
- 930665** Surface-mounted frame for 620x620 mm panel
 - 930668** Recessed frame for 620x620 mm panel



- Accessories for **100160**
- 930664** Surface-mounted frame for 595x595 mm panel
 - 930667** Recessed frame for 595x595 mm panel
 - 930907** Recessed frame 600x600 for standard panels






STANDARD RGBW

- For insertion into grid ceilings
- Can be installed in surface-mount or flush-mount frames
- Powerful and intense colours, incl. pastel tones
- Suitable for 24 V colour controllers
- Suitable for event spaces, reception rooms, hallways

Application Area


Reception / Communication, Object lighting / architecture, Wellness / Spa / Gym, Advertising lighting, Hotel / catering, Theatre / event, Refurbishment

Housing	Aluminium	Light Beam Angle	110 Degree
Height	11 mm	Control	Dimmable via optional controller
Power	94 W	CRI (Ra)	90
Rated Input Voltage	24 V/DC		
Power Supply Unit incl.	No		



100152

Article	Housing Color	Colour Temperature	Luminous Flux	Length	Width	Price
100156	☐ White	3000 K	4000 lm	595 mm	595 mm	€ 184.95
100152	☐ White	3000 K	4000 lm	620 mm	620 mm	€ 189.95
100157	☐ White	4000 K	4200 lm	595 mm	595 mm	€ 184.95
100153	☐ White	4000 K	4200 lm	620 mm	620 mm	€ 189.95



Accessories

862166	BASIC, CV, Q8H-24-100 W		€ 96.95
872091	IP, CV, V6-320-24		€ 219.95
843502	RF-smart, starter set RGB/W/CCT, 12-48 V, 20 A incl. remote, IP20		€ 99.95
843037	Casambi BT Dimmer CBU-PWM4 (CV, 12-24V, 6A DC)		€ 179.95
843279	MULTI-LED dimmer 1-4 channels, DMX/auto/manual, 12-48 V, 20 A, flicker-free		€ 114.95

Accessories for 100152, 100153

930665	Surface-mounted frame for 620x620 mm panel		€ 59.95
930668	Recessed frame for 620x620 mm panel		€ 57.95

Accessories for 100156, 100157

930664	Surface-mounted frame for 595x595 mm panel		€ 54.95
930667	Recessed frame for 595x595 mm panel		€ 52.95

Accessories for 100157

930907	Recessed frame 600x600 for standard panels		€ 54.95
---------------	--	--	---------

surface mounted wall lights



   
page 198



  
page 199



   
page 200



 
page 202



 
page 204





ACAMAR

Application Area
Reception / Communication, Object lighting / architecture, Home / Living, Hotel / catering

Housing	Aluminium	Power	6.9 W
Colour Temperature	3000 K	Rated Input Voltage	220-240 V/AC
Length	170 mm	Power Supply Unit incl.	Yes
Width	100 mm	Light Beam Angle	105 Degree
Height	80 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Base Length	120 mm	CRI (Ra)	90
Base Width	60 mm		
Base Height	33 mm		

Article	Housing Color		Luminous Flux	Price
341196	Black		300 lm	€ 154.95
341194	White		390 lm	€ 154.95
341195	Silver, White		400 lm	€ 154.95





APODIS


Application Area

Home / Living, Reception / Communication, Home office / study, Hotel / catering

Housing	Aluminium	Base Height	100 mm
Colour Temperature	3000 K	Rated Input Voltage	220-240 V/AC
Length	76 mm	Power Supply Unit incl.	Yes
Width	61 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Base Length	60 mm	CRI (Ra)	80
Base Width	18 mm		



Article	Housing Color	Luminous Flux	Height	Power	Light Beam Angle	Price
341200	Gold, Black	350 lm	500 mm	10.8 W	40 Degree	€ 229.95
341201	Rosé, Black	350 lm	500 mm	10.8 W	40 Degree	€ 229.95
341202	Gold, Black	450 lm	800 mm	14.7 W	30 Degree	€ 279.95
341203	Rosé, Black	450 lm	800 mm	14.7 W	30 Degree	€ 279.95





CUBE

Little cube, big effect: The cube emits its light up and down in equal measure, drawing the eye to spacial elements and bringing structure. The compact cube made from concrete or plaster [available in the colour tones beige, grey, dark grey, white and black] with its subdued design has the essentials in focus, assuming a back seat presence.



CUBE

- Exchangeable lamp
- A variety of concrete/plaster colour variants
- Can be painted over [white variant only]


Application Area

Home / Living, Hotel / catering

Length	115 mm	Max. Power	1x max. 25 W
Width	115 mm	Rated Input Voltage	220-240 V/AC
Height	115 mm	Control	Dimmable via optional light source
Base Length	57 mm	Colour of Light Output	White
Base Width	57 mm		
Base Height	63 mm		

Article	Housing Color	Housing	Paintable	Price
341183	Grey	Concrete		€ 69.95
341184	Dark grey	Concrete		€ 69.95
341250	Black	Plaster		€ 72.95
341249	White	Plaster	Yes	€ 72.95







CAN IP20

- Customised lighting solution thanks to replaceable light source
- combinable with the extensive product family of the CAN series

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Max. Power	1x max. 7.5 W
Length	72 mm	Rated Input Voltage	220-240 V/AC
Height	125 mm	Control	Dimmable via optional light source
Ø	60 mm		

Article	Housing Color	Price
341341	White	€ 44.95
341342	Black	€ 44.95



Accessories

930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930301	Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930302	Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930366	Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930303	Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
931065	Acrylic attachment for Can		€ 4.95



page 46



page 88



page 90



page 92




page 414



CAN UP & DOWN IP20

The CAN wall light provides versatile lighting options for various commercial and private projects. The up/down variant with light emission on both sides can be adapted perfectly to individual room concepts. The GU10 base enables simple replacement of the lamp, while the screw-on cylinder allows tool-free access. Installation for rigid and flexible conductors is particularly easy due to the integrated push terminals. Individual accents can be created with the optional, interchangeable decorative rings. The CAN wall light is part of a comprehensive series and is also available as a pendant, ceiling, reading and outdoor light.





CAN UP & DOWN IP20

- Customised lighting solution thanks to replaceable light source
- combinable with the extensive product family of the CAN series

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Max. Power	2x max. 7.5 W
Length	72 mm	Rated Input Voltage	220-240 V/AC
Height	230 mm	Control	Dimmable via optional light source
Ø	60 mm		

Article	Housing Color	Price
341343	White	€ 54.95
341344	Black	€ 54.95



Accessories

930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930301	Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930302	Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930366	Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930303	Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
931065	Acrylic attachment for Can		€ 4.95



Seite 46



Seite 88



Seite 92



Seite 93



Seite 414

built in wall lights



 page 208



 page 210



 page 212



   page 214



   page 215





ALWAID PRO


- integrated power supply unit for 230V direct connection
- through-wiring possible
- dimmable via leading edge/trailing edge phase
- suitable for 68 mm switch boxes of normal and deep design

Housing	Aluminium, Polycarbonate	Installation Depth	39 mm
Height	41 mm	Cut Out Ø	68 mm
Ø	71.5 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Power	4 W	CRI (Ra)	80
Rated Input Voltage	220-240 V/AC	IK Protection Class	IK05
Power Supply Unit incl.	Yes	Light Direction	Front

Article	Housing Color	Colour Temperature	Luminous Flux	Price
565733	☐ White	2700 K	610 lm	€ 59.95
565734	☐ White	3000 K	630 lm	€ 59.95



5-year guarantee
Benefit from the maximum quality promise:
All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.



ALWAID PRO

Article	Housing Color	Housing	Housing shape	Light cone	L x W	Height	Ø	Price
931013	White	Aluminium	round	triangular		18 mm	71.5 mm	€ 12.95
931015	Black	Aluminium	round	triangular		18 mm	71.5 mm	€ 12.95
931025	White	Aluminium	round	narrow		18 mm	75 mm	€ 12.95
931027	Black	Aluminium	round	narrow		18 mm	75 mm	€ 12.95
931007	White	Aluminium	angular	triangular	75 x 75 mm	18 mm		€ 12.95
931009	Black	Aluminium	angular	triangular	75 x 75 mm	18 mm		€ 12.95
931019	White	Aluminium	angular	narrow	75 x 75 mm	18 mm		€ 12.95
931021	Black	Aluminium	angular	narrow	75 x 75 mm	18 mm		€ 12.95
931037	White	Glass / Polycarbonate	round	semicircular		23 mm	78 mm	€ 18.95
931039	Black	Glass / Polycarbonate	round	semicircular		23 mm	78 mm	€ 18.95
931031	White	Glass / Polycarbonate	angular	square	78 x 78 mm	23 mm		€ 18.95
931033	Black	Glass / Polycarbonate	angular	square	78 x 78 mm	23 mm		€ 18.95

IP20



ALWAID PRO MOTION

- integrated power supply unit for 230V direct connection
- with motion detector
- through-wiring possible
- power adjustable in 2 stages
- suitable for 68 mm switch boxes of normal and deep design

Housing	Aluminium, Polycarbonate	Power Supply Unit incl.	Yes
Height	41 mm	Installation Depth	39 mm
Ø	71.5 mm	Cut Out Ø	68 mm
Power Selectable	2 W, 4 W	CRI (Ra)	80
Rated Input Voltage	220-240 V/AC	IK Protection Class	IK05
		Light Direction	Front

Article	Housing Color	Colour Temperature	Luminous Flux	Price
565736	☐ White	2700 K	610 lm	€ 64.95
565737	☐ White	3000 K	630 lm	€ 64.95



Lighting design
Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.



ALWAID PRO MOTION

Article	Housing Color	Housing	Housing shape	Light cone	L x W	Height	Ø	Price
931016	White	Aluminium	round	triangular		18 mm	71.5 mm	€ 15.95
931018	Black	Aluminium	round	triangular		18 mm	71.5 mm	€ 15.95
931028	White	Aluminium	round	narrow		18 mm	75 mm	€ 15.95
931030	Black	Aluminium	round	narrow		18 mm	75 mm	€ 15.95
931010	White	Aluminium	angular	triangular	75 x 75 mm	18 mm		€ 15.95
931012	Black	Aluminium	angular	triangular	75 x 75 mm	18 mm		€ 15.95
931022	White	Aluminium	angular	narrow	75 x 75 mm	18 mm		€ 15.95
931024	Black	Aluminium	angular	narrow	75 x 75 mm	18 mm		€ 15.95
931040	White	Glass / Polycarbonate	round	semicircular		23 mm	78 mm	€ 21.95
931042	Black	Glass / Polycarbonate	round	semicircular		23 mm	78 mm	€ 21.95
931034	White	Glass / Polycarbonate	angular	square	78 x 78 mm	23 mm		€ 21.95
931036	Black	Glass / Polycarbonate	angular	square	78 x 78 mm	23 mm		€ 21.95

IP20



ALWAID 2

The ALWAID 2 recessed wall light fits into any 68 mm standard or deep switch box thanks to its compact design. Furthermore, it does not require an additional power supply. The variety of covers allows you to find a style that suits your space and illuminates your surroundings with beautiful indirect light. The article includes the base only; covers are not included in the scope of delivery.






ALWAID 2

- 230 V direct connection
- Feed-through wiring possible
- Can be dimmed using leading-edge phase dimmers or trailing-edge phase dimmers
- Suitable for 68 mm standard and deep switch boxes

Application Area


Home / Living, Corridor / stairwell, Hotel / catering, Stairs / steps

Housing	Aluminium	Installation Depth	39.9 mm
Height	39.9 mm	Light Beam Angle	100 Degree
Ø	71.2 mm	Cut Out Ø	61.5 mm
Power	4.8 W	Control	Trailing-edge dimmer
Rated Input Voltage	220-240 V/AC	CRI (Ra)	90
Power Supply Unit incl.	Yes		



563010

Article	Housing Color	Colour Temperature	Luminous Flux	Price
563009	☐ White	WW 2700 K	200 lm	€ 49.95
563010	☐ White	WW 3000 K	215 lm	€ 49.95
563011	☐ White	NW 4000 K	230 lm	€ 49.95



IP20



Technical data sheet

New in the onlineshop: The technical data sheets offer even more information: Light and energy data, light distribution curves, dimensional drawings and more.



ALWAID II - ANGULAR COVER

- A variety of shapes and colours for every application
- Ideally suited as a staircase light or night light
- Glass covers for soft, glare-free light
- Aluminium covers for different light cones

Article	Housing Color	Housing	light output	Length	Width	Height	Price
930485	White	Aluminium	step	75 mm	75 mm	19 mm	€ 14.95
930486	Light gray	Aluminium	step	75 mm	75 mm	19 mm	€ 14.95
930487	Black	Aluminium	step	75 mm	75 mm	19 mm	€ 14.95
930491	White	Aluminium	round	75 mm	75 mm	19.1 mm	€ 14.95
930492	Light gray	Aluminium	round	75 mm	75 mm	19.1 mm	€ 14.95
930493	Black	Aluminium	round	75 mm	75 mm	19.1 mm	€ 14.95
930482	White	Aluminium	square	75 mm	75 mm	19.8 mm	€ 14.95
930483	Light gray	Aluminium	square	75 mm	75 mm	19.8 mm	€ 14.95
930484	Black	Aluminium	square	75 mm	75 mm	19.8 mm	€ 14.95
930488	White	Aluminium	trapeze	75 mm	75 mm	19.8 mm	€ 14.95
930489	Light gray	Aluminium	trapeze	75 mm	75 mm	19.8 mm	€ 14.95
930490	Black	Aluminium	trapeze	75 mm	75 mm	19.8 mm	€ 14.95
930480	White	Glass	milky	78.2 mm	78.2 mm	22.9 mm	€ 19.95
930842	Black	Glass	milky	78.2 mm	78.2 mm	22.9 mm	€ 19.95
930860	Light gray	Glass	milky	78.2 mm	78.2 mm	22.9 mm	€ 23.74

IP20



ALWAID II - ROUND COVER

- A variety of shapes and colours for every application
- Ideally suited as a staircase light or night light
- Glass covers for soft, glare-free light
- Aluminium covers for different light cones

Article	Housing Color	Housing	light output	Height	Ø	Price
930497	White	Aluminium	step	19 mm	75 mm	€ 14.95
930498	Light gray	Aluminium	step	19 mm	75 mm	€ 14.95
930499	Black	Aluminium	step	19 mm	75 mm	€ 14.95
930500	White	Aluminium	round	19.8 mm	75 mm	€ 14.95
930501	Light gray	Aluminium	round	19.8 mm	75 mm	€ 14.95
930502	Black	Aluminium	round	19.8 mm	75 mm	€ 14.95
930503	White	Aluminium	square	19.8 mm	75 mm	€ 14.95
930504	Light gray	Aluminium	square	19.8 mm	75 mm	€ 14.95
930505	Black	Aluminium	square	19.8 mm	75 mm	€ 14.95
930494	White	Aluminium	trapeze	20.4 mm	74.9 mm	€ 14.95
930495	Light gray	Aluminium	trapeze	20.4 mm	74.9 mm	€ 14.95
930496	Black	Aluminium	trapeze	20.4 mm	74.9 mm	€ 14.95
930481	White	Glass	milky	22.8 mm	78 mm	€ 19.95
930843	Black	Glass	milky	22.8 mm	78 mm	€ 19.95
930861	Light gray	Glass	milky	22.8 mm	78 mm	€ 19.95

IP20

reading lights



page 218



page 219



page 220



page 222





BRAHE ROUND

The BRAHE wall light with indirect lighting and narrow light emission angle of 25° means anyone else in the bed can sleep peacefully while the person on the other side is still reading. The simple design of the BRAHE also impresses in other areas, such as reading nooks.



page 232



page 233



BRAHE ROUND


·Direct and indirect lighting can be switched on separately

Application Area

Home / Living, Hotel / catering

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Colour Temperature	3000 K	Power Supply Unit incl.	Yes
Height	110 mm	Light Beam Angle	25 Degree
Ø	150 mm	Swivelling Angle	360 Degree
Power	8.5 W	CRI (Ra)	80

Article	Housing Color		Luminous Flux	Price
341243	Black		395 lm	€ 104.95
341242	White		490 lm	€ 104.95




BRAHE ANGULAR

- High-quality, flexible gooseneck
- Gooseneck with silicone sleeve for easy cleaning
- Individually adjustable via flexible gooseneck

Application Area

Home / Living, Hotel / catering

Housing	Aluminium	Base Height	25 mm
Colour Temperature	3000 K	Power	3.3 W
Length	310 mm	Rated Input Voltage	100-240 V/AC
Height	80 mm	Power Supply Unit incl.	Yes
Ø	25 mm	Light Beam Angle	25 Degree
Base Length	80 mm	Swivelling Angle	360 Degree
Base Width	80 mm	CRI (Ra)	80



341236


Article	Housing Color		Luminous Flux	Price
341237	Black		165 lm	€ 64.95
341236	White		175 lm	€ 67.95





CAN TILT SQUARE

The square CAN reading light is the ideal choice for modern hotel rooms and sophisticated living spaces. It offers a convenient charging option for smartphones and other devices via USB-C and USB-A (article no. 341339 and 341340 only). The widely used GU10 base enables the quick replacement of the lamp, while the screw-on cylinder housing allows tool-free access. Individual accents can be set with the optional, replaceable decorative rings. The CAN reading light is part of a versatile lighting family, which is also available as a pendant, ceiling, wall and outdoor light.





CAN TILT SQUARE

- Flat and discreet lamp base
- Replaceable lamp to offer an individual lighting solution
- Can be customised with a wide range of accessories
- Can be combined with the comprehensive product family of the CAN series
- Can be charged via USB-C/USB-A [art. nos. 341339 and 341340 only]

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Max. Power	1x max. 7.5 W
Length	102 mm	Rated Input Voltage	220-240 V/AC
Height	105 mm	Control	Dimmable via optional light source
Ø	60 mm	Rotation Angle	355 Degree
Base Width	100 mm	Swivelling Angle	90 Degree
Base Height	100 mm		

Article	Housing Color	Charging connection	Price
341337	White		€ 49.95
341338	Black		€ 49.95
341339	White	1 x USB type A / 1 x USB type C	€ 69.95
341340	Black	1 x USB type A / 1 x USB type C	€ 69.95



Accessories


930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930301	Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930302	Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930366	Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930303	Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
931065	Acrylic attachment for Can		€ 4.95





CAN TILT ROUND

The round CAN reading light is the ideal choice for modern hotel rooms and sophisticated living spaces. It offers a convenient charging option for smartphones and other devices via USB-C and USB-A (article no. 341335 and 341336 only). The widely used GU10 base enables the quick replacement of the lamp, while the screw-on cylinder housing allows tool-free access. Individual accents can be set with the optional, replaceable decorative rings. The CAN reading light is part of a versatile lighting family, which is also available as a pendant, ceiling, wall and outdoor light.





CAN TILT ROUND

- Flat and discreet lamp base
- Can be customised with a wide range of accessories
- Replaceable lamp to offer an individual lighting solution
- Can be combined with the comprehensive product family of the CAN series
- Can be charged via USB-C/USB-A [art. nos. 341335 and 341336 only]

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Length	102 mm	Control	Dimmable via optional light source
Height	105 mm		
Ø	60 mm	Rotation Angle	355 Degree
Base Ø	100 mm	Swivelling Angle	90 Degree
Max. Power	1x max. 7.5 W		

Article	Housing Color	Charging connection	Price
341333	White		€ 49.95
341334	Black		€ 49.95
341335	White	1 x USB type A / 1 x USB type C	€ 69.95
341336	Black	1 x USB type A / 1 x USB type C	€ 69.95



Accessories

930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930301	Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930302	Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930366	Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930303	Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
931065	Acrylic attachment for Can		€ 4.95





CANTILT SQUARE BASE MIX'N MATCH 1/3

- flat and discreet light base
- charging option via USB-C / USB-A [only item no. 341347 and 341348]
- can be customised with cylinder housing in 6 different colours

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Height	105 mm	Control	Dimmable via optional light source
Ø	60 mm	Rotation Angle	340 Degree
Base Length	100 mm	Swivelling Angle	90 Degree
Base Width	100 mm		
Max. Power	1x max. 7.5 W		

Article	Housing Color	Price
341345	☐ White	€ 41.95
341346	☒ Black	€ 41.95
341347	☐ White	€ 61.95
341348	☒ Black	€ 61.95



CANTILT ROUND BASE MIX'N MATCH 1/3

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Height	105 mm	Control	Dimmable via optional light source
Ø	60 mm	Rotation Angle	340 Degree
Base Ø	100 mm	Swivelling Angle	90 Degree
Max. Power	1x max. 7.5 W		

Article	Housing Color	Charging connection	Price
341349	☐ White		€ 41.95
341350	☒ Black		€ 41.95
341351	☐ White	1 x USB type A / 1 x USB type C	€ 61.95
341352	☒ Black	1 x USB type A / 1 x USB type C	€ 61.95





CYLINDER HOUSING FOR CAN MIX'N MATCH 2/3

Housing Aluminium Ø 60 mm
Height 95 mm

Article	Housing Color	Price
931059	 White	€ 7.95
931060	 Black	€ 7.95
931061	 Bronze	€ 18.95
931062	 Brass	€ 18.95
931063	 Black gray	€ 18.95
931064	 Rosé	€ 18.95

IP20



REFLECTOR RING CAN SERIES MIX'N MATCH 3/3

Housing Plastic Ø 57 mm
Height 28 mm

Article	Housing Color	Price
930301	 White	€ 4.95
930302	 Black	€ 4.95
930303	 Gold	€ 4.95
930366	 Silver	€ 4.95

IP20

table and floor lights



page 228



page 229



page 230



page 230



page 232



page 233



page 234





CAN

- customisable with extensive accessories
- customised lighting solution thanks to replaceable light source
- combinable with the extensive product family of the CAN series

Application Area

Home / Living, Hotel / catering

Housing	Aluminium	Primary Cable Length	2 m
Height	1115 mm	Primary Connection End	Safety plug
Ø	60 mm	Control	Dimmable via optional light source
Base Ø	252 mm	Rotation Angle	340 Degree
Max. Power	1x max. 75 W	Swivelling Angle	90 Degree
Rated Input Voltage	220-240 V/AC		

Article	Housing Color	Price
343037	White	€ 129.95
343038	Black	€ 129.95



Accessories

930301	Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930302	Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930303	Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930366	Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
931065	Acrylic attachment for Can		€ 4.95



CAN

- customisable with extensive accessories
- customised lighting solution thanks to replaceable light source
- combinable with the extensive product family of the CAN series

Application Area

Home / Living, Hotel / catering

Housing	Aluminium	Primary Cable Length	2 m
Height	400 mm	Primary Connection End	Safety plug
Ø	60 mm	Control	Dimmable via optional light source
Base Ø	182 mm	Rotation Angle	340 Degree
Max. Power	1x max. 7.5 W	Swivelling Angle	90 Degree
Rated Input Voltage	220-240 V/AC		

Article	Housing Color	Price
346086	White	€ 95.95
346087	Black	€ 95.95



Accessories

- 930301 Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series
- 930302 Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series
- 930303 Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series
- 930307 Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series
- 930308 Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series
- 930309 Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series
- 930310 Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series
- 930366 Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series
- 931065 Acrylic attachment for Can

	€ 4.95
	€ 4.95
	€ 4.95
	€ 8.95
	€ 8.95
	€ 8.95
	€ 8.95
	€ 4.95
	€ 4.95



CAN BASE MIX'N MATCH 1/3

- customisable with extensive accessories
- individual lighting solution thanks to interchangeable light source
- can be customised with cylinder housing in 6 different colours
- can be combined with the extensive product family of the CAN series

Application Area

Home / Living, Hotel / catering

Housing	Aluminium	Primary Connection End	Safety plug
Height	1115 mm	Control	Dimmable via optional light source
Base Ø	252 mm	Rotation Angle	340 Degree
Max. Power	1x max. 7.5 W	Swivelling Angle	90 Degree
Rated Input Voltage	220-240 V/AC		
Primary Cable Length	2 m		

Article	Housing Color	Price
343039	White	€ 121.95
343040	Black	€ 121.95



CAN BASE MIX'N MATCH 1/3

Housing	Aluminium	Primary Connection End	Safety plug
Height	400 mm	Control	Dimmable via optional light source
Base Ø	182 mm	Rotation Angle	340 Degree
Max. Power	1x max. 7.5 W	Swivelling Angle	90 Degree
Rated Input Voltage	220-240 V/AC		
Primary Cable Length	2 m		

Article	Housing Color	Price
346088	White	€ 87.95
346089	Black	€ 87.95





CYLINDER HOUSING FOR CAN MIX'N MATCH 2/3

Housing Aluminium Ø 60 mm
Height 95 mm

Article	Housing Color	Price
931059	 White	€ 7.95
931060	 Black	€ 7.95
931061	 Bronze	€ 18.95
931062	 Brass	€ 18.95
931063	 Black gray	€ 18.95
931064	 Rosé	€ 18.95

IP20



REFLECTOR RING CAN SERIES MIX'N MATCH 3/3

Housing Plastic Ø 57 mm
Height 28 mm

Article	Housing Color	Price
930301	 White	€ 4.95
930302	 Black	€ 4.95
930303	 Gold	€ 4.95
930366	 Silver	€ 4.95

IP20




BRAHE

- Can be rotated and swivelled
- Direct and indirect lighting can be switched on separately

Application Area
Home / Living, Hotel / catering

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000 K	Light Beam Angle	25 Degree
Height	455 mm	Swivelling Angle	90 Degree
Ø	150 mm	Primary Connection End	Power plug IP20
Power	8.5 W	CRI (Ra)	80
Rated Input Voltage	220-240 V/AC		

Article	Housing Color		Luminous Flux	Price
346016		Black 	370 lm	€ 155.95
346015		White 	470 lm	€ 155.95





BRAHE


- Can be rotated and swivelled
- Direct and indirect lighting can be switched on separately

Application Area

Home / Living, Hotel / catering

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Colour Temperature	3000 K	Power Supply Unit incl.	Yes
Luminous Flux	530 lm	Light Beam Angle	25 Degree
Height	1387 mm	Swivelling Angle	90 Degree
Ø	305 mm	Primary Connection End	Power plug IP20
Power Selectable	3 W, 8 W	CRI (Ra)	80

Article	Housing Color	Price
343025	 White 	€ 259.95
343026	 Black 	€ 259.95





ADHARA

Classic design interpreted in a modern way - the ADHARA made from aluminium captivates with its classic lines, ultra-modern materials and high degree of flexibility. The ADHARA can be optimally adjusted to any situation via its two or three joints. Its powerful LED module delivers 950 lumens and can also be dimmed thanks to a touch sensor. Whether for the boss's office or for a child's desk, the ADHARA looks great anywhere.



ADHARA

- Can be rotated and swivelled via joints
- Dimmable in three stages using touch sensor

Application Area

Home / Living, Reception / Communication, Home office / study

Housing	Aluminium	Power	12 W
Colour Temperature	3000 K	Rated Input Voltage	100-240 V/AC
Luminous Flux	950 lm	Power Supply Unit incl.	Yes
Length	498 mm	Light Beam Angle	120 Degree
Height	480 mm	Swivelling Angle	180 Degree
Ø	150 mm	Primary Cable Length	1.6 m
Base Height	21.5 mm	Primary Connection End	Power plug
Base Ø	180 mm	CRI (Ra)	80

Article	Housing Color		Price
346026		Black 	€ 199.95
346027		White 	€ 199.95
346028		Silver 	€ 199.95



showcase lights



page 239



page 240



page 242



page 243



HERCULIS

Small helpers, big effect. With HERCULIS display luminaires in high-quality aluminium housings, you can reach all corners of a showcase. The luminaire head with its 40° beam angle can be freely rotated and swivelled in any direction. In addition, the intelligent cable routing and the ready-to-plugin system allow easy surface and recessed mounting in showcases, counters, sales areas or in the living room.






HERCULIS MAGNETIC

- High output with compact design
- Magnetic lamp head
- Ball head allows lamp to be directed as desired
- For surface mounting
- Ready-to-use system

Application Area


Shop / Retail / Sales area, Trade fair construction / shop fitting

Housing	Aluminium	Rated Input Voltage	3 V/DC
Height	42.2 mm	Rated Current	350 mA
Ø	31 mm	Power Supply Unit incl.	No
Base Height	5 mm	Light Beam Angle	40 Degree
Base Ø	31 mm	Swivelling Angle	180 Degree
Power	1 W	CRI (Ra)	90



688026

Article	Housing Color	Colour Temperature	Luminous Flux	Price
688025	Black	3000 K	100 lm	€ 59.95
688026	Silver	3000 K	100 lm	€ 59.95
688027	Black	4000 K	105 lm	€ 59.95
688028	Silver	4000 K	105 lm	€ 59.95



Accessories

- 930594** LED power supply incl. 3-way distributor for Herculis
- 930592** LED power supply incl. 6-way distributor for Herculis



€ 32.95

€ 39.95



Lighting design

Interested in our lighting design service?

Your contact person will be happy to answer any questions you may have.




HERCULIS SINGLE

- High output with compact design
- Rotating and swivelling head
- For panel and surface mounting due to intelligent cable routing
- Ready-to-use system
- Available in two sizes

Application Area


Shop / Retail / Sales area, Trade fair construction / shop fitting

Housing	Aluminium	Rated Input Voltage	3 V/DC
Luminous Flux	100 lm	Rated Current	350 mA
Ø	39.2 mm	Power Supply Unit incl.	No
Base Height	4.5 mm	Light Beam Angle	30 Degree
Base Ø	39.2 mm	Swivelling Angle	350 Degree
Power	1 W	CRI (Ra)	90



688029

Article	Housing Color	Colour Temperature	Height	Price
688029	Black	3000 K	150 mm	€ 82.95
688030	Silver	3000 K	150 mm	€ 82.95
688034	Black	3000 K	250 mm	€ 83.95
688035	Silver	3000 K	250 mm	€ 83.95
688031	Black	4000 K	150 mm	€ 82.95
688033	Silver	4000 K	150 mm	€ 82.95
688036	Black	4000 K	250 mm	€ 83.95
688037	Silver	4000 K	250 mm	€ 83.95



Accessories

- 930594** LED power supply incl. 3-way distributor for Herculis
- 930592** LED power supply incl. 6-way distributor for Herculis



€ 32.95

€ 39.95






HERCULIS DOUBLE

- High performance with compact design
- Rotating and swivelling heads
- for recessed and surface mounting thanks to intelligent cable routing
- Ready-to-plug-in system

Application Area


Shop / Retail / Sales area, Trade fair construction / shop fitting

Housing	Aluminium	Rated Input Voltage	6 V/DC
Height	200 mm	Rated Current	350 mA
Ø	39.2 mm	Power Supply Unit incl.	No
Base Height	4.5 mm	Light Beam Angle	30 Degree
Base Ø	39.2 mm	Swivelling Angle	350 Degree
Power	2 W	CRI (Ra)	90



688038

Article	Housing Color	Colour Temperature	Luminous Flux	Price
688038	Black	3000 K	185 lm	€ 119.95
688039	Silver	3000 K	185 lm	€ 119.95
688040	Black	4000 K	195 lm	€ 119.95
688041	Silver	4000 K	195 lm	€ 119.95



Accessories

- 930594** LED power supply incl. 3-way distributor for Herculis
- 930592** LED power supply incl. 6-way distributor for Herculis



€ 32.95

€ 39.95




HERCULISTRIPLÉ

- High performance with compact design
- Rotating and swivelling heads
- for recessed and surface mounting thanks to intelligent cable routing
- Ready-to-plug-in system

Application Area

Shop / Retail / Sales area, Trade fair construction / shop fitting

Housing	Aluminium	Rated Input Voltage	9 V/DC
Height	250 mm	Rated Current	350 mA
Ø	39.2 mm	Power Supply Unit incl.	No
Base Height	4.5 mm	Light Beam Angle	30 Degree
Base Ø	39.2 mm	Swivelling Angle	350 Degree
Power	3 W	CRI (Ra)	90



688042

Article	Housing Color	Colour Temperature	Luminous Flux	Price
688042	Black	3000 K	263 lm	€ 139.95
688043	Silver	3000 K	294 lm	€ 139.95
688044	Black	4000 K	290 lm	€ 139.95
688045	Silver	4000 K	290 lm	€ 139.95



Accessories

- 930594** LED power supply incl. 3-way distributor for Herculis
930592 LED power supply incl. 6-way distributor for Herculis



€ 32.95

€ 39.95

office lights



□ ■ □
page 246



■ □ □
page 248



■ □ □
page 250



□ □ ■
page 252



□ □
page 254



□
page 256



□ □ ■
page 264



□ □ ■
page 265



□ □ ■
page 266



□ □ ■
page 267






ROUND TRANSPARENT LED PANEL

The LED pendant light is equipped with a transparent acrylic glass pane for soft direct and indirect light distribution, which is almost transparent when switched off. When switched on, the pane distributes the light almost entirely without glare.

With a glare rating [UGR] of under 22, this pendant light is suitable for various communal or even conference rooms. Bright, efficient and with a sophisticated design, this light not only stands out from all other office equipment, but can also be integrated into any other modern interior.






ROUND TRANSPARENT LED PANEL

- Eligible for BEG German federal funding for energy-efficient buildings (art. no. 342251/342252/342253 only)
- Light colour adjustable in three stages (art. no. 342251/342252/342253 only)
- Particularly delicate frame
- Low glare value
- Transparent luminous element

Application Area

Reception / Communication, Office / conference, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Base Ø	215 mm
Colour Temperature	3000/3500/4000 K	Power Supply Unit incl.	Yes
Power	50 W	Light Beam Angle	140 Degree
Rated Input Voltage	200-240 V/AC	Light Beam Angle 2	150 Degree
Height	12 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Ø	633 mm	CRI (Ra)	90
Pendulum Length	1800 mm	IK Protection Class	IK04
Base Height	43 mm		



Article	Housing Color		Luminous Flux	Price
342252	Black	WW NW	6000/6100/6100 lm	€ 419.95
342253	Light gray	WW NW	6100/6200/6200 lm	€ 419.95
342251	White	WW NW	6200/6400/6400 lm	€ 419.95



Accessories

843340 DALI, Triac dimmer, 100-240 V, 400 W, IP20




€ 74.95



LED PANEL TRANSPARENT ANGULAR

The LED pendant lamp has transparent glass for direct and indirect light distribution that is almost see-through when switched off. When the light is switched on, the pane distributes the light almost entirely without glare.

This pendant lamp is fully office-compatible with a glare value [UGR] of under 19. Bright, efficient and with a sophisticated design, this light not only stands out in any type of office environment.



LED PANEL TRANSPARENT ANGULAR

- Very low glare value
- Light colour adjustable in 2 stages
- Transparent luminous element
- Max. suspended mounting 1,800 mm

Application Area

Reception / Communication, Office / conference, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Base Length	570 mm
Colour Temperature	3000/4000 K	Base Width	80 mm
Luminous Flux	5600/6100 lm	Base Height	50 mm
Power	53 W	Power Supply Unit incl.	Yes
Rated Input Voltage	220-240 V/AC	Light Beam Angle	360 Degree
Length	295 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Width	1195 mm	CRI (Ra)	90
Height	12 mm		
Pendulum Length	1800 mm		

Article	Housing Color		Price
342219	Black	WW NW	€ 299.95
342220	Light gray	WW NW	€ 299.95
342221	White	WW NW	€ 299.95





D PROFESSION DOWN

Due to their flexible control options, you can use the D PROFESSION pendant lamps both in private and in commercial applications. In private settings, the dimmable Down version creates an exceptional atmosphere of illumination that blends perfectly with its modern design.






D PROFESSION DOWN

- High light output
- Very low glare value
- Dimmable
- Max. suspended mounting 3,000 mm

Application Area

Office / conference, Home office / study, Reception / Communication

Housing	Aluminium	Pendulum Length	3000 mm
Colour Temperature	4000 K	Base Length	560 mm
Luminous Flux	3165 lm	Base Width	65 mm
Power	28 W	Base Height	38 mm
Rated Input Voltage	200-240 V/AC	Power Supply Unit incl.	Yes
Length	1177.4 mm	Light Beam Angle	24 Degree
Width	53 mm	CRI (Ra)	80
Height	53 mm		



620057

Article	Housing Color		Control	Price
620102		Black	1-10 V	€ 339.95
620106		White	1-10 V	€ 339.95
620109		Silver	1-10 V	€ 339.95
620057		Black	DALI 1.0 / DT6	€ 359.95
620105		White	DALI 1.0 / DT6	€ 359.95
620108		Silver	DALI 1.0 / DT6	€ 359.95
620103		Black	Leading-edge dimmer / Trailing-edge dimmer	€ 329.95
620107		White	Leading-edge dimmer / Trailing-edge dimmer	€ 329.95
620110		Silver	Leading-edge dimmer / Trailing-edge dimmer	€ 329.95





D PROFESSION UP & DOWN

Due to their flexible control options, you can use the D PROFESSION pendant lamps both in private and in commercial applications. The Up and Down version emits its light in two directions. Whilst the LEDs directed upwards generate pleasant, indirect room lighting, the LEDs directed downwards ensure defined, powerful and UGR-compliant office and work lighting for desks and more.






D PROFESSION UP & DOWN

- High light output
- Low glare value
- Max. suspended mounting 3,000 mm
- Dimmable

Application Area

Office / conference, Home office / study, Reception / Communication

Housing	Aluminium	Pendulum Length	3000 mm
Colour Temperature	4000 K	Base Length	560 mm
Luminous Flux	7180 lm	Base Width	65 mm
Power	60 W	Base Height	38 mm
Rated Input Voltage	200-240 V/AC	Power Supply Unit incl.	Yes
Length	1177.4 mm	Light Beam Angle	110 Degree
Width	53 mm	Light Beam Angle 2	24 Degree
Height	53 mm	CRI (Ra)	80



620104

Article	Housing Color		Control	Price
620113			1-10 V	€ 399.95
620114			1-10 V	€ 399.95
620115			1-10 V	€ 399.95
620116			DALI 1.0 / DT6	€ 429.95
620117			DALI 1.0 / DT6	€ 429.95
620118			DALI 1.0 / DT6	€ 429.95
620104			Leading-edge dimmer / Trailing-edge dimmer	€ 399.95
620111			Leading-edge dimmer / Trailing-edge dimmer	€ 399.95
620112			Leading-edge dimmer / Trailing-edge dimmer	€ 399.95





OFFICE THREE

The pendant lamp is an appropriate addition to the OFFICE THREE MOTION standing lamp. As the glare value is under 10, this sophisticated light can be thought of as being almost entirely glare-free. The LEDs directed upwards create room lighting, whilst the LEDs directed downwards emit clearly defined and powerful light onto the work area.



OFFICE THREE

- Very low UGR value
- High luminous flux
- Controlled using DALI 2.0
- Including uplight for indirect light

Application Area

Reception / Communication, Office / conference, Home office / study, Education / school / lecture theatre

Housing	Aluminium	Base Length	600 mm
Colour Temperature	4000 K	Base Width	56.5 mm
Luminous Flux	7000 lm	Base Height	35 mm
Power	60 W	Power Supply Unit incl.	Yes
Rated Input Voltage	200-240 V/AC	Light Beam Angle	115 Degree
Length	1179 mm	Light Beam Angle 2	55 Degree
Width	64 mm	Control	DALI 2 / DT6
Height	35 mm	CRI (Ra)	80
Pendulum Length	2500 mm		

Article	Housing Color		Price
342146		Silver 	€ 599.95
342147		White 	€ 599.95






OFFICE ONE

- Very low glare value
- Service life 50,000 h L80B10
- Dimmable using touch sensor
- Ready to use

Application Area

Reception / Communication, Office / conference, Home office / study, Education / school / lecture theatre

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Length	610 mm	Power Supply Unit incl.	Yes
Width	310 mm	Light Beam Angle	110 Degree
Height	1950 mm	Light Beam Angle 2	90 Degree
Base Length	460 mm	Primary Cable Length	1.5 m
Base Width	300 mm	Primary Connection End	Power plug
Base Height	8 mm	CRI (Ra)	80
Power	80 W		



343030

Article	Housing Color	Colour Temperature	Luminous Flux	Price
343034	Silver	3000 K	6700 lm	€ 819.95
343030	Silver	4000 K	7400 lm	€ 819.95





OFFICE ONE MOTION

- Very low glare value
- Service life 50,000 h L80B10
- Dimmable using touch sensor
- Motion sensor
- Ready to use


Application Area

Reception / Communication, Office / conference, Home office / study, Education / school / lecture theatre

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Length	610 mm	Power Supply Unit incl.	Yes
Width	310 mm	Light Beam Angle	110 Degree
Height	1950 mm	Light Beam Angle 2	90 Degree
Base Length	460 mm	Primary Cable Length	1.5 m
Base Width	300 mm	Primary Connection End	Power plug
Base Height	8 mm	CRI (Ra)	80
Power	80 W	Motion Detector	Yes

Article	Housing Color	Colour Temperature	Luminous Flux	Price
343035	Silver	3000 K	6700 lm	€ 949.95
343032	Silver	4000 K	7400 lm	€ 949.95







OFFICE ONE TRANSPARENT

Application Area
Reception / Communication, Office / conference, Home office / study, Education / school / lecture theatre

Housing	Aluminium	Power	55 W
Colour Temperature	4000 K	Rated Input Voltage	200-240 V/AC
Luminous Flux	6245 lm	Power Supply Unit incl.	No
Length	610 mm	Light Beam Angle	150 Degree
Width	310 mm	Light Beam Angle 2	150 Degree
Height	1950 mm	Primary Cable Length	2.5 m
Base Length	500 mm	Primary Connection End	Power plug
Base Width	225 mm	CRI (Ra)	80
Base Height	8 mm		

Article	Housing Color		Price
343022	Silver	NW	€ 819.95







OFFICE TWO

- Very low glare value
- Service life 50,000 h L80B10
- Dimmable using rotary switch
- Ready to use including 2.5 m connecting cable

Application Area

Reception / Communication, Office / conference, Home office / study, Education / school / lecture theatre

Housing	Aluminium	Rated Input Voltage	200-240 V/AC
Colour Temperature	4000 K	Power Supply Unit incl.	No
Luminous Flux	8300 lm	Light Beam Angle	110 Degree
Length	610 mm	Light Beam Angle 2	90 Degree
Width	280 mm	Primary Cable Length	2.5 m
Height	1950 mm	Primary Connection End	Power plug
Power	80 W	CRI (Ra)	80

Article	Housing Color		Price
343016	Silver		€ 749.95





OFFICE THREE

The OFFICE THREE series is our bestseller and problem solver for lighting individual workstations. Available as a free-standing or table lamp, the OFFICE THREE impresses with excellent light quality [Ra95] and glare-free [UGR<6] and ensures fatigue-free working in any situation. Thanks to the individually adjustable brightness for direct and indirect light, OFFICE THREE enables high-quality and flexible illumination of individual workstations. Optimised for tables with standard dimensions of 160 x 80 cm, the series is also suitable for other table sizes.



High-precision radar presence detector

- The 24Ghz presence sensor recognises even the smallest movements on the desk - such as movements of the computer mouse - and switches the light on automatically. Faulty switch-offs are effectively prevented despite the short run-on time.
- Without movement, the brightness is reduced to 30% after 5*/15/30 minutes [*default setting].
- If there is no movement, the light switches off after a further 5*/15/30 minutes [*default setting].

Daylight sensor

- Switch on the light and dim to the desired brightness [this setting is saved by the daylight sensor as the default].
- As soon as the ambient light changes, the sensor adjusts the brightness according to the stored standard [10% tolerance].



Touch panel

- Brightness of direct and indirect light separately or synchronised, infinitely adjustable
- Direct and indirect light can be switched separately
- Continuously adjustable light colour [PRO models only]
- Adjustable run-on time of the presence sensor



Universal table clamp

- table clamp can be used for table tops with a total thickness of 15-65 mm [incl. substructure] as required
- If part of the frame construction runs in the clamping area of the luminaire, the hard rubber buffers supplied must be used to compensate for the unevenness and create a flush clamping area.
- The universal design of the table clamp allows it to be mounted on almost all table tops.



Optional mounting kit

- For larger table tops or for free positioning on the table, the optional mounting kit can be used instead of the pre-installed table clamp. This is simply mounted through a drill hole in the table.
- suitable for table tops with a total thickness of 15-35 mm
- suitable for hole diameters from 22-30 mm



OFFICE THREE STANDARD FLOOR

- Ideal for high-quality illumination of individual workstations
- Redesigned and extended lamp head for optimal illumination of 160x80 cm tables
- Direct and indirect light can be dimmed and switched separately using touch panel
- Light colour adjustable via touch panel
- High-precision radar presence detector detects the smallest movements
- Daylight sensor for dynamic brightness adjustment

Application Area

Reception / Communication, Office / conference, Home office / study, Education / school / lecture theatre

Housing	Aluminium	Power	80 W
Colour Temperature	4000 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	10100 lm	Power Supply Unit incl.	Yes
Length	1240 mm	Light Beam Angle	120 Degree
Width	64 mm	Light Beam Angle 2	50 Degree
Height	1950 mm	Primary Cable Length	2.5 m
Base Length	530 mm	Primary Connection End	Safety plug
Base Width	225 mm	CRI (Ra)	95
Base Height	10 mm	Motion Detector	Yes

Article	Housing Color		Price
342228	White	NW	€ 1249.95
342229	Light gray	NW	€ 1249.95
342230	Black	NW	€ 1249.95





OFFICE THREE STANDARD TABLE

- Ideal for high-quality illumination of height-adjustable individual workstations
- Newly designed and extended lamp head for ideal illumination of 160x80 cm tables
- Suitable for table designs with 15-65 mm thickness
- Direct and indirect light can be dimmed and switched separately using touch panel
- High-precision radar presence detector detects the smallest movements
- Adjustable switch-off delay of the sensor [5/15/30 mins]
- Daylight sensor for dynamic brightness adjustment
- Incl. 2.5 m connecting cable with safety plug and C21 mains plug
- Incl. hard rubber buffers for lining table designs running close to the edge



Application Area

Reception / Communication, Office / conference, Home office / study, Education / school / lecture theatre

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Colour Temperature	4000 K	Power Supply Unit incl.	Yes
Luminous Flux	10100 lm	Light Beam Angle	120 Degree
Length	1159 mm	Light Beam Angle 2	50 Degree
Width	64 mm	Primary Cable Length	2.5 m
Height	1194 mm	Primary Connection End	Safety plug
Base Length	500 mm	CRI (Ra)	95
Base Width	225 mm	Motion Detector	Yes
Power	80 W		

Article	Housing Color	Price
346063	White	€ 1049.95
346064	Light gray	€ 1049.95
346065	Black	€ 1049.95



Accessories for 346063

930727 Assembly kit for table lamp Office Three

€ 39.95

Accessories for 346064

930728 Assembly kit for table lamp Office Three

€ 39.95

Accessories for 346065

930729 Assembly kit for table lamp Office Three

€ 39.95



OFFICE THREE PRO FLOOR

- Ideal for high-quality illumination of individual workstations
- Redesigned and extended lamp head for ideal illumination of 160 x 80 cm tables
- Direct and indirect light can be dimmed and switched separately using touch panel
- High-precision radar presence detector detects the smallest movements
- Adjustable switch-off delay of the sensor [5/15/30 mins]
- Daylight sensor for dynamic brightness adjustment

Application Area

Reception / Communication, Office / conference, Home office / study, Education / school / lecture theatre

Housing	Aluminium	Power	80 W
Colour Temperature	2700-6500 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	9000/9800 lm	Power Supply Unit incl.	Yes
Length	1240 mm	Light Beam Angle	120 Degree
Width	64 mm	Light Beam Angle 2	50 Degree
Height	1950 mm	Primary Cable Length	2.5 m
Base Length	530 mm	Primary Connection End	Safety plug
Base Width	225 mm	CRI (Ra)	95
Base Height	10 mm	Motion Detector	Yes

Article	Housing Color		Price
342231	White		€ 1459.95
342232	Light gray		€ 1459.95
342233	Black		€ 1459.95





OFFICE THREE PRO TABLE

- Ideal for high-quality illumination of height-adjustable individual workstations
- Redesigned and extended lamp head for ideal illumination of 160 x 80 cm tables
- Suitable for table designs with 15-65 mm thickness
- Direct and indirect light can be dimmed and switched separately using touch panel
- Light colour adjustable via touch panel
- High-precision radar presence detector detects the smallest movements
- Daylight sensor for dynamic brightness adjustment



Application Area

Reception / Communication, Office / conference, Home office / study, Education / school / lecture theatre

Housing	Aluminium	Rated Input Voltage	200-240 V/AC
Colour Temperature	2700-6500 K	Power Supply Unit incl.	Yes
Luminous Flux	9000/9800 lm	Light Beam Angle	120 Degree
Length	1240 mm	Light Beam Angle 2	50 Degree
Width	64 mm	Primary Cable Length	2.5 m
Height	1194 mm	Primary Connection End	Safety plug
Base Length	500 mm	CRI (Ra)	95
Base Width	225 mm	Motion Detector	Yes
Power	80 W		

Article	Housing Color	Price
346066	☐ White WW CW	€ 1249.95
346067	☐ Light gray WW CW	€ 1249.95
346068	☒ Black WW CW	€ 1249.95



Accessories for 346066

930727 Assembly kit for table lamp Office Three

 € 39.95

Accessories for 346067

930728 Assembly kit for table lamp Office Three

 € 39.95

Accessories for 346068

930729 Assembly kit for table lamp Office Three

 € 39.95

hall floodlights



■
page 270



■
page 272



■
page 274



■
page 277







HIGHBAY BASIC

- cost-effective and powerful
- particularly energy-efficient and economical
- power adjustable in three stages
- light colour adjustable in three stages

Application Area

Workshop / Craft / Warehouse, DIY store / discount store / supermarket / car dealership, Industry / production / high-bay warehouse

Housing	Aluminium, Polycarbonate, Steel	Power Selectable	210 W, 160 W, 110 W
Colour Temperature	4000/4500/5700 K	Rated Input Voltage	100-277 V/AC
Luminous Flux	33500/34500/33500 lm	Power Supply Unit incl.	Yes
Height	111 mm	Light Beam Angle	90 Degree
Ø	302 mm	CRI (Ra)	80
		IK Protection Class	IK08

Article	Housing Color	Price
732162	Black	€ 175.95



Accessories

930977	60° Lens for Highbay Basic		€ 19.95
930978	120° Lens for Highbay Basic		€ 19.95
930641	Chain suspension 1 m for Alludra / Highbay Basic / Vega		€ 14.95
930685	Chain suspension 3 m for Alludra / Highbay Basic / Vega		€ 24.95
930742	Wall assembly arm for Vega OnOff, Highbay Basic		€ 39.95
930571	Outdoor cable conn. 2 cables 4-14 mm, 2-5 strands 0.5-4 mm², 450 V AC/24 A		€ 9.95
930573	Outdoor Y connector for 3 cables 4-14 mm, 3 strands, 0.5-4 mm², 450 V AC/24 A		€ 10.95





HIGHBAY BASIC DALI

- cost-effective and powerful
- particularly energy-efficient and economical
- power adjustable in three stages
- light colour adjustable in three stages
- with Intelli-Data: Dali Parts 251, 252, 253 for luminaire, energy and maintenance data

Application Area

Workshop / Craft / Warehouse, DIY store / discount store / supermarket / car dealership, Industry / production / high-bay warehouse


Housing	Aluminium, Polycarbonate, Steel	Power Selectable	210 W, 160 W, 110 W
Colour Temperature	4000/4500/5700 K	Rated Input Voltage	100-277 V/AC
Luminous Flux	33500/34500/33500 lm	Power Supply Unit incl.	Yes
Height	111 mm	Light Beam Angle	90 Degree
Ø	302 mm	Control	DALI 2 / DT6 D4i
		CRI (Ra)	80
		IK Protection Class	IK08

Article	Housing Color	Price
732163	Black	€ 209.95



Accessories

930977	60° Lens for Highbay Basic		€ 19.95
930978	120° Lens for Highbay Basic		€ 19.95
930641	Chain suspension 1 m for Alludra / Highbay Basic / Vega		€ 14.95
930685	Chain suspension 3 m for Alludra / Highbay Basic / Vega		€ 24.95
930742	Wall assembly arm for Vega OnOff, Highbay Basic		€ 39.95
930571	Outdoor cable conn. 2 cables 4-14 mm, 2-5 strands 0.5-4 mm², 450 V AC/24 A		€ 9.95



VEGA

The VEGA high-bay light - quality that shines through. The high-bay light is the perfect solution for industrial halls/warehouses where first-class lighting is required. The variant with three selectable output levels can adapt to your requirements. The spotlights are also very energy efficient, which has a positive effect on your operating costs. A long service life of 50,000 hours (L80B20) ensures reliable, no-compromise lighting for a long time to come. With optional lenses, the VEGA spotlights can achieve a UGR value below 19, ensuring glare-free light. We also offer variants with DALI control capability for those wanting precise lighting control. The high-bay lights are also eligible for BEG German federal funding for energy-efficient buildings.




VEGA

- High-quality, flexible and powerful high-bay lights
- Suitable for fire-prone facilities (EN60598-2-24)
- Output adjustable in three stages
- UGR <19 with optional lens
- Particularly energy efficient

Application Area

Workshop / Craft / Warehouse, DIY store / discount store / supermarket / car dealership, Industry / production / high-bay warehouse

Housing	Aluminium	Rated Input Voltage	100-277 V/AC
Surface	Powder-coated	Power Supply Unit incl.	Yes
Luminous Flux	15300/23400/28800 lm	Light Beam Angle	120 Degree
Height	120 mm	Primary Cable Length	1.5 m
Ø	400 mm	CRI (Ra)	80
Power Selectable	90 W, 130 W, 160 W	IK Protection Class	IK09



Article	Housing Color	Colour Temperature	Price
732156	Black	NW 4000 K	€ 319.95
732158	Black	CW 5700 K	€ 319.95



Accessories

- 930742 Wall assembly arm for Vega OnOff, Highbay Basic
- 930743 60° lens for Vega
- 930641 Chain suspension 1 m for Alludra / Highbay Basic / Vega
- 930685 Chain suspension 3 m for Alludra / Highbay Basic / Vega

	€ 39.95
	€ 49.95
	€ 14.95
	€ 24.95






VEGA DALI

- High-quality, flexible and powerful high-bay lights
- Suitable for fire-prone facilities (EN60598-2-24)
- UGR <19 with optional lens
- Particularly energy efficient

Application Area

Workshop / Craft / Warehouse, DIY store / discount store / supermarket / car dealership, Industry / production / high-bay warehouse

Housing	Aluminium	Power Supply Unit incl.	Yes
Surface	Powder-coated	Light Beam Angle	120 Degree
Luminous Flux	28800 lm	Control	DALI 2 / DT6
Height	122 mm	Primary Cable Length	1.5 m
Ø	400 mm	CRI (Ra)	80
Power	160 W	IK Protection Class	IK09
Rated Input Voltage	100-277 V/AC		



732157

Article	Housing Color	Colour Temperature	Price
732157	Black	NW 4000 K	€ 369.95
732159	Black	CW 5700 K	€ 369.95



Accessories

- 930743 60° lens for Vega
- 930775 Wall assembly arm for Vega DALI
- 930641 Chain suspension 1 m for Alludra / Highbay Basic / Vega
- 930685 Chain suspension 3 m for Alludra / Highbay Basic / Vega



damp-proof luminaires



■
page 280



■
page 282



■
page 283



□
page 284



□
page 285



□ ■ ■
page 286



□ ■ ■
page 288



□ ■ ■
page 289







TRI PROOF BASIC

- Eligible for BEG German federal funding for energy-efficient buildings
- Particularly energy efficient
- Long service life of 50,000 hours L80B50
- Pre-installed feed-through wiring 3x1.5 mm²/5x1.5 mm²
- Cable entry point on the back
- Stainless steel clips on the cover can be locked with screws
- Robust polycarbonate [PC] plastic housing

Application Area

Garage / carport / car park, Workshop / Craft / Warehouse, Industry / production / high-bay warehouse, Basement / damp room, Multi-storey car park / underground car park

Housing	Polycarbonate, Steel	Number in Row max.	15
Colour Temperature	4000 K	Power Supply Unit incl.	Yes
Width	82 mm	Light Beam Angle	120 Degree
Height	75 mm	CRI (Ra)	80
Rated Input Voltage	220-240 V/AC	IK Protection Class	IK08

Article	Housing Color		Luminous Flux	Length	Power	Price
730509	Light gray	NW	1400 lm	610 mm	10.0 W	€ 49.95
730483	Light gray	NW	2520 lm	610 mm	18.0 W	€ 54.95
730510	Light gray	NW	2800 lm	1210 mm	20.0 W	€ 69.95
730511	Light gray	NW	4200 lm	1510 mm	30.0 W	€ 79.95
730486	Light gray	NW	5040 lm	1210 mm	36.0 W	€ 79.95
730489	Light gray	NW	7700 lm	1510 mm	55.0 W	€ 94.95




Accessories

930713 Cable suspension for Tri Proof Basic



€ 19.95



TRI PROOF BASIC MOTION

- Eligible for German BEG federal funding
- Particularly energy efficient
- Long service life of 50,000 hours (L80B50)
- Continuous 3x1.5 mm²/5x1.5 mm² wiring pre-installed
- Cable entry point on the back
- Stainless steel clips on the cover can be locked with screws
- Robust polycarbonate (PC) plastic housing
- Adjustable radar motion sensor

Application Area

Garage / carport / car park, Workshop / Craft / Warehouse, Industry / production / high-bay warehouse, Basement / damp room, Multi-storey car park / underground car park

Housing	Polycarbonate (PC)/iron	Number in Row max.	15
		Power Supply Unit incl.	Yes
Colour Temperature	4000 K	Light Beam Angle	120 Degree
Width	82 mm	CRI (Ra)	80
Height	75 mm	Motion Detector	Yes
Rated Input Voltage	220-240 V/AC	IK Protection Class	IK08

Article	Housing Color		Luminous Flux	Length	Power	Price
730484		Light gray	2520 lm	610 mm	18.0 W	€ 74.95
730487		Light gray	5040 lm	1210 mm	36.0 W	€ 99.95
730490		Light gray	7700 lm	1510 mm	55.0 W	€ 114.95



Accessories

930713 Cable suspension for Tri Proof Basic



€ 19.95



Technical data sheet
New in the onlineshop: The technical data sheets offer even more information: Light and energy data, light distribution curves, dimensional drawings and more.



TRI PROOF BASIC DALI

- Eligible for BEG German federal funding for energy-efficient buildings
- Emergency power capable [180-264 V/DC EOFI: 15 %]
- Particularly energy efficient
- Long service life of 50,000 hours L80B50
- Pre-installed feed-through wiring 3x 1.5 mm²/5x 1.5 mm² [DALI]
- Cable entry point on the back
- Stainless steel clips on the cover can be locked with screws
- Robust plastic housing

Application Area

Garage / carport / car park, Workshop / Craft / Warehouse, Industry / production / high-bay warehouse, Basement / damp room, Multi-storey car park / underground car park, Safety lighting / emergency lighting

Housing	Polycarbonate (PC)/iron	Power Supply Unit incl.	Yes
Colour Temperature	4000 K	Light Beam Angle	120 Degree
Width	82 mm	Control	DALI 2 / DT6, Intelli Push-Dim
Height	75 mm	CRI (Ra)	80
Rated Input Voltage	220-240 V/AC	IK Protection Class	IK08
Number in Row max.	15		

Article	Housing Color	Luminous Flux	Length	Power	Price
730485	Light gray	2520 lm	610 mm	18.0 W	€ 104.95
730488	Light gray	5040 lm	1210 mm	36.0 W	€ 129.95
730491	Light gray	7700 lm	1510 mm	55.0 W	€ 159.95



Accessories

930713 Cable suspension for Tri Proof Basic



€ 19.95



5-year guarantee

Benefit from the maximum quality promise:

All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.




TRI PROOF

- Pre-installed feed-through wiring
- Including mounting clips

Application Area

Garage / carport / car park, Workshop / Craft / Warehouse, Industry / production / high-bay warehouse, Basement / damp room, Multi-storey car park / underground car park


Housing	Plastic	Rated Input Voltage	180-240 V/AC
Surface	Matt	Power Supply Unit incl.	Yes
Colour Temperature	4000 K	Light Beam Angle	120 Degree
Width	61 mm	CRI (Ra)	80
Height	56 mm	IK Protection Class	IK08



730419

Article	Housing Color		Luminous Flux	Length	Power	Number in Row max.	Price
730419	☐ White	NW	1430 lm	696 mm	17.0 W	25	€ 53.95
730424	☐ White	NW	2980 lm	1296 mm	35.0 W	15	€ 82.95
730425	☐ White	NW	3820 lm	1598 mm	44.0 W	10	€ 88.95






TRI PROOF MOTION

- High impact resistance
- Pre-installed feed-through wiring
- Including mounting clips

Application Area

Garage / carport / car park, Workshop / Craft / Warehouse, Industry / production / high-bay warehouse, Basement / damp room, Multi-storey car park / underground car park

Housing	Plastic	Power Supply Unit incl.	Yes
Surface	Matt	Light Beam Angle	120 Degree
Colour Temperature	4000 K	CRI (Ra)	80
Width	61 mm	Motion Detector	Yes
Height	56 mm	IK Protection Class	IK08
Rated Input Voltage	220-240 V/AC		



730450

Article	Housing Color	Luminous Flux	Length	Power	Price
730450	☐ White NW	1900 lm	665 mm	18.5 W	€ 62.95
730455	☐ White NW	2500 lm	1145 mm	24.5 W	€ 74.95




Accessories


- 930071** Cable suspension adjustable for Tri Proof lamp, 2 pieces
- 930072** Surface-mounted holder for Tri Proof lamp, 2 pieces



€ 14.95

€ 14.95





SOTANO

- Classic cellar light with modern LED technology
- Colour temperature adjustable (3,000/4,000 K) via slide switch
- Output adjustable in two stages (4.5/7.5 W) via slide switch
- Six cable entry points on multiple sides
- Flexible installation

Application Area

Garage / carport / car park, Workshop / Craft / Warehouse, Basement / damp room, Multi-storey car park / underground car park, Refurbishment

Housing	Polycarbonate	Power Selectable	4.5 W, 7.5 W
Colour Temperature	3000/4000 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	450/750 lm	Power Supply Unit incl.	Yes
Length	165 mm	Light Beam Angle	120 Degree
Width	120 mm	IK Protection Class	IK08
Height	65 mm		

Article	Housing Color		Price
731160	White	NW	€ 16.95
731161	Grey	NW	€ 16.95
731162	Black	NW	€ 16.95



Lighting design

Interested in our lighting design service?

Your contact person will be happy to answer any questions you may have.



SOTANO RETRO ROUND

- Classic, low-cost cellar lamp
- Replaceable lamp [E27]
- Cable entry on multiple sides
- Several mounting points for flexible installation

Application Area

Garage / carport / car park, Workshop / Craft / Warehouse, Basement / damp room

Housing	PP - Polypropylene	Rated Input Voltage	220-240 V/AC
Height	100 mm	Control	Dimmable via optional light source
Ø	180 mm	IK Protection Class	IK06
Max. Power	1x max. 60 W		

Article	Housing Color	Price
731163	White	€ 13.95
731164	Grey	€ 13.95
731165	Black	€ 13.95



Light sources
For all lights and bases:
You can find the right light sources in the »Light sources« section.



SOTANO RETRO OVAL

- Classic, low-cost cellar lamp
- Replaceable lamp [E27]
- Cable entry on multiple sides
- Several mounting points for flexible installation

Application Area

Garage / carport / car park, Workshop / Craft / Warehouse, Basement / damp room

Housing	PP - Polypropylene	Rated Input Voltage	220-240 V/AC
Length	186 mm	Control	Dimmable via optional light source
Width	122 mm	IK Protection Class	IK06
Height	108 mm		
Max. Power	1x max. 60 W		

Article	Housing Color	Price
731166	White	€ 10.95
731167	Grey	€ 10.95
731168	Black	€ 10.95



Light sources

For all lights and bases:


You can find the right light sources in the »Light sources« section.





SINGLE-PHASE LIGHTS

294 single-phase lights



single-phase lights



page 296



page 298



SANOTRUNK UNIVERSAL – THE SMART SOLUTION FOR MODERN LIGHTING REFURBISHMENTS

Want to modernize old T5 and T8 trunking systems efficiently and sustainably? With SANOTRUNK UNIVERSAL, you can make almost any trunking system fit for the future.

SANOTRUNK UNIVERSAL sets new standards in terms of compatibility. Thanks to quick-fit clips and tool-free installation, the system can be integrated into almost all standard trunking systems - whether from Philips, RIDI, Trilux, Zumtobel or other manufacturers. The continuous halogen-free 5 or 7-core through-wiring, the integrated plug connectors and a selection of interchangeable lens optics [including 30°, 90°, 25° asymmetrical on one or both sides] make adaptation to any application child's play. The conversion is carried out in five simple steps:



1 - old light inserts removed [wiring remains in]



2 - hang new LED modules in old mounting rail



3 - connect modules and adjust power if necessary



4 - click in the modules



5 - finished


COMPATIBILITY OVERVIEW

brand	trunk name	shape
AEG	Gealux-TS XX	
AEG/PHILIPS	Maxos	
Antaris	Antaris	
Antaris	trunking system	
ClickLUX Tragschiene	701501880016/ 703002880017/ 704503880018	
Fluolite	TRX / TRZ	
Fluora	Mini-Fix	
Kandem	SV70 / SV75	
Lite Licht	E-STN	
Lite Licht	Q-EMMS	
Lite Licht	Q-Rail Q-TS	
Lite Licht	Q-STN***	
Litec		
Ludwig	TR50W	
Lunix	Q-STN***	
MOLTOMX	Prestige	
Newlec	HSDT	
Norton	NSL	
OMS	Prestige	
Philips	Maxos TL5 / Maxos TL-D	
Philips	TTX150	
Philips	TTX200	
Philips	TTX400	
Philips	TTX400 T5 / TTX400 T8	
Regent	Traq	

brand	trunk name	shape
Regent	ICE**	
Regiolux	SDT	
Regiolux	SDT XX	
Regiolux	SMT / SPT	
RIDI	VLG XX	
RIDI, new trunking system	VLT***	
RIDI, new trunking system	VLT XX	
RZB	Planos	
Siemens	5LJ80XX	
Siemens	5LJ9*	
Siemens	5LS8..	
Siteco	DUS*	
Siteco	Modario	
Thron	090554 / 098287	
Trilux	07650XX	
Trilux	07690XX	
Trilux	218120 (7761/7861)	
Trilux	7910X** / 7920X**	
Trilux	7770	
VEKO	PRN	
Zumtobel	PNR	
Zumtobel	Tecton	
Zumtobel	ZX1	
Zumtobel	ZX2 T8 / ZX2 T5	

with optional mounting bracket

* 930931 | ** 930932 | *** 930933



SANOTRUNK UNIVERSAL

The SANOTRUNK light strip system is a specially developed renovation solution for the fast and cost-efficient modernisation of existing T5 and T8 light strip systems. The complete continued use of the existing mounting rail systems minimises the installation costs and effort and enables tool-free installation.

Due to the compatible system architecture, SANOTRUNK can be integrated into existing mounting rails from leading manufacturers such as Philips, Trilux, Siteco, Zumtobel, Regiolux, Ridi, Fluolite and many more. The pre-assembled through-wiring with 2.5 mm² cable cross-section allows seamless power supply over long light strips and multiple circuits.

The lighting can be individually adjusted using integrated power switch technology or DALI control (depending on the model). Optional dummy covers and connectors enable a versatile light strip design so that modules that are not required can be left out or customised distances can be achieved.





SANOTRUNK UNIVERSAL

- Renovation solution for T5/T8 light strip systems
- Continued use of existing mounting rails possible
- Easy, quick and reliable installation
- Compatible with leading manufacturers
- Eligible for BEG German federal funding for energy-efficient buildings
- Can run on emergency power
- Can be individually adapted to the lighting circumstances

Application Area

Shop / Retail / Sales area, DIY store / discount store / supermarket / car dealership, Industry / production / high-bay warehouse, Refurbishment, Safety lighting / emergency lighting


Housing	Aluminium	Height	31 mm
Colour Temperature	4000 K	Rated Input Voltage	198-264 V/AC
Length	1528 mm	CRI (Ra)	80
Width	65.6 mm	IK Protection Class	IK04

Article	Housing Color	Luminous Flux	Power Selectable	Light Beam Angle	Price
707228	☐ White	NW 11600 lm	75 / 68 / 59 / 52 / 42 / 36 / 27 / 21 W	120 Degree	€ 224.95
707227	☐ White	NW 12200 lm	70 / 64 / 55 / 49 / 39 / 34 / 26 / 20 W	90 Degree	€ 224.95
707226	☐ White	NW 12400 lm	70 / 64 / 55 / 49 / 39 / 34 / 26 / 20 W	30 Degree	€ 224.95




Accessories


930915	Sanotrunk Universal Lense, Set 5 pcs, 30 degree		€ 29.95
930916	Sanotrunk Universal Lense, Set 5 pcs, 60 degree		€ 29.95
930917	Sanotrunk Universal Lense, Set 5 pcs, 90 degree		€ 29.95
930918	Sanotrunk Universal Lense, Set 5 pcs, 25 degree, single side asymmetrical		€ 29.95
930919	Sanotrunk Universal Lense, Set 5 pcs, 25 degree, double side asymmetrical		€ 29.95
930920	Sanotrunk universal dummy cover, shortenable, PC		€ 19.95
930922	Sanotrunk Universal Blind Cover Aluminium		€ 39.95
930921	Sanotrunk universal mounting clips for blind cover, can be shortened 2 pcs.		€ 4.95
930931	Sanotrunk universal mounting clips Siteco DUS / Simens 5LJ9 2 pcs.		€ 4.95
930932	Sanotrunk universal mounting clamps Regent ICE 2 pcs.		€ 4.95
930933	Sanotrunk universal mounting clips RIDI VLT(old) / Lite-Light Q-STN / Lunux Q-STN 2 pcs.		€ 4.95
930923	Sanotrunk Universal Power feed socket WAGO 267-501		€ 11.95
930924	Sanotrunk Universal Power supply plug WAGO 267-510		€ 11.95
930925	Sanotrunk Universal Power supply socket On/Off wired WAGO 267-501		€ 14.95
930927	Sanotrunk Universal Power supply plug On/Off wired WAGO 267-510		€ 17.95
930929	Connector, Sanotrunk Universal		€ 44.95




30°




90°




120°



60°



25°, asymmetrical on one side



25°, double-sided asymmetrical





SANOTRUNK UNIVERSAL DALI

- Renovation solution for T5/T8 light strip systems
- Continued use of existing mounting rails possible
- Easy, quick and reliable installation
- Compatible with leading manufacturers
- Eligible for BEG German federal funding for energy-efficient buildings
- Can run on emergency power
- DALI versions with Intelli-Data: Dali parts 251, 252, 253 for lighting, energy and main-tenance data
- Can be individually adapted to the lighting circumstances

Application Area

Shop / Retail / Sales area, DIY store / discount store / supermarket / car dealership, Industry / production / high-bay warehouse, Refurbish-ment, Safety lighting / emergency lighting

Housing	Aluminium	Rated Input Voltage	198-264 V/AC
Colour Temperature	4000 K	Control	DALI 2 / DT6, Push-Dim
Length	1528 mm	CRI (Ra)	80
Width	65.6 mm	IK Protection Class	IK04
Height	31 mm		

Article	Housing Color	Luminous Flux	Power	Light Beam Angle	Price
707231	 White 	11600 lm	75.0 W	120 Degree	€ 274.95
707230	 White 	12200 lm	70.0 W	90 Degree	€ 274.95
707229	 White 	12400 lm	70.0 W	30 Degree	€ 274.95



Accessories

930915	Sanotrunk Universal Lense, Set 5 pcs, 30 degree		€ 29.95
930916	Sanotrunk Universal Lense, Set 5 pcs, 60 degree		€ 29.95
930917	Sanotrunk Universal Lense, Set 5 pcs, 90 degree		€ 29.95
930918	Sanotrunk Universal Lense, Set 5 pcs, 25 degree, single side asymmetrical		€ 29.95
930919	Sanotrunk Universal Lense, Set 5 pcs, 25 degree, double side asymmetrical		€ 29.95
930920	Sanotrunk universal dummy cover, shortenable, PC		€ 19.95
930922	Sanotrunk Universal Blind Cover Aluminium		€ 39.95
930921	Sanotrunk universal mounting clips for blind cover, can be shortened 2 pcs.		€ 4.95
930931	Sanotrunk universal mounting clips Siteco DUS / Simens 5LJ9 2 pcs.		€ 4.95
930932	Sanotrunk universal mounting clamps Regent ICE 2 pcs.		€ 4.95
930933	Sanotrunk universal mounting clips RIDI VLT(old) / Lite-Light Q-STN / Lunux Q-STN 2 pcs.		€ 4.95
930923	Sanotrunk Universal Power feed socket WAGO 267-501		€ 11.95
930924	Sanotrunk Universal Power supply plug WAGO 267-510		€ 11.95
930926	Sanotrunk Universal Power supply socket DALI wired WAGO 267-501		€ 14.95
930928	Sanotrunk Universal Power supply plug DALI wired WAGO 267-510		€ 17.95
930930	Connector, Sanotrunk Universal		€ 49.95



POWER RAILS

- 304 D ONE 1-phase power rail system
- 322 1-phase power rail luminaires
- 338 D LINE 3-phase power rail system
- 370 D LINE DALI 3-phase power rail system
- 398 power rail luminaires

D ONE system



page 308



page 310



page 310



page 311



page 312



page 312



page 313



page 313



page 314



page 314



page 315



page 316



☐ ☒
page 316



☐ ☒
page 316



☐ ☒
page 317



☐ ☒
page 318





















☐ ☒
page 318

D ONE MOUNTING POWER RAIL SYSTEM 1-PHASE 230V


mounting modules	illust.	white	black	page
mounting power rail L: 1000 mm	01	720000	720003	309
mounting power rail L: 2000 mm	01	720001	720004	309
mounting power rail L: 3000 mm	01	720002	720005	309
feeder left	02	720006	720007	310
feeder right	03	720008	720009	310
flex feeder with ceiling canopy	04	720010	720011	311
electrical straight connector with center feed option	05	720012	720013	312
electrical connector	06	720014	720015	312
90°-joint left	07	720016	720017	313
90°-joint right	08	720018	720019	313
T-joint left-right-right	09	720020	720021	315
T-joint right-right-left	10	720022	720023	314
T-joint left-left-right	11	720024	720025	315
T-joint right-left-left	12	720026	720027	314
X-joint left-left-right-right	13	720028	720029	316
endcap	14	720030	720031	316
cover panel	15	720038	720039	316
ceiling mounting bracket flex	16	720032	720033	318
wire suspension bracket 3000 mm	17	720034	720035	318
1-phase adapter for light installation	18	720036	720037	317

ILLUSTRATIONS WITH PLANNING-RELEVANT DIMENSIONS




FIXING POINTS

power rail	a	b	c	d
1000 mm	125 mm			
2000 mm	125 mm	870 mm		
3000 mm	125 mm		790 mm	1160 mm




MECHANICAL LOAD TRACK POWER RAIL 1000 MM

10 N ± 1,02 kg
 dimension in mm




MECHANICAL LOAD TRACK POWER RAIL 2000MM

10 N ± 1,02 kg
 dimension in mm




MECHANICAL LOAD TRACK POWER RAIL 3000MM

10 N ± 1,02 kg
 dimension in mm



PLANNING GUIDE D ONE TRACK SYSTEM 1-PHASE 230V





D ONE SURFACE-MOUNTED POWER TRACK

D ONE is the single-phase, 230 V busbar system from DEKO-LIGHT. This extremely compact and sophisticated system combines the benefits of 48 V low-voltage busbars [slim design] with the practical advantages of fully fledged 230 V systems [no transformer required for operation]. Their small size allows all D ONE components to integrate seamlessly into an extremely wide variety of environments, adding a timeless, understated, premium look to private dwellings and commercial facilities like shops and bars. All D ONE components are available in the universally suitable colours black and white, allowing a wide variety of installation options for flexible and universal use. The flexible infeed with ceiling canopy even allows D ONE busbars to be installed in places where there is no power supply available in the immediate vicinity.



D ONE SURFACE-MOUNTED POWER TRACK

- elegant and compact mini design
- easy to install
- many different designs available
- Mini design with one current phase

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Width	26.2 mm	Output Current	16 A
Height	22.2 mm		

Article	Housing Color	Length	Price
720000	☐ White	1000 mm	€ 39.95
720003	☒ Black	1000 mm	€ 39.95
720001	☐ White	2000 mm	€ 69.95
720004	☒ Black	2000 mm	€ 69.95
720002	☐ White	3000 mm	€ 99.95
720005	☒ Black	3000 mm	€ 99.95



Accessories for **720000, 720001, 720002**
720038 D One cover panel for integrated busbar, white

 € 5.95

Accessories for **720003, 720004, 720005**
720039 D One cover panel for integrated busbar, black

 € 5.95



Lighting design
Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.



D ONE ELECTRIC FEEDER LEFT

- Power can be fed in from above (ceiling) or from the side
- Elegant and compact mini design
- Simple installation
- Enables flexible installation options

Housing	Plastic	Height	22.2 mm
Length	71 mm	Rated Input Voltage	220-240 V/AC
Width	26 mm	Output Current	16 A

Article	Housing Color	Price
720006	 White	€ 13.95
720007	 Black	€ 13.95



D ONE ELECTRIC FEEDER RIGHT

- Power can be fed in from above (ceiling) or from the side
- elegant and compact mini design
- easy to install
- enables flexible installation options

Housing	Plastic	Height	22.2 mm
Length	71 mm	Rated Input Voltage	220-240 V/AC
Width	26 mm	Output Current	16 A

Article	Housing Color	Price
720008	 White	€ 13.95
720009	 Black	€ 13.95





D ONE FLEX FEEDER WITH CEILING CANOPY

- Elegant and compact mini design
- Easy to install
- Power supply via ceiling baldachin/current track adapter (200-1,000 mm)
- Enables various installation options

Housing	Plastic, Metal	Rated Input Voltage	220-240 V/AC
Length	1000 mm	Output Current	6 A
Width	120 mm	Connected Load max.	1320 W
Height	28 mm		

Article	Housing Color	Price
720010	White	€ 39.95
720011	Black	€ 39.95





D ONE ELECTRICAL STRAIGHT CONNECTOR WITH FEED OPTION

- Elegant and compact mini design
- Easy to install
- Power supply from above (from ceiling)

Housing	Plastic	Height	22.2 mm
Length	121 mm	Rated Input Voltage	220-240 V/AC
Width	26 mm	Output Current	16 A

Article	Housing Color	Price
720012	 White	€ 24.95
720013	 Black	€ 24.95




D ONE MINI-STRAIGHT CONNECTOR

- elegant and compact mini design
- easy to install

Housing	Plastic	Height	22 mm
Length	62 mm	Rated Input Voltage	220-240 V/AC
Width	26 mm	Output Current	16 A

Article	Housing Color	Price
720014	 White	€ 8.95
720015	 Black	€ 8.95






D ONE 90°-CONNECTOR LEFT

- Optional power supply from above (from ceiling)
- Elegant and compact mini design
- Easy to install
- Many different design shapes possible

Housing	Plastic	Height	22.2 mm
Length	73 mm	Rated Input Voltage	220-240 V/AC
Width	73 mm	Output Current	16 A

Article	Housing Color	Price
720016	 White	€ 24.95
720017	 Black	€ 24.95




D ONE 90°-CONNECTOR RIGHT

- Optional power supply from above (from ceiling)
- Elegant and compact mini design
- Easy to install
- Many different design shapes possible

Housing	Plastic	Height	22.2 mm
Length	73 mm	Rated Input Voltage	220-240 V/AC
Width	73 mm	Output Current	16 A

Article	Housing Color	Price
720018	 White	€ 24.95
720019	 Black	€ 24.95






D ONE T-CONNECTOR RIGHT-LEFT-LEFT

- Optional power supply from above (from ceiling)
- Elegant and compact mini design
- Easy to install
- Many different design shapes possible

Housing	Plastic	Height	22.2 mm
Length	121 mm	Rated Input Voltage	220-240 V/AC
Width	73 mm	Output Current	16 A

Article	Housing Color	Price
720026	White	€ 34.95
720027	Black	€ 34.95




D ONE T-CONNECTOR RIGHT-RIGHT-LEFT

- Optional power supply from above (from ceiling)
- Elegant and compact mini design
- Easy to install
- Many different design shapes possible

Housing	Plastic	Height	22.2 mm
Length	121 mm	Rated Input Voltage	220-240 V/AC
Width	73 mm	Output Current	16 A

Article	Housing Color	Price
720022	White	€ 34.95
720023	Black	€ 34.95






D ONE T-CONNECTOR LEFT-RIGHT-RIGHT

- Power can be fed in from above [via ceiling]
- Elegant and compact mini design
- Easy to install
- Enables many different design shapes

Housing	Plastic	Height	22.2 mm
Length	121 mm	Rated Input Voltage	220-240 V/AC
Width	73 mm	Output Current	16 A

Article	Housing Color	Price
720020	 White	€ 34.95
720021	 Black	€ 34.95



D ONE T-CONNECTOR LEFT-LEFT-RIGHT

- Power can be fed in from above [via ceiling]
- Elegant and compact mini design
- Easy to install
- Enables many different design shapes

Housing	Plastic	Height	22.2 mm
Length	121 mm	Rated Input Voltage	220-240 V/AC
Width	73 mm	Output Current	16 A

Article	Housing Color	Price
720024	 White	€ 34.95
720025	 Black	€ 34.95






D ONE X-CONNECTOR

- Power can be fed in from above [via ceiling]
- Easy to install

Housing	Plastic	Height	22.2 mm
Length	121 mm	Rated Input Voltage	220-240 V/AC
Width	121 mm	Output Current	16 A



Article	Housing Color	Price
720028	White	€ 49.95
720029	Black	€ 49.95



D ONE COVER PANEL

- suitable for D-One surface-mounted system
- for covering live busbars < 2.30 m high (contact zone)

Housing	Plastic	Width	16.5 mm
Length	1000 mm	Height	6.8 mm

Article	Housing Color	Price
720038	White	€ 5.95
720039	Black	€ 5.95



D ONE END CAP

- Current touch protection
- For closing open current track ends

Housing	Plastic	Width	26 mm
Length	15 mm	Height	22.2 mm

Article	Housing Color	Price
720030	White	€ 3.95
720031	Black	€ 3.95



D ONE 1-PHASE ADAPTER FOR LIGHT INSTALLATION

- Elegant and compact mini design
- Easy to install
- 230 V adapter for converting lights
- Delivery incl. mounting material (reduction bush, flat M10 nut, strain relief)

Housing	Plastic, Metal	Rated Input Voltage	220-240 V/AC
Length	70 mm	Output Current	6 A
Width	26 mm	Loading Weight max.	1 kg
Height	30 mm	Load Force max.	100 N

Article	Housing Color	Price
720036	☐ White	€ 16.95
720037	☒ Black	€ 16.95





D ONE MOUNTING BRACKET FLEX

- Simplifies the installation of more complex track shapes
- Enables numerous design forms
- Expands options for installation

Housing	Metal	Width	28 mm
Length	30 mm	Height	10.5 mm

Article	Housing Color	Price
720032	 White	€ 5.95
720033	 Black	€ 5.95



D ONE ROPE SUSPENSION BRACKET

- Stylish and sophisticated suspended mounting
- Enables numerous design forms
- Expands options for installation
- Can be cut to length for hanger lengths: 70-3,020 mm

Housing	Metal	Width	28 mm
Length	120 mm	Height	3020 mm

Article	Housing Color	Price
720034	 White	€ 19.95
720035	 Black	€ 19.95



1-phase power rail luminaires



page 322



page 325



page 326



page 328



page 329



page 330



page 332



page 333



page 334



page 335







CAN

- customised lighting solution thanks to replaceable light source
- can be combined with the product family of the CAN series

Application Area

Home / Living, Reception / Communication, Hotel / catering

Housing	Aluminium, Polycarbonate	Rated Input Voltage	220-240 V/AC
Length	134 mm	Control	Dimmable via optional light source
Ø	60 mm	Rotation Angle	350 Degree
Max. Power	1x max. 7.5 W	Swivelling Angle	90 Degree

Article	Housing Color	Price
707155	White	€ 41.95
707156	Black	€ 41.95



Accessories

930301	Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series	€ 4.95
930302	Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series	€ 4.95
930303	Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series	€ 4.95
930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series	€ 8.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series	€ 8.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series	€ 8.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series	€ 8.95
930366	Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series	€ 4.95
931065	Acrylic attachment for Can	€ 4.95



page 46

page 88

page 92

page 202

page 222

page 414

page 507





CAN

- customisable with extensive accessories
- customised lighting solution thanks to replaceable light source
- combinable with the extensive product family of the CAN series

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Ø	60 mm	Control	Dimmable via optional light source
Pendulum Length	1500 mm		
Max. Power	1x max. 7.5 W		

Article	Housing Color	Height	Price
707253	White	150 mm	€ 77.95
707254	Black	150 mm	€ 77.95
707257	White	350 mm	€ 91.95
707258	Black	350 mm	€ 91.95



Accessories

930301	Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930302	Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930303	Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930366	Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
931065	Acrylic attachment for Can		€ 4.95



CAN BASE MIX'N MATCH 1/3

- customised lighting solution thanks to interchangeable light source
- can be customised with cylinder housing in 6 different colours
- can be combined with the extensive product family of the CAN series

Housing	Aluminium	Control	Dimmable via optional light source
Height	74 mm	Rotation Angle	350 Degree
Ø	70 mm	Swivelling Angle	90 Degree
Max. Power	1x max. 7.5 W		
Rated Input Voltage	220-240 V/AC		

Article	Housing Color	Price
707249	White	€ 35.99
707250	Black	€ 35.99



Light sources
For all lights and bases:
You can find the right light sources in the »Light sources« section.



CYLINDER HOUSING FOR CAN MIX'N MATCH 2/3

Housing Aluminium Ø 60 mm
Height 98 mm

Article	Housing Color	Price
931053	White	€ 7.95
931054	Black	€ 7.95
931055	Bronze	€ 18.95
931056	Brass	€ 18.95
931057	Black gray	€ 18.95
931058	Rosé	€ 18.95

IP20



REFLECTOR RING CAN SERIES MIX'N MATCH 3/3

Housing Plastic Ø 57 mm
Height 28 mm

Article	Housing Color	Price
930301	 White	€ 4.95
930302	 Black	€ 4.95
930303	 Gold	€ 4.95
930366	 Silver	€ 4.95

IP20



NIHAL MINI

- can be rotated and swivelled
- can be customised with a wide range of accessories

Application Area

Home / Living, Reception / Communication, Hotel / catering

Housing	Aluminium, Polycarbonate	Rated Input Voltage	220-240 V/AC
Colour Temperature	2700 K	Power Supply Unit incl.	Yes
Luminous Flux	720 lm	Light Beam Angle	36 Degree
Length	94 mm	Rotation Angle	350 Degree
Width	102 mm	Swivelling Angle	350 Degree
Height	126 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Ø	60 mm	CRI (Ra)	90
Power	10.9 W		

Article	Housing Color	Price
707185	White	€ 151.95
707186	Black	€ 151.95



Accessories

930297	Side cover white for Nihal Mini series	€ 3.95
930298	Side cover black for Nihal Mini series	€ 3.95
930364	Side cover silver for Nihal Mini series	€ 3.95
930299	Side cover gold for Nihal Mini series	€ 3.95
930300	Side cover walnut wood look for Nihal Mini series	€ 5.95
930768	Side cover natural oak wood look for Nihal Mini series	€ 5.95
930301	Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series	€ 4.95
930302	Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series	€ 4.95
930303	Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series	€ 4.95
930366	Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series	€ 4.95
930765	24° reflector for Nihal Mini series	€ 10.95
930305	36° reflector for Klara/Nihal Mini/Rigel Mini/Uni II series	€ 3.60
930306	48° reflector for Klara/Nihal Mini/Rigel Mini/Uni II series	€ 8.95
930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series	€ 8.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series	€ 8.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series	€ 8.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series	€ 8.95
930767	12° lens for Nihal Mini series	€ 10.95



UNI 2 MINI

- „Glow“ effect on the reflector ring
- Rotatable and swivelling
- Can be customised with a wide range of accessories

Application Area

Home / Living, Reception / Communication, Hotel / catering

Housing	Aluminium, Steel, Polycarbonate	Power Supply Unit incl.	Yes
Colour Temperature	2700 K	Light Beam Angle	36 Degree
Height	128 mm	Rotation Angle	350 Degree
Ø	75 mm	Swivelling Angle	90 Degree
Power	11.3 W	Control	Leading-edge dimmer, Trailing-edge dimmer
Rated Input Voltage	220-240 V/AC	CRI (Ra)	90

Article	Housing Color	Luminous Flux	Price
707188	Black	700 lm	€ 135.96
707187	White	730 lm	€ 135.96



Accessories

930327	Rear black cover for Uni II Mini series		€ 3.45
930328	White heat sink cover for Uni II Mini series		€ 3.55
930329	Black heat sink cover for Uni II Mini series		€ 2.95
930330	Reflector ring white for Uni II Mini series		€ 10.95
930331	Reflector ring black for Uni II Mini series		€ 10.95
930332	Reflector ring gold for Uni II Mini series		€ 10.95
930333	Reflector ring chrome for Uni II Mini series		€ 10.95
930770	Reflector 24° for Uni II Mini series		€ 10.95
930771	Reflector 48° for Uni II Mini series		€ 10.95






SLIM

- glare-free thanks to low UGR value (<19)
- slim design with just 39 mm diameter
- incl. silver-coloured reflector ring

Application Area

Home / Living, Reception / Communication, Hotel / catering

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	2700 K	Light Beam Angle	36 Degree
Luminous Flux	500 lm	Rotation Angle	330 Degree
Length	197 mm	Swivelling Angle	60 Degree
Ø	39 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Power	5 W	CRI (Ra)	90
Rated Input Voltage	220-240 V/AC		



707201

Article	Housing Color		Price
707201	White		€ 83.95
707202	Black		€ 83.95



Accessories

930744	Reflector ring white for Slim series		€ 4.95
930745	Reflector ring black for Slim series		€ 4.95
930746	Reflector ring gold-coloured for Slim series		€ 5.95
930748	36° lens for Slim series		€ 4.95
930749	60° lens for Slim series		€ 4.95




SLIM

- Extra-soft fabric cable
- Glare-free, due to low UGR value [<19]
- Slim design at just 39 mm in diameter
- Max. suspended mounting: 1,800 mm

Application Area

Home / Living, Reception / Communication, Hotel / catering

Housing	Aluminium	Power	5 W
Colour Temperature	2700 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	500 lm	Power Supply Unit incl.	Yes
Length	1800 mm	Light Beam Angle	24 Degree
Height	300 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Ø	39 mm	CRI (Ra)	90
Pendulum Length	1800 mm		



707163

Article	Housing Color		Price
707163	Black	WW	€ 93.95
707164	White	WW	€ 93.95



Accessories

930744	Reflector ring white for Slim series		€ 4.95
930745	Reflector ring black for Slim series		€ 4.95
930746	Reflector ring gold-coloured for Slim series		€ 5.95
930748	36° lens for Slim series		€ 4.95
930749	60° lens for Slim series		€ 4.95



page 39



page 40



page 440




LUCEA

- incl. black reflector ring
- Can be customised with a wide range of accessories

Application Area

Home / Living, Reception / Communication, Hotel / catering

Housing	Aluminium	Rotation Angle	350 Degree
Colour Temperature	2700 K	Swivelling Angle	90 Degree
Height	157 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Ø	65 mm	CRI (Ra)	90
Rated Input Voltage	200-240 V/AC	IK Protection Class	IK03
Power Supply Unit incl.	Yes		
Light Beam Angle	36 Degree		



Article	Housing Color		Luminous Flux	Power	Price	
707165		White		800 lm	6.0 W	€ 88.95
707166		Black		800 lm	6.0 W	€ 88.95
707167		White		1300 lm	10.0 W	€ 94.95
707168		Black		1300 lm	10.0 W	€ 94.95



Accessories

930679	Lens 24° for Lucea 6/10		€ 9.95
930752	Door panel for Lucea 6/10 white		€ 22.95
930753	Door panel for Lucea 6/10 black		€ 22.95
930756	Reflector ring for Lucea 6/10 white		€ 4.95
930757	Reflector ring for Lucea 6/10 black		€ 4.95
930758	Reflector ring for Lucea 6/10 gold		€ 4.95





LUCEA

- Particularly soft textile cable
- incl. black reflector ring

Application Area

Home / Living, Reception / Communication, Hotel / catering

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	2700 K	Light Beam Angle	36 Degree
Height	157 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Ø	65 mm	CRI (Ra)	90
Pendulum Length	1600 mm	IK Protection Class	IK03
Rated Input Voltage	200-240 V/AC		

Article	Housing Color		Luminous Flux	Power	Price
707175	White		800 lm	6.0 W	€ 119.95
707176	Black		800 lm	6.0 W	€ 119.95
707177	White		1300 lm	10.0 W	€ 124.95
707178	Black		1300 lm	10.0 W	€ 124.95



Accessories

930679	Lens 24° for Lucea 6/10		€ 9.95
930752	Door panel for Lucea 6/10 white		€ 22.95
930753	Door panel for Lucea 6/10 black		€ 22.95
930756	Reflector ring for Lucea 6/10 white		€ 4.95
930757	Reflector ring for Lucea 6/10 black		€ 4.95
930758	Reflector ring for Lucea 6/10 gold		€ 4.95






LUCEA DTW

- Dim-to-warm 1,800K - 2,700K
- incl. black reflector ring
- Can be customised with a wide range of accessories

Application Area

Home / Living, Reception / Communication, Hotel / catering

Housing	Aluminium	Light Beam Angle	36 Degree
Colour Temperature	1800-2700 K	Rotation Angle	350 Degree
Luminous Flux	750 lm	Swivelling Angle	90 Degree
Height	249 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Ø	65 mm	CRI (Ra)	90
Power	10 W	IK Protection Class	IK03
Rated Input Voltage	200-240 V/AC		
Power Supply Unit incl.	Yes		



707211

Article	Housing Color		Price
707211	White		€ 104.95
707212	Black		€ 104.95



Accessories

930752	Door panel for Lucea 6/10 white		€ 22.95
930753	Door panel for Lucea 6/10 black		€ 22.95
930756	Reflector ring for Lucea 6/10 white		€ 4.95
930757	Reflector ring for Lucea 6/10 black		€ 4.95
930758	Reflector ring for Lucea 6/10 gold		€ 4.95





LUCEA DTW

- high colour rendering
- Dim-to-warm 1,800K-2,700K
- incl. black reflector ring

Application Area

Home / Living, Reception / Communication, Hotel / catering

Housing	Aluminium	Rated Input Voltage	200-240 V/AC
Colour Temperature	1800-2700 K	Power Supply Unit incl.	Yes
Luminous Flux	750 lm	Light Beam Angle	36 Degree
Height	157 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Ø	65 mm	CRI (Ra)	90
Pendulum Length	1800 mm	IK Protection Class	IK03
Power	10 W		

Article	Housing Color		Price
707215	White		€ 135.96
707216	Black		€ 135.96



Accessories

930752	Door panel for Lucea 6/10 white		€ 22.95
930753	Door panel for Lucea 6/10 black		€ 22.95
930756	Reflector ring for Lucea 6/10 white		€ 4.95
930757	Reflector ring for Lucea 6/10 black		€ 4.95
930758	Reflector ring for Lucea 6/10 gold		€ 4.95



D LINE system



  
page 346




page 348




page 348



  
page 349



  
page 350



  
page 350



  
page 351



  
page 351



  
page 352



  
page 352



  
page 353



  
page 354



□ ■ ■
page 354



□ ■ ■
page 355



□ ■ ■ □
page 356



□ ■
page 356



□ ■ ■
page 357



□ ■ ■
page 357



□ ■ ■
page 358



□ ■ ■
page 359



□ ■ ■
page 359



□ ■ ■
page 360



□ ■ ■
page 360



■
page 361



■
page 361



□ ■ ■
page 363



□ ■ ■
page 364



□ ■
page 365



□ ■ ■
page 366



□ ■ ■
page 366




□ ■ ■
page 367

D LINE MOUNTING POWER RAIL SYSTEM 3-PHASE 220-440V

mounting modules	illust.	white	grey	black	page
mounting power rail L: 1000 mm	01	710000	710001	710002	347
mounting power rail L: 2000 mm	01	710003	710004	710005	347
mounting power rail L: 3000 mm	01	710006	710007	710008	347
mounting adapter for lights	02	710045	710046	710047	349
live end feeder left	03	710009	710010	710011	350
live end feeder right side	04	710012	710013	710014	350
electrical straight connector with center feed option	05	710042	710043	710044	351
flexible-connector left-right side	06	710039	710040	710041	351
electrical joint	07	710015	710016	710017	352
mechanical joint	08	710018	710019	710020	352
90°-joint left-right with exchange mechanism	09	710036	710037	710038	353
T-joint left-left-right with exchange mechanism	10	710027	710028	710029	354
T-joint right-right-left with exchange mechanism	11	710030	710031	710032	354
X-joint left-left-right-right	12	710033	710034	710035	355
cover plate built in track	13	710077	-	710079	356
endcap	14	710066	710067	710068	356
ceiling mounting bracket flex	15	710063	710064	710065	357
suspension clamp for track connection	16	710057	710058	710059	359
ceiling suspension rigid [635 mm] with canopy	17	710078	710085	710084	359
extension for ceiling suspension [300 mm]	17	710086	710088	710087	359
wire suspension bracket with ceiling rosette 1500 mm	18	710048	710049	710050	360
rope suspension bracket Mini mit Abhängeseil 5000 mm	19	710094	710095	710096	360
quick mounting bracket for grid ceilings	20	710051	710052	710053	363
wall bracket	21	710104	710105	710106	357
truss adapter silver coloured	22	-	710083	-	361
quick mounting clamp for exhibition stand construction	23	-	-	710082	361
3-circuits adapter for light installation	24	710097	710098	710099	364
3-circuits adapter with Multi CC power supply 250/350/450/500 mA 6,30 - 21,00 W 25-42V	25	862180	-	862183	365
3-circuits adapter with Multi CC power supply 600/700/750/800 mA 15,00 - 33,60 W 25-42V	25	862181	-	862184	365
3-circuits adapter with Multi CC power supply 850/900/950/1050 mA 23,00 - 44,10 W 27-42V	25	862182	-	862185	363
electrical outlet adapter	26	710024	710025	710026	366
mounting adapter for additional components max. 10kg	27	710054	710055	710056	366
signs hook, max. load 5kg	28	710060	710061	710062	367

ILLUSTRATIONS WITH PLANNING-WRELEVANT DIMENSIONS


























D LINE BUILT IN POWER RAL SYSTEM 3-PHASE 220-440V

built in modules	illust.	white	illust.	cover	page
built in power rail L:1000 mm	01	710069		-	348
built in power rail L: 2000 mm	01	710070		-	348
built in power rail L: 3000 mm	01	710071		-	348
electric feeder left side	02	710009	19	710089	350
electric feeder right side	03	710012	19	710089	350
electrical straight connector with center feed option	04	710042	20	710090	351
electrical joint	05	710015		-	352
mechanical joint	06	710018		-	352
90°-joint left-right	07	710036	21	710091	353
T-joint left-left-right	08	710027	22	710093	354
T-joint right-right-left	09	710030	22	710093	354
X-joint left-left-right-right	10	710033	23	710092	355
cover plate built in track	11	710077			356
endcap	12	710103		-	356
quick-mounting bracket for installation rail	13	710107			348
3-circuits adapter for light installation	14	710097		-	364
3-circuits adapter with Multi CC power supply 250/350/450/500 mA 6,30 - 21,00 W 25-42V	15	862180			365
3-circuits adapter with Multi CC power supply 600/700/750/800 mA 15,00 - 33,60 W 25-42V	15	862181			365
3-circuits adapter with Multi CC power supply 850/900/950/1050 mA 23,00 - 44,10 W 27-42V	15	862182			365
electrical outlet adapter	16	710024		-	366
mounting adapter for additional components max. 10kg	17	710054		-	366
signs hook, max. load 5kg	18	710060		-	367




Unlike other systems, you will not need any additional or special electrical components such as feeders, connectors, corners or T-connectors for the recessed tracks in the future. All standard components of the system are used and only the matching plastic cover is exchanged, and the recessed version is ready. This simplifies stock-keeping and gives significantly more flexibility here as well.

ILLUSTRATIONS WITH PLANNINGRELEVANT DIMENSIONS




FIXING POINTS




MECHANICAL LOAD TRACK POWER RAIL 1000 MM

50 N $\triangleq$ 5,09 kg
dimension in mm






MECHANICAL LOAD TRACK POWER RAIL 2000/3000 MM

50 N $\triangleq$ 5,09 kg
dimension in mm




PLANNING GUIDE D LINE MOUNTING POWER RAIL SYSTEM 3-PHASE 220-440V




D LINE POWER RAIL SYSTEM 3-PHASE 220-440V

The D LINE track system is available exclusively from DEKO-LIGHT and is extremely easy to plan and install thanks to its components, some of which have been completely redesigned. It is also compatible with all common track adapters and luminaires. The elegant and timeless design is available in white, black and grey, and the wide range

of accessories and mounting components means that there are no limits to its use and installation. Thanks to the interchangeable mechanism of the 90° and T connectors, planning is easier than ever before and the installation of even complex shapes will be child's play in the future.



COMPATIBILITY OVERVIEW



D LINE 3-phase track is compatible with the following track lights / adapters:

manufacturer	system name
DEKO-LIGHT	all 3-phase spotlights
Molto Luce	3-Phase-Track*
Global / Nordic	Trac Pro 3*
Ivela	LKM Square / Quadro*
Erco	3-Phasen*
Hoffmeister	3-Phasen*
Zumtobel / Staff	3-Phasen*
Eutrac	One Track*
SLV	S-Track

*compatible with all DEKO-LIGHT 3-phase spotlights, except ALNITAK series [S. 403] and 3-phase adapter with integrated multi-CC power supply [S. 365].

All data without guarantee. Technical data and dimensions are subject to change without prior notice. Check against samples when planning a project to ensure functionality.



On request, all D LINE busbars can be supplied ready-made and cut to size according to your specifications for a small surcharge. This allows you to start installation directly on site at the customer's premises. Please contact our sales department for more information.



D LINE SURFACE-MOUNTED POWER TRACK

The D LINE busbar system is available exclusively from DEKO-LIGHT and is now extremely easy to plan and install thanks to a complete redesign of several components. It is also compatible with all common busbar adapters and lights. The elegant and timeless design is available in white, black and grey, and with a huge range of accessories and assembly components available, the possibilities are almost endless when it comes to application and installation. The reversal mechanism of the 90° and T-connectors makes planning easier than ever before, and in the future installing even complex shapes will be a breeze.




D LINE SURFACE-MOUNTED POWER TRACK

- Up to three phases (3x 16 A) can be fed in
- Numerous attachment options

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Aluminium	Height	35.5 mm
Mounting Type	Top mounting	Rated Input Voltage	220-440 V/AC
Width	35.2 mm	Output Current	16 A

Article	Housing Color	Length	Price
710000	 White	1000 mm	€ 44.95
710001	 Light gray	1000 mm	€ 44.95
710002	 Black	1000 mm	€ 44.95
710003	 White	2000 mm	€ 89.95
710004	 Light gray	2000 mm	€ 89.95
710005	 Black	2000 mm	€ 89.95
710006	 White	3000 mm	€ 129.95
710007	 Light gray	3000 mm	€ 129.95
710008	 Black	3000 mm	€ 129.95



Accessories for 710000, 710003, 710006
710077 D Line/Dali cover panel for integrated busbar, white

 € 5.95

Accessories for 710001, 710002, 710004, 710005, 710007, 710008
710079 D Line/Dali cover panel for integrated busbar, black

 € 5.95



D LINE BUILT-IN POWER TRACK


- Up to three phases (3x 16 A) can be fed in
- Suitable for recessed system
- Side wings for optimal ceiling installation

Application Area

Home / Living, Shop / Retail / Sales area

Housing	Aluminium	Height	35.5 mm
Mounting Type	Top mounting	Rated Input Voltage	220-440 V/AC
Width	56 mm	Output Current	16 A

Article	Housing Color	Length	Price
710069	☐ White	1000 mm	€ 54.95
710070	☐ White	2000 mm	€ 99.95
710071	☐ White	3000 mm	€ 144.95



Accessories

710077 D Line/Dali cover panel for integrated busbar, white



€ 5.95



D LINE QUICK-MOUNTING BRACKET FOR INSTALLATION RAIL

- Suitable for recessed system
- Simplifies installation of recessed current tracks
- No additional substructure is required for mounting

Application Area

Home / Living, Shop / Retail / Sales area

Housing	Steel	Width	45 mm
Mounting Type	Installation mounting	Height	25 mm
Length	70 mm		

Article	Housing Color	Price
710107	☐ Silver	€ 4.95





D LINE SURFACE-MOUNTED ADAPTER


- Surface-mounted housing for converting busbar spotlights
- Single phase (1x 16 A) feed
- Easy to install

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic	Ø	110 mm
Mounting Type	Top mounting	Rated Input Voltage	220-240 V/AC
Height	35 mm	Output Current	16 A

Article	Housing Color	Price
710045	 White	€ 29.95
710046	 Light gray	€ 29.95
710047	 Black	€ 29.95






D LINE ELECTRIC FEEDER LEFT

- Up to three phases (3x 16 A) can be fed in
- Power can be fed in from above (ceiling) or from the side
- Suitable for surface-mounted and recessed systems

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	35.5 mm
Mounting Type	Top mounting	Rated Input Voltage	220-440 V/AC
Length	98.5 mm	Output Current	16 A
Width	35.2 mm		

Article	Housing Color	Price
710009	 White	€ 15.95
710010	 Light gray	€ 15.95
710011	 Black	€ 15.95



D LINE ELECTRIC FEEDER RIGHT

- Up to three phases (3x 16 A) can be fed in
- Power can be fed in from above (ceiling) or from the side
- Suitable for surface-mounted and recessed systems

Application Area
Home / Living, Shop / Retail / Sales area


Housing	Plastic	Height	35.5 mm
Mounting Type	Top mounting	Rated Input Voltage	220-440 V/AC
Length	98.5 mm	Output Current	16 A
Width	35.2 mm		

Article	Housing Color	Price
710012	 White	€ 15.95
710013	 Light gray	€ 15.95
710014	 Black	€ 15.95





D LINE ELECTRICAL LONGITUDINAL CONNECTOR WITH FEED OPTION




- Up to three phases (3x 16 A) can be fed in
- Power supply from above (from ceiling)
- Suitable for surface-mounted and recessed systems

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	35.5 mm
Mounting Type	Top mounting	Rated Input Voltage	220-440 V/AC
Length	166 mm	Output Current	16 A
Width	35 mm		

Article	Housing Color	Price
710042	White	€ 32.95
710043	Light gray	€ 32.95
710044	Black	€ 32.95



Accessories
710090 D Line/Dali cover panel for longitudinal connector, white € 3.95



D LINE FLEX CONNECTOR LEFT-RIGHT

- Compensates for height or angle differences within a track system
- Suitable for surface-mounted systems

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	35.5 mm
Mounting Type	Top mounting	Rated Input Voltage	220-440 V/AC
Length	248 mm	Output Current	16 A
Width	35 mm		

Article	Housing Color	Price
710039	White	€ 42.95
710040	Light gray	€ 42.95
710041	Black	€ 42.95





D LINE ELECTRIC CONNECTOR

·suitable for surface-mounted and recessed systems

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	26.5 mm
Mounting Type	Top mounting	Rated Input Voltage	220-440 V/AC
Length	68 mm	Output Current	16 A
Width	20.5 mm		

Article	Housing Color	Price
710015	 White	€ 9.95
710016	 Light gray	€ 9.95
710017	 Black	€ 9.95



D LINE MECHANICAL CONNECTOR



- Mechanical connector without electrical contacts
- For electrical separation of two different power circuits within one track system
- Suitable for surface-mounted and recessed systems

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic	Width	20 mm
Mounting Type	Top mounting	Height	27 mm
Length	66.4 mm		

Article	Housing Color	Price
710018	 White	€ 6.95
710019	 Light gray	€ 6.95
710020	 Black	€ 6.95





D LINE 90° CONNECTOR LEFT-RIGHT WITH REVERSAL MECHANISM

- With reversal mechanism for switching the orientation between left and right
- Suitable for surface-mounted and recessed systems

Housing	Plastic	Height	35.5 mm
Mounting Type	Top mounting	Rated Input Voltage	220-440 V/AC
Length	100.7 mm	Output Current	16 A
Width	100.7 mm		


Article	Housing Color	Price
710036	 White	€ 34.95
710037	 Light gray	€ 34.95
710038	 Black	€ 34.95



Accessories
710091 D Line/Dali cover panel for 90° connector, white



€ 3.95




D LINE T-CONNECTOR LEFT-LEFT-RIGHT WITH REVERSAL MECHANISM

- with reversal mechanism for switching the orientation between left / right
- suitable for surface-mounted and recessed systems

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	35.5 mm
Mounting Type	Top mounting	Rated Input Voltage	220-440 V/AC
Length	166 mm	Output Current	16 A
Width	101 mm		

Article	Housing Color	Price
710027	White	€ 49.95
710028	Light gray	€ 49.95
710029	Black	€ 49.95



D LINE T-CONNECTOR RIGHT/RIGHT/LEFT WITH EXCHANGE MECHANICS

- with reversal mechanism for switching the orientation between left / right
- suitable for surface-mounted and recessed systems

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	35.5 mm
Mounting Type	Top mounting	Rated Input Voltage	220-440 V/AC
Length	166 mm	Output Current	16 A
Width	101 mm		

Article	Housing Color	Price
710030	White	€ 49.95
710031	Light gray	€ 49.95
710032	Black	€ 49.95



Accessories
710093 D Line/Dali cover panel for T-connector, white



€ 3.95




D LINE X-CONNECTOR LEFT-LEFT-RIGHT-RIGHT

- Easy to install
- Suitable for surface-mounted and recessed systems

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	35.5 mm
Mounting Type	Top mounting	Rated Input Voltage	220-440 V/AC
Length	166 mm	Output Current	16 A
Width	166 mm		

Article	Housing Color	Price
710033	White	€ 66.95
710034	Light gray	€ 66.95
710035	Black	€ 66.95



Accessories
710092 D Line/Dali cover panel for X-connector, white



€ 4.95



D LINE COVER PANEL

- Suitable for surface-mounted and recessed systems
- For sealing publicly accessible busbars within a contact zone of less than 2.30 m

Housing	Plastic	Width	21.5 mm
Mounting Type	Top mounting	Height	7.5 mm
Length	1000 mm		

Article	Housing Color	Price
710077	 White	€ 5.95
710079	 Black	€ 5.95



D LINE END CAP

- For closing open current track ends (touch protection)
- Easy to install
- Suitable for surface-mounted systems

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	32.5 mm
---------	---------	--------	---------

Article	Housing Color	Mounting Type	Length	Width	Price
710066	 White	Top mounting	31.3 mm	35.2 mm	€ 2.95
710067	 Light gray	Top mounting	31.3 mm	35.2 mm	€ 2.95
710068	 Black	Top mounting	31.3 mm	35.2 mm	€ 2.95
710103	 White	Installation mounting	56 mm	47.9 mm	€ 2.95



D LINE MOUNTING BRACKET FLEX

- Suitable for surface-mounted systems
- Simplifies installation of complex shapes
- Current track can still be slid during installation

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Metal	Width	33.8 mm
Mounting Type	Top mounting	Height	12.5 mm
Length	40 mm		

Article	Housing Color	Price
710063	 White	€ 5.95
710064	 Light gray	€ 5.95
710065	 Black	€ 5.95



D LINE WALL BRACKET

- Suitable for surface-mounted systems
- Simplifies installation of current tracks near walls
- Ideal for illuminating pictures and objects, for example in exhibitions, collections and museums

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Aluminium	Width	25 mm
Mounting Type	Top mounting	Height	80 mm
Length	91.9 mm		

Article	Housing Color	Price
710104	 White	€ 14.95
710105	 Light gray	€ 14.95
710106	 Black	€ 14.95

IP20



D LINE SUSPENSION CONNECTION BRACKET

- Suitable for surface-mounted systems
- For chain installation or similar (chain not included in the scope of delivery)

Housing	Metal	Width	32 mm
Mounting Type	Top mounting	Height	20 mm
Length	181 mm		

Article	Housing Color	Price
710057	 White	€ 9.95
710058	 Light gray	€ 9.95
710059	 Black	€ 9.95



D LINE CEILING SUSPENSION RIGID

- Sturdy, elegant ceiling hanger
- Suitable for surface-mounted systems
- Hanger dimension 635 mm (can be shortened to 335 mm)
- Hanger can be extended with accessories



Application Area
Home / Living, Shop / Retail / Sales area

Housing	Aluminium	Length	635 mm
Mounting Type	Top mounting	Width	60 mm

Article	Housing Color	Price
710078	 White	€ 32.95
710084	 Black	€ 32.95
710085	 Light gray	€ 32.95



D LINE EXTENSION FOR CEILING SUSPENSION RIGID

- Suitable for rigid ceiling hangers
- Extends the hanger length by 300 mm

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Aluminium	Length	310 mm
Mounting Type	Top mounting	Width	10 mm

Article	Housing Color	Price
710086	 White	€ 5.95
710087	 Black	€ 5.95
710088	 Light gray	€ 5.95



D LINE ROPE SUSPENSION BRACKET

- Can be cut to length for suspension dimension: 120-1,500 mm
- suitable for surface-mounted systems

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Metal	Width	31 mm
Mounting Type	Top mounting	Height	52 mm
Length	120 mm		

Article	Housing Color	Price
710048	 White	€ 14.95
710049	 Light gray	€ 14.95
710050	 Black	€ 14.95

Accessories

710081 D Line/Dali cable for cable suspension 4.0 m



€ 7.95



D LINE ROPE SUSPENSION BRACKET MINI

- Stylish and sophisticated suspended mounting
- Can be cut to length for hanger lengths: 90-4,960 mm
- Suitable for surface-mounted systems

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Metal	Width	31 mm
Mounting Type	Top mounting	Height	58 mm
Length	120 mm		

Article	Housing Color	Price
710094	 White	€ 19.95
710095	 Light gray	€ 19.95
710096	 Black	€ 19.95



D LINE FAST-MOUNTING BRACKET

- Suitable for surface-mounted systems
- Current track can be installed without tools using knurled thumb screw and spring clamps
- Quick installation and removal for e.g. trade fair construction

Application Area

Home / Living, Shop / Retail / Sales area

Housing	Aluminium	Width	30 mm
Mounting Type	Top mounting	Height	11.9 mm
Length	40 mm		

Article	Housing Color	Price
710082	 Black	€ 10.95



D LINE TRUSS ADAPTER

- Suitable for surface-mounted systems
- Quick-action couplers for fast mounting of current tracks on cross rail structures
- Fits all 50 mm aluminium cross rails in event/trade fair construction

Application Area

Home / Living, Shop / Retail / Sales area

Housing	Aluminium	Width	30 mm
Mounting Type	Top mounting	Height	11.9 mm
Length	40 mm		

Article	Housing Color	Price
710083	 Silver	€ 29.95



This little »jack-of-all-trades« makes mounting a track on an existing grid ceiling child's play. The installation time is only a fraction of what it used to be. In the first step, the clip is simply clicked into the visible metal strips of the grid ceiling and is held bomb-proof on the ceiling by means of a safety spring clip. After that, the conductor rail is simply pushed onto it and the installation is finished.





D LINE GRID CEILING FAST-MOUNTING BRACKET

- Suitable for surface-mounted systems
- Quick and easy to install on grid ceilings
- Mechanical load up to 15.0 kg/150 N
- Suitable for 22-24 mm ceiling grid support rails

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Metal	Width	31 mm
Mounting Type	Top mounting	Height	11 mm
Length	120 mm		

Article	Housing Color	Price
710051	 White	€ 11.95
710052	 Light gray	€ 11.95
710053	 Black	€ 11.95





D LINE 3-PHASE ADAPTER FOR LIGHT INSTALLATION

- Suitable for surface-mounted and recessed systems
- Includes reduction bush, M10 flat nut and strain relief grommet
- Easy to install
- Integrated secondary drop protection
- Max. load 10 kg/100 N

Housing	Plastic	Height	54 mm
Mounting Type	Top mounting	Rated Input Voltage	220-240 V/AC
Length	84 mm	Output Current	10 A
Width	32 mm		

Article	Housing Color	Price
710097	 White	€ 18.95
710098	 Light gray	€ 18.95
710099	 Black	€ 18.95





D LINE THREE-PHASE ADAPTER WITH INTEGRATED MULTI CC POWER SUPPLY

- Suitable for surface-mounted and recessed systems
- Integrated secondary drop protection
- Supplied with trumpet nipple and M10 flat nut
- Stable integrated adjustable power supply [CC]
- Check suitability of the intended lamp
- Max. 10 kg/100 N
- Exclusively for D LINE, Ivela and Hoffmeister three-phase current tracks

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	41 mm
Length	162 mm	Rated Input Voltage	220-240 V/AC
Width	31 mm	Mounting Location	Inside

Article		Output Current Selectable	Power	Output Voltage	Price
862180	☐	250 mA / 350 mA / 450 mA / 500 mA	6.2-21.0 W	25-42 V/DC	€ 32.95
862183	☒	250 mA / 350 mA / 450 mA / 500 mA	6.2-21.0 W	25-42 V/DC	€ 32.95
862181	☐	600 mA / 700 mA / 750 mA / 800 mA	15.0-33.0 W	25-42 V/DC	€ 35.95
862184	☒	600 mA / 700 mA / 750 mA / 800 mA	15.0-33.0 W	25-42 V/DC	€ 35.95
862182	☐	850 mA / 900 mA / 950 mA / 1050 mA	22.0-44.0 W	27-42 V/DC	€ 37.95
862185	☒	850 mA / 900 mA / 950 mA / 1050 mA	22.0-44.0 W	27-42 V/DC	€ 37.95





D LINE SOCKET ADAPTER

- easy to install
- suitable for surface-mounted and recessed systems
- as power distribution system in current tracks
- max. 1,380 W
- integrated plug fuse

Housing	Plastic	Width	53.5 mm
Mounting Type	Top mounting, Installation mounting	Height	103 mm
Length	58.5 mm	Rated Input Voltage	230 V/AC
		Output Current	6 A

Article	Housing Color	Price
710024	White	€ 28.95
710025	Light gray	€ 28.95
710026	Black	€ 28.95



D LINE MOUNTING ADAPTER FOR ADDITIONAL COMPONENTS

- Suitable for surface-mounted and recessed systems
- Mounting adapter (M6 thread) for holding additional devices and lights
- Ideal for use with optional D Line socket adapter
- Load max. 10 kg/100 N

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Metal, Plastic	Width	31.5 mm
Mounting Type	Top mounting	Height	84 mm
Length	66.5 mm		

Article	Housing Color	Price
710054	White	€ 10.95
710055	Light gray	€ 10.95
710056	Black	€ 10.95



D LINE SIGN HOOK

- Suitable for surface-mounted and recessed systems
- Hook for attaching information signs etc.
- Load max. 5kg / 50N

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic, Steel	Height	52 mm
Mounting Type	Top mounting	Ø	25 mm

Article	Housing Color	Price
710060	 White	€ 2.95
710061	 Light gray	€ 2.95
710062	 Black	€ 2.95



D LINE DALI system



  
page 348



  
page 352



  
page 357



  
page 357



  
page 358



  
page 359



  
page 359



  
page 360



  
page 360



  
page 363



  
page 366



  
page 366



☐ ☐ ☐
page 367



☐ ☐
page 376



☐ ☐
page 377



☐ ☐
page 378



☐ ☐
page 380



☐ ☐
page 380



☐ ☐
page 381



☐ ☐
page 381



☐ ☐
page 382



☐ ☐
page 383



☐ ☐
page 384



☐ ☐
page 384




☐ ☐
page 385

D LINE DALI MOUNTING POWER RAIL SYSTEM 3-PHASE 220-440V


mounting modules	illust.	white	black	page
mounting power rail L: 1000 mm	01	710500	710501	376
mounting power rail L: 2000 mm	01	710502	710503	376
mounting power rail L: 3000 mm	01	710504	710505	376
mounting adapter for lights	02	710512	710513	377
live end feeder left	03	710514	710515	380
live end feeder right side	04	710516	710517	380
electrical straight connector with center feed option	05	710520	710521	381
flexible-connector left-right side	06	710523	710524	381
electrical joint	07	710525	710526	382
mechanical joint	08	710018	710020	382
90°-joint left-right with exchange mechanism	09	710527	710528	383
T-joint left-left-right with exchange mechanism	10	710530	710531	384
T-joint right-right-left with exchange mechanism	11	710532	710533	384
X-joint left-left-right-right	12	710535	710536	385
cover plate	13	710077	710079	386
endcap	14	710066	710068	386
ceiling mounting bracket flex	15	710063	710065	387
suspension clamp for track connection	16	710057	710059	388
ceiling suspension rigid [635 mm] with canopy	17	710078	710084	389
extension for ceiling suspension [300 mm]	17	710086	710087	389
wire suspension bracket with ceiling rosette 1500 mm	18	710048	710050	390
rope suspension bracket Mini mit Abhängeseil 5000 mm	19	710094	710096	390
quick mounting bracket for grid ceilings	20	710051	710053	393
wall bracket	21	710104	710106	387
truss adapter silver coloured	22	710083	710083	391
quick mounting clamp for exhibition stand construction	23	-	710082	391
3-circuits adapter for light installation	24	710539	710540	394
electrical outlet adapter	25	710024	710026	394
mounting adapter for additional components max. 10kg	26	710054	710056	395
signs hook, max. load 5kg	27	710060	710062	395

ILLUSTRATIONS WITH PLANNING RELEVANT DIMENSIONS

01



02




03




04



05



06




07




08




09




10



11



12



13



14




15




16




17




18




19




20



21




22




23



24



25



26



27



D LINE DALI BUILT IN POWER RAL SYSTEM 3-PHASE 220-440V

built in modules	illust.	white	cover	black	cover	page
built in power rail L:1000 mm	01	710506	-	710507	-	378
built in power rail L: 2000 mm	01	710508	-	710509	-	378
built in power rail L: 3000 mm	01	710510	-	710511	-	378
electric feeder left side	02+18	710514	710518	710515	710519	380
electric feeder right side	03+18	710516	710518	710517	710519	380
electrical straight connector with center feed option	04+19	710520	710090	710521	710522	381
electrical joint	05	710525	-	710526	-	382
mechanical joint	06	710018	-	710020	-	382
90°-joint left-right	07+20	710527	710091	710528	710529	383
T-joint left-left-right	08+21	710530	710093	710531	710534	384
T-joint right-right-left	09+21	710532	710093	710533	710534	384
X-joint left-left-right-right	10+22	710535	710092	710536	710537	385
cover plate	11	710077	-	710079	-	386
endcap	12	710103	-	710538	-	386
quick-mounting bracket for installation rail	13	710107	-	-	-	379
3-circuits adapter for light installation	14	710539	-	710540	-	394
electrical outlet adapter	15	710024	-	710026	-	394
mounting adapter for additional components max. 10kg	16	710054	-	710056	-	395
signs hook, max. load 5kg	17	710060	-	710062	-	395

























710535




710092

Unlike other Dali systems, you do not need any additional or special electrical components such as feeders, connectors, corners or T-connectors for the recessed tracks, corners or T-connectors. All the standard components of the system are used and only the matching plastic cover is replaced; the recessed version is ready. This simplifies stock-keeping and also provides significantly more flexibility.

ILLUSTRATIONS WITH PLANNING RELEVANT DIMENSIONS




FIXING POINTS




MECHANICAL LOAD TRACK POWER RAIL 1000 MM

60 N $\triangleq$ 6,12 kg
dimension in mm






MECHANICAL LOAD TRACK POWER RAIL 2000/3000 MM

30 N $\triangleq$ 3,06 kg
dimension in mm



PLANNING GUIDE D LINE DALI MOUNTING POWER RAIL SYSTEM 220-440V





D LINE DALI SURFACE-MOUNTED TRACK RAIL

- Can be controlled with DALI
- Up to three phases [3x 16 A] can be fed in
- Cutting tool required for in-house assembly
- Numerous attachment options

Application Area

Reception / Communication, Corridor / stairwell, Home / Living, Office / conference, Shop / Retail / Sales area

Housing	Aluminium	Rated Input Voltage	220-440 V/AC
Width	35.2 mm	Output Current	16 A
Height	35.5 mm		

Article	Housing Color	Length	Price
710500	☐ White	1000 mm	€ 48.95
710501	☒ Black	1000 mm	€ 48.95
710502	☐ White	2000 mm	€ 92.95
710503	☒ Black	2000 mm	€ 92.95
710504	☐ White	3000 mm	€ 134.95
710505	☒ Black	3000 mm	€ 134.95



Accessories

931066 D LINE DALI, cut-back tool for shortening the DALI wires  € 199.95

Accessories for 710500, 710502, 710504

710077 D Line/Dali cover panel for integrated busbar, white  € 5.95

Accessories for 710501, 710503, 710505

710079 D Line/Dali cover panel for integrated busbar, black  € 5.95



D LINE DALI SURFACE-MOUNTED ADAPTER

- Can be controlled with DALI
- Surface-mounted housing for converting busbar spotlights
- Single phase (1x 16 A) feed
- Easy to install

Application Area

Reception / Communication, Corridor / stairwell, Home / Living, Office / conference, Shop / Retail / Sales area

Housing	Plastic	Rated Input Voltage	220-240 V/AC
Height	35 mm	Output Current	16 A
Ø	143 mm		

Article	Housing Color	Price
710512	White	€ 34.95
710513	Black	€ 34.95





D LINE DALI RECESSED TRACK RAIL

- Can be controlled with DALI
- Up to three phases [3x 16 A] can be fed in
- Cutting tool required for in-house assembly
- Numerous attachment options

Application Area

Reception / Communication, Corridor / stairwell, Home / Living, Office / conference, Shop / Retail / Sales area

Housing	Aluminium	Rated Input Voltage	220-440 V/AC
Width	56 mm	Output Current	16 A
Height	35.5 mm		

Article	Housing Color	Length	Price
710506	☐ White	1000 mm	€ 57.95
710507	☒ Black	1000 mm	€ 57.95
710508	☐ White	2000 mm	€ 104.95
710509	☒ Black	2000 mm	€ 104.95
710510	☐ White	3000 mm	€ 149.95
710511	☒ Black	3000 mm	€ 149.95



Accessories

931066 D LINE DALI, cut-back tool for shortening the DALI wires € 199.95

Accessories for 710506, 710508, 710510

710077 D Line/Dali cover panel for integrated busbar, white € 5.95

Accessories for 710507, 710509, 710511

710079 D Line/Dali cover panel for integrated busbar, black € 5.95



D LINE QUICK-MOUNTING BRACKET FOR INSTALLATION RAIL

- Suitable for recessed system
- Simplifies installation of recessed current tracks
- No additional substructure is required for mounting




Application Area
Home / Living, Shop / Retail / Sales area

Housing	Steel	Width	45 mm
Mounting Type	Installation mounting	Height	25 mm
Length	70 mm		

Article	Housing Color	Price
710107	 Silver	€ 4.95

IP20



D LINE DALI ELECTRIC FEEDER LEFT


- Can be controlled using DALI
- Up to three phases (3x 16 A) can be fed in
- Power can be fed in from above (ceiling) or from the side
- Suitable for surface-mounted and recessed systems

Application Area

Reception / Communication, Corridor / stairwell, Home / Living, Office / conference, Shop / Retail / Sales area

Housing	Plastic	Height	35.5 mm
Length	139 mm	Rated Input Voltage	220-440 V/AC
Width	35.2 mm	Output Current	16 A

Article	Housing Color	Price
710514	 White	€ 18.95
710515	 Black	€ 18.95



D LINE DALI ELECTRIC FEEDER RIGHT

- Can be controlled using DALI
- Up to three phases (3x 16 A) can be fed in
- Power can be fed in from above (ceiling) or from the side
- Suitable for surface-mounted and recessed systems

Application Area

Reception / Communication, Corridor / stairwell, Home / Living, Office / conference, Shop / Retail / Sales area

Housing	Plastic	Height	35.5 mm
Length	139 mm	Rated Input Voltage	220-440 V/AC
Width	35.2 mm	Output Current	16 A

Article	Housing Color	Price
710516	 White	€ 18.95
710517	 Black	€ 18.95




- Accessories for 710516
- 710518 D Line DALI cover panel feed left/right, white
- Accessories for 710517
- 710519 D Line DALI cover panel feed left/right, black





D LINE DALI STRAIGHT CONNECTOR WITH FEED OPTION



- Can be controlled using DALI
- Up to three phases (3x 16 A) can be fed in
- Power supply from above (ceiling)
- Suitable for surface-mounted and recessed systems

Application Area

Reception / Communication, Corridor / stairwell, Home / Living, Office / conference, Shop / Retail / Sales area

Housing	Plastic	Height	35.5 mm
Length	203 mm	Rated Input Voltage	220-440 V/AC
Width	35.2 mm	Output Current	16 A

Article	Housing Color	Price
710520	White	€ 34.95
710521	Black	€ 34.95



Accessories for 710520


710090 D Line/Dali cover panel for longitudinal connector, white  **€ 3.95**

Accessories for 710521

710522 D Line DALI cover panel for longitudinal connector, black  **€ 3.95**



D LINE DALI FLEX CONNECTOR



- Can be controlled using DALI
- Easy to install
- Compensates for height or angle differences within a track system
- Suitable for surface-mounted systems

Application Area

Reception / Communication, Corridor / stairwell, Home / Living, Office / conference, Shop / Retail / Sales area

Housing	Plastic	Height	35.5 mm
Length	285 mm	Rated Input Voltage	220-440 V/AC
Width	35.2 mm	Output Current	16 A

Article	Housing Color	Price
710523	White	€ 46.95
710524	Black	€ 46.95





D LINE DALI ELECTRIC CONNECTOR

- easy to install
- suitable for surface-mounted and recessed systems

Application Area
Reception / Communication, Corridor / stairwell, Home / Living, Office / conference, Shop / Retail / Sales area

Housing	Plastic	Height	26.5 mm
Length	107 mm	Rated Input Voltage	220-440 V/AC
Width	20.5 mm	Output Current	16 A

Article	Housing Color	Price
710525	White	€ 11.95
710526	Black	€ 11.95



D LINE MECHANICAL CONNECTOR



- Mechanical connector without electrical contacts
- For electrical separation of two different power circuits within one track system
- Suitable for surface-mounted and recessed systems

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic	Width	20 mm
Mounting Type	Top mounting	Height	27 mm
Length	66.4 mm		

Article	Housing Color	Price
710018	White	€ 6.95
710020	Black	€ 6.95





D LINE DALI 90°-CONNECTOR

- with reversal mechanism for switching the orientation between left and right
- easy to install
- suitable for surface-mounted and recessed systems

Application Area

Reception / Communication, Corridor / stairwell, Home / Living, Office / conference, Shop / Retail / Sales area

Housing	Plastic	Height	35.5 mm
Length	119 mm	Rated Input Voltage	220-440 V/AC
Width	119 mm	Output Current	16 A

Article	Housing Color	Price
710527	White	€ 38.95
710528	Black	€ 38.95



Accessories for 710527

710091 D Line/Dali cover panel for 90° connector, white




€ 3.95

Accessories for 710528

710529 D Line DALI cover panel for 90° connector, black



€ 3.95



D LINE DALI T-CONNECTOR LEFT-LEFT-RIGHT


- with reversal mechanism for switching the orientation between left and right
- easy to install
- suitable for surface-mounted and recessed systems

Application Area

Reception / Communication, Corridor / stairwell, Home / Living, Office / conference, Shop / Retail / Sales area

Housing	Plastic	Height	35.5 mm
Length	203 mm	Rated Input Voltage	220-440 V/AC
Width	119 mm	Output Current	16 A

Article	Housing Color	Price
710530	 White	€ 54.95
710531	 Black	€ 54.95



D LINE DALI T-CONNECTOR RIGHT-RIGHT-LEFT

- with reversal mechanism for switching the orientation between left and right
- easy to install
- suitable for surface-mounted and recessed systems

Application Area

Reception / Communication, Corridor / stairwell, Home / Living, Office / conference, Shop / Retail / Sales area


Housing	Plastic	Height	35.5 mm
Length	203 mm	Rated Input Voltage	220-440 V/AC
Width	119 mm	Output Current	16 A

Article	Housing Color	Price
710532	 White	€ 54.95
710533	 Black	€ 54.95



- Accessories for **710532**
- 710093** D Line/Dali cover panel for T-connector, white
- Accessories for **710533**
- 710534** D Line DALI cover panel for T-connector, black





D LINE DALI X-CONNECTOR

- easy to install
- suitable for surface-mounted and recessed systems

Application Area
Reception / Communication, Corridor / stairwell, Home / Living, Office / conference, Shop / Retail / Sales area

Housing	Plastic	Height	35.5 mm
Length	203 mm	Rated Input Voltage	220-440 V/AC
Width	203 mm	Output Current	16 A

Article	Housing Color	Price
710535	 White	€ 69.95
710536	 Black	€ 69.95



Accessories for **710535**
710092 D Line/Dali cover panel for X-connector, white

 € 4.95

Accessories for **710536**
710537 D Line DALI cover panel for X-connector, black

 € 4.95



D LINE COVER PANEL

- Suitable for surface-mounted and recessed systems
- For sealing publicly accessible busbars within a contact zone of less than 2.30 m

Housing	Plastic	Width	21.5 mm
Mounting Type	Top mounting	Height	7.5 mm
Length	1000 mm		

Article	Housing Color	Price
710077	 White	€ 5.95
710079	 Black	€ 5.95



D LINE END CAP

- For closing open current track ends (touch protection)
- Easy to install
- Suitable for surface-mounted systems

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	32.5 mm
---------	---------	--------	---------

Article	Housing Color	Mounting Type	Length	Width	Price
710066	 White	Top mounting	31.3 mm	35.2 mm	€ 2.95
710068	 Black	Top mounting	31.3 mm	35.2 mm	€ 2.95
710103	 White	Installation mounting	56 mm	47.9 mm	€ 2.95
710538	 Black	Installation mounting	56 mm	47.9 mm	€ 2.95



D LINE MOUNTING BRACKET FLEX

- Suitable for surface-mounted systems
- Simplifies installation of complex shapes
- Current track can still be slid during installation

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Metal	Width	33.8 mm
Mounting Type	Top mounting	Height	12.5 mm
Length	40 mm		

Article	Housing Color	Price
710063	☐ White	€ 5.95
710065	☒ Black	€ 5.95



D LINE WALL BRACKET

- Suitable for surface-mounted systems
- Simplifies installation of current tracks near walls
- Ideal for illuminating pictures and objects, for example in exhibitions, collections and museums

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Aluminium	Width	25 mm
Mounting Type	Top mounting	Height	80 mm
Length	91.9 mm		

Article	Housing Color	Price
710104	☐ White	€ 14.95
710106	☒ Black	€ 14.95

IP20



D LINE SUSPENSION CONNECTION BRACKET

- Suitable for surface-mounted systems
- For chain installation or similar (chain not included in the scope of delivery)

Housing	Metal	Width	32 mm
Mounting Type	Top mounting	Height	20 mm
Length	181 mm		

Article	Housing Color	Price
710057	 White	€ 9.95
710059	 Black	€ 9.95



D LINE CEILING SUSPENSION RIGID

- Sturdy, elegant ceiling hanger
- Suitable for surface-mounted systems
- Hanger dimension 635 mm (can be shortened to 335 mm)
- Hanger can be extended with accessories

Application Area

Home / Living, Shop / Retail / Sales area

Housing	Aluminium	Length	635 mm
Mounting Type	Top mounting	Width	60 mm

Article	Housing Color	Price
710078	☐ White	€ 32.95
710084	☒ Black	€ 32.95



D LINE EXTENSION FOR CEILING SUSPENSION RIGID

- Suitable for rigid ceiling hangers
- Extends the hanger length by 300 mm

Application Area

Home / Living, Shop / Retail / Sales area

Housing	Aluminium	Length	310 mm
Mounting Type	Top mounting	Width	10 mm

Article	Housing Color	Price
710086	☐ White	€ 5.95
710087	☒ Black	€ 5.95



D LINE ROPE SUSPENSION BRACKET

- Can be cut to length for suspension dimension: 120-1,500 mm
- suitable for surface-mounted systems

Application Area

Home / Living, Shop / Retail / Sales area

Housing	Metal	Width	31 mm
Mounting Type	Top mounting	Height	52 mm
Length	120 mm		

Article	Housing Color	Price
710048	☐ White	€ 14.95
710050	☒ Black	€ 14.95

Accessories

710081 D Line/Dali cable for cable suspension 4.0 m



€ 7.95



D LINE ROPE SUSPENSION BRACKET MINI

- Stylish and sophisticated suspended mounting
- Can be cut to length for hanger lengths: 90-4,960 mm
- Suitable for surface-mounted systems

Application Area

Home / Living, Shop / Retail / Sales area

Housing	Metal	Width	31 mm
Mounting Type	Top mounting	Height	58 mm
Length	120 mm		

Article	Housing Color	Price
710094	☐ White	€ 19.95
710096	☒ Black	€ 19.95



D LINE FAST-MOUNTING BRACKET

- Suitable for surface-mounted systems
- Current track can be installed without tools using knurled thumb screw and spring clamps
- Quick installation and removal for e.g. trade fair construction

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Aluminium	Width	30 mm
Mounting Type	Top mounting	Height	11.9 mm
Length	40 mm		

Article	Housing Color	Price
710082	 Black	€ 10.95



D LINE TRUSS ADAPTER

- Suitable for surface-mounted systems
- Quick-action couplers for fast mounting of current tracks on cross rail structures
- Fits all 50 mm aluminium cross rails in event/trade fair construction

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Aluminium	Width	30 mm
Mounting Type	Top mounting	Height	11.9 mm
Length	40 mm		

Article	Housing Color	Price
710083	 Silver	€ 29.95



This little »jack-of-all-trades« makes mounting a track on an existing grid ceiling child's play. The installation time is only a fraction of what it used to be. In the first step, the clip is simply clicked into the visible metal strips of the grid ceiling and is held bomb-proof on the ceiling by means of a safety spring clip. After that, the conductor rail is simply pushed onto it and the installation is finished.





D LINE GRID CEILING FAST-MOUNTING BRACKET

- Suitable for surface-mounted systems
- Quick and easy to install on grid ceilings
- Mechanical load up to 15.0 kg/150 N
- Suitable for 22-24 mm ceiling grid support rails

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Metal	Width	31 mm
Mounting Type	Top mounting	Height	11 mm
Length	120 mm		

Article	Housing Color	Price
710051	☐ White	€ 11.95
710053	☒ Black	€ 11.95





D LINE DALI THREE-PHASE ADAPTER FOR INSTALLING LAMPS

- can be controlled with DALI, up to three phases can be fed in
- easy to install
- suitable for surface-mounted and recessed systems

Application Area

Reception / Communication, Corridor / stairwell, Home / Living, Office / conference, Shop / Retail / Sales area

Housing	Plastic	Height	51 mm
Length	113 mm	Rated Input Voltage	220-240 V/AC
Width	32 mm	Output Current	10 A

Article	Housing Color	Price
710539	 White	€ 23.95
710540	 Black	€ 23.95



D LINE SOCKET ADAPTER

- easy to install
- suitable for surface-mounted and recessed systems
- as power distribution system in current tracks
- max. 1,380 W
- integrated plug fuse

Housing	Plastic	Width	53.5 mm
Mounting Type	Top mounting, Installation mounting	Height	103 mm
Length	58.5 mm	Rated Input Voltage	230 V/AC
		Output Current	6 A

Article	Housing Color	Price
710024	 White	€ 28.95
710026	 Black	€ 28.95





D LINE MOUNTING ADAPTER FOR ADDITIONAL COMPONENTS

- Suitable for surface-mounted and recessed systems
- Mounting adapter (M6 thread) for holding additional devices and lights
- Ideal for use with optional D Line socket adapter
- Load max. 10 kg/100 N

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Metal, Plastic	Width	31.5 mm
Mounting Type	Top mounting	Height	84 mm
Length	66.5 mm		

Article	Housing Color	Price
710054	 White	€ 10.95
710056	 Black	€ 10.95



D LINE SIGN HOOK

- Suitable for surface-mounted and recessed systems
- Hook for attaching information signs etc.
- Load max. 5kg / 50N

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic, Steel	Height	52 mm
Mounting Type	Top mounting	Ø	25 mm

Article	Housing Color	Price
710060	 White	€ 2.95
710062	 Black	€ 2.95



3-phases power luminaires



☐ ☒
page 398



☐
page 399



☐
page 399



☐ ☐
page 400



☐ ☒
page 402



☐ ☒
page 402



☐ ☐ ☒
page 403



☐ ☒
page 406



☐ ☒
page 407



☐ ☒
page 408



☐ ☒
page 409



☐ ☒
page 410



□ ■
page 411



□ ■
page 413



□ ■ ■
page 414



□ ■ ■
page 416



■ □
page 418



□ ■
page 420



■ □
page 421



□ ■ ■
page 422



□ ■ ■
page 423



□ ■
page 425



□ ■
page 430



□ ■
page 431



□ ■
page 432



□ ■
page 433



□ ■
page 436



□ ■
page 438



□ ■
page 439



■ □
page 440



□ ■
page 441



■ ■
page 442




PANEL TRACK LIGHT

- Ideal for homogeneous basic lighting
- Can be rotated and swivelled
- High luminous flux

Application Area

Shop / Retail / Sales area, DIY store / discount store / supermarket / car dealership, Trade fair construction / shop fitting

Housing	Aluminium	Rated Input Voltage	110-240 V/AC
Length	300 mm	Power Supply Unit incl.	Yes
Width	110 mm	Light Beam Angle	110 Degree
Height	8.5 mm	Swivelling Angle	90 Degree
Power	20 W	CRI (Ra)	80



707134

Article	Housing Color	Colour Temperature	Luminous Flux	Price
707134	White	3000 K	2000 lm	€ 114.95
707135	Black	3000 K	2000 lm	€ 114.95
707136	White	4000 K	2200 lm	€ 109.95
707137	Black	4000 K	2200 lm	€ 109.95





FLOOD SMD 15 W

- Can be rotated and swivelled
- Large tilt angle

Application Area

Shop / Retail / Sales area, Trade fair construction / shop fitting

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Length	192 mm	Power Supply Unit incl.	Yes
Width	180 mm	Light Beam Angle	90 Degree
Height	38 mm	Swivelling Angle	180 Degree
Base Length	179 mm	CRI (Ra)	80
Base Width	20 mm	IK Protection Class	IK07
Power	15 W		

Article	Housing Color	Colour Temperature	Luminous Flux	Price
707130	☐ White	3000 K	1575 lm	€ 99.95
707138	☐ White	4000 K	1650 lm	€ 99.95



FLOOD SMD 30 W

- Can be rotated and swivelled
- Large tilt angle

Application Area

Shop / Retail / Sales area, Trade fair construction / shop fitting

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Length	261 mm	Power Supply Unit incl.	Yes
Width	236 mm	Light Beam Angle	90 Degree
Height	41 mm	Swivelling Angle	180 Degree
Base Length	237 mm	CRI (Ra)	80
Base Width	25 mm	IK Protection Class	IK07
Power	30 W		

Article	Housing Color	Colour Temperature	Luminous Flux	Price
707139	☐ White	3000 K	3150 lm	€ 139.95
707140	☐ White	4000 K	3300 lm	€ 139.95





DRACONIS

The DRACONIS series from DEKO-LIGHT allows flexible ceiling lighting for a variety of applications in the areas of industry, trade and logistics. With the DRACONIS light for optional use as a surface-mounted ceiling light or in a 3-phase track system, the power [45, 55 or 72 W] and light colour [2,700, 3,500 or 4,000 K] can be flexibly adjusted using a switch on the back of the housing. To be able to integrate the DRACONIS into almost any environment, we offer several lenses for asymmetrical or symmetrical lighting in different light emission angles. The maximum luminous flux is 8,250 lumens.





DRACONIS

- Output adjustable in three stages
- Light colour adjustable in three stages
- High luminous flux
- Replaceable lenses

Application Area

Shop / Retail / Sales area, DIY store / discount store / supermarket / car dealership, Trade fair construction / shop fitting

Housing	Aluminium	Base Width	88 mm
Colour Temperature	2700/3500/4000 K	Base Height	25 mm
Luminous Flux	7330/8210/8250 lm	Power Selectable	45 W, 55 W, 72 W
Length	577.6 mm	Rated Input Voltage	220-240 V/AC
Width	188.6 mm	Power Supply Unit incl.	Yes
Height	128.7 mm	Light Beam Angle	60 Degree
Base Length	102 mm	CRI (Ra)	80

Article	Housing Color		Price
620119		Light gray  	€ 349.95
620120		White  	€ 349.95



Accessories

930544	20° lens for surface-mounted ceiling lamp Draconis, symmetrical		€ 9.95
930545	30° lens for surface-mounted ceiling lamp Draconis, symmetrical		€ 9.95
930546	90° lens for surface-mounted ceiling lamp Draconis, symmetrical		€ 9.95
930577	15° lens for surface-mounted ceiling lamp Draconis, asymmetrical		€ 9.95





LINEAR 60

- low height
- homogeneous illumination


Application Area

Shop / Retail / Sales area, Home / Living, Trade fair construction / shop fitting, Hotel / catering

Housing	Aluminium	Power	18 W
Surface	Matt	Rated Input Voltage	200-240 V/AC
Length	687 mm	Power Supply Unit incl.	Yes
Width	32 mm	Light Beam Angle	110 Degree
Height	62 mm	CRI (Ra)	80



Article	Housing Color	Colour Temperature	Luminous Flux	Price
707148	Black	3000 K	1950 lm	€ 143.95
707147	White	3000 K	2100 lm	€ 143.95
707150	Black	4000 K	2100 lm	€ 143.95
707149	White	4000 K	2300 lm	€ 143.95



LINEAR 100

- low height
- homogeneous illumination


Application Area

Shop / Retail / Sales area, Home / Living, Trade fair construction / shop fitting, Hotel / catering

Housing	Aluminium	Power	28 W
Surface	Matt	Rated Input Voltage	200-240 V/AC
Length	1087 mm	Power Supply Unit incl.	Yes
Width	32 mm	Light Beam Angle	110 Degree
Height	62 mm	CRI (Ra)	80



Article	Housing Color	Colour Temperature	Luminous Flux	Price
707152	Black	3000 K	3100 lm	€ 184.95
707151	White	3000 K	3200 lm	€ 184.95
707154	Black	4000 K	3200 lm	€ 184.95
707153	White	4000 K	3400 lm	€ 184.95






ALNITAK

- power adjustable in four stages
- rotatable and swivelling
- low glare value

Application Area

Reception / Communication, Office / conference, Home / Living, Trade fair construction / shop fitting, Hotel / catering

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Length	336 mm	Power Supply Unit incl.	Yes
Width	49 mm	Light Beam Angle	36 Degree
Height	98 mm	Swivelling Angle	25 Degree
Power Selectable	23 W, 28 W, 30 W, 32 W	CRI (Ra)	80



707110

Article	Housing Color	Colour Temperature	Luminous Flux	Price
707110	White	WW 3000 K	3010 lm	€ 169.95
707112	Light gray	WW 3000 K	3020 lm	€ 169.95
707114	Black	WW 3000 K	3030 lm	€ 169.95
707113	Light gray	NW 4000 K	3050 lm	€ 169.95
707115	Black	NW 4000 K	3130 lm	€ 169.95
707111	White	NW 4000 K	3150 lm	€ 169.95



Accessories

930386	Reflector for lamp Ain, Alnitak 12°	€ 1.95
930387	Reflector for lamp Ain, Alnitak 48°	€ 1.95
930388	Ceti spot anti glare white	€ 2.95





LINEAR PRO

The LINEAR PRO 3-circuit track luminaires are the ideal solution for illuminating shelves and aisles in supermarkets and more.

The LINEAR PRO is a 3-phase luminaire and is available in three versions: FOLD, TILT and Standard. Each variant offers special advantages in lighting design and enables precise illumination of products and other objects. While the standard version has a particularly large, fixed beam angle of 120°, the LINEAR PRO TILT and LINEAR PRO FOLD can be flexibly aligned to the respective shop areas.

LINEAR PRO



LINEAR PRO TILT




LINEAR PRO FOLD



TILT or FOLD?

The LINEAR PRO TILT can either shine downwards as a whole or be swivelled individually by up to 30° to the side. In contrast, the LINEAR PRO FOLD is based on a three-part construction with two LED wings, which are supplemented by a diffuse light strip in the centre. This makes the LINEAR PRO FOLD particularly suitable for the homogeneous illumination of complete aisles with shelves on both sides, while the LINEAR PRO TILT can be flexibly aligned to individual shelves.



3 ADVANTAGES

ADJUSTABLE POWER


The power of the LINEAR PRO 3-circuit track lights can be adjusted in four stages. The luminaires are also DC-capable and can be integrated into emergency power systems.

BEG SUBSIDY

The LINEAR PRO luminaires fulfil the requirements of the BEG subsidy for efficient LED luminaires and are subsidised by the Federal Ministry for Economic Affairs and Climate Protection with 15%.

SEAMLESSLY COMBINABLE

The 1500 mm versions of the LINEAR PRO have a sliding track adapter and are each available in a 50% mirrored A/B version to allow for seamless side-by-side installation, even across track connectors.




LINEAR PRO FOLD

- Eligible for BEG German federal funding for energy-efficient buildings
- Emergency power capable [198-264 V/DC EOFI: 100 %]
- Long service life of 60,000 hours [L80B50]
- Can be swivelled up to 30° to each side
- Particularly energy efficient
- Output adjustable in four steps

Application Area

Reception / Communication, Shop / Retail / Sales area, Workshop / Craft / Warehouse, DIY store / discount store / supermarket / car dealership, Trade fair construction / shop fitting, Industry / production / high-bay warehouse, Safety lighting / emergency lighting

Housing	Aluminium	Light Beam Angle	30 Degree
Width	120 mm	Light Beam Angle 2	90 Degree
Height	68 mm	CRI (Ra)	90
Rated Input Voltage	198-264 V/AC	IK Protection Class	IK03
Power Supply Unit incl.	Yes		



707189

Article	Housing Color	Colour Temperature	Luminous Flux	Length	Power Selectable	Price
707205	White	3000 K	2900 lm	600 mm	14.0 W / 16.0 W / 18.0 W / 20.0 W	€ 174.95
707206	Black	3000 K	2900 lm	600 mm	14.0 W / 16.0 W / 18.0 W / 20.0 W	€ 174.95
707207	White	3000 K	7250 lm	1493 mm	35.0 W / 40.0 W / 45.0 W / 50.0 W	€ 209.95
707208	Black	3000 K	7250 lm	1493 mm	35.0 W / 40.0 W / 45.0 W / 50.0 W	€ 209.95
707189	White	4000 K	2900 lm	600 mm	14.0 W / 16.0 W / 18.0 W / 20.0 W	€ 174.95
707190	Black	4000 K	2900 lm	600 mm	14.0 W / 16.0 W / 18.0 W / 20.0 W	€ 174.95
707191	White	4000 K	7250 lm	1493 mm	35.0 W / 40.0 W / 45.0 W / 50.0 W	€ 209.95
707192	Black	4000 K	7250 lm	1493 mm	35.0 W / 40.0 W / 45.0 W / 50.0 W	€ 209.95






LINEAR PRO FOLD DALI

- Eligible for BEG German federal funding for energy-efficient buildings
- Emergency power capable [198-264 V/DC EOFI: 15 %]
- Long service life of 60,000 hours [L80B50]
- Can be swivelled up to 30° on each side
- Power adjustable in four stages
- Particularly energy efficient

Application Area
Reception / Communication, Shop / Retail / Sales area, Workshop / Craft / Warehouse, DIY store / discount store / supermarket / car dealership, Trade fair construction / shop fitting, Industry / production / high-bay warehouse, Safety lighting / emergency lighting

Housing	Aluminium	Power Supply Unit incl.	Yes
Length	1493 mm	Light Beam Angle	30 Degree
Width	120 mm	Light Beam Angle 2	90 Degree
Height	68 mm	Control	DALI 2 / DT6
Power	50 W	CRI (Ra)	90
Rated Input Voltage	198-264 V/AC	IK Protection Class	IK03



707193

Article	Housing Color	Colour Temperature	Luminous Flux	Price
707210	Black	3000 K	7000 lm	€ 239.95
707209	White	3000 K	7250 lm	€ 239.95
707194	Black	4000 K	7000 lm	€ 239.95
707193	White	4000 K	7250 lm	€ 239.95





LINEAR PRO TILT

- Eligible for BEG German federal funding for energy-efficient buildings
- Emergency power capable [198-264 V/DC EOFI: 100 %]
- Can be locked shining downwards
- Can be swivelled up to 30° to each side
- Long service life of 60,000 hours [L80B50]
- Particularly energy efficient
- Output adjustable in three stages

Application Area

Reception / Communication, Shop / Retail / Sales area, Workshop / Craft / Warehouse, DIY store / discount store / supermarket / car dealership, Trade fair construction / shop fitting, Industry / production / high-bay warehouse, Safety lighting / emergency lighting

Housing	Steel	Light Beam Angle	60 Degree
Width	60 mm	Swivelling Angle	60 Degree
Height	54 mm	CRI (Ra)	90
Rated Input Voltage	198-264 V/AC	IK Protection Class	IK03
Power Supply Unit incl.	Yes		

Article	Housing Color	Colour Temperature	Luminous Flux	Length	Power Selectable	Price
707195	 White	 3000 K	3200 lm	600 mm	14.0 W / 16.0 W / 18.0 W / 20.0 W	€ 153.95
707196	 Black	 3000 K	3200 lm	600 mm	14.0 W / 16.0 W / 18.0 W / 20.0 W	€ 153.95
707197	 White	 3000 K	8000 lm	1493 mm	35.0 W / 40.0 W / 45.0 W / 50.0 W	€ 189.95
707198	 Black	 3000 K	8000 lm	1493 mm	35.0 W / 40.0 W / 45.0 W / 50.0 W	€ 189.95
707141	 White	 4000 K	3200 lm	600 mm	14.0 W / 16.0 W / 18.0 W / 20.0 W	€ 153.95
707142	 Black	 4000 K	3200 lm	600 mm	14.0 W / 16.0 W / 18.0 W / 20.0 W	€ 153.95
707143	 White	 4000 K	8000 lm	1493 mm	35.0 W / 40.0 W / 45.0 W / 50.0 W	€ 189.95
707144	 Black	 4000 K	8000 lm	1493 mm	35.0 W / 40.0 W / 45.0 W / 50.0 W	€ 189.95





LINEAR PRO TILT DALI

- Eligible for BEG German federal funding for energy-efficient buildings
- Emergency power capable [198-264 V/DC EOFI: 15 %]
- Can be locked shining downwards
- Can be swivelled up to 30° to each side
- Power adjustable in four stages
- Long service life of 60,000 hours [L80B50]
- Particularly energy efficient

Application Area

Reception / Communication, Shop / Retail / Sales area, Workshop / Craft / Warehouse, DIY store / discount store / supermarket / car dealership, Trade fair construction / shop fitting, Industry / production / high-bay warehouse, Safety lighting / emergency lighting

Housing	Steel	Power Supply Unit incl.	Yes
Luminous Flux	8000 lm	Light Beam Angle	60 Degree
Length	1493 mm	Swivelling Angle	60 Degree
Width	60 mm	Control	DALI 2 / DT6
Height	54 mm	CRI (Ra)	90
Power	50 W	IK Protection Class	IK03
Rated Input Voltage	198-264 V/AC		

Article	Housing Color	Colour Temperature	Price
707199	White	3000 K	€ 219.95
707200	Black	3000 K	€ 219.95
707145	White	4000 K	€ 219.95
707146	Black	4000 K	€ 219.95





LINEAR PRO DALI

- Eligible for BEG German federal funding for energy-efficient buildings
- Emergency power capable [198-264 V/DC EOFI: 15 %]
- Power adjustable in four stages
- Long service life of 60,000 hours [L80B50]
- Particularly energy efficient

Application Area

Reception / Communication, Shop / Retail / Sales area, Workshop / Craft / Warehouse, DIY store / discount store / supermarket / car dealership, Trade fair construction / shop fitting, Industry / production / high-bay warehouse, Safety lighting / emergency lighting

Housing	Aluminium	Rated Input Voltage	198-264 V/AC
Length	602 mm	Power Supply Unit incl.	Yes
Width	61.1 mm	Light Beam Angle	120 Degree
Height	58 mm	Control	DALI 2 / DT6
Power Selectable	14 W, 16 W, 18 W, 20 W	CRI (Ra)	90
		IK Protection Class	IK03

Article	Housing Color	Colour Temperature	Luminous Flux	Price
707220	Black	3000 K	2800 lm	€ 143.95
707219	White	3000 K	2850 lm	€ 143.95
707222	Black	4000 K	2850 lm	€ 143.95
707221	White	4000 K	2900 lm	€ 143.95





LINEAR PRO DALI CCT

- Eligible for German BEG federal funding
- Can run on emergency power
- Power adjustable in four stages
- Long service life of 60,000 hours (L80B50)
- Particularly energy efficient

Application Area

Reception / Communication, Shop / Retail / Sales area, Workshop / Craft / Warehouse, DIY store / discount store / supermarket / car dealership, Trade fair construction / shop fitting, Industry / production / high-bay warehouse, Safety lighting / emergency lighting

Housing	Aluminium	Rated Input Voltage	198-264 V/AC
Colour Temperature	3000/3500/4000 K	Power Supply Unit incl.	Yes
Length	1196 mm	Light Beam Angle	120 Degree
Width	61.1 mm	Control	DALI 2 / DT6
Height	58 mm	CRI (Ra)	90
Power Selectable	28 W, 32 W, 36 W, 40 W	IK Protection Class	IK03

Article	Housing Color			Luminous Flux	Price
707224	 Black	 		4800/5000/4900 lm	€ 184.95
707223	 White	 		4900/5100/5000 lm	€ 184.95







CAN

- customisable with extensive accessories
- customised lighting solution thanks to replaceable light source
- combinable with the extensive product family of the CAN series

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Ø	60 mm	Control	Dimmable via optional light source
Pendulum Length	1500 mm		
Max. Power	1x max. 7.5 W		

Article	Housing Color	Height	Price
707251	White	150 mm	€ 69.95
707252	Black	150 mm	€ 69.95
707255	White	350 mm	€ 84.95
707256	Black	350 mm	€ 84.95



Accessories

930301	Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930302	Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930303	Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930366	Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
931065	Acrylic attachment for Can		€ 4.95





CAN

- customised lighting solution thanks to replaceable light source
- can be combined with the product family of the CAN series

Application Area

Home / Living, Reception / Communication, Hotel / catering, Trade fair construction / shop fitting

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Length	134 mm	Control	Dimmable via optional light source
Ø	60 mm	Swivelling Angle	90 Degree
Max. Power	1x max. 7.5 W		

Article	Housing Color	Price
707079	White	€ 49.95
707080	Silver	€ 49.95
707081	Black	€ 49.95



Accessories

930301	Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930302	Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930303	Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930366	Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
931065	Acrylic attachment for Can		€ 4.95





CAN BASE MIX'N MATCH 1/3

- customised lighting solution thanks to replaceable light source
- can be customised with cylinder housing in 6 different colours
- can be combined with the extensive product family of the CAN series

Housing	Aluminium	Control	Dimmable via optional light source
Height	91 mm	Rotation Angle	350 Degree
Ø	76 mm	Swivelling Angle	90 Degree
Max. Power	1x max. 7.5 W		
Rated Input Voltage	220-240 V/AC		

Article	Housing Color	Price
707246	 White	€ 41.95
707247	 Black	€ 41.95
707248	 Silver	€ 41.95



Light sources
For all lights and bases:
You can find the right light sources in the »Light sources« section.



CYLINDER HOUSING FOR CAN MIX'N MATCH 2/3

Housing Aluminium Ø 60 mm
Height 98 mm

Article	Housing Color	Price
931053	 White	€ 7.95
931054	 Black	€ 7.95
931055	 Bronze	€ 18.95
931056	 Brass	€ 18.95
931057	 Black gray	€ 18.95
931058	 Rosé	€ 18.95

IP20



REFLECTOR RING CAN SERIES MIX'N MATCH 3/3

Housing Plastic Ø 57 mm
Height 28 mm

Article	Housing Color	Price
930301	 White	€ 4.95
930302	 Black	€ 4.95
930303	 Gold	€ 4.95
930366	 Silver	€ 4.95

IP20



HORUS

If you're looking for a slim, powerful and flexible three-phase spotlight, look no further than the Horus. The slimline housing and matt surface finish combined with the powerful chip for all wattages make the Horus a true jack-of-all-trades.




HORUS

- low glare value
- can be rotated and swivelled

Application Area

Shop / Retail / Sales area, Office / conference, Office / conference

Housing	Plastic	Light Beam Angle	40 Degree
Surface	Matt	Swivelling Angle	350 Degree
Rated Input Voltage	220-240 V/AC	CRI (Ra)	80
Power Supply Unit incl.	Yes		



707094

Article	Housing Color	Colour Temperature	Luminous Flux	Height	Ø	Power	EEL	Price
707094	Black	WW 3000 K	625 lm	125 mm	60 mm	7.0 W	E	€ 69.95
707095	White	WW 3000 K	625 lm	125 mm	60 mm	7.0 W	E	€ 69.95
707098	Black	WW 3000 K	915 lm	140 mm	70 mm	10.0 W	E	€ 79.95
707099	White	WW 3000 K	915 lm	140 mm	70 mm	10.0 W	E	€ 79.95
707102	Black	WW 3000 K	1705 lm	185 mm	80 mm	20.0 W	F	€ 89.95
707103	White	WW 3000 K	1705 lm	185 mm	80 mm	20.0 W	F	€ 89.95
707106	Black	WW 3000 K	2525 lm	210 mm	90 mm	30.0 W	F	€ 109.95
707107	White	WW 3000 K	2525 lm	210 mm	90 mm	30.0 W	F	€ 109.95
707096	Black	NW 4000 K	635 lm	125 mm	60 mm	7.0 W	E	€ 69.95
707097	White	NW 4000 K	635 lm	125 mm	60 mm	7.0 W	E	€ 69.95
707100	Black	NW 4000 K	1030 lm	140 mm	70 mm	10.0 W	E	€ 79.95
707101	White	NW 4000 K	1030 lm	140 mm	70 mm	10.0 W	E	€ 79.95
707104	Black	NW 4000 K	1785 lm	185 mm	80 mm	20.0 W	F	€ 89.95
707105	White	NW 4000 K	1785 lm	185 mm	80 mm	20.0 W	F	€ 89.95
707108	Black	NW 4000 K	2605 lm	210 mm	90 mm	30.0 W	F	€ 109.95
707109	White	NW 4000 K	2605 lm	210 mm	90 mm	30.0 W	F	€ 109.95






UNI 2

- „Glow“ effect on reflector ring
- Can be rotated and swivelled
- Can be customised with a comprehensive range of accessories

Application Area


Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Trade fair construction / shop fitting

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000 K	Light Beam Angle	36 Degree
Height	167 mm	Swivelling Angle	90 Degree
Ø	100 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Power	17 W	CRI (Ra)	90
Rated Input Voltage	220-240 V/AC		



707044


Article	Housing Color		Luminous Flux	Price
707131	 Black		1080 lm	€ 185.95
707044	 White		1110 lm	€ 185.95



Accessories

930339	Reflector ring black for Uni II series		€ 10.95
930340	Reflector ring gold for Uni II series		€ 10.95
930341	Reflector ring chrome for Uni II series		€ 10.95
930335	Rear black cover for Uni II series		€ 2.95
930337	Black heat sink cover for Uni II series		€ 7.95
930306	48° reflector for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95






AARON

- can be rotated and swivelled
- high luminous flux

Application Area

Shop / Retail / Sales area, DIY store / discount store / supermarket / car dealership, Trade fair construction / shop fitting

Housing	Aluminium	Power	79 W
Surface	Matt	Rated Input Voltage	220-240 V/AC
Luminous Flux	7400 lm	Power Supply Unit incl.	Yes
Length	120 mm	Light Beam Angle	40 Degree
Width	182 mm	Swivelling Angle	90 Degree
Height	255 mm	CRI (Ra)	90
Ø	120 mm		



Article	Housing Color	Colour Temperature	EEI	Price
707090	Black	3000 K	E	€ 499.95
707092	White	3000 K	E	€ 499.95
707091	Black	4000 K	F	€ 499.95
707093	White	4000 K	F	€ 499.95



Lighting design
Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.




NIHAL

- can be rotated and swivelled
- large tilt angle

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Trade fair construction / shop fitting

Housing	Aluminium	Power Supply Unit incl.	Yes
Length	135 mm	Light Beam Angle	33 Degree
Width	138 mm	Swivelling Angle	180 Degree
Height	188 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Ø	86 mm	CRI (Ra)	90
Rated Input Voltage	220-240 V/AC		



707040

Article	Housing Color	Colour Temperature	Luminous Flux	Power	Price
707056	Silver	3000 K	2470 lm	33.0 W	€ 229.95
707041	Black	3000 K	2580 lm	33.0 W	€ 229.95
707040	White	3000 K	2880 lm	33.0 W	€ 229.95
707043	Black	4000 K	2660 lm	33.0 W	€ 229.95
707057	Silver	4000 K	2700 lm	35.0 W	€ 229.95
707042	White	4000 K	3100 lm	34.0 W	€ 229.95



Accessories

930315	Reflector ring white for Nihal series
930316	Reflector ring black for Nihal series
930365	Reflector ring silver for Nihal series
930317	Reflector ring gold for Nihal series
930311	Side cover white for Nihal series
930312	Side cover black for Nihal series
930363	Side cover silver for Nihal series
930313	Side cover gold for Nihal series
930314	Side cover walnut wood look for Nihal series
930769	Side cover natural oak wood look for Nihal series
930318	15° reflector for Nihal series
930320	50° reflector for Nihal series
930321	Honeycomb filter for Nihal series
930322	Spread lens for Nihal 37° series
930323	Softening lens for Nihal 37° series
930324	Linear spread lens for Nihal 40°/80° series






NIHAL MINI

- Can be rotated and swivelled
- Large tilt angle

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Trade fair construction / shop fitting

Housing	Aluminium	Power Supply Unit incl.	Yes
Length	94 mm	Light Beam Angle	35 Degree
Width	102 mm	Swivelling Angle	180 Degree
Height	139 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Ø	60 mm	CRI (Ra)	90
Power	15 W		
Rated Input Voltage	220-240 V/AC		



707036

Article	Housing Color	Colour Temperature	Luminous Flux	Price
707037	Black	3000 K	1080 lm	€ 177.95
707054	Silver	3000 K	1100 lm	€ 177.95
707036	White	3000 K	1240 lm	€ 177.95
707039	Black	4000 K	1160 lm	€ 177.95
707055	Silver	4000 K	1190 lm	€ 177.95
707038	White	4000 K	1330 lm	€ 177.95



Accessories

930301	Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930302	Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930303	Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930297	Side cover white for Nihal Mini series		€ 3.95
930298	Side cover black for Nihal Mini series		€ 3.95
930364	Side cover silver for Nihal Mini series		€ 3.95
930299	Side cover gold for Nihal Mini series		€ 3.95
930300	Side cover walnut wood look for Nihal Mini series		€ 5.95
930768	Side cover natural oak wood look for Nihal Mini series		€ 5.95
930306	48° reflector for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 8.95
930366	Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series		€ 4.95
930767	12° lens for Nihal Mini series		€ 10.95



RF-SMART EVENTUS RGB+CCT

The EVENTUS RGB+CCT swivelling and tilting track spotlight combines smart control with powerful LED technology. With a total output of up to 30 W, it offers dynamic light in 16 million colours and variable colour temperature. Thanks to 18 automatic programmes, dimmable brightness and colour saturation, atmospheric lighting scenes can be individually designed.

Can be controlled via 2.4 GHz RF remote control or via Zigbee 3.0-compatible systems such as Amazon Alexa, Google Assistant or Tuya [gateway required]. The integrated repeater function ensures reliable synchronisation of multiple components - ideal for smart lighting solutions in retail, exhibitions or modern living spaces.



RF-SMART EVENTUS RGB+CCT

- rotatable and swivelling
- brightness and colour saturation dimmable
- RGB 3x 6W (max. 18W), CW/WW 2x 30W (max. 30W), max. total output 30W
- 16 million colours and colour temperature adjustable
- 18 automatic programmes pre-installed
- program and remote control synchronisation when operating multiple RF-smart components [repeater function]
- opt. controllable with RF-smart radio remote controls [2.4Ghz, range approx. 30 m]
- controllable with all Zigbee 3.0 compatible controllers / apps such as Amazon Echo [Alexa], Google Assistant, Tuya [corresponding gateway required, outdoor range up to 100 m]

Housing	Plastic, Metal	Rated Input Voltage	100-240 V/AC
Surface	Powder-coated, Fine structure, Matt	Power Supply Unit incl.	Yes
Colour Temperature	2700-6000 K	Light Beam Angle	36 Degree
Luminous Flux	1800 lm	Rotation Angle	350 Degree
Length	205 mm	Swivelling Angle	90 Degree
Width	246 mm	Control	RF-Smart, ZigBee 3.0
Height	31 mm	CRI (Ra)	90
Power	30 W	Light Direction	Front

Article	Housing Color	Price
843530	White	€ 199.95
843531	Black	€ 199.95



Accessories

843510	RF-smart, remote control, white, 1 zone, RGB/RGBW/RGB+CCT, IP20		€ 38.95
843511	RF-smart, remote control, black, 1 zone, RGB/RGBW/RGB+CCT, IP20		€ 38.95
843512	RF-smart, remote control, black, 8 zones, single/CCT/RGB/RGBW/RGB+CCT		€ 49.95
843525	RF-smart, Standard Remote, black, 3 zones, Single/CCT/RGB/RGBW/RGB+C-CT		€ 49.95
843513	RF-smart, wall remote control, white, 3 V, 4 zones, single/CCT/RGB/W/+CCT		€ 69.95
843522	RF-smart, wall remote control, white, 230 V, 4 zones, single/CCT/RGB/W/+C-CT		€ 74.95
843514	RF-smart, wall remote control, white, 8 zones, single/CCT/RGB/RGBW/RGB+CCT		€ 109.95
843527	RF-smart, PIR motion detector, white, 120deg/7m, 3V		€ 38.95
843529	RF-smart, DMX-Gateway, 5V DC, 16 Zonen Single/CCT/RGB/W+CCT		€ 59.95

LUCEA

The LUCEA series includes pendant, ceiling and track luminaires and impresses with its timeless design and flexible customisation options.



lenses

Depending on the model, you can narrow or widen the beam angle of the LUCEA luminaires using the easily replaceable lenses.

reflector rings

With the reflector rings [available for all models in black, white and gold], you can set colourful accents depending on the surroundings and atmosphere.

door panels

With the optional barn door trim, you can limit the light emission of the LUCEA luminaires with particular precision using four individually adjustable wings.

LUCEA-VARIETY

surface-mounted lights

The LUCEA surface-mounted luminaires are available as pendant luminaires, as swivelling and tilting ceiling luminaires with a base and as fixed spotlights.



1-phase luminaires

The pendant luminaires with a particularly soft textile cable and the spotlights for use on single-circuit track systems are primarily aimed at private users looking for a slim and versatile solution for the home.




3-phase luminaires

The LUCEA luminaires for 3-phase 230V track systems are available as ceiling and pendant versions and, thanks to the CCT dip switch, are particularly suitable for commercial use in bars, restaurants or offices.



FLEXIBLE COLOUR TEMPERATURE


The colour temperature has a decisive influence on the lighting effect in the room. For this reason, the LUCEA series is available in different colour temperatures, depending on the model and intended use. With an Ra value >90, the LUCEA luminaires also guarantee true-to-life colour rendering of walls, ceilings and objects. Using the LUCEA ceiling light as an example, you can see in the illustrations below how the light colour and lighting mood change depending on the model version - from warm white to neutral white and as a flexible dim-to-warm version.



dim-to-warm


[1,800K - 2.700K]

In the dim-to-warm version, the colour temperature adjusts automatically when dimming [the lower the light intensity, the warmer the colour temperature].



2,700 K

For private users: the lights with extra warm white 2,700K.



3,000 K

For commercial applications: The surface-mounted and 3-phase luminaires offer a CCT dip switch to switch between 3,000K [warm white] and 4,000K [neutral white].



4,000 K


In addition to the CCT versions, the 3-phase spotlights with 40W are also available as a pure 4,000K [neutral white] version.

FLEXIBLE BEAM ANGLE


Wide, soft light or a precise, focussed spot – with the LUCEA series you have the choice, even retrospectively. In addition to the standard beam angle of 36°, the luminaires can be narrowed or widened in all versions (surface-mounted, pendant, track) using optionally available lenses. You are even more flexible with the optional, colour-matching barn door cover. With its four wings, the light emission can be adapted to different room and object geometries. The illustrations below show how the light emission of the LUCEA changes through the use of different lenses and the barn door.







24°
narrow beam angle with optional 24° lens



36°
standard beam angle with 36° lens [standard]




60°
wide beam angle with optional 60° lens



door panels

individual limitation of the beam angle with the wings of the barn door panel



LUCEA DALI

- emergency current capable [176-280V/DC EOFI: 100%]
- incl. black reflector ring

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Trade fair construction / shop fitting


Housing	Aluminium	EOFI	100 %
Colour Temperature	2700 K	Power Supply Unit incl.	Yes
Luminous Flux	1300 lm	Pendulum Length	1600 mm
Width	65 mm	Light Beam Angle	36 Degree
Height	184 mm	Control	DALI 2 / DT6, Push-Dim
Power	10 W	CRI (Ra)	90
Rated Input Voltage	200-240 V/AC	IK Protection Class	IK03
Voltage range emergency lighting	176-280 V/DC		

Article	Housing Color		Price
707244	White		€ 149.95
707245	Black		€ 149.95



Accessories

930679	Lens 24° for Lucea 6/10		€ 9.95
930756	Reflector ring for Lucea 6/10 white		€ 4.95
930757	Reflector ring for Lucea 6/10 black		€ 4.95
930758	Reflector ring for Lucea 6/10 gold		€ 4.95





LUCEA CCT DALI

- emergency current capable [176-280V/DC EOFI: 100%]
- light colour adjustable in two stages
- incl. black reflector ring



Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Trade fair construction / shop fitting

Housing	Aluminium	Pendulum Length	1600 mm
Colour Temperature	3000/4000 K	Light Beam Angle	36 Degree
Rated Input Voltage	200-240 V/AC	Control	DALI 2 / DT6, Push-Dim
Voltage range emergency lighting	176-280 V/DC	CRI (Ra)	90
EOFI	100 %	IK Protection Class	IK03
Power Supply Unit incl.	Yes		

Article	Housing Color		Luminous Flux	Width	Height	Power	Price
707234	White		930/1000 lm	65 mm	184 mm	11.0 W	€ 154.95
707235	Black		930/1000 lm	65 mm	184 mm	11.0 W	€ 154.95
707238	White		1930/2000 lm	85 mm	186 mm	20.0 W	€ 199.95
707239	Black		1930/2000 lm	85 mm	186 mm	20.0 W	€ 199.95



Accessories for **707234, 707235**

930679	Lens 24° for Lucea 6/10		€ 9.95
930756	Reflector ring for Lucea 6/10 white		€ 4.95
930757	Reflector ring for Lucea 6/10 black		€ 4.95
930758	Reflector ring for Lucea 6/10 gold		€ 4.95

Accessories for **707238, 707239**


930680	Lens 24° for Lucea 15/20		€ 12.95
930681	Lens 60° for Lucea 15/20		€ 12.95
930759	Reflector ring for Lucea 15/20 white		€ 5.95
930760	Reflector ring for Lucea 15/20 black		€ 5.95
930761	Reflector ring for Lucea 15/20 gold		€ 5.95



5-year guarantee

Benefit from the maximum quality promise:

All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.




LUCEA CCT

- Light colour adjustable in two stages
- Incl. black reflector ring

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Trade fair construction / shop fitting

Housing	Aluminium	Light Beam Angle	36 Degree
Colour Temperature	3000/4000 K	Control	Leading-edge dimmer, Trailing-edge dimmer
Rated Input Voltage	220-240 V/AC	CRI (Ra)	90
Power Supply Unit incl.	Yes	IK Protection Class	IK03
Pendulum Length	1800 mm		



707124

Article	Housing Color		Luminous Flux	Height	Ø	Power	Price
707124		White  	930/1000 lm	157 mm	65 mm	10.0 W	€ 149.95
707125		Black  	930/1000 lm	157 mm	65 mm	10.0 W	€ 149.95
707126		White  	1460/1500 lm	178 mm	85 mm	15.0 W	€ 177.95
707127		Black  	1460/1500 lm	178 mm	85 mm	15.0 W	€ 177.95
707128		White  	1930/2000 lm	178 mm	85 mm	20.0 W	€ 189.95
707129		Black  	1930/2000 lm	178 mm	85 mm	20.0 W	€ 189.95



Accessories for 707124, 707125

930679	Lens 24° for Lucea 6/10		€ 9.95
930756	Reflector ring for Lucea 6/10 white		€ 4.95
930757	Reflector ring for Lucea 6/10 black		€ 4.95
930758	Reflector ring for Lucea 6/10 gold		€ 4.95

Accessories for 707126, 707127, 707128, 707129

930680	Lens 24° for Lucea 15/20		€ 12.95
930681	Lens 60° for Lucea 15/20		€ 12.95
930759	Reflector ring for Lucea 15/20 white		€ 5.95
930760	Reflector ring for Lucea 15/20 black		€ 5.95
930761	Reflector ring for Lucea 15/20 gold		€ 5.95





LUCEA DTW

- high colour rendering
- Dim-to-warm 1,800K-2,700K
- incl. black reflector ring

Application Area

Home / Living, Reception / Communication, Hotel / catering

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	1800-2700 K	Pendulum Length	1800 mm
Luminous Flux	750 lm	Light Beam Angle	36 Degree
Height	157 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Ø	65 mm	CRI (Ra)	90
Power	10 W	IK Protection Class	IK03
Rated Input Voltage	200-240 V/AC		

Article	Housing Color		Price
707217	White		€ 135.95
707218	Black		€ 135.95



Accessories

930756	Reflector ring for Lucea 6/10 white		€ 4.95
930757	Reflector ring for Lucea 6/10 black		€ 4.95
930758	Reflector ring for Lucea 6/10 gold		€ 4.95



Technical data sheet

New in the onlineshop: The technical data sheets offer even more information: Light and energy data, light distribution curves, dimensional drawings and more.



LUCEA DALI

- emergency current capable [176-280V/DC EOFI: 100%]
- incl. black reflector ring
- can be customised with a wide range of accessories

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Trade fair construction / shop fitting

Housing	Aluminium	Control	DALI 2 / DT6, Intelli
Rated Input Voltage	200-240 V/AC		Push-Dim
Power Supply Unit incl.	Yes	CRI (Ra)	90
Light Beam Angle	36 Degree	IK Protection Class	IK03

Article	Housing Color	Colour Temperature	Luminous Flux	Width	Height	Power	Price
707240	 White	 2700 K	1950 lm	85 mm	269 mm	15.0 W	€ 159.95
707241	 Black	 2700 K	1950 lm	85 mm	269 mm	15.0 W	€ 159.95
707242	 White	 4000 K	4480 lm	100 mm	315 mm	40.0 W	€ 214.95
707243	 Black	 4000 K	4480 lm	100 mm	315 mm	40.0 W	€ 214.95



Accessories for 707240, 707241

930680	Lens 24° for Lucea 15/20		€ 12.95
930681	Lens 60° for Lucea 15/20		€ 12.95
930754	Door panel for Lucea 15/20 white		€ 23.95
930755	Door panel for Lucea 15/20 black		€ 23.95
930759	Reflector ring for Lucea 15/20 white		€ 5.95
930760	Reflector ring for Lucea 15/20 black		€ 5.95
930761	Reflector ring for Lucea 15/20 gold		€ 5.95

Accessories for 707242, 707243

930677	Door panel for Lucea 30/40 white		€ 24.95
930678	Door panel for Lucea 30/40 black		€ 24.95
930682	Lens 24° for Lucea 30		€ 15.95
930684	Lens 60° for Lucea 30		€ 15.95
930762	Reflector ring for Lucea 30/40 white		€ 6.95
930763	Reflector ring for Lucea 30/40 black		€ 6.95
930764	Reflector ring for Lucea 30/40 gold		€ 6.95



LUCEA CCT DALI

- emergency current capable [176-280V/DC EOFI: 100%]
- light colour adjustable in 2 shades
- incl. black reflector ring
- can be customised with a wide range of accessories

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Trade fair construction / shop fitting

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000/4000 K	Light Beam Angle	36 Degree
Luminous Flux	2700/2900 lm	Control	DALI 2 / DT6, Intelli Push-Dim
Width	100 mm	CRI (Ra)	90
Height	302 mm	IK Protection Class	IK03
Power	33 W		
Rated Input Voltage	200-240 V/AC		


Article	Housing Color		Price
707232	White	NW	€ 214.95
707233	Black	NW	€ 214.95



Accessories

930677	Door panel for Lucea 30/40 white
930678	Door panel for Lucea 30/40 black
930682	Lens 24° for Lucea 30
930684	Lens 60° for Lucea 30
930762	Reflector ring for Lucea 30/40 white
930763	Reflector ring for Lucea 30/40 black
930764	Reflector ring for Lucea 30/40 gold

	€ 24.95
	€ 24.95
	€ 15.95
	€ 15.95
	€ 6.95
	€ 6.95
	€ 6.95




LUCEA CCT

- Incl. black reflector ring
- Can be customised with a comprehensive range of accessories
- Light colour adjustable in two stages

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Trade fair construction / shop fitting

Housing	Aluminium	Swivelling Angle	90 Degree
Colour Temperature	3000/4000 K	Control	Leading-edge dimmer, Trailing-edge dimmer
Rated Input Voltage	220-240 V/AC	CRI (Ra)	90
Power Supply Unit incl.	Yes	IK Protection Class	IK03
Light Beam Angle	36 Degree		
Rotation Angle	350 Degree		



707116

Article	Housing Color			Luminous Flux	Height	Ø	Power	Price
707116	 White	 		930/1000 lm	249 mm	65 mm	10.0 W	€ 139.95
707117	 Black	 		930/1000 lm	249 mm	65 mm	10.0 W	€ 139.95
707118	 White	 		1460/1500 lm	269 mm	85 mm	15.0 W	€ 159.95
707119	 Black	 		1460/1500 lm	269 mm	85 mm	15.0 W	€ 159.95
707120	 White	 		1930/2000 lm	269 mm	85 mm	20.0 W	€ 179.95
707121	 Black	 		1930/2000 lm	269 mm	85 mm	20.0 W	€ 179.95
707122	 White	 		2700/2900 lm	302 mm	100 mm	30.0 W	€ 199.95
707123	 Black	 		2700/2900 lm	302 mm	100 mm	30.0 W	€ 199.95



Lighting design
Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.

Accessories for **707116, 707117**

930679	Lens 24° for Lucea 6/10		€ 9.95
930752	Door panel for Lucea 6/10 white		€ 22.95
930753	Door panel for Lucea 6/10 black		€ 22.95
930756	Reflector ring for Lucea 6/10 white		€ 4.95
930757	Reflector ring for Lucea 6/10 black		€ 4.95
930758	Reflector ring for Lucea 6/10 gold		€ 4.95

Accessories for **707118, 707119, 707120, 707121**

930680	Lens 24° for Lucea 15/20		€ 12.95
930681	Lens 60° for Lucea 15/20		€ 12.95
930754	Door panel for Lucea 15/20 white		€ 23.95
930755	Door panel for Lucea 15/20 black		€ 23.95
930759	Reflector ring for Lucea 15/20 white		€ 5.95
930760	Reflector ring for Lucea 15/20 black		€ 5.95
930761	Reflector ring for Lucea 15/20 gold		€ 5.95

Accessories for **707122, 707123**

930677	Door panel for Lucea 30/40 white		€ 24.95
930678	Door panel for Lucea 30/40 black		€ 24.95
930682	Lens 24° for Lucea 30		€ 15.95
930684	Lens 60° for Lucea 30		€ 15.95
930762	Reflector ring for Lucea 30/40 white		€ 6.95
930763	Reflector ring for Lucea 30/40 black		€ 6.95
930764	Reflector ring for Lucea 30/40 gold		€ 6.95



page 42



page 80



page 82



page 332



page 432





LUCEA

- Incl. black reflector ring
- Can be customised with a comprehensive range of accessories

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Trade fair construction / shop fitting

Housing	Aluminium	Light Beam Angle	36 Degree
Colour Temperature	4000 K	Rotation Angle	350 Degree
Luminous Flux	4480 lm	Swivelling Angle	90 Degree
Height	211 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Ø	100 mm	CRI (Ra)	90
Power	40 W	IK Protection Class	IK03
Rated Input Voltage	200-240 V/AC		
Power Supply Unit incl.	Yes		

Article	Housing Color	Price
707183	White	€ 199.95
707184	Black	€ 199.95



Accessories

930682	Lens 24° for Lucea 30		€ 15.95
930684	Lens 60° for Lucea 30		€ 15.95
930677	Door panel for Lucea 30/40 white		€ 24.95
930678	Door panel for Lucea 30/40 black		€ 24.95
930762	Reflector ring for Lucea 30/40 white		€ 6.95
930763	Reflector ring for Lucea 30/40 black		€ 6.95
930764	Reflector ring for Lucea 30/40 gold		€ 6.95



LUCEA DTW

- Dim-to-warm 1,800K - 2,700K
- incl. black reflector ring
- Can be customised with a wide range of accessories

Application Area

Home / Living, Reception / Communication, Hotel / catering

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	1800-2700 K	Light Beam Angle	36 Degree
Luminous Flux	750 lm	Control	Leading-edge dimmer, Trailing-edge dimmer
Height	249 mm	CRI (Ra)	90
Ø	65 mm	IK Protection Class	IK03
Power	10 W		
Rated Input Voltage	200-240 V/AC		

Article	Housing Color		Price
707213	White		€ 109.95
707214	Black		€ 109.95



Accessories

930752	Door panel for Lucea 6/10 white		€ 22.95
930753	Door panel for Lucea 6/10 black		€ 22.95
930756	Reflector ring for Lucea 6/10 white		€ 4.95
930757	Reflector ring for Lucea 6/10 black		€ 4.95
930758	Reflector ring for Lucea 6/10 gold		€ 4.95



page 42

page 80

page 82

page 432




SLIM

- Extra-soft fabric cable
- Glare-free due to low UGR value [<19]
- Suspended mounting up to 1,800 mm
- Slim design at just 39 mm in diameter

Application Area

Home / Living, Reception / Communication, Hotel / catering

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Colour Temperature	2700 K	Power Supply Unit incl.	Yes
Luminous Flux	500 lm	Pendulum Length	1500 mm
Length	1800 mm	Light Beam Angle	24 Degree
Height	300 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Ø	39 mm	CRI (Ra)	90
Power	5 W		



707162

Article	Housing Color		Price
707161	Black	www	€ 93.95
707162	White	www	€ 93.95



Accessories

930748	36° lens for Slim series		€ 4.95
930749	60° lens for Slim series		€ 4.95
930744	Reflector ring white for Slim series		€ 4.95
930745	Reflector ring black for Slim series		€ 4.95
930746	Reflector ring gold-coloured for Slim series		€ 5.95






SLIM

- glare-free, thanks to low UGR value [<19]
- slim design with a diameter of only 39 mm
- incl. silver-coloured reflector ring

Application Area

Home / Living, Reception / Communication, Hotel / catering

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	2700 K	Light Beam Angle	36 Degree
Luminous Flux	500 lm	Rotation Angle	330 Degree
Length	213 mm	Swivelling Angle	60 Degree
Ø	39 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Power	5 W	CRI (Ra)	90
Rated Input Voltage	220-240 V/AC		



707203

Article	Housing Color		Price
707203	White	WW	€ 82.95
707204	Black	WW	€ 82.95



Accessories

930744	Reflector ring white for Slim series		€ 4.95
930745	Reflector ring black for Slim series		€ 4.95
930746	Reflector ring gold-coloured for Slim series		€ 5.95
930748	36° lens for Slim series		€ 4.95
930749	60° lens for Slim series		€ 4.95



STUDIO PAR 30

- replaceable lamp (E27)
- can be rotated and swivelled
- integrated mesh chip guard
- incl. adapter

Application Area

Home / Living, Trade fair construction / shop fitting, Theatre / event

Housing	Aluminium	Max. Power	1x max. 42 W
Length	158.8 mm	Rated Input Voltage	220-240 V/AC
Width	158.8 mm	Control	Dimmable via optional light source
Height	270.8 mm		

Article	Housing Color	Price
707082	 Black	€ 72.95
707083	 Silver	€ 72.95




Accessories

001623	Door panel		€ 29.95
001621	Door panel		€ 29.95



Onlineshop
You can find more information about the products in the onlineshop:
Detailed images, videos, project reports, LDT files, EPREL data sheets and more.








BATTERY AND SOLAR LIGHTS

- 448 battery lights
- 456 solar lights



battery and solar lights



page 448



page 450



page 454



page 454



page 455



page 455



page 456



page 457



page 458



page 459





CANIS BUNDLE

Discover our portable cordless LED lamps from the CANIS series. With a 3.5 W output and 270 lm of brightness, our lamps provide a particularly wide and pleasant light distribution. And the infinitely variable dimming function allows you to set the perfect illumination using the practical touch sensor. Choose from two light colour levels to create the perfect atmosphere. And the best part? One battery charge is enough for more than eight hours of lighting. You can charge up to six lamps at the same time with the optional charging dock, so you always have enough lights to hand. Choose from eight colours, including trendy pastel tones, to reflect your personal style.

Note: Includes USB charging base





CANIS BUNDLE

- Pleasant and wide light distribution
- More than eight hours of light after charging
- Infinitely dimmable via touch sensor
- Light colour adjustable in two stages
- Charge up to six cordless lamps using the stackable charging dock [optional]
- Includes USB charging base

Application Area

Garden / Terrace / Balcony / Walkways, Reception / Communication, Home / Living, Hotel / catering

Housing	Aluminium	Ø	112 mm
Surface	Matt	Power	3.5 W
Colour Temperature	2200/3000 K	Rated Input Voltage	3.7 V/DC
Luminous Flux	270 lm	Light Beam Angle	100 Degree
Height	370 mm	CRI (Ra)	80

Article	Housing Color	Price
620194	 Sand	 € 109.95
620195	 Medium gray	 € 109.95
620196	 Terracotta	 € 109.95
620197	 Blue	 € 109.95
620198	 Rust	 € 109.95
620199	 White	 € 109.95
620200	 Black	 € 109.95
620201	 Dark grey	 € 109.95



Accessories

- 930716** 6-way charging station incl. power supply for Canis light
- 930887** USB-A plug-in power supply 5 V DC, 1,000 mA, black

	€ 199.95
	€ 8.95



CANIS MINI BUNDLE

Discover our portable cordless LED lamps from the CANIS series. With a 2.3 W output and 110 lm of brightness, our lamps provide a particularly wide and pleasant light distribution. And the infinitely variable dimming function allows you to set the perfect illumination using the practical touch sensor. Choose from two light colour levels to create the perfect atmosphere. And the best part? One battery charge is enough for more than eight hours of lighting. You can charge up to 15 lamps at the same time with the optional charging station, so you always have enough lights to hand. Choose from eight colours, including trendy pastel tones, to reflect your personal style.

Note: Includes USB charging base





CANIS MINI BUNDLE

- Pleasant and wide light distribution
- More than eight hours of light after charging
- Infinitely dimmable using touch sensor
- Light colour adjustable in two stages
- Charge up to 15 cordless lamps using the stackable charging dock [optional]
- Includes USB charging base

Application Area

Garden / Terrace / Balcony / Walkways, Reception / Communication, Home / Living, Hotel / catering

Housing	Aluminium	Ø	76 mm
Surface	Matt	Power	2.3 W
Colour Temperature	2200/3000 K	Rated Input Voltage	3.7 V/DC
Luminous Flux	110 lm	CRI (Ra)	80
Height	208 mm		

Article	Housing Color	Price
620202	 Sand 	€ 99.95
620203	 Medium gray 	€ 99.95
620204	 Terracotta 	€ 99.95
620205	 Blue 	€ 99.95
620206	 Rust 	€ 99.95
620207	 White 	€ 99.95
620208	 Black 	€ 99.95
620209	 Dark grey 	€ 99.95



Accessories

- 930734** 15-way charging station incl. power supply unit for Canis Mini light
- 930887** USB-A plug-in power supply 5 V DC, 1,000 mA, black



€ 299.95

€ 8.95

MIRAM

Combine & shine – with the MIRAM series, there are no more limits to your creativity. Simply combine the luminaire head in your favourite colour with a stand, a wall bracket or a pendant fixture of your choice. In this way, you can create your very own individual luminaire in the twinkling of an eye and recombine it at any time without tools. Flexible, simple, chic - that is MIRAM combine & shine.

it's that simple:

- choose a luminaire head in your favourite colour
- select the desired fastening in your favourite colour

your advantages::

- USB-C cable included
- 147 possible combinations



346025



346033



346032



346034



346035



346036



346037



930625



930627



930626



930628



930629



930630



930631



930618



930620



930619



930621



930622



930623



930624



930611



930613



930612



930614




930615



930616



930617





MIRAM

Application Area
Garden / Terrace / Balcony / Walkways, Reception / Communication, Home / Living

Housing	Aluminium	Power	2.2 W
Colour Temperature	3000 K	Rated Input Voltage	3.7 V/DC
Luminous Flux	196 lm	Power Supply Unit incl.	No
Height	30 mm	Light Beam Angle	47 Degree
Ø	120 mm	CRI (Ra)	80

Article	Housing Color	Price
346025	 White	 € 99.95
346032	 Black	 € 99.95
346033	 Light gray	 € 99.95
346034	 Red	 € 99.95
346035	 Yellow	 € 99.95
346036	 Blue	 € 99.95
346037	 Light gray	 € 99.95



STAND FOR MAGNETIC LIGHT MIRAM

Housing	Aluminium	Ø	102 mm
Height	270 mm		

Article	Housing Color	Price
930611	 White	€ 34.95
930612	 Black	€ 34.95
930613	 Grey	€ 34.95
930614	 Red	€ 34.95
930615	 Yellow	€ 34.95
930616	 Blue	€ 34.95
930617	 Green	€ 34.95



WALL BRACKET, MIRAM SERIES

Housing	Aluminium	Height	96 mm
Width	85 mm	Base Ø	60 mm

Article	Housing Color	Price
930618	 White	€ 19.95
930619	 Black	€ 19.95
930620	 Grey	€ 19.95
930621	 Red	€ 19.95
930622	 Yellow	€ 19.95
930623	 Blue	€ 19.95
930624	 Green	€ 19.95



PENDANT, MIRAM SERIES

Housing	Aluminium	Height	185 mm
Width	205 mm	Pendulum Length	2190 mm

Article	Housing Color	Price
930625	 White	€ 34.95
930626	 Black	€ 34.95
930627	 Grey	€ 34.95
930628	 Red	€ 34.95
930629	 Yellow	€ 34.95
930630	 Blue	€ 34.95
930631	 Green	€ 34.95



SAMAS SOLAR

Need lighting but don't have an available power supply? We have the solution. The SAMAS SOLAR series only needs sunlight - and not even consistent sunlight. Thanks to its clever energy-saving mode, in which it emits just 15 % light output in standby mode, it lasts an impressively long time. When the built-in sensor detects movement, it switches to full light output. The lighting can also be switched off using a button. The powerful light output combined with state-of-the-art technology for long runtimes makes it the perfect solution for walls, tables and gardens.



SAMAS SOLAR

- Motion/twilight sensor
- Highly efficient solar panel
- Includes 3.70 V and 2,200 mAh Li-ion rechargeable battery
- Incl. ground spike

Application Area

Garden / Terrace / Balcony / Walkways

Housing	Aluminium	Rated Input Voltage	3.7 V/DC
Colour Temperature	3000 K	Power Supply Unit incl.	No
Length	140 mm	Light Beam Angle	98 Degree
Width	140 mm	CRI (Ra)	80
Power	2.2 W	Motion Detector	Yes

Article	Housing Color	Luminous Flux	Height	Price
733050	Dark grey	135 lm	500 mm	€ 149.95
733049	Dark grey	170 lm	340 mm	€ 139.95



SAMAS SOLAR

- Motion/twilight sensor
- Highly efficient solar panel
- Includes 3.70 V and 2,200 mAh Li-ion rechargeable battery

Application Area

Garden / Terrace / Balcony / Walkways, House wall / facade / front door

Housing	Aluminium	Power	2.2 W
Colour Temperature	3000 K	Rated Input Voltage	3.7 V/DC
Luminous Flux	130 lm	Power Supply Unit incl.	No
Length	154 mm	Light Beam Angle	106 Degree
Width	140 mm	CRI (Ra)	80
Height	290 mm	Motion Detector	Yes

Article	Housing Color	Price
731122	Dark grey	€ 139.95





STANDING LIGHT SOLAR PREMIUM

The SOLAR PREMIUM series features an impressive futuristic design and provides both innovative and decorative lighting outdoors and in gardens. Power is supplied by a built-in rechargeable battery with solar panel, eliminating the need for unsightly or expensive cable installations.



STANDING LIGHT SOLAR PREMIUM

- Motion/twilight sensor
- highly efficient solar panel
- includes 3.70 V and 2,200 mAh Li-ion rechargeable battery
- tilting lamp head

Application Area
Garden / Terrace / Balcony / Walkways

Housing	Aluminium	Power	1.6 W
Colour Temperature	3000 K	Rated Input Voltage	3.7 V/DC
Luminous Flux	170 lm	Power Supply Unit incl.	No
Length	200 mm	Light Beam Angle	110 Degree
Width	151 mm	Swivelling Angle	180 Degree
Height	1000 mm	CRI (Ra)	80

Article	Housing Color		Price
733046	Dark grey		€ 219.95




SOLAR PREMIUM

- Motion/twilight sensor
- Highly efficient solar panel
- Includes 3.70 V and 2,200 mAh Li-ion rechargeable battery
- Tilting lamp head

Application Area
Garden / Terrace / Balcony / Walkways, House wall / facade / front door

Housing	Aluminium	Power	1.6 W
Colour Temperature	3000 K	Rated Input Voltage	3.7 V/DC
Luminous Flux	170 lm	Power Supply Unit incl.	No
Length	160.5 mm	Light Beam Angle	110 Degree
Width	233.2 mm	Swivelling Angle	180 Degree
Height	152 mm	CRI (Ra)	80



731116


Article	Housing Color		Price
731116	Dark grey		€ 149.95






OUTDOOR LIGHTS

- 464 bollard lights
- 484 surface mounted wall lights
- 522 ceiling and wall lights
- 526 built in wall lights
- 532 spherical lamps
- 536 energy distributor
- 546 surface mounted / ground spike lights
- 556 wall washer
- 560 ground recessed lights
- 580 floodlight
- 586 display lights



bollard lights



page 464



page 465



page 466



page 468



page 470



page 472



page 474



page 476



page 478



page 480





ESTADA

Application Area
 Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Home / Living, Hotel / catering

Housing	Stainless steel	Rated Input Voltage	220-240 V/AC
Height	1000 mm	Control	Dimmable via optional light source
Ø	100 mm		
Max. Power	1x max. 11 W		

Article	Housing Color	Price
730009	 Silver	€ 119.95





NOVA


- E27 socket suitable for A19 LED lamps
- with motion/twilight sensor [art. no. 730032 only]

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Home / Living

Housing	Stainless steel	Max. Power	1x max. 40 W
Height	1100 mm	Rated Input Voltage	220-240 V/AC
Ø	75 mm	Colour of Light Output	White

Article	Housing Color	Dimmable	Control	Motion Detector	Type of Motion Detector	Price
730032	 Silver				Yes	Infrared € 99.95
730007	 Silver	Yes	Dimmable via optional light source		No	€ 79.95





FACADO 2 SQUARE

Our FACADO series bollard lights feature IP65 degree of protection for excellent weather resistance. Choose between an opal diffuser or a transparent diffuser with smoked glass to suit your requirements. The series is available in two different sizes (650 mm/1,000 mm) and features an E27 socket for replaceable lamps. The newly designed lamp head provides even better illumination. The FACADO light is made from high-quality die-cast aluminium and available in dark grey or rust and in square or rounded designs.

The IP67 connection box features a double M20 cable gland suitable for buried cables in sizes $3 \times 1.5 \text{ mm}^2$, $5 \times 1.5 \text{ mm}^2$ or $3 \times 2.5 \text{ mm}^2$, and more.



FACADO 2 SQUARE

- IP65 weather resistance
- IP67 connection box suitable for e.g. buried cables 3x1.5 mm²/5x1.5 mm²/3x2.5 mm²
- Newly designed lamp head for improved illumination
- Available with an opal diffuser or a transparent diffuser with smoked glass
- Ideal for e.g. ST64 bulbs and A60/70 bulbs

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Home / Living, Hotel / catering

Housing	Aluminium, Polycarbonate	Max. Power	1x max. 20 W
Surface	Matt	Rated Input Voltage	220-240 V/AC
Length	108 mm	Control	Dimmable via optional light source
Width	108 mm		

Article	Housing Color	Height	Colour of Light Output	Price
730496	Dark grey	650 mm	Smoke-coloured	€ 149.95
730495	Dark grey	650 mm	White	€ 149.95
730497	Dark grey	1000 mm	Smoke-coloured	€ 199.95
730498	Dark grey	1000 mm	White	€ 199.95



Accessories

- 180359 MAS VLE E27 ST64 4 W 1,800 K gold-coloured
- 180361 CLA150 E27 DIM 18 W 3,300 K, matt



€ 39.95
€ 27.95



FACADO 2 ROUND

Our FACADO series bollard lights feature IP65 degree of protection for excellent weather resistance. Choose between an opal diffuser or a transparent diffuser with smoked glass to suit your requirements. The series is available in two different sizes (650 mm/1,000 mm) and features an E27 socket for replaceable lamps. The newly designed lamp head provides significantly improved illumination. The FACADO light is made of high-quality, die-cast aluminium and is available in dark grey or rust and in square or round designs. The IP67 connection box features a double M20 cable gland suitable for e.g. buried cables in sizes 3x1.5 mm², 5x1.5 mm² or 3x2.5 mm².





FACADO 2 ROUND

- IP65 weather resistance
- IP67 connection box suitable for e.g. buried cables 3x1.5 mm²/5x1.5 mm²/3x2.5 mm²
- Newly designed lamp head for improved illumination
- Available with an opal diffuser or a transparent diffuser with smoked glass
- Ideal for e.g. ST64 bulbs and A60/70 bulbs

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Home / Living, Hotel / catering

Housing	Aluminium, Polycarbonate	Max. Power	1x max. 20 W
Surface	Matt	Rated Input Voltage	220-240 V/AC
Ø	108 mm	Control	Dimmable via optional light source

Article	Housing Color	Height	Colour of Light Output	Price
730499	Dark grey	650 mm	Smoke-coloured	€ 149.95
730501	Rust	650 mm	Smoke-coloured	€ 149.95
730500	Dark grey	650 mm	White	€ 149.95
730502	Rust	650 mm	White	€ 149.95
730503	Dark grey	1000 mm	Smoke-coloured	€ 199.95
730505	Rust	1000 mm	Smoke-coloured	€ 199.95
730504	Dark grey	1000 mm	White	€ 199.95
730506	Rust	1000 mm	White	€ 199.95



Accessories

- 180359** MAS VLE E27 ST64 4 W 1,800 K gold-coloured
180361 CLA150 E27 DIM 18 W 3,300 K, matt




€ 39.95

€ 27.95



FARO

The solid FARO bollard lights made from die-cast aluminium are available in the sizes 25, 60 and 100 cm. Their design [more than 97 % of light directed downwards] and lens optics allow glare-free light distribution and a particularly large light beam of up to 10 metres in diameter. All variants are also DALI2 DT6 compatible. The FARO models can be equipped with an optional screening shade to illuminate surfaces on one side only. The IP68 connection box with possible feed-through wiring and the dirt-repellent powder coating in DB703 make the FARO bollard lights a long-lasting and high-quality choice for your outdoor lighting.






FARO

- Glare-free, light directed downwards (>97 %)
- Lens optics for wide homogeneous illumination with up to 4/7/10 m diameter
- Optional screening shade for darkening on one side
- IP68 connection box with feed-through wiring
- Particularly high-quality and solid construction
- Dirt-repellent powder coating in DB703
- Emergency power capable (180-264 V/DC EOFI: 100 %)

Application Area

Garden / Terrace / Balcony / Walkways, Park / public outdoor area, Object lighting / architecture

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000 K	Light Beam Angle	360 Degree
Luminous Flux	1030 lm	Light Beam Angle 2	180 Degree
Ø	180 mm	Control	DALI 2 / DT6
Power	24 W	CRI (Ra)	80
Rated Input Voltage	180-264 V/AC	IK Protection Class	IK10



730492

Article	Housing Color		Height	Price
730492	Dark grey		250 mm	€ 439.95
730493	Dark grey		600 mm	€ 509.95
730494	Dark grey		1000 mm	€ 589.95



Accessories

- 930731 Concrete anchor for Faro series
- 930776 Screening shade 180 degrees for Faro series




€ 24.95
€ 9.95



LERNA

LERNA series bollard lights offer a number of advantages. The ability to adjust the light colour in 2 stages (3,000 K/4,000 K) allows you to choose the colour temperature that sets the perfect ambience. The downward orientation of the lighting also fully guarantees efficient illumination without creating light pollution. LERNA series bollard lights are available in two different sizes (600 mm and 1,000 mm). With a power rating of 7.4 W and up to 256 lm, the light itself is incredibly bright.





LERNA

- Light colour adjustable in two stages
- Light directed fully downwards to prevent light pollution

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Home / Living, Hotel / catering

Housing	Aluminium	Rated Input Voltage	200-240 V/AC
Colour Temperature	3000/4000 K	Power Supply Unit incl.	Yes
Luminous Flux	237/256 lm	Light Beam Angle	50 Degree
Length	120 mm	Light Beam Angle 2	100 Degree
Width	100 mm	CRI (Ra)	80
Power	7.4 W	IK Protection Class	IK06

Article	Housing Color			Height	Price
733073		Dark grey	 	600 mm	€ 209.95
733072		Dark grey	 	1000 mm	€ 259.95






CATA

The CATA series impresses not only as a modern path light, but also as a standalone lighting and design feature when creating outdoor spaces. The LEDs not only ensure full-surface illumination of paths and entrance areas but also inevitably draw attention to the striking frame construction. Available in three sizes, the CATA IV models can also be combined really well.






CATA

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Home / Living, Hotel / catering

Housing	Aluminium	Base Height	20 mm
Colour Temperature	3000 K	Power	4 W
Luminous Flux	170 lm	Rated Input Voltage	100-240 V/AC
Length	151 mm	Power Supply Unit incl.	Yes
Width	61 mm	Light Beam Angle	120 Degree
Base Length	145 mm	Primary Connection End	Connection box IP65
Base Width	55 mm	CRI (Ra)	80



733040

Article	Housing Color	Height	Price
733040	Dark grey	500 mm	€ 199.95
733041	Dark grey	700 mm	€ 219.95
733042	Dark grey	1000 mm	€ 239.95





CHERTAN

With its extraordinary mix of materials consisting of die-cast aluminium housing and base made of weather-resistant, fibreglass-reinforced concrete, the CHERTAN outdoor standing light certainly stands apart from other models just on looks alone. With its pleasantly warm white light and light emission angle of 120°, the outdoor light is perfectly suited for decorative use in entrance areas, on paths or in the garden.

Note: As concrete is a natural product, every surface is unique and forms a distinct patina over time, depending on local conditions. It is therefore normal in wet conditions for a blotchy surface to form that disappears again when dried, yet produces an individual patina over the long-term.





CHERTAN

· Fibreglass-reinforced and weather-resistant concrete base

Application Area

Garden / Terrace / Balcony / Walkways, Hotel / catering

Housing	Aluminium	Power	13 W
Colour Temperature	3000 K	Rated Input Voltage	100-277 V/AC
Length	170 mm	Power Supply Unit incl.	Yes
Width	72 mm	Light Beam Angle	120 Degree
Base Length	160 mm	Primary Connection End	Connection box IP54
Base Width	30 mm	CRI (Ra)	90
Base Height	40 mm		

Article	Housing Color	Luminous Flux	Height	Price
733043	 Dark grey 	480 lm	450 mm	€ 199.95
733044	 Dark grey 	530 lm	600 mm	€ 219.95
733045	 Dark grey 	640 lm	1000 mm	€ 239.95





ORTIS

The Ortis LED bollard light cuts an excellent figure anywhere with its dark grey aluminium housing and, thanks to its IP54 certification, is suitable for flexible outdoor use in gardens, entrances and as path lighting. In addition, the Ortis has an internal slatted insert in the lamp head, which ensures a pleasant dimmed light that is directed downwards (warm white, 3,000 K).





ORTIS

·Light directed downwards, dimmed by the slatted insert

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Home / Living, Hotel / catering

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Colour Temperature	3000 K	Power Supply Unit incl.	Yes
Luminous Flux	510 lm	Light Beam Angle	360 Degree
Height	1000 mm	Primary Connection End	Connection box
Ø	120 mm	CRI (Ra)	80
Power	15.9 W	IK Protection Class	IK05

Article	Housing Color	Price
733004	 Dark grey 	€ 219.95





TUCANAE

With its slim, unfussy housing design, the TUCANAE is a modern outdoor light that can be integrated almost anywhere. The 100-cm-high bollard light emits its warm white light diagonally downwards onto paths and other surfaces and, in the MOTION variant, has an integrated twilight switch with adjustable brightness threshold and operating time.






TUCANAE

- Powerful and energy saving
- Uniform illumination
- Adjustable brightness threshold and operating time [733068]

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Home / Living, Hotel / catering


Housing	Aluminium	Base Height	10 mm
Colour Temperature	3000 K	Power	18 W
Luminous Flux	1650 lm	Rated Input Voltage	110-240 V/AC
Length	206 mm	Power Supply Unit incl.	Yes
Width	180 mm	Light Beam Angle	110 Degree
Height	1000 mm	Primary Connection End	Connection box
Base Length	120 mm	CRI (Ra)	80
Base Width	180 mm		




733068

Article	Housing Color	IP Protection Type	Motion Detector	Type of Motion Detector	Price
733068	Dark grey	IP 54	Yes	Infrared	€ 293.95
733069	Dark grey	IP 65	No		€ 259.95





surface mounted wall lights



■ ■ □
page 484



■ ■ □
page 485



■ ■ □
page 486



■ ■ □
page 487



■ ■ □
page 488



■ ■ □
page 489



■ ■ □
page 490



■ ■ □
page 491



■ ■ □
page 492



■ ■ □
page 493



■ ■ □
page 494



■ ■ □
page 495



■ ■ ■
page 496



■ ■ ■
page 497



■
page 498



■
page 499



■
page 500



■ ■ ■
page 501



■
page 502



■
page 503



■
page 505



■ ■ ■
page 505



■ ■
page 506



■ ■
page 507



■
page 508



■
page 510



■
page 512



■ ■
page 513



■
page 514



■
page 515



■
page 516



■
page 517



■ ■
page 518



SHORELINE PRO ROUND

- continuous wiring possible
- seawater-resistant
- easy and quick installation
- separable mounting plate with plug-in connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Max. Power	1x max. 7.5 W
Height	140 mm	Rated Input Voltage	220-240 V/AC
Ø	68 mm	Control	Dimmable via optional light source
Base Length	43 mm		
Base Width	55 mm	IK Protection Class	IK08
Base Height	130 mm	Colour of Light Output	Clear

Article	Housing Color	Price
731211	Light grey	€ 89.95
731212	Dark grey	€ 89.95
731213	White	€ 89.95



Accessories

930874	Spacer for ShoreLine Pro series, light grey	€ 5.95
930877	Spacer for ShoreLine Pro series, dark grey	€ 5.95
930880	Spacer for ShoreLine Pro series, white	€ 5.95
180275	PAR16, GU10, 230 V/AC, 2,700 K, 36 degrees	€ 6.95
180209	MASTER VALUE LEDspot VLE, GU10, 230 V/AC, DIM, 2,700 K, 36 degrees	€ 13.95
180208	MASTER VALUE LEDspot VLE, GU10, 230 V/AC, DIM, 2,700 K, 36 degrees	€ 14.95
180049	MASTER VALUE LEDspot MV, GU10, 230 V/AC, DIM, 2,700 K, 60 degrees	€ 14.95
180099	MASTER VALUE LEDspot MV, GU10, 230 V/AC, DIM, 3,000 K, 36 degrees	€ 14.95
180050	MASTER VALUE LEDspot MV, GU10, 230 V/AC, DIM, 3,000 K, 60 degrees	€ 14.95
180053	MASTER VALUE LEDspot MV, GU10, 230 V/AC, DIM, 4,000 K, 36 degrees	€ 14.95
180051	MASTER VALUE LEDspot MV, GU10, 230 V/AC, DIM, 4,000 K, 60 degrees	€ 14.95
180139	MASTER LEDspot Value, GU10, 230 V/AC, DIM, 3,000 K, 36 degrees	€ 20.95
180149	MASTER LEDspot Value, GU10, 230 V/AC, DIM, 4,000 K, 36 degrees	€ 20.95
180285	PAR16, GU10, 230 V/AC, DIM, 2,700 K, 60 degrees	€ 14.95





SHORELINE PRO ROUND UP+DOWN

- continuous wiring possible
- seawater-resistant
- easy and quick installation
- separable mounting plate with plug-in connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering


Housing	Aluminium	Max. Power	2x max. 7.5 W
Height	158 mm	Rated Input Voltage	220-240 V/AC
Ø	68 mm	Control	Dimmable via optional light source
Base Length	43 mm	IK Protection Class	IK08
Base Width	55 mm	Colour of Light Output	Clear
Base Height	130 mm		

Article	Housing Color	Price
731214	Light grey	€ 99.95
731215	Dark grey	€ 99.95
731216	White	€ 99.95



Accessories

930874	Spacer for ShoreLine Pro series, light grey	€ 5.95
930877	Spacer for ShoreLine Pro series, dark grey	€ 5.95
930880	Spacer for ShoreLine Pro series, white	€ 5.95
180275	PAR16, GU10, 230 V/AC, 2,700 K, 36 degrees	€ 6.95
180209	MASTER VALUE LEDspot VLE, GU10, 230 V/AC, DIM, 2,700 K, 36 degrees	€ 13.95
180208	MASTER VALUE LEDspot VLE, GU10, 230 V/AC, DIM, 2,700 K, 36 degrees	€ 14.95
180049	MASTER VALUE LEDspot MV, GU10, 230 V/AC, DIM, 2,700 K, 60 degrees	€ 14.95
180099	MASTER VALUE LEDspot MV, GU10, 230 V/AC, DIM, 3,000 K, 36 degrees	€ 14.95
180050	MASTER VALUE LEDspot MV, GU10, 230 V/AC, DIM, 3,000 K, 60 degrees	€ 14.95
180053	MASTER VALUE LEDspot MV, GU10, 230 V/AC, DIM, 4,000 K, 36 degrees	€ 14.95
180051	MASTER VALUE LEDspot MV, GU10, 230 V/AC, DIM, 4,000 K, 60 degrees	€ 14.95
180139	MASTER LEDspot Value, GU10, 230 V/AC, DIM, 3,000 K, 36 degrees	€ 20.95
180149	MASTER LEDspot Value, GU10, 230 V/AC, DIM, 4,000 K, 36 degrees	€ 20.95
180285	PAR16, GU10, 230 V/AC, DIM, 2,700 K, 60 degrees	€ 14.95



SHORELINE PRO SQUARE 70

- light colour adjustable in 2 stages
- through-wiring possible
- seawater resistant
- separable mounting plate through plug connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting
- opt. interchangeable reflector inserts / reflectors

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Base Height	130 mm
Colour Temperature	3000/4000 K	Power	6 W
Luminous Flux	480/550 lm	Rated Input Voltage	220-240 V/AC
Length	70 mm	Power Supply Unit incl.	Yes
Width	70 mm	Light Beam Angle	30 Degree
Height	150 mm	Control	Trailing-edge dimmer
Base Length	43 mm	CRI (Ra)	90
Base Width	55 mm	IK Protection Class	IK08

Article	Housing Color	Price
731205	Light grey	€ 179.95
731206	Dark grey	€ 179.95
731207	White	€ 179.95



Accessories

930867	Cover, 100, line, ShoreLine Pro Series, dark grey	€ 9.95
930868	Cover, 100, triangular, ShoreLine Pro Series, dark grey	€ 9.95
930878	Reflector, 68/70, ShoreLine Pro Series, 30 degrees, chrome	€ 7.95
930879	Reflector, 68/70, ShoreLine Pro Series, 60 degrees, chrome	€ 7.95
930874	Spacer for ShoreLine Pro series, light grey	€ 5.95
930877	Spacer for ShoreLine Pro series, dark grey	€ 5.95
930880	Spacer for ShoreLine Pro series, white	€ 5.95



SHORELINE PRO SQUARE 100

- Light colour adjustable in 2 stages
- through-wiring possible
- Seawater resistant
- separable mounting plate through plug connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting
- opt. interchangeable reflector inserts / reflectors

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Power	12 W
Colour Temperature	3000/4000 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	900/1000 lm	Power Supply Unit incl.	Yes
Length	100 mm	Light Beam Angle	36 Degree
Width	100 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Height	163 mm	CRI (Ra)	90
Base Length	40 mm	IK Protection Class	IK08
Base Width	80 mm		
Base Height	130 mm		

Article	Housing Color	Price
731202	Light grey	€ 189.95
731203	Dark grey	€ 189.95
731204	White	€ 189.95



Accessories

930867	Cover, 100, line, ShoreLine Pro Series, dark grey	€ 9.95
930868	Cover, 100, triangular, ShoreLine Pro Series, dark grey	€ 9.95
930875	Reflector, 100, ShoreLine Pro Series, 36 degrees, chrome	€ 14.95
930876	Reflector, 100, ShoreLine Pro Series, 60 degrees, chrome	€ 14.95
930874	Spacer for ShoreLine Pro series, light grey	€ 5.95
930877	Spacer for ShoreLine Pro series, dark grey	€ 5.95
930880	Spacer for ShoreLine Pro series, white	€ 5.95



SHORELINE PRO SQUARE 140

- light colour adjustable in 2 stages
- through-wiring possible
- seawater resistant
- separable mounting plate through plug connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting
- opt. interchangeable reflector inserts / reflectors

Application Area
 Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Colour Temperature	3000/4000 K	Power Supply Unit incl.	Yes
Length	140 mm	Light Beam Angle	36 Degree
Width	140 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Height	218 mm	CRI (Ra)	90
Base Length	44.5 mm	IK Protection Class	IK08
Base Width	80 mm		
Base Height	130 mm		

Article	Housing Color		Luminous Flux	Power	Price
731181		Light grey	 	2000/2300 lm	20.5 W € 269.95
731182		Dark grey	 	2000/2300 lm	20.5 W € 269.95
731183		White	 	2000/2300 lm	20.5 W € 269.95
731184		Light grey	 	3100/3400 lm	33.0 W € 299.95
731185		Dark grey	 	3100/3400 lm	33.0 W € 299.95
731186		White	 	3100/3400 lm	33.0 W € 299.95



Accessories

930869	Cover, 140, line, ShoreLine Pro Series, dark grey	€ 12.95
930870	Cover, 140, triangular, ShoreLine Pro Series, dark grey	€ 12.95
930871	Reflector, 140, ShoreLine Pro Series, 24 degrees, chrome	€ 17.95
930872	Reflector, 140, ShoreLine Pro Series, 36 degrees, chrome	€ 17.95
930873	Reflector, 140, ShoreLine Pro Series, 60 degrees, chrome	€ 17.95
930874	Spacer for ShoreLine Pro series, light grey	€ 5.95
930877	Spacer for ShoreLine Pro series, dark grey	€ 5.95
930880	Spacer for ShoreLine Pro series, white	€ 5.95



SHORELINE PRO ROUND 68

- light colour adjustable in 2 stages
- through-wiring possible
- seawater resistant
- separable mounting plate through plug connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting
- opt. interchangeable reflector inserts / reflectors

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Power	6 W
Colour Temperature	3000/4000 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	480/550 lm	Power Supply Unit incl.	Yes
Height	150 mm	Light Beam Angle	30 Degree
Ø	68 mm	Control	Trailing-edge dimmer
Base Length	43 mm	CRI (Ra)	90
Base Width	55 mm	IK Protection Class	IK08
Base Height	130 mm		

Article	Housing Color		Price
731217	Light grey	WW NW	€ 169.95
731218	Dark grey	WW NW	€ 169.95
731219	White	WW NW	€ 169.95



Accessories

930867	Cover, 100, line, ShoreLine Pro Series, dark grey	€ 9.95
930868	Cover, 100, triangular, ShoreLine Pro Series, dark grey	€ 9.95
930878	Reflector, 68/70, ShoreLine Pro Series, 30 degrees, chrome	€ 7.95
930879	Reflector, 68/70, ShoreLine Pro Series, 60 degrees, chrome	€ 7.95
930874	Spacer for ShoreLine Pro series, light grey	€ 5.95
930877	Spacer for ShoreLine Pro series, dark grey	€ 5.95
930880	Spacer for ShoreLine Pro series, white	€ 5.95



SHORELINE PRO ROUND 100

- light colour adjustable in 2 stages
- through-wiring possible
- seawater-resistant
- easy and quick installation
- separable mounting plate with plug-in connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting
- opt. interchangeable reflector inserts / reflectors

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Power	12 W
Colour Temperature	3000/4000 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	900/1000 lm	Power Supply Unit incl.	Yes
Height	163 mm	Light Beam Angle	36 Degree
Ø	100 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Base Length	40 mm	CRI (Ra)	92
Base Width	80 mm	IK Protection Class	IK08
Base Height	130 mm		

Article	Housing Color	Price
731196	Light grey	€ 189.95
731197	Dark grey	€ 189.95
731198	White	€ 189.95



Accessories

930867	Cover, 100, line, ShoreLine Pro Series, dark grey	€ 9.95
930868	Cover, 100, triangular, ShoreLine Pro Series, dark grey	€ 9.95
930875	Reflector, 100, ShoreLine Pro Series, 36 degrees, chrome	€ 14.95
930876	Reflector, 100, ShoreLine Pro Series, 60 degrees, chrome	€ 14.95
930874	Spacer for ShoreLine Pro series, light grey	€ 5.95
930877	Spacer for ShoreLine Pro series, dark grey	€ 5.95
930880	Spacer for ShoreLine Pro series, white	€ 5.95



SHORELINE PRO ROUND 140

- light colour adjustable in 2 stages
- through-wiring possible
- seawater resistant
- separable mounting plate through plug connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting
- opt. interchangeable reflector inserts / reflectors

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering


Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Colour Temperature	3000/4000 K	Power Supply Unit incl.	Yes
Height	218 mm	Light Beam Angle	36 Degree
Ø	140 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Base Length	40 mm	CRI (Ra)	92
Base Width	80 mm	IK Protection Class	IK08
Base Height	130 mm		

Article	Housing Color	Luminous Flux	Power	Price
731169	Light grey	2000/2200 lm	20.0 W	€ 259.95
731170	Dark grey	2000/2200 lm	20.0 W	€ 259.95
731171	White	2000/2200 lm	20.0 W	€ 259.95
731172	Light grey	3100/3400 lm	33.0 W	€ 299.95
731173	Dark grey	3100/3400 lm	33.0 W	€ 299.95
731174	White	3100/3400 lm	33.0 W	€ 299.95



Accessories

930869	Cover, 140, line, ShoreLine Pro Series, dark grey	€ 12.95
930870	Cover, 140, triangular, ShoreLine Pro Series, dark grey	€ 12.95
930871	Reflector, 140, ShoreLine Pro Series, 24 degrees, chrome	€ 17.95
930872	Reflector, 140, ShoreLine Pro Series, 36 degrees, chrome	€ 17.95
930873	Reflector, 140, ShoreLine Pro Series, 60 degrees, chrome	€ 17.95
930874	Spacer for ShoreLine Pro series, light grey	€ 5.95
930877	Spacer for ShoreLine Pro series, dark grey	€ 5.95
930880	Spacer for ShoreLine Pro series, white	€ 5.95



SHORELINE PRO SQUARE UP+DOWN 70

- light colour adjustable in 2 stages
- through-wiring possible
- seawater resistant
- separable mounting plate through plug connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting
- opt. interchangeable reflector inserts / reflectors

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Base Height	130 mm
Colour Temperature	3000/4000 K	Power	7.5 W
Luminous Flux	700/780 lm	Rated Input Voltage	220-240 V/AC
Length	70 mm	Power Supply Unit incl.	Yes
Width	70 mm	Light Beam Angle	30 Degree
Height	186 mm	Control	Trailing-edge dimmer
Base Length	43 mm	CRI (Ra)	90
Base Width	55 mm	IK Protection Class	IK08

Article	Housing Color	Price
731208	 Light grey  	€ 209.95
731209	 Dark grey  	€ 209.95
731210	 White  	€ 209.95



Accessories

930867	Cover, 100, line, ShoreLine Pro Series, dark grey	€ 9.95
930868	Cover, 100, triangular, ShoreLine Pro Series, dark grey	€ 9.95
930878	Reflector, 68/70, ShoreLine Pro Series, 30 degrees, chrome	€ 7.95
930879	Reflector, 68/70, ShoreLine Pro Series, 60 degrees, chrome	€ 7.95
930874	Spacer for ShoreLine Pro series, light grey	€ 5.95
930877	Spacer for ShoreLine Pro series, dark grey	€ 5.95
930880	Spacer for ShoreLine Pro series, white	€ 5.95



SHORELINE PRO SQUARE UP+DOWN 100

- light colour adjustable in 2 stages
- through-wiring possible
- seawater resistant
- separable mounting plate through plug connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting
- opt. interchangeable reflector inserts / reflectors

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Base Height	130 mm
Colour Temperature	3000/4000 K	Power	21 W
Luminous Flux	1800/2000 lm	Rated Input Voltage	220-240 V/AC
Length	100 mm	Power Supply Unit incl.	Yes
Width	100 mm	Light Beam Angle	36 Degree
Height	238 mm	Control	Trailing-edge dimmer
Base Length	40 mm	CRI (Ra)	92
Base Width	80 mm	IK Protection Class	IK08

Article	Housing Color		Price
731199	Light grey	WW NW	€ 259.95
731200	Dark grey	WW NW	€ 259.95
731201	White	WW NW	€ 259.95



Accessories

930867	Cover, 100, line, ShoreLine Pro Series, dark grey	€ 9.95
930868	Cover, 100, triangular, ShoreLine Pro Series, dark grey	€ 9.95
930875	Reflector, 100, ShoreLine Pro Series, 36 degrees, chrome	€ 14.95
930876	Reflector, 100, ShoreLine Pro Series, 60 degrees, chrome	€ 14.95
930874	Spacer for ShoreLine Pro series, light grey	€ 5.95
930877	Spacer for ShoreLine Pro series, dark grey	€ 5.95
930880	Spacer for ShoreLine Pro series, white	€ 5.95



SHORELINE PRO SQUARE UP+DOWN 140

- light colour adjustable in 2 stages
- through-wiring possible
- seawater resistant
- separable mounting plate through plug connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting
- opt. interchangeable reflector inserts / reflectors

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Colour Temperature	3000/4000 K	Power Supply Unit incl.	Yes
Length	140 mm	Light Beam Angle	36 Degree
Width	140 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Height	332 mm	CRI (Ra)	90
Base Length	44.5 mm	IK Protection Class	IK08
Base Width	80 mm		
Base Height	130 mm		

Article	Housing Color	Luminous Flux	Power	Price
731187	 Light grey  	3200/3400 lm	31.5 W	€ 369.95
731188	 Dark grey  	3200/3400 lm	31.5 W	€ 369.95
731189	 White  	3200/3400 lm	31.5 W	€ 369.95
731190	 Light grey  	5400/5800 lm	55.0 W	€ 459.95
731191	 Dark grey  	5400/5800 lm	55.0 W	€ 459.95
731192	 White  	5400/5800 lm	55.0 W	€ 459.95



Accessories

930869	Cover, 140, line, ShoreLine Pro Series, dark grey	€ 12.95
930870	Cover, 140, triangular, ShoreLine Pro Series, dark grey	€ 12.95
930871	Reflector, 140, ShoreLine Pro Series, 24 degrees, chrome	€ 17.95
930872	Reflector, 140, ShoreLine Pro Series, 36 degrees, chrome	€ 17.95
930873	Reflector, 140, ShoreLine Pro Series, 60 degrees, chrome	€ 17.95
930874	Spacer for ShoreLine Pro series, light grey	€ 5.95
930877	Spacer for ShoreLine Pro series, dark grey	€ 5.95
930880	Spacer for ShoreLine Pro series, white	€ 5.95



SHORELINE PRO ROUND UP+DOWN 68

- light colour adjustable in 2 stages
- through-wiring possible
- seawater resistant
- separable mounting plate through plug connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting
- opt. interchangeable reflector inserts / reflectors

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Power	7.5 W
Colour Temperature	3000/4000 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	700/780 lm	Power Supply Unit incl.	Yes
Height	186 mm	Light Beam Angle	30 Degree
Ø	68 mm	Control	Trailing-edge dimmer
Base Length	43 mm	CRI (Ra)	90
Base Width	55 mm	IK Protection Class	IK08
Base Height	130 mm		

Article	Housing Color		Price
731220	Light grey	WW NW	€ 199.95
731221	Dark grey	WW NW	€ 199.95
731222	White	WW NW	€ 199.95



Accessories

930867	Cover, 100, line, ShoreLine Pro Series, dark grey	€ 9.95
930868	Cover, 100, triangular, ShoreLine Pro Series, dark grey	€ 9.95
930878	Reflector, 68/70, ShoreLine Pro Series, 30 degrees, chrome	€ 7.95
930879	Reflector, 68/70, ShoreLine Pro Series, 60 degrees, chrome	€ 7.95
930874	Spacer for ShoreLine Pro series, light grey	€ 5.95
930877	Spacer for ShoreLine Pro series, dark grey	€ 5.95
930880	Spacer for ShoreLine Pro series, white	€ 5.95



SHORELINE PRO ROUND UP+DOWN 100

- light colour adjustable in 2 stages
- through-wiring possible
- seawater resistant
- separable mounting plate through plug connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting
- opt. interchangeable reflector inserts / reflectors

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Power	20 W
Colour Temperature	3000/4000 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	1700/1900 lm	Power Supply Unit incl.	Yes
Height	238 mm	Light Beam Angle	36 Degree
Ø	100 mm	Control	Trailing-edge dimmer
Base Length	40 mm	CRI (Ra)	92
Base Width	80 mm	IK Protection Class	IK08
Base Height	130 mm		

Article	Housing Color		Price
731193	 Light grey		€ 259.95
731194	 Dark grey		€ 259.95
731195	 White		€ 259.95



Accessories

930867	Cover, 100, line, ShoreLine Pro Series, dark grey	€ 9.95
930868	Cover, 100, triangular, ShoreLine Pro Series, dark grey	€ 9.95
930875	Reflector, 100, ShoreLine Pro Series, 36 degrees, chrome	€ 14.95
930876	Reflector, 100, ShoreLine Pro Series, 60 degrees, chrome	€ 14.95
930874	Spacer for ShoreLine Pro series, light grey	€ 5.95
930877	Spacer for ShoreLine Pro series, dark grey	€ 5.95
930880	Spacer for ShoreLine Pro series, white	€ 5.95



SHORELINE PRO ROUND UP+DOWN 140

- light colour adjustable in 2 stages
- through-wiring possible
- seawater resistant
- separable mounting plate through plug connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting
- opt. interchangeable reflector inserts / reflectors

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Colour Temperature	3000/4000 K	Power Supply Unit incl.	Yes
Height	332 mm	Light Beam Angle	36 Degree
Ø	140 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Base Length	40 mm	CRI (Ra)	92
Base Width	80 mm	IK Protection Class	IK08
Base Height	130 mm		

Article	Housing Color	Luminous Flux	Power	Price
731175	Light grey	3100/3400 lm	31.0 W	€ 359.95
731176	Dark grey	3100/3400 lm	31.0 W	€ 359.95
731177	White	3100/3400 lm	31.0 W	€ 359.95
731178	Light grey	5100/5600 lm	54.0 W	€ 459.95
731179	Dark grey	5100/5600 lm	54.0 W	€ 459.95
731180	White	5100/5600 lm	54.0 W	€ 459.95



Accessories

930869	Cover, 140, line, ShoreLine Pro Series, dark grey	€ 12.95
930870	Cover, 140, triangular, ShoreLine Pro Series, dark grey	€ 12.95
930871	Reflector, 140, ShoreLine Pro Series, 24 degrees, chrome	€ 17.95
930872	Reflector, 140, ShoreLine Pro Series, 36 degrees, chrome	€ 17.95
930873	Reflector, 140, ShoreLine Pro Series, 60 degrees, chrome	€ 17.95
930874	Spacer for ShoreLine Pro series, light grey	€ 5.95
930877	Spacer for ShoreLine Pro series, dark grey	€ 5.95
930880	Spacer for ShoreLine Pro series, white	€ 5.95



NOVA

·Motion/twilight sensor

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, House wall / facade / front door, Home / Living

Housing	Stainless steel	Base Ø	110 mm
Width	145 mm	Max. Power	1x max. 40 W
Height	388 mm	Rated Input Voltage	220-240 V/AC
Ø	75 mm	Colour of Light Output	White
Base Height	25 mm		

Article	Housing Color	Price
730034	 Silver	€ 79.95



Light sources
For all lights and bases:
You can find the right light sources in the »Light sources« section.




ORTIS

Application Area
Garden / Terrace / Balcony / Walkways, Garage / carport / car park, House wall / facade / front door, Home / Living, Hotel / catering


Housing	Aluminium	Base Width	77 mm
Colour Temperature	3000 K	Base Height	67 mm
Luminous Flux	510 lm	Power	15.9 W
Length	260 mm	Rated Input Voltage	220-240 V/AC
Width	120 mm	Power Supply Unit incl.	Yes
Height	181 mm	Light Beam Angle	360 Degree
Ø	120 mm	CRI (Ra)	80
Base Length	100 mm		

Article	Housing Color		Price
731031	Dark grey		€ 199.95



page 478





FACADO 2 SQUARE

- Feed-through wiring possible
- Mounting plate can be disconnected via plug
- Quick and secure installation
- IP65 weather resistance
- Newly designed lamp head for improved illumination

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, House wall / facade / front door, Home / Living, Hotel / catering

Housing	Aluminium, Polycarbonate	Height	261.5 mm
Surface	Matt	Max. Power	1x max. 20 W
Length	148 mm	Rated Input Voltage	220-240 V/AC
Width	108 mm	Control	Dimmable via optional light source

Article	Housing Color	Colour of Light Output	Price
731151	 Dark grey	Smoke-coloured	€ 124.95
731157	 Dark grey	White	€ 124.95



Accessories

- 180359** MAS VLE E27 ST64 4 W 1,800 K gold-coloured
- 180361** CLA150 E27 DIM 18 W 3,300 K, matt





FACADO 2 ROUND

- Feed-through wiring possible
- Mounting plate can be disconnected via plug
- Quick and secure installation
- IP65 weather resistance
- Newly designed lamp head for improved illumination

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, House wall / facade / front door, Home / Living, Hotel / catering

Housing	Aluminium, Polycarbonate	Ø	108 mm
Surface	Matt	Max. Power	1x max. 20 W
Length	144 mm	Rated Input Voltage	220-240 V/AC
Height	261.5 mm	Control	Dimmable via optional light source

Article	Housing Color	Colour of Light Output	Price
731153	Dark grey	Smoke-coloured	€ 124.95
731155	Rust	Smoke-coloured	€ 124.95
731154	Dark grey	White	€ 124.95
731156	Rust	White	€ 124.95



Accessories

180359	MAS VLE E27 ST64 4 W 1,800 K gold-coloured
180361	CLA150 E27 DIM 18 W 3,300 K, matt

	€ 39.95
	€ 27.95






TUCANAE

- Modern minimalist design
- Powerful and energy saving
- Uniform illumination
- Adjustable brightness threshold and operating time [model-dependent]

Application Area

Garden /Terrace / Balcony / Walkways, Garage / carport / car park, House wall / facade / front door, Home / Living, Hotel / catering

Housing	Aluminium	Base Width	135 mm
Colour Temperature	3000 K	Base Height	15 mm
Luminous Flux	1650 lm	Power	18 W
Length	140 mm	Rated Input Voltage	110-240 V/AC
Width	172 mm	Power Supply Unit incl.	Yes
Height	219 mm	Light Beam Angle	110 Degree
Base Length	125 mm	CRI (Ra)	80



731133

Article	Housing Color		IP Protection Type	Motion Detector	Price	
731133		Dark grey		IP 54	Yes	€ 198.95
731144		Dark grey		IP 65	No	€ 185.95



Accessories

180512 BASIC, CC, CC35018/18 W



€ 23.95





ACHERNAR

·Exchangeable lamp GU10 [retrofit]

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Hotel / catering

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Height	95 mm	Control	Dimmable via optional light source
Ø	63 mm		

Article	Housing Color	Length	Base Length	Base Width	Max. Power	Price
731130	■ Dark grey	108 mm			1x max. 50.0 W	€ 46.95
731131	■ Dark grey	158 mm	125 mm	135 mm	2x max. 35.0 W	€ 56.95








CUBODO 2

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Hotel / catering

Housing	Aluminium	Base Width	108 mm
Colour Temperature	3000 K	Rated Input Voltage	220-240 V/AC
Length	108 mm	Power Supply Unit incl.	Yes
Width	108 mm	Light Beam Angle	19 Degree
Height	115 mm	CRI (Ra)	80
Base Length	108 mm		



731026

Article	Housing Color	Luminous Flux	Power	Light Beam Angle	2 Light Direction	IK Protection Class	Price
731024	Dark grey	WW	600 lm	8.5 W		Below	IK04 € 159.95
731025	Light gray	WW	600 lm	8.5 W		Below	IK04 € 159.95
731026	White	WW	600 lm	8.5 W		Below	IK04 € 159.95
731015	Dark grey	WW	1300 lm	16.0 W	19 Degree	Top / Below	IK04 € 179.95
731019	Light gray	WW	1300 lm	16.0 W	19 Degree	Top / Below	IK04 € 179.95
731020	White	WW	1300 lm	16.0 W	19 Degree	Top / Below	IK04 € 179.95




CUBODO 2 MINI

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Hotel / catering

Housing	Aluminium	Base Height	20 mm
Colour Temperature	3000 K	Rated Input Voltage	220-240 V/AC
Length	90 mm	Power Supply Unit incl.	Yes
Width	68 mm	Light Beam Angle	46 Degree
Base Length	65 mm	CRI (Ra)	77
Base Width	65 mm		



731029


Article	Housing Color	Luminous Flux	Height	Power	Light Direction	Price
731029	Dark grey	WW	220 lm	70 mm	5.0 W Below	€ 119.95
731030	Dark grey	WW	440 lm	108 mm	9.9 W Top / Below	€ 149.95





CAN IP65

The CAN IP65 surface-mounted wall light is a robust and versatile solution for outdoor areas. Available as a classic wall light and as an up/down variant with light emission on both sides, it is ideal for demanding environments. The IP65 certification guarantees protection against dust and water. The widely used GU10 base enables quick and simple replacement of the lamp. Push terminals for rigid and flexible conductors facilitate simple installation. The CAN outdoor light is part of a versatile series and is also available as a pendant, ceiling, wall and reading light.



page 46



page 88



page 90



page 414



CAN IP65


- Replaceable lamp to offer an individual lighting solution
- Can be combined with the comprehensive product family of the CAN series

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Hotel / catering

Housing	Aluminium	Max. Power	1x max. 7.5 W
Length	87 mm	Rated Input Voltage	220-240 V/AC
Height	108 mm	Control	Dimmable via optional light source
Ø	80 mm		

Article	Housing Color	Price
731223	White	€ 59.95
731224	Black	€ 59.95



CAN UP & DOWN IP65

- Replaceable lamp to offer an individual lighting solution
- Can be combined with the comprehensive product family of the CAN series

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Hotel / catering

Housing	Aluminium	Max. Power	2x max. 7.5 W
Length	87 mm	Rated Input Voltage	220-240 V/AC
Height	212 mm	Control	Dimmable via optional light source
Ø	80 mm		

Article	Housing Color	Price
731225	White	€ 89.95
731226	Black	€ 89.95





JABBAH

The square JABBAH uses integrated COB LEDs in warm white, emitting its light asymmetrically at an angle of 75° onto walls in a cone of illumination - in a simple variant providing 915 lumens, as an UP AND DOWN version providing a total of 1,850 lumens. In addition, the two-sided JABBAH can be dimmed to 60 % luminous flux using a dip switch, if a more subtle light is desired.






JABBAH

- Feed-through wiring possible
- Mounting plate can be disconnected via plug
- Quick and secure installation
- Incl. wall spacer for surface-mounted cable entry
- Power adjustable in 2 stages (model-dependent)

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Power Selectable	13 W, 25 W
Colour Temperature	3000 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	1850 lm	Power Supply Unit incl.	Yes
Length	150 mm	Light Beam Angle	75 Degree
Width	150 mm	CRI (Ra)	80
Height	150 mm		




731127

Article	Housing Color		Price
731127	 Dark grey		€ 345.95




Lighting design
Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.



ARCTURUS

The ARCTURUS LED wall-mounted light has a modern cube design [optionally also elongated] and is suitable for flexible lighting outdoors. Using an integrated shutter, the beam angle of the IP54 light can be adjusted between 0° and 90° in order to generate a different light pattern depending on the requirements of the application. Protected in the dark grey die-cast aluminium housing are the two high-power LEDs, which generate 5.5 W of warm-white light.

IP54




ARCTURUS

- Continuously adjustable light emission angle 0-90°
- Uplight and downlight separately adjustable
- Ideal for customised lighting accents

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Hotel / catering

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000 K	Light Beam Angle	90 Degree
Power	6 W	CRI (Ra)	80
Rated Input Voltage	220-240 V/AC		



731099

Article	Housing Color		Luminous Flux	Length	Width	Height	Base Length	Price
731099	Dark grey	WW	200 lm	110 mm	79 mm	172 mm	68 mm	€ 109.95
731100	Dark grey	WW	208 lm	105 mm	140 mm	145 mm	75 mm	€ 109.95



Technical data sheet


New in the onlineshop: The technical data sheets offer even more information: Light and energy data, light distribution curves, dimensional drawings and more.



LINEAR 250

Application Area
 Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Base Width	53 mm
Colour Temperature	3000 K	Base Height	15 mm
Length	250 mm	Rated Input Voltage	220-240 V/AC
Width	60 mm	Power Supply Unit incl.	Yes
Height	60 mm	Light Beam Angle	100 Degree
Base Length	242 mm	CRI (Ra)	80



731135


Article	Housing Color	Luminous Flux	Power Light Direction	Price
731135	Dark grey	600 lm	8.0 W Below	€ 149.95
731136	Dark grey	1155 lm	14.0 W Top / Below	€ 184.95



LINEAR 500

Application Area
 Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Base Width	53 mm
Colour Temperature	3000 K	Base Height	15 mm
Length	500 mm	Rated Input Voltage	220-240 V/AC
Width	60 mm	Power Supply Unit incl.	Yes
Height	60 mm	Light Beam Angle	100 Degree
Base Length	493 mm	CRI (Ra)	80



731129

Article	Housing Color	Luminous Flux	Power Light Direction	EEL	Price
731134	Dark grey	1230 lm	14.0 W Below		€ 194.95
731129	Dark grey	1760 lm	20.0 W Top / Below		€ 214.95





RILONGO

Application Area
Garden / Terrace / Balcony / Walkways, Garage / carport / car park, House wall / facade / front door, Home / Living

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Length	250 mm	Control	Dimmable via optional light source
Width	110 mm		
Max. Power	1x max. 18 W		

Article	Housing Color	Height	Base Length	Base Width	Colour of Light Output	Price
730330	Dark grey	103 mm	250 mm	110 mm	White	€ 79.95
730331	Brown	103 mm	250 mm	110 mm	White	€ 79.95
731060	Dark grey	110 mm	100 mm	70 mm		€ 79.95





ALKES

The ALKES series is not a traditional wall-mounted light, but, with its SMD-LED panel, has floodlight similarities. The highlight: the upper housing part is tilted forwards 45° from the façade to direct the warm white light in a targeted manner onto the surface to be illuminated. In addition, the ALKES also looks great when switched off with its modern design and rounded edges.




ALKES

- high luminous efficacy
- homogeneous light distribution

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Hotel / catering

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000 K	Light Beam Angle	110 Degree
Rated Input Voltage	220-240 V/AC	CRI (Ra)	80



731138

Article	Housing Color		Luminous Flux	Length	Width	Height	Power	Price
731138	Dark grey	WW	920 lm	200 mm	126 mm	184 mm	21.0 W	€ 104.95
731140	Dark grey	WW	1720 lm	297 mm	165 mm	240 mm	36.0 W	€ 175.95




ALKES MOTION

- high luminous efficacy
- homogeneous light distribution

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Hotel / catering

Housing	Aluminium	Light Beam Angle	110 Degree
Colour Temperature	3000 K	CRI (Ra)	80
Rated Input Voltage	220-240 V/AC	Motion Detector	Yes
Power Supply Unit incl.	Yes		



731139

Article	Housing Color		Luminous Flux	Length	Width	Height	Power	Price
731139	Dark grey	WW	735 lm	200 mm	126 mm	184 mm	21.0 W	€ 124.95
731141	Dark grey	WW	1720 lm	297 mm	165 mm	240 mm	36.0 W	€ 195.95





GRUMIUM ANGULAR CCT

Modular, compact, impactful - the GRUMIUM wall-mounted light can be installed on patios, building walls or in entrances to living spaces and, due to its optional covers in different designs, provides a flexible universal solution for many areas of application. The permanently installed and energy-saving LEDs delivering max. 10 watts are encompassed by a diffuser made of milky plastic and produce a pleasant warm-white light with a luminous flux of 730 lm. The Grumium outdoor light with die-cast aluminium housing comes in an angular and rounded design and has degree of protection IP54.



GRUMIUM ANGULAR CCT

• light colour adjustable in 2 stages

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, House wall / facade / front door, Home / Living

Housing	Aluminium	Base Height	15 mm
Colour Temperature	3000/4000 K	Base Ø	195 mm
Length	100 mm	Power	10 W
Width	70 mm	Rated Input Voltage	220-240 V/AC
Height	200 mm	Power Supply Unit incl.	Yes
Base Width	95 mm	CRI (Ra)	80

Article	Housing Color	Shape	Luminous Flux	Light Beam Angle	Light Direction	Price
620124	Dark grey	lines diagonal	WW NW 205 lm	138 Degree	Top / Below / Side	€ 114.95
620125	Dark grey	lines horizontally	WW NW 280 lm	138 Degree	Top / Below / Side	€ 114.95
620126	Dark grey	lines vertical	WW NW 300 lm	180 Degree	Top / Below / Side	€ 114.95
620127	Dark grey	upside/below	WW NW 440 lm	150 Degree	Side	€ 114.95
620123	Dark grey	borders	WW NW 450 lm	138 Degree	Top / Below / Side	€ 114.95




GRUMIUM ROUND

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, House wall / facade / front door, Home / Living


Housing	Aluminium	Base Height	15 mm
Colour Temperature	3000 K	Base Ø	195 mm
Length	100 mm	Power	10 W
Width	70 mm	Rated Input Voltage	220-240 V/AC
Height	200 mm	Power Supply Unit incl.	Yes
Base Width	95 mm	CRI (Ra)	80



620128

Article	Housing Color	Shape	Luminous Flux	Light Beam Angle	Light Direction	Price
620129	Dark grey	Taille	WW 210 lm	160 Degree	Top / Below / Side	€ 114.95
620130	Dark grey	lines horizontally	WW 250 lm	160 Degree	Top / Below / Side	€ 114.95
620128	Dark grey	upside/below	WW 325 lm	180 Degree	Side	€ 114.95






CASA

The CASA house number light has space for up to four digits and/or letters each 10 cm high, ensuring house numbers can be easily read. With a configurable twilight switch, the wall light automatically adjusts to the ambient brightness. The light colour can also be adjusted in two stages (3,000 K/4,000 K).

Multiple cable entries and the option of feed-through wiring mean that installation is simple and flexible. Anti-theft protection also prevents unauthorised removal.

Note: Stickers for numbers/letters are optionally available





CASA

- Space for four digits and letters each 10 cm high
- Adjustable daylight sensor
- Adjustable light colour 3,000/4,000 K
- Multiple cable entries incl. feed-through wiring
- Easy and quick mounting with anti-theft protection
- Set of number/letter stickers optionally available

Application Area

Reception / Communication, Garden /Terrace / Balcony / Walkways, Garage / carport / car park

Surface	Matt	Power	3 W
Colour Temperature	3000/4000 K	Rated Input Voltage	200-240 V/AC
Length	275 mm	Power Supply Unit incl.	Yes
Width	275 mm	Light Beam Angle	120 Degree
Height	64 mm	CRI (Ra)	80
Base Height	14 mm	Light Direction	Front
Base Ø	245 mm	IK Protection Class	IK08

Article	Housing Color		Luminous Flux Housing	Price
731159	Black		250/260 lm PP - Polypropylene	€ 109.95
731158	White		270/280 lm Polycarbonate	€ 109.95




Accessories

- 930807** Numbers set 0-9 for Casa
- 930808** Letters set A-F for Casa




€ 10.95

€ 6.95



ceiling and wall lights



page 522



page 522



page 523





MOB

Housing	Aluminium	Max. Power	1x max. 9 W
Height	92 mm	Rated Input Voltage	220-240 V/AC
Ø	108 mm	Control	Dimmable via optional light source
Base Ø	100 mm		


Article	Housing Color	Price
730408	 Dark grey	€ 72.95



ASCELLA

Application Area
Garden / Terrace / Balcony / Walkways, Garage / carport / car park, House wall / facade / front door, Home / Living

Housing	Aluminium	Power	30 W
Colour Temperature	3000 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	2300 lm	Power Supply Unit incl.	Yes
Height	50 mm	Light Beam Angle	113 Degree
Base Height	12 mm	CRI (Ra)	80
Base Ø	270 mm		



348070

Article	Housing Color	Length	Width	Ø	Price
348069	 Dark grey 			340 mm	€ 259.95
348070	 Dark grey 	340 mm	340 mm		€ 259.95





MENSÆ

- Corridor function
- Adjustable motion detector [hold time / detection area]
- Daylight sensor


Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, House wall / facade / front door


Housing	Aluminium	Rated Input Voltage	100-240 V/AC
Colour Temperature	3000 K	Power Supply Unit incl.	Yes
Height	54 mm	CRI (Ra)	80
Base Height	28.5 mm	Motion Detector	Yes
Base Ø	170 mm	IK Protection Class	IK08
Power	16 W		

Article	Housing Color		Luminous Flux	Length	Width	Ø	Light Beam Angle	Price
348071	Dark grey	WW	1400 lm	300 mm	300 mm		115 Degree	€ 249.95
348072	Dark grey	WW	1500 lm			300 mm	110 Degree	€ 249.95





built in wall lights



page 526



page 527



page 528



page 529





LIGHT BASE 2

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Colour Temperature	3000 K	Power Supply Unit incl.	Yes
Luminous Flux	55 lm	Installation Depth	70 mm
Length	96 mm	Cut Out Length	95 mm
Width	96 mm	Cut Out Width	95 mm
Height	77 mm	CRI (Ra)	80
Power	1.3 W		

Article	Housing Color		Price
763025	 Grey		€ 99.95





COVER, LIGHT BASE II COB OUTDOOR SERIES

Housing Length	Aluminium 100 mm	Width 100 mm		
Article	Housing Color	light output	Height	Price
930419	White	stripe	8 mm	€ 20.95
930414	Light gray	stripe	8 mm	€ 19.95
930420	Black	stripe	8 mm	€ 19.95
930416	White	step	24 mm	€ 19.95
930417	Light gray	step	24 mm	€ 19.95
930418	Black	step	24 mm	€ 19.95
930421	White	linear	24 mm	€ 20.95
930422	Light gray	linear	24 mm	€ 19.95
930415	Black	linear	24 mm	€ 19.95
930413	White	round	24 mm	€ 20.95
930423	Light gray	round	24 mm	€ 19.95
930424	Black	round	24 mm	€ 19.95



LIGHT BASE 3

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Colour Temperature	3000 K	Power Supply Unit incl.	Yes
Luminous Flux	88 lm	Installation Depth	78 mm
Length	245 mm	Light Beam Angle	115 Degree
Width	85 mm	Cut Out Length	245 mm
Height	78 mm	Cut Out Width	85 mm
Power	4,3 W	CRI (Ra)	90

Article	Housing Color	Price
763026	 Black 	€ 119.95







COVER, LIGHT BASE III OUTDOOR SERIES

Housing Aluminium Width 90 mm
Length 250 mm

Article	Housing Color	light output	Height	Price
930470	 White	stripe	9 mm	€ 59.95
930471	 Grey	stripe	9 mm	€ 59.95
930472	 Black	stripe	9 mm	€ 59.95
930461	 White	step	24 mm	€ 59.95
930468	 Grey	step	24 mm	€ 59.95
930469	 Black	step	24 mm	€ 59.95
930473	 White	angled	24 mm	€ 59.95
930474	 Grey	angled	24 mm	€ 59.95
930475	 Black	angled	24 mm	€ 59.95
930476	 White	rounded	24 mm	€ 59.95
930477	 Grey	rounded	24 mm	€ 59.95
930478	 Black	rounded	24 mm	€ 59.95



spherical lamps







DORADUS

Light in its most beautiful form - The sphere is and remains one of the most striking of shapes. With the opportunity to illuminate it from within, what could be better. The spherical light looks great both indoors and outdoors. Optimum effect is achieved by using a dimmable LED lamp with RGB or colour change function. Be mesmerized with cosy red, calming green and deep blue. With a warm white lamp too, the light emanating from this spherical light is something rather special.



DORADUS

- ball housing IP65 protected
- seawater resistant
- ready to plug in with 3 m connection cable
- incl. ground spike

Application Area

Garden / Terrace / Balcony / Walkways, Hotel / catering

Housing	Polyethylene	Primary Connection End	Power plug IP44
Sockets	1 PCS	Control	Dimmable via optional light source
Max. Power	1x max. 23 W	IP Protection Type Plug	IP 44
Rated Input Voltage	220-240 V/AC		
Primary Cable Length	3 m		

Article	Housing Color	Height	Ø	Price
836011	☐ White	230 mm	250 mm	€ 139.95
836930	☐ White	350 mm	380 mm	€ 169.95
836014	☐ White	420 mm	450 mm	€ 199.95
836931	☐ White	530 mm	560 mm	€ 319.95




Accessories


843533	RF-smart, E27, Zigbee, 6 W, RGB+2700-6500 K, 220 Grad		€ 46.95
843510	RF-smart, remote control, white, 1 zone, RGB/RGBW/RGB+CCT, IP20		€ 38.95
843511	RF-smart, remote control, black, 1 zone, RGB/RGBW/RGB+CCT, IP20		€ 38.95
843512	RF-smart, remote control, black, 8 zones, single/CCT/RGB/RGBW/RGB+CCT		€ 49.95
843513	RF-smart, wall remote control, white, 3 V, 4 zones, single/CCT/RGB/W/+CCT		€ 69.95
843514	RF-smart, wall remote control, white, 8 zones, single/CCT/RGB/RGBW/RGB+CCT		€ 109.95
843522	RF-smart, wall remote control, white, 230 V, 4 zones, single/CCT/RGB/W/+CCT		€ 74.95

Accessories for 836931

843534	RF-smart, E27, Zigbee, 12 W, RGB+2700-6500 K, 220 Grad		€ 64.95
--------	--	--	---------



energy distributor



page 536



page 538



page 540



page 542





ARAWAN

Sometimes it's about more than just light. With our multiple socket tower, available with or without light, another gap in our range is filled. Design your garden even more flexibly, in proven DEKO-LIGHT quality of course and at a price that won't break the bank.





ARAWAN

- Safe power distribution outdoors
- Total load max. 3,680 W
- Outlets and lights can be switched on separately
- Connection box with IP67 and accessories including in scope of delivery
- Feed-through wiring possible

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Home / Living, Hotel / catering

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Ø	100 mm	Primary Connection End	Connection box IP67
Connected Load max.	3680 W		

Article	Housing Color	Colour Temperature	Luminous Flux	Height	Power	Power Supply Unit incl.	EEL	Price
733055	Dark grey			400 mm				€ 119.95
733054	Dark grey	3000 K	150 lm	478 mm	4.8 W	Yes		€ 169.95






PUKA MANA

A garden is pure nature and yet needs power in several different places. With the PUKA MANA, you can flexibly access power to operate lawnmowers and other gardening tools or simply to charge your e-bike or smartphone. The multiple socket tower has two socket outlets and can be installed particularly easily using our multi-outdoor cable connectors. The sophisticated cable routing ensures a clean visual design.





PUKA MANA

- Door can be completely closed when angled plugs are plugged in
- Total load: max. 3,680 W
- Easy to install thanks to IP68 cable connector
- Light can be switched on separately [only art. no. 733067]

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Home / Living, Hotel / catering

Housing	Aluminium	Connected Load max.	3680 W
Length	100 mm	Rated Input Voltage	220-240 V/AC
Width	100 mm	Primary Connection End	Connection box IP67

Article	Housing Color	Height	Socket / Base	Max. Power	Price
733066	 Dark grey	420 mm			€ 169.95
733067	 Dark grey	620 mm	E27	1x max. 13.0 W	€ 249.95



Accessories

931073 Cover for Multiple socket tower Puka Mana 420 mm

 € 9.95



FACADO SOCKET

FACADO series standing lights have been proving quite the hit for some time on paved paths in gardens. Now, the classically elegant outdoor lights are becoming that much more versatile: The FACADO SOCKET contains two electrical outlet points, serving as a practical power distributor in gardens, on patios or on paths. The lamps can also be changed thanks to the E27 base and adapted to the desired lighting atmosphere. The FACADO SOCKET is available in two heights [65 and 100 cm].





FACADO SOCKET

- Total load: max. 3,680 W
- Outlets and light can be switched on separately
- Feed-through wiring possible
- Replaceable lamp [E27]

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Home / Living, Hotel / catering

Housing	Aluminium	Max. Power	1x max. 20 W
Width	108 mm	Connected Load max.	3680 W
Height	108 mm	Rated Input Voltage	220-240 V/AC

Article	Housing Color	Length	Price
733064	 Dark grey	650 mm	€ 199.95
733065	 Dark grey	1000 mm	€ 219.95





LERNA

LERNA series power distributors offer a number of advantages. With two sockets and a total load of 3,680 W, they allow you to connect various devices while providing reliable lighting. Light and sockets can be switched separately (separate L+N). The socket cover latches open for additional convenience. The ability to adjust the light colour in two stages (3,000 K/4,000 K) allows you to choose the colour temperature that sets the perfect ambience. The downward orientation of the lighting also fully guarantees efficient illumination without creating light pollution. LERNA series bollard lights are available in two different sizes (600 mm and 1,000 mm). With an output of 6 W and 516 lm, the light itself is incredibly bright.





LERNA

- Socket cover latches open
- Total socket output: 3,680 W
- Light colour adjustable in two stages
- Light and socket can be switched separately (separate L+N)
- Light directed fully downwards to prevent light pollution

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Home / Living, Hotel / catering

Housing	Aluminium	Rated Input Voltage	200-240 V/AC
Colour Temperature	3000/4000 K	Power Supply Unit incl.	Yes
Luminous Flux	237/256 lm	Light Beam Angle	50 Degree
Length	120 mm	Light Beam Angle 2	100 Degree
Width	100 mm	CRI (Ra)	80
Power	7.4 W	IK Protection Class	IK06
Connected Load max.	3680 W		

Article	Housing Color		Height	Price
733071		Dark grey  	600 mm	€ 269.95
733070		Dark grey  	1000 mm	€ 309.95



surface mounted / ground spike



page 546



page 548



page 549



page 550



page 551



page 552



page 553





DEKO-LIGHT RF-SMART SPOTLIGHT RGB+CCT RF + ZIGBEE

The RF-Smart SPOT spotlight with ground spike offers dimmable brightness and colour saturation, 16 million colours and adjustable colour temperatures. This spotlight has eight pre-installed automatic programs and the ability to synchronise with other RF-Smart components, offering maximum flexibility. Can be controlled using RF-smart wireless remote controls (2.4 GHz, range approx. 30 m, not in scope of delivery) as well as all Zigbee 3.0 compatible controllers and apps such as Amazon Echo (Alexa), Google Assistant and Tuya (appropriate gateway required). The very narrow beam angle makes it ideal for column lighting and similar applications.





DEKO-LIGHT RF-SMART SPOTLIGHT RGB+CCT RF + ZIGBEE

- Adjustable brightness and colour saturation
- 16 million available colours and adjustable colour temperature
- 18 automatic programmes pre-installed
- Program and remote control synchronisation when operating multiple RF smart components (repeater function)
- Can be controlled with RF smart wireless remote controls (2.4 GHz, range approx. 30 m, not included in the scope of delivery)
- Can be controlled with all Zigbee 3.0 compatible controllers/apps such as Amazon Echo (Alexa), Google Assistant, Tuya (relevant gateway required, outdoor range up to 100 m)
- Very narrow light emission angle, perfect for column lighting or similar

Application Area

Object lighting / architecture, Garage / carport / car park

Housing	Aluminium, Plastic	Power Supply Unit incl.	Yes
Colour Temperature	2700-6500 K	Light Beam Angle	15 Degree
Luminous Flux	1700 lm	Swivelling Angle	355 Degree
Length	170 mm	Control	RF-Smart, ZigBee 3.0
Width	65 mm	Primary Cable Length	1.5 m
Height	180 mm	CRI (Ra)	80
Power	25 W	Light Direction	Front
Rated Input Voltage	100-240 V/AC	IP Protection Type Plug	IP 44

Article	Housing Color	Colour Temperature	Price
843521	Anthracite	RGB WW CW 2700-6500 K	€ 239.95



Accessories

843510	RF-smart, remote control, white, 1 zone, RGB/RGBW/RGB+CCT, IP20		€ 38.95
843511	RF-smart, remote control, black, 1 zone, RGB/RGBW/RGB+CCT, IP20		€ 38.95
843512	RF-smart, remote control, black, 8 zones, single/CCT/RGB/RGBW/RGB+CCT		€ 49.95
843513	RF-smart, wall remote control, white, 3 V, 4 zones, single/CCT/RGB/W/+CCT		€ 69.95
843522	RF-smart, wall remote control, white, 230 V, 4 zones, single/CCT/RGB/W/+CCT		€ 74.95
843514	RF-smart, wall remote control, white, 8 zones, single/CCT/RGB/RGBW/RGB+CCT		€ 109.95
930659	Wall bracket/display arm, metal, black, length: 800 mm		€ 59.95



SPIKY

- Replaceable GU10 lamp (retrofit)
- Incl. 2 m connecting cable with IP44 plug
- Incl. ground spike
- Incl. cover (art. no. 732161 only)

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Home / Living, Hotel / catering

Housing	Aluminium, Plastic	Control	Dimmable via optional light source
Surface	Matt	Swivelling Angle	180 Degree
Max. Power	1x max. 35 W	IP Protection Type Plug	IP 44
Rated Input Voltage	220-240 V/AC		
Primary Connection End	Power plug		

Article	Housing Color	Height	Ø	Primary Cable Length	Price
732161	 Black	345 mm	100 mm	2.5 m	€ 34.95
732160	 Dark grey	420 mm	60 mm	2 m	€ 39.95



Accessories

843532	RF-smart, GU10, Zigbee, 4 W, RGB+2700-6500 K, 25 Degree		€ 46.95
843510	RF-smart, remote control, white, 1 zone, RGB/RGBW/RGB+CCT, IP20		€ 38.95
843511	RF-smart, remote control, black, 1 zone, RGB/RGBW/RGB+CCT, IP20		€ 38.95
843512	RF-smart, remote control, black, 8 zones, single/CCT/RGB/RGBW/RGB+CCT		€ 49.95
843513	RF-smart, wall remote control, white, 3 V, 4 zones, single/CCT/RGB/W/+CCT		€ 69.95
843522	RF-smart, wall remote control, white, 230 V, 4 zones, single/CCT/RGB/W/+CCT		€ 74.95
843514	RF-smart, wall remote control, white, 8 zones, single/CCT/RGB/RGBW/RGB+CCT		€ 109.95



KEID

Application Area
Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Home / Living, Hotel / catering

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000 K	Light Beam Angle	45 Degree
Length	120 mm	Swivelling Angle	180 Degree
Height	457 mm	Primary Cable Length	0.5 m
Ø	75 mm	Primary Connection End	Connection box IP65
Rated Input Voltage	220-240 V/AC	CRI (Ra)	80

Article	Housing Color		Luminous Flux	Power	Price
732094	Dark grey	WW	800 lm	10.3 W	€ 139.95
732095	Dark grey	WW	1350 lm	21.5 W	€ 149.95






COLT 8 W COB + 8 W RGBW

- Replaceable reflectors
- Including clear/frosted glass pane
- Including honeycomb filter
- Feed-through wiring possible

Application Area

Object lighting / architecture, Garage / carport / car park, Reception / Communication

Housing	Aluminium	Ø	77 mm
Colour Temperature	3000 K	Base Height	50 mm
Length	66 mm	Base Ø	96 mm
Height	185 mm	Swivelling Angle	180 Degree



732108

Article	Housing Color	Luminous Flux	Power	Rated Input Voltage	Light Beam Angle	Power Supply incl.	Price
732127	Dark grey	389 lm	8.6 W	24 V/DC	20°	No	€ 299.95
732108	Dark grey	470 lm	7.0 W	220-240 V/AC	40°	Yes	€ 199.95



Accessories

- 930441** Surface-mounted housing for Colt 8 W series
- 930426** Ground spike for Colt series 4/8 W, M5



€ 59.95

€ 9.95

Accessories for 732108

- 930431** 12° reflector for Colt 8 W series
- 930432** 22° reflector for Colt 8 W series
- 930587** Connecting cable with 230 V power plug



€ 8.95

€ 8.95

€ 19.95

Accessories for 732127

- 862122** FLAT, CV, UT 24 V/50 W
- 862230** OCTO, CV, Mini 24 V/12 W
- 872083** IP, CV, V6-40-24



€ 52.95

€ 21.95

€ 74.95




COLT 15 W COB + 16 W RGBW

- Replaceable reflectors
- Including clear/frosted glass pane
- Including honeycomb filter
- Feed-through wiring possible

Application Area
Object lighting / architecture, Garage / carport / car park, Reception / Communication

Housing	Aluminium	Ø	110 mm
Colour Temperature	3000 K	Base Height	56 mm
Length	88 mm	Base Ø	120 mm
Height	220 mm	Swivelling Angle	180 Degree



732109

Article	Housing Color		Luminous Flux	Power	Rated Input Voltage	Light Beam Angle	Power Supply incl.	Price
732128	Dark grey		780 lm	16.0 W	24 V/DC	20°	No	€ 449.95
732109	Dark grey		1090 lm	14.0 W	220-240 V/AC	40°	Yes	€ 249.95



Accessories

930442	Surface-mounted housing for Colt 15/30 W series		€ 69.95
930427	Ground spike for Colt series 15/25/30/36/65 W, M10		€ 11.95

Accessories for 732109

930434	12° reflector for Colt 15 W series		€ 10.95
930435	22° reflector for Colt 15 W series		€ 11.95
930587	Connecting cable with 230 V power plug		€ 19.95

Accessories for 732128

862122	FLAT, CV, UT 24 V/50 W		€ 52.95
862164	BASIC, CV, Q8H-24-75 W		€ 74.95
872083	IP, CV, V6-40-24		€ 74.95
872085	IP, CV, V6-75-24		€ 94.95
930426	Ground spike for Colt series 4/8 W, M5		€ 9.95




COLT 30 W COB + 25 W RGBW

- Replaceable reflectors
- Including clear/frosted glass pane
- Including honeycomb filter
- Feed-through wiring possible

Application Area
 Object lighting / architecture, Garage / carport / car park, Reception / Communication

Housing	Aluminium	Ø	131 mm
Colour Temperature	3000 K	Base Height	56 mm
Length	112 mm	Base Ø	120 mm
Height	260 mm	Swivelling Angle	180 Degree



732110

Article	Housing Color		Luminous Flux	Power	Rated Input Voltage	Light Beam Angle	Power Supply incl.	Price
732129	Dark grey		1140 lm	25.0 W	24 V/DC	20°	No	€ 499.95
732110	Dark grey		2320 lm	29.0 W	220-240 V/AC	40°	Yes	€ 289.95



Accessories

930442	Surface-mounted housing for Colt 15/30 W series		€ 69.95
930427	Ground spike for Colt series 15/25/30/36/65 W, M10		€ 11.95

Accessories for 732110

930437	12° reflector for Colt 30 W series		€ 12.95
930438	22° reflector for Colt 30 W series		€ 12.95
930587	Connecting cable with 230 V power plug		€ 19.95

Accessories for 732129

862163	BASIC, CV, Q8H-24-40 W		€ 46.95
862164	BASIC, CV, Q8H-24-75 W		€ 74.95
872083	IP, CV, V6-40-24		€ 74.95
872085	IP, CV, V6-75-24		€ 94.95
872094	IP, CV, V6-100-24		€ 114.95



COLT 65 W COB + 36 W RGBWW

- Replaceable reflectors
- Including clear/frosted glass pane
- Including honeycomb filter
- Feed-through wiring possible

Application Area

Object lighting / architecture, Garage / carport / car park, Reception / Communication

Housing	Aluminium	Power	36 W
Colour Temperature	2700 K	Rated Input Voltage	24 V/DC
Luminous Flux	1500 lm	Power Supply Unit incl.	Yes
Length	162 mm	Light Beam Angle	20 Degree
Height	192 mm	Swivelling Angle	90 Degree
Ø	182 mm	Control	Dimmable via optional controller
Base Height	65 mm	CRI (Ra)	80
Base Ø	160 mm		


Article	Housing Color		Price
732137	 Dark grey		€ 679.95



Accessories

930558	Surface-mounted housing for Colt 65 W COB/36 W RGBW series
862163	BASIC, CV, Q8H-24-40 W
862164	BASIC, CV, Q8H-24-75 W
862168	BASIC, CV, Q8H-24-150 W
872083	IP, CV, V6-40-24
872085	IP, CV, V6-75-24
872087	IP, CV, V6-150-24
872094	IP, CV, V6-100-24

	€ 89.95
	€ 46.95
	€ 74.95
	€ 129.95
	€ 74.95
	€ 94.95
	€ 149.95
	€ 114.95




page 556




page 557

wall washer







WALLWASHER CAPH 24 V


- Including 0.5 m connecting cable with WEIPU plug
- Including 0.5 m connecting cable with WEIPU plug

Application Area

Garden / Terrace / Balcony / Walkways, Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Advertising lighting

Housing	Aluminium	Power Supply Unit incl.	No
Colour Temperature	3000 K	Control	Dimmable via optional controller
Length	1000 mm	Primary Cable Length	0.5 m
Width	53.36 mm	Primary Connection End	WEIPU plug 5-pole
Height	81.07 mm	CRI (Ra)	80
Power	60 W		
Rated Input Voltage	24 V/DC		

Article	Housing Color		Luminous Flux	Light Beam Angle	Light Beam Angle 2	Light Distribution	Price
732072	Dark grey		2480 lm	40 Degree	15 Degree	Asymetric	€ 415.95
732071	Dark grey		2800 lm	25 Degree		Symmetric	€ 415.95



Accessories

- 862164** BASIC, CV, Q8H-24-75 W
- 872085** IP, CV, V6-75-24
- 843502** RF-smart, starter set RGB/W/CCT, 12-48 V, 20 A incl. remote, IP20



- € 74.95
- € 94.95
- € 99.95




WALLWASHER CAPH 230V

·Including 2 m connecting cable with IP44 shaped plug

Application Area

Garden / Terrace / Balcony / Walkways, Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Advertising lighting


Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Colour Temperature	3000 K	Power Supply Unit incl.	Yes
Length	1000 mm	Primary Cable Length	2 m
Width	53.36 mm	Primary Connection End	Power plug IP44
Height	81.07 mm	CRI (Ra)	80
Power	38 W	IP Protection Type Plug	IP 44




732080

Article	Housing Color		Luminous Flux	Light Beam Angle	Light Beam Angle 2	Light Distribution	Price
732080	Dark grey	WW	2580 lm	40 Degree	15 Degree	Asymmetric	€ 415.95
732079	Dark grey	WW	3000 lm	25 Degree		Symmetric	€ 415.95





ground recessed lights



page 560



page 560



page 561



page 562



page 563



page 564



page 564



page 565



page 566



page 567



page 568



page 569



□
page 570



□
page 570



□
page 571



□
page 572



□
page 572



■
page 573



□
page 574



□
page 574



■
page 576



ATON

Application Area
Garden / Terrace / Balcony / Walkways

Housing	Stainless steel, Aluminium	Rated Input Voltage	220-240 V/AC
Height	111 mm	Cut Out Ø	70 mm
Installation Depth	148 mm	Control	Dimmable via optional light source
Max. Power	1x max. 7 W		

Article	Housing Color	Length	Width	Ø	Price
730474	 Silver			97 mm	€ 56.95
730475	 Silver	97 mm	97 mm		€ 56.95



PAVO

•Swivelling insert

Application Area
Garden / Terrace / Balcony / Walkways

Housing	Stainless steel, Aluminium	Rated Input Voltage	220-240 V/AC
Height	156 mm	Cut Out Ø	100 mm
Installation Depth	193 mm	Control	Dimmable via optional light source
Max. Power	1x max. 9 W	Swivelling Angle	25 Degree

Article	Housing Color	Length	Width	Ø	Price
730478	 Silver			160 mm	€ 114.95
730479	 Silver	160 mm	160 mm		€ 114.95






ALZIRR

·Including 1 m connecting cable with WEIPU plug

Application Area
Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Park / public outdoor area

Housing	Stainless steel, Aluminium	Installation Depth	98 mm
Colour Temperature	3000 K	Light Beam Angle	30 Degree
Luminous Flux	180 lm	Cut Out Ø	48 mm
Height	82.5 mm	Control	Dimmable via optional controller
Ø	55 mm	CRI (Ra)	80
Power	2.4 W	Primary Cable Length	1 m
Rated Input Voltage	24 V/DC	Primary Connection End	WEIPU plug 2-pole
Power Supply Unit incl.	No	Light Distribution	Symmetric

Article	Housing Color	Price
730470	Silver	€ 109.95



Accessories	
862230	OCTO, CV, Mini 24 V/12 W
872083	IP, CV, V6-40-24
843501	RF-smart, starter set LED single/CCT, 12-48 V, 20 A incl. remote control

	€ 21.95
	€ 74.95
	€ 99.95



5-year guarantee
Benefit from the maximum quality promise:
All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.



FORNAC


- Asymmetrical
- Including 1 m connecting cable with WEIPU plug

Application Area

Garden / Terrace / Balcony / Walkways

Housing	Stainless steel, Aluminium	Light Beam Angle	45 Degree
Colour Temperature	3000 K	Light Beam Angle 2	35 Degree
Luminous Flux	110 lm	Cut Out Ø	48 mm
Height	80 mm	Control	Dimmable via optional controller
Ø	55 mm	CRI (Ra)	80
Power	2.7 W	Primary Cable Length	1 m
Rated Input Voltage	24 V/DC	Primary Connection End	WEIPU plug 2-pole
Power Supply Unit incl.	No	Light Distribution	Asymetric
Installation Depth	98 mm		

Article	Housing Color	Price
730447	 Silver 	€ 124.95



Accessories

862230	OCTO, CV, Mini 24 V/12 W
872083	IP, CV, V6-40-24
843501	RF-smart, starter set LED single/CCT, 12-48 V, 20 A incl. remote control

	€ 21.95
	€ 74.95
	€ 99.95



Technical data sheet
 New in the onlineshop: The technical data sheets offer even more information: Light and energy data, light distribution curves, dimensional drawings and more.



PEACOCK

·Including 0.5 m connecting cable with protected connection socket

Application Area

Garden / Terrace / Balcony / Walkways

Housing	Stainless steel, Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000 K	Installation Depth	48 mm
Luminous Flux	150 lm	Light Beam Angle	30 Degree
Height	43 mm	Cut Out Ø	44 mm
Ø	58 mm	CRI (Ra)	80
Power	2 W	Primary Connection End	Connection box IP67
Rated Input Voltage	220-240 V/AC	IK Protection Class	IK08
		Light Distribution	Symmetric

Article	Housing Color	Price
730459	 Silver	 € 114.95





FLAT 24V

Application Area
Garden / Terrace / Balcony / Walkways

Housing	Stainless steel, Aluminium	Installation Depth	50 mm
Luminous Flux	510 lm	Light Beam Angle	30 Degree
Height	38 mm	Cut Out Ø	150 mm
Ø	173 mm	Control	Dimmable via optional controller
Power	17 W	Primary Cable Length	0.5 m
Rated Input Voltage	24 V/DC	Primary Connection End	WEIPU plug 4-pole
Power Supply Unit incl.	No	Light Distribution	Symmetric

Article	Housing Color	Price
100116	Silver	€ 319.95



- Accessories
- 872083** IP, CV, V6-40-24
 - 843502** RF-smart, starter set RGB/W/CCT, 12-48 V, 20 A incl. remote, IP20



€ 74.95
€ 99.95



FLAT 230V 20 DEGREE


·Including 0.5 m connecting cable

Application Area
Garden / Terrace / Balcony / Walkways

Housing	Stainless steel, Aluminium	Light Beam Angle	20 Degree
Colour Temperature	3000 K	CRI (Ra)	80
Rated Input Voltage	220-240 V/AC	Primary Cable Length	0.5 m
Power Supply Unit incl.	Yes	Primary Connection End	Connection box
		Light Distribution	Symmetric

Article	Housing Color	Luminous Flux	Height	Ø	Power	Installation Depth	Price
100111	Silver	400 lm	44 mm	116 mm	5.8 W	44 mm	€ 194.95
100114	Silver	860 lm	42 mm	173 mm	12.2 W	42 mm	€ 279.95





FLAT 230V 120 DEGREE

Application Area
Garden / Terrace / Balcony / Walkways

Housing	Stainless steel, Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000 K	Installation Depth	43 mm
Luminous Flux	40 lm	Light Beam Angle	120 Degree
Height	42 mm	Cut Out Ø	100 mm
Ø	116 mm	CRI (Ra)	65
Power	1.3 W	Primary Cable Length	0.5 m
Rated Input Voltage	220-240 V/AC	Primary Connection End	Connection box
		Light Distribution	Symmetric

Article	Housing Color		Price
730336	 Silver		€ 154.95






CANUM 24V SYMMETRICAL

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Park / public outdoor area

Housing	Stainless steel, Aluminium	Installation Depth	150 mm
Colour Temperature	3000 K	Light Beam Angle	45 Degree
Luminous Flux	370 lm	Cut Out Ø	102 mm
Height	102 mm	Control	Dimmable via optional controller
Ø	116 mm	CRI (Ra)	80
Power	5.8 W	Primary Cable Length	2 m
Rated Input Voltage	24 V/DC	Primary Connection End	WEIPU plug 2-pole
Power Supply Unit incl.	No	Light Distribution	Symmetric

Article	Housing Color	Price
100133	Silver	€ 195.98



Accessories

862230	OCTO, CV, Mini 24 V/12 W
872083	IP, CV, V6-40-24
843501	RF-smart, starter set LED single/CCT, 12-48 V, 20 A incl. remote control



€ 21.95
€ 74.95
€ 99.95



Lighting design
Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.



CANUM 24V ASYMMETRICAL


- Including 0.5 m connecting cable with WEIPU plug
- Asymmetrical

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Park / public outdoor area

Housing	Stainless steel, Aluminium	Light Beam Angle	45 Degree
Colour Temperature	3000 K	Light Beam Angle 2	35 Degree
Luminous Flux	800 lm	Cut Out Ø	157 mm
Height	111 mm	Control	Dimmable via optional controller
Ø	173 mm	CRI (Ra)	80
Power	14 W	Primary Cable Length	0.5 m
Rated Input Voltage	24 V/DC	Primary Connection End	WEIPU plug 2-pole
Power Supply Unit incl.	No	Light Distribution	Asymetric
Installation Depth	153 mm		

Article	Housing Color	Price
730296	 Silver 	€ 269.95



Accessories

- 872083** IP, CV, V6-40-24
- 843501** RF-smart, starter set LED single/CCT, 12-48 V, 20 A incl. remote control



- € 74.95
- € 99.95



Onlineshop
You can find more information about the products in the onlineshop:
Detailed images, videos, project reports, LDT files, EPREL data sheets and more.



CANUM RGB 24V SYMMETRICAL

Application Area
Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Park / public outdoor area

Housing	Stainless steel, Aluminium	Installation Depth	150 mm
Luminous Flux	370 lm	Light Beam Angle	30 Degree
Height	102 mm	Cut Out Ø	102 mm
Ø	116 mm	Control	Dimmable via optional controller
Power	7.4 W	Primary Cable Length	0.5 m
Rated Input Voltage	24 V/DC	Primary Connection End	WEIPU plug 4-pole
Power Supply Unit incl.	No	Light Distribution	Symmetric

Article	Housing Color		Price
730276	 Silver		€ 219.95

CV





IP67






3 CH

Accessories

872083	IP, CV, V6-40-24		€ 74.95
843502	RF-smart, starter set RGB/W/CCT, 12-48 V, 20 A incl. remote, IP20		€ 99.95





CANUM RGB 24V ASYMMETRICAL

·Including 0.5 m connecting cable with WEIPU plug

Application Area
Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Park / public outdoor area

Housing	Stainless steel, Aluminium	Light Beam Angle	50 Degree
Luminous Flux	650 lm	Light Beam Angle 2	35 Degree
Height	111 mm	Cut Out Ø	157 mm
Ø	173 mm	Control	Dimmable via optional controller
Power	16.9 W	Primary Cable Length	0.5 m
Rated Input Voltage	24 V/DC	Primary Connection End	WEIPU plug 4-pole
Power Supply Unit incl.	No	IK Protection Class	IK07
Installation Depth	153 mm	Light Distribution	Asymetric

Article	Housing Color	Price
730454	 Silver 	€ 359.95



Accessories

- 872083** IP, CV, V6-40-24
- 843502** RF-smart, starter set RGB/W/CCT, 12-48 V, 20 A incl. remote, IP20



- € 74.95
- € 99.95





CANUM 230V SYMMETRICAL

•Including connecting cable

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Park / public outdoor area

Housing	Stainless steel, Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000 K	Installation Depth	150 mm
Luminous Flux	280 lm	Light Beam Angle	30 Degree
Height	102 mm	Cut Out Ø	102 mm
Ø	116 mm	CRI (Ra)	80
Power	4.1 W	Primary Cable Length	0.5 m
Rated Input Voltage	220-240 V/AC	Primary Connection End	Connection box
		Light Distribution	Symmetric

Article	Housing Color		Price
730255	Silver		€ 179.95



CANUM 230V ASYMMETRICAL

•Asymmetrical

•Including 0.5 m connecting cable

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Park / public outdoor area

Housing	Stainless steel, Aluminium	Installation Depth	153 mm
Colour Temperature	3000 K	Light Beam Angle	45 Degree
Luminous Flux	700 lm	Light Beam Angle 2	35 Degree
Height	111 mm	Cut Out Ø	157 mm
Ø	173 mm	CRI (Ra)	80
Power	11.9 W	Primary Cable Length	0.5 m
Rated Input Voltage	220-240 V/AC	Primary Connection End	Connection box
Power Supply Unit incl.	Yes	IK Protection Class	IK09
		Light Distribution	Asymetric

Article	Housing Color		Price
730289	Silver		€ 269.95





SOFT FLEX

- Adjustable light emission angle
- Including 1 m connecting cable
- Including honeycomb filter

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Park / public outdoor area

Housing	Stainless steel, Aluminium	Swivelling Angle	60 Degree
Colour Temperature	3000 K	CRI (Ra)	80
Rated Input Voltage	220-240 V/AC	Primary Cable Length	1 m
Power Supply Unit incl.	Yes	Primary Connection End	Connection box
Installation Depth	220 mm	Light Distribution	Symmetric

Article	Housing Color		Luminous Flux	Height	Ø	Power	Light Beam Angle	Price
730267	Silver	WW	480 lm	128 mm	173 mm	9.3 W	15 Degree	€ 359.95
730266	Silver	WW	770 lm	190 mm	250 mm	18.4 W	25 Degree	€ 599.95





SQUARE BEAM

•Including 0.5 m connecting cable

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Park / public outdoor area

Housing	Stainless steel, Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000 K	Installation Depth	95 mm
Luminous Flux	700 lm	Light Beam Angle	25 Degree
Length	125 mm	Cut Out Length	112 mm
Width	125 mm	Cut Out Width	112 mm
Height	75 mm	CRI (Ra)	80
Power	7.7 W	Primary Cable Length	0.5 m
Rated Input Voltage	220-240 V/AC	Primary Connection End	Connection box
		Light Distribution	Symmetric

Article	Housing Color		Price
730209	 Silver		€ 169.95



SQUARE SOFT

•Incl. two glass lenses [prism, white]


Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Park / public outdoor area

Housing	Stainless steel, Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000 K	Installation Depth	95 mm
Luminous Flux	215 lm	Light Beam Angle	120 Degree
Length	125 mm	Cut Out Length	113.5 mm
Width	125 mm	Cut Out Width	113.5 mm
Height	75 mm	CRI (Ra)	80
Power	3.2 W	Primary Cable Length	0.5 m
Rated Input Voltage	220-240 V/AC	Primary Connection End	Connection box
		Light Distribution	Symmetric

Article	Housing Color		Price
730248	 Silver		€ 179.95





HELIOS



·Incl. four heavy-duty anchors

Application Area

Garden / Terrace / Balcony / Walkways, Object lighting / architecture, Park / public outdoor area, Stairs / steps, Hotel / catering

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000 K	Light Beam Angle	60 Degree
Height	54 mm	CRI (Ra)	80
Ø	210 mm	IK Protection Class	IK10
Rated Input Voltage	220-240 V/AC		

Article	Housing Color	Number of light outlets	Luminous Flux	Power	EEL	Price
732143	Dark grey	WW 1	34 lm	2.5 W		€ 119.95
732049	Dark grey	WW 2	65 lm	3.8 W	G	€ 119.95
732050	Dark grey	WW 3	150 lm	5.5 W	G	€ 119.95





LINE

·Incl. connecting cable

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Park / public outdoor area

Housing	Stainless steel, Aluminium	Light Beam Angle	20 Degree
Colour Temperature	3000 K	Cut Out Width	68 mm
Width	68 mm	CRI (Ra)	80
Height	31.5 mm	Primary Cable Length	0.5 m
Rated Input Voltage	220-240 V/AC	Primary Connection End	Connection box
Power Supply Unit incl.	Yes	IK Protection Class	IK07
Installation Depth	80 mm	Light Distribution	Symmetric

Article	Housing Color		Luminous Flux	Length	Power	Cut Out Length	Price
730434	Silver		1100 lm	549 mm	18.0 W	527 mm	€ 389.95
730432	Silver		2300 lm	1025 mm	36.0 W	1007 mm	€ 628.95



LINE ASYMMETRICAL

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Park / public outdoor area

Housing	Stainless steel, Aluminium	Installation Depth	90 mm
Colour Temperature	3000 K	Light Beam Angle	45 Degree
Width	63 mm	Light Beam Angle 2	35 Degree
Height	65 mm	Cut Out Width	58 mm
Rated Input Voltage	220-240 V/AC	CRI (Ra)	80
Power Supply Unit incl.	Yes	Primary Connection End	Connection box
		Light Distribution	Asymetric

Article	Housing Color		Luminous Flux	Length	Power	Cut Out Length	Primary Cable Length	Price
730292	Silver		340 lm	195 mm	5.5 W	180 mm	0.5 m	€ 185.95
730262	Silver		730 lm	328 mm	11.9 W	313 mm	1 m	€ 259.95







TABIT

The TABIT series recessed floor lights have a remarkable square, angular shape and an output of up to 3.7 W at 3,000 K. The lights' paving stone appearance makes them compatible with common paving dimensions. Each lamp is supplied with a 30 cm long connecting cable with open cable ends. They can withstand a load of 5,000 N and can be walked on, though not driven on.





TABIT


- Paving stone look
- Suitable for common paving dimensions
- Incl. 30 cm connection line with open cable ends
- Can be walked on, cannot be driven on
- 5,000 N load

Application Area


Garden / Terrace / Balcony / Walkways

Housing	Polycarbonate	Light Beam Angle	120 Degree
Surface	Transparent	CRI (Ra)	80
Colour Temperature	3000 K	Primary Cable Length	0.3 m
Height	68 mm	Primary Connection End	With free strand / conductor ends
Rated Input Voltage	220-240 V/AC	IK Protection Class	IK10
Power Supply Unit incl.	Yes		
Installation Depth	68 mm		


Article	Housing Color		Luminous Flux	Length	Width	Power	Price
730480	Grey		120 lm	100 mm	100 mm	2.3 W	€ 29.95
730481	Grey		240 lm	200 mm	100 mm	3.7 W	€ 59.95
730482	Grey		240 lm	200 mm	200 mm	3.7 W	€ 99.95



5-year guarantee
Benefit from the maximum quality promise:
All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.



floodlight



page 580



page 581



page 582



page 583






DEKO-LIGHT RF-SMART FLOODLIGHT RGB+CCT RF + ZIGBEE

- Adjustable brightness and colour saturation
- 16 million available colours and adjustable colour temperature
- 18 automatic programmes pre-installed
- Program and remote control synchronisation when operating multiple RF smart components (repeater function)
- Can be controlled with RF smart wireless remote controls (2.4 GHz, range approx. 30 m, not included in the scope of delivery)
- Can be controlled with all Zigbee 3.0 compatible controllers/apps such as Amazon Echo (Alexa), Google Assistant, Tuya (relevant gateway required, outdoor range up to 100 m)

Application Area

Object lighting / architecture, Garage / carport / car park

Housing	Aluminium, Plastic	Control	RF-Smart, ZigBee 3.0
Colour Temperature	2700-6500 K	Primary Cable Length	1.5 m
Rated Input Voltage	100-240 V/AC	CRI (Ra)	80
Power Supply Unit incl.	Yes	Light Direction	Front
Light Beam Angle	160 Degree	IP Protection Type Plug	IP 44
Swivelling Angle	345 Degree		



843518

Article	Housing Color		Luminous Flux	Length	Width	Height	Power	Price
843518	Anthracite	RGB WW CW	3300 lm	167 mm	40 mm	227 mm	30.0 W	€ 249.95
843519	Anthracite	RGB WW CW	4800 lm	220 mm	48 mm	311 mm	50.0 W	€ 349.95
843520	Anthracite	RGB WW CW	10000 lm	295 mm	60 mm	403 mm	100.0 W	€ 549.95



Accessories

843510	RF-smart, remote control, white, 1 zone, RGB/RGBW/RGB+CCT, IP20	€ 38.95
843511	RF-smart, remote control, black, 1 zone, RGB/RGBW/RGB+CCT, IP20	€ 38.95
843512	RF-smart, remote control, black, 8 zones, single/CCT/RGB/RGBW/RGB+CCT	€ 49.95
843513	RF-smart, wall remote control, white, 3 V, 4 zones, single/CCT/RGB/WW+CCT	€ 69.95
843522	RF-smart, wall remote control, white, 230 V, 4 zones, single/CCT/RGB/WW+C-CT	€ 74.95
843514	RF-smart, wall remote control, white, 8 zones, single/CCT/RGB/RGBW/RGB+CCT	€ 109.95
930659	Wall bracket/display arm, metal, black, length: 800 mm	€ 59.95



FLOOD SMD

- Including 1.2 m connecting cable with IP44 shaped plug
- Housing made of durable, die-cast aluminium and glass

Application Area

Garage / carport / car park, Workshop / Craft / Warehouse, Basement / damp room

Housing	Aluminium	Primary Connection End	Power plug IP44
Rated Input Voltage	220-240 V/AC	CRI (Ra)	80
Power Supply Unit incl.	Yes	IP Protection Type Plug	IP 44
Light Beam Angle	100 Degree	IK Protection Class	IK08
Primary Cable Length	1.2 m		

Article	Housing Color	Colour Temperature	Luminous Flux	L x W x H	Power	EEL	Price
732147	Silver	3000 K	1800 lm	179 x 143,6 x 27 mm	15 W	E	€ 89.95
732148	Black	3000 K	1800 lm	179 x 143,6 x 27 mm	15 W	E	€ 89.95
732150	Silver	3000 K	3600 lm	237 x 250 x 40,5 mm	30 W	E	€ 129.95
732151	Black	3000 K	3600 lm	237 x 250 x 40,5 mm	30 W	E	€ 129.95
732149	Silver	4000 K	1950 lm	179 x 143,6 x 27 mm	15 W	E	€ 89.95
732152	Silver	4000 K	3900 lm	179 x 143,6 x 27 mm	30 W	D	€ 129.95



page 399

page 399



Onlineshop
You can find more information about the products in the onlineshop:
Detailed images, videos, project reports, LDT files, EPREL data sheets and more.




BRACHIUM

·Including 2 m connecting cable with IP44 plug

Application Area

Garage / carport / car park, Industry / production / high-bay warehouse

Housing	Aluminium	Power Supply Unit incl.	Yes
Length	316 mm	Light Beam Angle	75 Degree
Width	286 mm	Swivelling Angle	180 Degree
Height	41 mm	Primary Cable Length	2 m
Base Length	327 mm	Primary Connection End	Power plug IP44
Base Width	28 mm	CRI (Ra)	80
Base Height	160 mm	IP Protection Type Plug	IP 44
Power	82 W	IK Protection Class	IK08
Rated Input Voltage	220-240 V/AC		



732105

Article	Housing Color	Colour Temperature	Luminous Flux	Price
732064	Black	3000 K	8100 lm	€ 199.95
732105	Black	4000 K	8400 lm	€ 199.95






ATIK

- IEC62662 - Protection against mechanical effects (IK Code)
- EN60598-2-24 - Lights for use in explosive gas and dust atmosphere (D designation)
- Including 2 m connecting cable with IP44 plug

Application Area

Garage / carport / car park, Industry / production / high-bay warehouse

Housing	Aluminium	Swivelling Angle	180 Degree
Colour Temperature	4000 K	Primary Cable Length	2 m
Length	319 mm	Primary Connection End	Power plug IP44
Width	90 mm	CRI (Ra)	80
Height	411 mm	IP Protection Type Plug	IP 44
Power Supply Unit incl.	Yes	IK Protection Class	IK08
Light Beam Angle	110 Degree		




732102

Article	Housing Color		Luminous Flux	Power	Rated Input Voltage	EEL	Price
732096		Black		21350 lm	152.0 W	220-240 V/AC	€ 439.95
732097		Black		28450 lm	202.0 W	220-240 V/AC	€ 554.95
732098		Black		31800 lm	242.0 W	220-240 V/AC	€ 624.95
732102		Black		39900 lm	302.0 W	100-240 V/AC	€ 699.95




5-year guarantee
Benefit from the maximum quality promise:
All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.



page 586

display lights







ATIS

When it comes to illuminating signs, façades, billboards or images, display lights are the perfect choice. They are easy to install, exceptionally efficient and suit almost any environment thanks to their timeless design. With corresponding IP protection, they can also be used outdoors, purposefully providing an additional lighting source in such environments.




ATIS

•Rotatable and swivelling lamp head

Application Area
Object lighting / architecture, Advertising lighting

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Colour Temperature	3000 K	Power Supply Unit incl.	Yes
Luminous Flux	1150 lm	Light Beam Angle	100 Degree
Length	526 mm	Swivelling Angle	90 Degree
Width	144 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Base Length	95 mm	CRI (Ra)	80
Base Height	40 mm		
Power	15 W		



688020

Article	Housing Color	Price
688020	White	€ 229.95
688021	Dark grey	€ 229.95




Lighting design
Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.






SYSTEM LAUTARO

- 592 pendant lights
 - 598 surface mounted ceiling lights
- 



SYSTEM LAUTARO




page 594





page 595




page 596




page 597




page 598






LAUTARO

LAUTARO is a new luminaire series which, despite its enormous configuration options, has one thing in common: it is round or ring-shaped and has a surrounding LED ring. But that is where the similarities end. All other product features can be selected, which is why LAUTARO is suitable for a wide range of commercial [and private] applications, including cafés, hotel lobbies, schools, stores and much more.



Is your desired variant not included in the standard range? Then simply configure your customised LAUTARO using our online configurator.



PLEASANT LIGHT ALL ROUND - YOUR BENEFITS AT A GLANCE:

- BEG-eligible [for approx. 50% of models]
- DALI dimmable thanks to integrated power supply unit
- emergency current capable
- through-wiring for simple series connection
- tool-free connection with spring terminals
- easy to install and maintain thanks to durable, easily replaceable components
- invisible screw connection for a clean appearance

1,080 VARIANTS AS STANDARD - SPECIAL DESIGNS ON REQUEST MODULAR SYSTEM FOR MAXIMUM DESIGN FREEDOM:

- three profile sizes: 60×40 / 80×55 / 100×80 mm
- three colours: RAL 9005 [black] / RAL 9006 [silver] / RAL 9016 [white]
- four diameters: 600 / 900 / 1,200 / 1,500 mm
- three light colors: 2,700 K / 3,000 K / 4,000 K
- surface-mounted luminaires for direct light
- pendant luminaires for direct or direct-indirect light [separately switchable and dimmable]
- custom-made products on request - e.g. individual sizes or RAL of your choice



LAUTARO 900/60 DOWN, SUSPENSION CENTRE

- DALI dimmable with integrated power supply
- continuous wiring possible
- tool-free connection with plug-in terminals
- easy to install / maintain
- long-lasting, easily replaceable components
- invisible screw connections
- customised designs available on request

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, DIY store / discount store / supermarket / car dealership, Trade fair construction / shop fitting

Housing	Aluminium, Steel	Power Supply Unit incl.	Yes
Power	59 W	Light Beam Angle	90 Degree
Rated Input Voltage	198-264 V/AC	Control	DALI 2 / DT6, Push-Dim
Height	60 mm	CRI (Ra)	90
Ø	900 mm	IK Protection Class	IK05
Pendulum Length	3000 mm		

Article	Housing Color	Colour Temperature	Gloss level lens	Luminous Flux	Price
950216	Light gray	2700 K	opal	5780 lm	€ 919.95
950217	Black	2700 K	opal	5780 lm	€ 919.95
950218	White	2700 K	opal	5780 lm	€ 919.95
950225	Light gray	2700 K	microprismatic	6200 lm	€ 949.95
950226	Black	2700 K	microprismatic	6200 lm	€ 949.95
950227	White	2700 K	microprismatic	6200 lm	€ 949.95
950219	Light gray	3000 K	opal	6370 lm	€ 919.95
950220	Black	3000 K	opal	6370 lm	€ 919.95
950221	White	3000 K	opal	6370 lm	€ 919.95
950228	Light gray	3000 K	microprismatic	6790 lm	€ 949.95
950229	Black	3000 K	microprismatic	6790 lm	€ 949.95
950230	White	3000 K	microprismatic	6790 lm	€ 949.95
950222	Light gray	4000 K	opal	7020 lm	€ 919.95
950223	Black	4000 K	opal	7020 lm	€ 919.95
950224	White	4000 K	opal	7020 lm	€ 919.95
950231	Light gray	4000 K	microprismatic	7380 lm	€ 949.95
950232	Black	4000 K	microprismatic	7380 lm	€ 949.95
950233	White	4000 K	microprismatic	7380 lm	€ 949.95





LAUTARO 900/60 DOWN, SUSPENSION PARALLEL

- DALI dimmable with integrated power supply
- continuous wiring possible
- tool-free connection with plug-in terminals
- easy to install / maintain
- long-lasting, easily replaceable components
- invisible screw connections
- customised designs available on request

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, DIY store / discount store / supermarket / car dealership, Trade fair construction / shop fitting

Housing	Aluminium, Steel	Power Supply Unit incl.	Yes
Power	59 W	Light Beam Angle	90 Degree
Rated Input Voltage	198-264 V/AC	Control	DALI 2 / DT6, Push-Dim
Height	60 mm	CRI (Ra)	90
Ø	900 mm	IK Protection Class	IK05
Pendulum Length	3000 mm		

Article	Housing Color	Colour Temperature	Gloss level lens	Luminous Flux	Price
950234	Light gray	2700 K	opal	5780 lm	€ 919.95
950235	Black	2700 K	opal	5780 lm	€ 919.95
950236	White	2700 K	opal	5780 lm	€ 919.95
950243	Light gray	2700 K	microprismatic	6200 lm	€ 949.95
950244	Black	2700 K	microprismatic	6200 lm	€ 949.95
950245	White	2700 K	microprismatic	6200 lm	€ 949.95
950237	Light gray	3000 K	opal	6370 lm	€ 919.95
950238	Black	3000 K	opal	6370 lm	€ 919.95
950239	White	3000 K	opal	6370 lm	€ 919.95
950246	Light gray	3000 K	microprismatic	6790 lm	€ 949.95
950247	Black	3000 K	microprismatic	6790 lm	€ 949.95
950248	White	3000 K	microprismatic	6790 lm	€ 949.95
950240	Light gray	4000 K	opal	7020 lm	€ 919.95
950241	Black	4000 K	opal	7020 lm	€ 919.95
950242	White	4000 K	opal	7020 lm	€ 919.95
950249	Light gray	4000 K	microprismatic	7380 lm	€ 949.95
950250	Black	4000 K	microprismatic	7380 lm	€ 949.95
950251	White	4000 K	microprismatic	7380 lm	€ 949.95





LAUTARO 900/60 UP/DOWN, SUSPENSION CENTRE

- DALI dimmable with integrated power supply
- continuous wiring possible
- tool-free connection with plug-in terminals
- easy to install / maintain
- long-lasting, easily replaceable components
- invisible screw connections
- customised designs available on request

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, DIY store / discount store / supermarket / car dealership, Trade fair construction / shop fitting

Housing	Aluminium, Steel	Power Supply Unit incl.	Yes
Power	83.5 W	Light Beam Angle	90 Degree
Rated Input Voltage	198-264 V/AC	Control	DALI 2 / DT6, Push-Dim
Height	60 mm	CRI (Ra)	90
Ø	900 mm	IK Protection Class	IK05
Pendulum Length	3000 mm		

Article	Housing Color	Colour Temperature	Gloss level lens	Luminous Flux	Price
950254	White	2700 K	opal	7800 lm	€ 1289.95
950252	Light gray	2700 K	opal	7800 lm	€ 1289.95
950253	Black	2700 K	opal	7800 lm	€ 1289.95
950263	White	2700 K	microprismatic	8330 lm	€ 1299.95
950261	Light gray	2700 K	microprismatic	8330 lm	€ 1299.95
950262	Black	2700 K	microprismatic	8330 lm	€ 1299.95
950257	White	3000 K	opal	8590 lm	€ 1289.95
950255	Light gray	3000 K	opal	8590 lm	€ 1289.95
950256	Black	3000 K	opal	8590 lm	€ 1289.95
950266	White	3000 K	microprismatic	9130 lm	€ 1299.95
950264	Light gray	3000 K	microprismatic	9130 lm	€ 1299.95
950265	Black	3000 K	microprismatic	9130 lm	€ 1299.95
950260	White	4000 K	opal	9440 lm	€ 1289.95
950258	Light gray	4000 K	opal	9440 lm	€ 1289.95
950259	Black	4000 K	opal	9440 lm	€ 1289.95
950269	White	4000 K	microprismatic	9940 lm	€ 1299.95
950267	Light gray	4000 K	microprismatic	9940 lm	€ 1299.95
950268	Black	4000 K	microprismatic	9940 lm	€ 1299.95





LAUTARO 900/60 UP/DOWN, SUSPENSION PARALLEL

- DALI dimmable with integrated power supply
- continuous wiring possible
- tool-free connection with plug-in terminals
- easy to install / maintain
- long-lasting, easily replaceable components
- invisible screw connections
- customised designs available on request

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, DIY store / discount store / supermarket / car dealership, Trade fair construction / shop fitting

Housing	Aluminium, Steel	Power Supply Unit incl.	Yes
Power	83.5 W	Light Beam Angle	90 Degree
Rated Input Voltage	198-264 V/AC	Control	DALI 2 / DT6, Push-Dim
Height	60 mm	CRI (Ra)	90
Ø	900 mm	IK Protection Class	IK05
Pendulum Length	3000 mm		

Article	Housing Color	Colour Temperature	Gloss level lens	Luminous Flux	Price
950272	White	2700 K	opal	7800 lm	€ 1289.95
950270	Light gray	2700 K	opal	7800 lm	€ 1289.95
950271	Black	2700 K	opal	7800 lm	€ 1289.95
950281	White	2700 K	microprismatic	8330 lm	€ 1299.95
950279	Light gray	2700 K	microprismatic	8330 lm	€ 1299.95
950280	Black	2700 K	microprismatic	8330 lm	€ 1299.95
950275	White	3000 K	opal	8590 lm	€ 1289.95
950273	Light gray	3000 K	opal	8590 lm	€ 1289.95
950274	Black	3000 K	opal	8590 lm	€ 1289.95
950284	White	3000 K	microprismatic	9130 lm	€ 1299.95
950282	Light gray	3000 K	microprismatic	9130 lm	€ 1299.95
950283	Black	3000 K	microprismatic	9130 lm	€ 1299.95
950278	White	4000 K	opal	9440 lm	€ 1289.95
950276	Light gray	4000 K	opal	9440 lm	€ 1289.95
950277	Black	4000 K	opal	9440 lm	€ 1289.95
950287	White	4000 K	microprismatic	9940 lm	€ 1299.95
950285	Light gray	4000 K	microprismatic	9940 lm	€ 1299.95
950286	Black	4000 K	microprismatic	9940 lm	€ 1299.95





LAUTARO 900/60


Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, DIY store / discount store / supermarket / car dealership, Trade fair construction / shop fitting

Housing	Aluminium, Steel	Pendulum Length	3000 mm
Height	60 mm	Light Beam Angle	90 Degree
Ø	900 mm	Control	DALI 2 / DT6, Push-Dim
Power	59 W	CRI (Ra)	90
Rated Input Voltage	198-264 V/AC	IK Protection Class	IK05
Power Supply Unit incl.	Yes		

Article	Housing Color	Colour Temperature	Gloss level lens	Luminous Flux	Price
950918	Light gray	2700 K	opal	5780 lm	€ 819.95
950919	Black	2700 K	opal	5780 lm	€ 819.95
950920	White	2700 K	opal	5780 lm	€ 819.95
950927	Light gray	2700 K	microprismatic	6200 lm	€ 849.95
950928	Black	2700 K	microprismatic	6200 lm	€ 849.95
950929	White	2700 K	microprismatic	6200 lm	€ 849.95
950921	Light gray	3000 K	opal	6370 lm	€ 819.95
950922	Black	3000 K	opal	6370 lm	€ 819.95
950923	White	3000 K	opal	6370 lm	€ 819.95
950930	Light gray	3000 K	microprismatic	6790 lm	€ 849.95
950931	Black	3000 K	microprismatic	6790 lm	€ 849.95
950932	White	3000 K	microprismatic	6790 lm	€ 849.95
950924	Light gray	4000 K	opal	7020 lm	€ 819.95
950925	Black	4000 K	opal	7020 lm	€ 819.95
950926	White	4000 K	opal	7020 lm	€ 819.95
950933	Light gray	4000 K	microprismatic	7380 lm	€ 849.95
950934	Black	4000 K	microprismatic	7380 lm	€ 849.95
950935	White	4000 K	microprismatic	7380 lm	€ 849.95










SYSTEM PLANO


604 luminaire system

622 profile system





PLANO luminaire system





PLANO LUMINAIRE SYSTEM

Whether as a recessed version, surface-mounted ceiling luminaire or pendant luminaire as well as for wall mounting: the PLANO series is more than just another combination of profile and LED strip and is produced entirely in Europe.


The linear lighting solutions are based on four different profiles and can be configured individually. Thus, there are hardly any limits to the possible applications - whether in the office, in schools, in private living areas, in stores, showrooms and many more.



INDIVIDUAL SOLUTION

A PLANO profile luminaire always has the same design - and yet it is individual. Inside sits a profile with LED illumination in 2,700, 3,000 or 4,000 K. The surrounding luminaire body is made of extruded aluminum and has an anodized or powder-coated surface. You can individually determine the length, equipment as well as the

basic shape of the body, because the PLANO series is an individual lighting solution.



PROFIL

- colour
- length
- basic shape

ASSEMBLY

- installation
- built-in
- ceiling
- pendant
- wall

RADIATION DIRECTION

- up
- up / down

COLOUR TEMPERATURE


- 2700 K
- 3000 K
- 4000 K

COVER

- opal
- opal U
- microprismatic

CONTROL

- switchable
- DALI
- phase angle / section
- Casambi



PLANO DS
LUMINAIRE SYSTEM


- aluminium die casting
- direct light

assembly				cover			length	radiation dir.		colour	colour temperature			control			
ceiling structure	pendulum	wall structure	ceiling mounting	opal	opal U	micropismatic	individual	down	up+down	individual	2700 K	3000 K	4000 K	switchable	DALI	phase angle/section	Casambi
x	x			x	x	x	x	x		x	x	x	x	x	x	x	x

LED

Ra>90

IP20




CONFIGURATION EXAMPLE

- DS surface-mounted luminaire | 2400 mm | black
- 74 W
- 3000 K | 6827 lm
- EVG | DALI
- incl. U-cover opal
- incl. end caps

price on demand

Of course, you can configure our PLANO system entirely according to your wishes and circumstances.





PLANO ES
LUMINAIRE SYSTEM


- aluminium die casting
- direct light

assembly				cover			length	radiation dir.		colour	colour temperature			control			
ceiling structure	pendulum	wall structure	ceiling mounting	opal	opal U	microprismatic	individual	down	up+down	individual	2700 K	3000 K	4000 K	switchable	DALI	phase angle/section	Casambi
x	x			x	x	x	x	x	x	x	x	x	x	x	x	x	x

LED

Ra>90

IP20





CONFIGURATION EXAMPLE

- ES surface-mounted luminaire | 2400 mm | black
- 74 W
- 3000 K | 5425 lm
- EVG | DALI
- incl. U-cover flat opal
- incl. end caps

price on demand

Of course, you can configure our PLANO system entirely according to your wishes and circumstances.





PLANO ES
LUMINAIRE SYSTEM


- aluminium die casting
- direct light

assembly				cover			length	radiation dir.		colour	colour temperature			control			
ceiling structure	pendulum	wall structure	ceiling mounting	opal	opal U	micropismatic	individual	down	up+down	individual	2700 K	3000 K	4000 K	switchable	DALI	phase angle/section	Casambi
		x		x	x	x	x	x	x	x	x	x	x	x	x	x	x

LED

Ra>90

IP20





CONFIGURATION EXAMPLE

- ES wall-mounted luminaire | 2400 mm | black
- 97 W
- 3000 K | 7201 lm
- EVG | DALI
- incl. U-cover flat opal
- incl. end caps and wall bracket

price on demand

Of course, you can configure our PLANO system entirely according to your wishes and circumstances.





PLANO ES RECESSED LUMINAIRE SYSTEM


- aluminium die casting
- direct light

assembly				cover			length	radiation dir.		colour	colour temperature			control			
ceiling structure	pendulum	wall structure	ceiling mounting	opal	opal U	microprismatic	individual	down	up+down	individual	2700 K	3000 K	4000 K	switchable	DALI	phase angle/section	Casambi
			x	x	x	x	x	x		x	x	x	x	x	x	x	x

LED

Ra>90

IP20





CONFIGURATION EXAMPLE

- ES recessed ceiling luminaire | 2400 mm | black
- 97 W
- 3000 K | 7201 lm
- EVG | DALI
- incl. U-cover flat opal
- incl. end caps and mounting bracket

price on demand

Of course, you can configure our PLANO system entirely according to your wishes and circumstances.





PLANO MS
LUMINAIRE SYSTEM





- aluminium die casting
- direct light

assembly				cover			length	radiation dir.		colour	colour temperature			control			
ceiling structure	pendulum	wall structure	ceiling mounting	opal	opal U	micropismatic	individual	down	up+down	individual	2700 K	3000 K	4000 K	switchable	DALI	phase angle/section	Casambi
x	x			x	x	x	x	x	x	x	x	x	x	x	x	x	x

LED

Ra>90

IP20



CONFIGURATION EXAMPLE

- MS surface-mounted luminaire | 2400 mm | black
- 74 W
- 3000 K | 6990 lm
- EVG | DALI
- incl. U-cover opal
- incl. end caps

price on demand

Of course, you can configure our PLANO system entirely according to your wishes and circumstances.





PLANO MS RECESSED LUMINAIRE SYSTEM


- aluminium die casting
- direct light

assembly				cover			length	radiation dir.		colour	colour temperature			control			
ceiling structure	pendulum	wall structure	ceiling mounting	opal	opal U	microprismatic	individual	down	up+down	individual	2700 K	3000 K	4000 K	switchable	DALI	phase angle/section	Casambi
			x	x	x	x	x	x		x	x	x	x	x	x	x	x

LED

Ra>90

IP20



CONFIGURATION EXAMPLE

- MS recessed ceiling luminaire | 2400 mm | black
- 74 W
- 3000 K | 6990 lm
- EVG | DALI
- incl. U-cover opal
- incl. end caps and mounting bracket

price on demand

Of course, you can configure our PLANO system entirely according to your wishes and circumstances.





PLANO BSH
LUMINAIRE SYSTEM


- aluminium die casting
- direct light

assembly				cover			length	radiation dir.		colour	colour temperature			control			
ceiling structure	pendulum	wall structure	ceiling mounting	opal	opal U	microprismatic	individual	down	up+down	individual	2700 K	3000 K	4000 K	switchable	DALI	phase angle/section	Casambi
		x		x	x	x	x	x	x	x	x	x	x	x	x	x	x

LED

Ra>90

IP20



CONFIGURATION EXAMPLE

- BSH wall-mounted luminaire | 2400 mm | black
- 174 W,
- 3000 K | 10822 lm
- EVG | DALI
- incl. U-cover opal
- incl. end caps

price on demand

Of course, you can configure our PLANO system entirely according to your wishes and circumstances.






PLANO profiles



  
page 622




  
page 623



  
page 624





PROFILE PLANO ES

- universal light profile
- Uplight for LED strips up to 15 mm wide
- Downlight for LED strips up to 22 mm wide
- incl. LED carrier

Housing Aluminium

Article	Housing Color	Surface	Length	Price
970574	 Black		2000 mm	€ 129.95
970576	 White		2000 mm	€ 189.95
970575	 Black		2500 mm	€ 159.95
970577	 White		2500 mm	€ 239.95
970572	 Aluminium	Anodised	2000 mm	€ 129.95
970573	 Aluminium	Anodised	2500 mm	€ 159.95

Accessories

988111	Plano ES opal indirect cover, 2 m		€ 24.95
988112	Plano ES opal indirect cover, 2.5 m		€ 29.95
988201	PLANO ES longitudinal connector		€ 9.95
988204	PLANO ES corner connector		€ 18.95
988206	PLANO aluminium wall bracket		€ 49.95
988095	PLANO ES and MS - cable suspension set, in pairs		€ 89.95

Accessories for 970572, 970573

988092	PLANO ES end cap surface-mounted, aluminium anodised		€ 24.95
988114	PLANO ES end cap high surface-mounted, black		€ 24.95
988207	Plano ES and MS anodised aluminium uplight dummy cover		€ 139.95

Accessories for 970572, 970574, 970576

988086	PLANO ES and BSH and MS flat opal uplight cover, 2 m		€ 39.95
988088	PLANO ES and BSH high opal cover, 2 m		€ 84.95
988090	PLANO ES and BSH and MS flat microprism uplight cover, 2 m		€ 69.95

Accessories for 970573, 970575, 970577


988087	PLANO ES and BSH and MS flat opal uplight cover, 2.5 m		€ 49.95
988089	PLANO ES and BSH high opal cover, 2.5 m		€ 104.95
988091	PLANO ES and BSH and MS flat microprism uplight cover, 2.5 m		€ 84.95

Accessories for 970574, 970575

988093	PLANO ES end cap surface-mounted, black		€ 24.95
988115	PLANO glued laminated timber end cap high surface-mounted, aluminium anodised		€ 39.95
988208	Plano ES and MS black uplight dummy cover		€ 99.90

Accessories for 970576, 970577

988094	PLANO ES end cap surface-mounted, white		€ 29.95
988209	Plano ES and MS white uplight dummy cover		€ 99.95



PROFILE PLANO MS

- universal light profile
- Uplight for LED strips up to 24 mm wide
- Downlight for LED strips up to 24 mm wide
- incl. LED carrier

Housing

Aluminium

Article	Housing Color	Surface	Length	Price
970580	 Black		2000 mm	€ 274.95
970582	 White		2000 mm	€ 339.95
970581	 Black		2500 mm	€ 339.95
970583	 White		2500 mm	€ 419.95
970578	 Aluminium	Anodised	2000 mm	€ 274.95
970579	 Aluminium	Anodised	2500 mm	€ 339.95

Accessories

988109	PLANO MS end cap high surface-mounted, aluminium anodised		€ 24.95
988110	PLANO MS end cap high surface-mounted, black		€ 24.95
988200	PLANO MS longitudinal connector		€ 9.95
988203	PLANO MS corner connector		€ 18.95
988206	PLANO aluminium wall bracket		€ 49.95

Accessories for **970578, 970579**

988102	PLANO MS end cap surface-mounted, aluminium anodised		€ 24.95
988207	Plano ES and MS anodised aluminium uplight dummy cover		€ 139.95
988210	Plano MS anodised aluminium downlight dummy cover		€ 89.90

Accessories for **970578, 970580, 970582**

988086	PLANO ES and BSH and MS flat opal uplight cover, 2 m		€ 39.95
988090	PLANO ES and BSH and MS flat microprism uplight cover, 2 m		€ 69.95
988096	PLANO MS flat opal downlight cover, 2 m		€ 49.95
988098	PLANO MS high opal downlight cover, 2 m		€ 99.95
988100	PLANO MS flat microprism downlight cover, 2 m		€ 69.95

Accessories for **970579, 970581, 970583**


988087	PLANO ES and BSH and MS flat opal uplight cover, 2.5 m		€ 49.95
988091	PLANO ES and BSH and MS flat microprism uplight cover, 2.5 m		€ 84.95
988097	PLANO MS flat opal downlight cover, 2.5 m		€ 64.95
988099	PLANO MS high opal downlight cover, 2.5 m		€ 124.95
988101	PLANO MS flat microprism downlight cover, 2.5 m		€ 84.95

Accessories for **970580, 970581**

988103	PLANO MS end cap surface-mounted, black		€ 29.95
988208	Plano ES and MS black uplight dummy cover		€ 99.90
988211	Plano MS black downlight dummy cover		€ 139.90

Accessories for **970582, 970583**

988095	PLANO ES and MS - cable suspension set, in pairs		€ 89.95
988104	PLANO MS end cap surface-mounted, white		€ 29.95
988209	Plano ES and MS white uplight dummy cover		€ 99.95
988212	Plano MS white downlight dummy cover		€ 139.95



PROFILE PLANO BSH

- universal light profile
- Uplight for LED strips up to 31 mm wide
- Downlight for LED strips up to 31 mm wide
- incl. LED carrier

Housing		Aluminium		
Article	Housing Color	Surface	Length	Price
970586	 Black		2000 mm	€ 199.95
970588	 White		2000 mm	€ 199.95
970587	 Black		2500 mm	€ 249.95
970589	 White		2500 mm	€ 249.95
970584	 Aluminium	Anodised	2000 mm	€ 139.95
970585	 Aluminium	Anodised	2500 mm	€ 169.95

Accessories

988202	PLANO BSH longitudinal connector		€ 9.95
988205	PLANO BSH corner connector		€ 18.95
988206	PLANO aluminium wall bracket		€ 49.95
988095	PLANO ES and MS - cable suspension set, in pairs		€ 89.95

Accessories for 970584, 970585

988106	PLANO glued laminated timber end cap surface-mounted, aluminium anodised		€ 24.95
988115	PLANO glued laminated timber end cap high surface-mounted, aluminium anodised		€ 39.95

Accessories for 970584, 970586, 970588

988086	PLANO ES and BSH and MS flat opal uplight cover, 2 m		€ 39.95
988088	PLANO ES and BSH high opal cover, 2 m		€ 84.95
988090	PLANO ES and BSH and MS flat microprism uplight cover, 2 m		€ 69.95

Accessories for 970585, 970587, 970589


988087	PLANO ES and BSH and MS flat opal uplight cover, 2.5 m		€ 49.95
988089	PLANO ES and BSH high opal cover, 2.5 m		€ 104.95
988091	PLANO ES and BSH and MS flat microprism uplight cover, 2.5 m		€ 84.95

Accessories for 970586, 970587

988107	PLANO glued laminated timber end cap surface-mounted, black		€ 29.95
988116	PLANO glued laminated timber end cap high surface-mounted, black		€ 39.95

Accessories for 970588, 970589

988108	PLANO glued laminated timber end cap surface-mounted, white		€ 29.95
--------	---	--	---------







SYSTEM COMBO

630 concrete profile

636 built-in profile

640 facade profile

644 insulation profile

646 click profile





page 634



page 635



page 638



page 639



page 642



page 643



page 645



page 645



page 648



page 649



page N/A


COMBO profiles



COMBO PROFILE SYSTEM – INSTALLATION-FRIENDLY PROFILE-IN-PROFILE SOLUTION

Facades, gardens, living spaces: The patented COMBO PROFILE SYSTEM lends every architectural design a distinctive character. The linear system solution can be integrated into all common building materials. The profile system not only creates perfect light lines in exposed concrete, concrete, brick, stone, plasterboard, thermal insulation, wood, or facade panels — the installation profiles CONCRETE, DRYWALL, FACADE, and INSULATION can also be quickly and cleanly installed by bricklayers, drywall or facade builders.

Equally important as the appearance is the fact that the lighting solutions can be easily integrated into the building structure even under challenging installation conditions. The lighting insert profile is simply clipped into the installation profiles after construction is completed.






MOUNTING / TRANSFORMER PROFILE CONCRETE


The mounting profile is installed during formwork construction and provides sufficient space for the luminaire profile as well as additional cabling. Optional plaster trim makes all work around the light line easier.

The transformer profile is used to house power supplies, allowing them to be concealed behind the luminaire in the case of long light lines or different circuit configurations.




INSTALLATION INSTRUCTIONS CONCRETE




1. Planning of mounting / transformer profile





2. Installation, finishing work



3. Installation of luminaire profile and power supply






PROFILE, SERIES COMBO, CONCRETE, MOUNTING PROFILE

Housing Aluminium

Article	Housing Color	Length	Price
970800	Black	2000 mm	€ 114.95
970801	White	2000 mm	€ 114.95
970802	Black	3000 mm	€ 143.95
970803	White	3000 mm	€ 143.95

Accessories

988180	Combo plaster moulding - flush, polystyrene 24x29x1000, white		€ 8.95
988179	Combo plaster moulding - plaster edge, polystyrene 40x29x1000, white		€ 8.95
988167	Combo concrete mounting bar wood, 1 m		€ 15.95
988168	Combo concrete mounting bar wood, 2 m		€ 31.95
970811	Combo connection profile for indoor plastering, natural aluminium, 2.5 m		€ 78.95
970812	Combo connection profile for indoor plastering, white, 2.5 m		€ 114.95
970810	Combo connection profile for indoor plastering, black, 2.5 m		€ 114.95
970814	Combo connection profile for filling jobs, natural aluminium, 2 m		€ 13.95
970818	Combo connection profile for filling jobs, white, 2 m		€ 28.95
970816	Combo connection profile for filling jobs, black, 2 m		€ 28.95
988133	Combo concrete end cap 2 pcs. mounting profile with edge covering, white		€ 5.90
988132	Combo concrete end cap 2 pcs. mounting profile with edge covering, black		€ 5.90
988165	Combo concrete connecting piece mounting profile, white		€ 5.95
988164	Combo concrete connecting piece mounting profile, black		€ 5.95
988161	Combo concrete connector and guard rail for concrete recessed profile		€ 22.95



PROFILE, SERIES COMBO, CONCRETE, TRANSFORMER PROFILE

Housing Aluminium

Article	Housing Color	Length	Price
970804	Black	1000 mm	€ 85.95
970805	White	1000 mm	€ 85.95
970806	Black	2000 mm	€ 172.95
970807	White	2000 mm	€ 172.95
970808	Black	3000 mm	€ 258.95
970809	White	3000 mm	€ 258.95

Accessories


988180	Combo plaster moulding - flush, polystyrene 24x29x1000, white
988179	Combo plaster moulding - plaster edge, polystyrene 40x29x1000, white
988167	Combo concrete mounting bar wood, 1 m
988168	Combo concrete mounting bar wood, 2 m
970811	Combo connection profile for indoor plastering, natural aluminium, 2.5 m
970812	Combo connection profile for indoor plastering, white, 2.5 m
970810	Combo connection profile for indoor plastering, black, 2.5 m
970814	Combo connection profile for filling jobs, natural aluminium, 2 m
970818	Combo connection profile for filling jobs, white, 2 m
970816	Combo connection profile for filling jobs, black, 2 m
988135	Combo concrete end cap 2 pcs. transformer profile with edge covering, white
988134	Combo concrete end cap 2 pcs. transformer profile with edge covering, black
988163	Combo concrete connecting piece mounting profile - transformer profile, white
988162	Combo concrete connecting piece mounting profile - transformer profile, black

	€ 8.95
	€ 8.95
	€ 15.95
	€ 31.95
	€ 78.95
	€ 114.95
	€ 114.95
	€ 13.95
	€ 28.95
	€ 28.95
	€ 5.90
	€ 5.90
	€ 5.95
	€ 5.95

MOUNTING & TRANSFORMER PROFILE DRYWALL


The mounting profile can be neatly integrated on site and provides sufficient space for concealed cable routing – perfect for preparing light lines in drywall, plastered brick, thermal insulation, wood, fiberboard, etc. The luminaire profile is simply clipped in at the end.

For direct wall connection, the mounting flanges feature a predetermined breaking point for a clean separation. The transformer profile is used to house power supplies, allowing them to be concealed behind the luminaire in the case of long light lines or different circuit configurations.




INSTALLATION INSTRUCTIONS BRICK, PLASTERBOARD, WOOD




1. Planning of mounting / transformer profile



2. Installation, finishing work



3. Installation of luminaire profile and power supply






PROFILE, SERIES COMBO, BUILT-IN, MOUNTING PROFILE

Housing
 Aluminium

Article	Housing Color	Length	Price
970820	 Aluminium	1000 mm	€ 39.95
970821	 Black	1000 mm	€ 54.95
970822	 White	1000 mm	€ 54.95
970823	 Aluminium	2000 mm	€ 80.95
970824	 Black	2000 mm	€ 108.95
970825	 White	2000 mm	€ 108.95
970826	 Aluminium	3000 mm	€ 120.95
970827	 Black	3000 mm	€ 163.95
970828	 White	3000 mm	€ 163.95

Accessories

988180	Combo plaster moulding - flush, polystyrene 24x29x1000, white		€ 8.95
988179	Combo plaster moulding - plaster edge, polystyrene 40x29x1000, white		€ 8.95
970814	Combo connection profile for filling jobs, natural aluminium, 2 m		€ 13.95
970818	Combo connection profile for filling jobs, white, 2 m		€ 28.95
970816	Combo connection profile for filling jobs, black, 2 m		€ 28.95
988174	Combo connector and fall protection		€ 22.95
988177	Combo connector set 2 pcs. 0/0, natural aluminium		€ 11.95
988178	Combo connector set 2 pcs. 0/90, natural aluminium		€ 11.95
988175	Combo connector set 2 pcs. 90/0, natural aluminium		€ 11.95
988137	Combo built-in end cap 2 pcs. mounting profile without bar, white		€ 5.90
988136	Combo built-in end cap 2 pcs. mounting profile without bar, black		€ 5.90



PROFILE, SERIES COMBO, BUILT-IN, TRANSFORMER PROFILE

Housing

Aluminium

Article	Housing Color	Length	Price
970833	Aluminium	1000 mm	€ 57.95
970834	Black	1000 mm	€ 107.95
970835	White	1000 mm	€ 107.95
970836	Aluminium	2000 mm	€ 114.95
970837	Black	2000 mm	€ 215.95
970838	White	2000 mm	€ 215.95
970839	Aluminium	3000 mm	€ 172.95
970840	Black	3000 mm	€ 273.95
970841	White	3000 mm	€ 273.95

Accessories

988180	Combo plaster moulding - flush, polystyrene 24x29x1000, white		€ 8.95
988179	Combo plaster moulding - plaster edge, polystyrene 40x29x1000, white		€ 8.95
970814	Combo connection profile for filling jobs, natural aluminium, 2 m		€ 13.95
970818	Combo connection profile for filling jobs, white, 2 m		€ 28.95
970816	Combo connection profile for filling jobs, black, 2 m		€ 28.95
988174	Combo connector and fall protection		€ 22.95
988177	Combo connector set 2 pcs. 0/0, natural aluminium		€ 11.95
988178	Combo connector set 2 pcs. 0/90, natural aluminium		€ 11.95
988175	Combo connector set 2 pcs. 90/0, natural aluminium		€ 11.95
988141	Combo built-in end cap 2 pcs. transformer profile, white		€ 5.90
988138	Combo built-in end cap 2 pcs. transformer profile, black		€ 5.90
988140	Combo built-in end cap 2 pcs. connecting piece mounting-/transformer profile, white		€ 5.90
988139	Combo built-in end cap 2 pcs. connecting piece mounting-/transformer profile, black		€ 5.90


**MOUNTING / TRANSFORMER PROFILE
FACADE**



The 3 mm mounting profile enables lighting solutions in areas with low installation height, such as Trespa or aluminium facade panels. Installation takes place behind the facade panel; any height difference of more than 3 mm can be adjusted during installation of the light profiles using the mounting clips. In combination with a thermal insulation connection profile CT, the 3 mm mounting profile can also be subsequently inserted into the insulation before plastering work. Thanks to the thermal and mechanical separation from the luminaire profile, cracks along the light line are avoided.


By adding the 3 mm transformer profile, users can—beyond the applications of the 3 mm mounting profile—also integrate the corresponding power supplies into the light line. This allows for on-site replacement if needed. The mechanical separation between the light and transformer profiles ensures that damage, especially on plastered facades, is prevented.



INSTALLATION INSTRUCTIONS INSULATION AND FACADE PANELS



INSTALLATION INSTRUCTIONS INSULATION AND PLASTER



PROFILES, COMBO SERIES, FACADE, TRANSFORMER PROFILE



Housing
 Aluminium

Article	Housing Color	Length	Price
970869	 Black	1000 mm	€ 107.95
970870	 White	1000 mm	€ 107.95
970871	 Black	2000 mm	€ 215.95
970872	 White	2000 mm	€ 215.95

Accessories

970814	Combo connection profile for filling jobs, natural aluminium, 2 m
970816	Combo connection profile for filling jobs, black, 2 m
970818	Combo connection profile for filling jobs, white, 2 m
988136	Combo facade end cap 2 pcs. mounting profile without bar, black
988137	Combo facade end cap 2 pcs. mounting profile without bar, white
988138	Combo facade end cap 2 pcs. transformer profile, black
988139	Combo facade end cap 2 pcs. connecting piece mounting / transformer profile, black
988140	Combo facade end cap 2 pcs. connecting piece mounting / transformer profile, white
988141	Combo facade end cap 2 pcs. transformer profile, white
988169	Combo connection profile with fabric for levelling work, 3mm, 2m, orange
988175	Combo connector set 2 pcs. 90/0, natural aluminium
988176	Combo connector set of 2 with angle joint 0/20-160°, natural aluminium
988177	Combo connector set 2 pcs. 0/0, natural aluminium
988178	Combo connector set 2 pcs. 0/90, natural aluminium
988179	Combo plaster moulding - plaster edge, polystyrene 40x29x1000, white
988180	Combo plaster moulding - flush, polystyrene 24x29x1000, white

	€ 13.95
	€ 28.95
	€ 28.95
	€ 5.90
	€ 5.90
	€ 5.90
	€ 5.90
	€ 28.95
	€ 11.95
	€ 12.95
	€ 11.95
	€ 11.95
	€ 8.95
	€ 8.95



PROFILES, COMBO SERIES, FAÇADE, MOUNTING PROFILE

Housing

Aluminium


Article	Housing Color	Length	Price
970829	Black	2000 mm	€ 108.95
970830	White	2000 mm	€ 108.95
970831	Black	3000 mm	€ 163.95
970832	White	3000 mm	€ 163.95


Accessories

970814	Combo connection profile for filling jobs, natural aluminium, 2 m		€ 13.95
970816	Combo connection profile for filling jobs, black, 2 m		€ 28.95
970818	Combo connection profile for filling jobs, white, 2 m		€ 28.95
988136	Combo facade end cap 2 pcs. mounting profile without bar, black		€ 5.90
988137	Combo facade end cap 2 pcs. mounting profile without bar, white		€ 5.90
988138	Combo facade end cap 2 pcs. transformer profile, black		€ 5.90
988139	Combo facade end cap 2 pcs. connecting piece mounting / transformer profile, black		€ 5.90
988140	Combo facade end cap 2 pcs. connecting piece mounting / transformer profile, white		€ 5.90
988141	Combo facade end cap 2 pcs. transformer profile, white		€ 5.90
988169	Combo connection profile with fabric for levelling work, 3mm, 2m, orange		€ 28.95
988175	Combo connector set 2 pcs. 90/0, natural aluminium		€ 11.95
988176	Combo connector set of 2 with angle joint 0/20-160°, natural aluminium		€ 12.95
988177	Combo connector set 2 pcs. 0/0, natural aluminium		€ 11.95
988178	Combo connector set 2 pcs. 0/90, natural aluminium		€ 11.95
988179	Combo plaster moulding - plaster edge, polystyrene 40x29x1000, white		€ 8.95
988180	Combo plaster moulding - flush, polystyrene 24x29x1000, white		€ 8.95

**MOUNTING / TRANSFORMER PROFILE
INSULATION**

The mounting profile allows for easy installation of recessed profiles into thermal insulation and can be equipped with all profiles after the surface has been finished. The mounting profile allows for easy installation of recessed profiles into thermal insulation and can be equipped with all profiles after the surface has been finished.





COMBO SERIES, INSULATION, MOUNTING PROFILE


Housing EPS Length 2000 mm

Article	Housing Color	Price
988170	Black	€ 503.95
988171	White	€ 503.95

Accessories

988180	Combo plaster moulding - flush, polystyrene 24x29x1000, white
988178	Combo connector set 2 pcs. 0/90, natural aluminium
988175	Combo connector set 2 pcs. 90/0, natural aluminium
988177	Combo connector set 2 pcs. 0/0, natural aluminium
988137	Combo insulation end cap 2 pcs. mounting profile without bar, white
988136	Combo insulation end cap 2 pcs. mounting profile without bar, black

	€ 8.95
	€ 11.95
	€ 11.95
	€ 11.95
	€ 5.90
	€ 5.90



COMBO SERIES, INSULATION, TRANSFORMER PROFILE

Housing EPS Length 1000 mm

Article	Housing Color	Price
988172	Black	€ 273.95
988173	White	€ 273.95

Accessories

988180	Combo plaster moulding - flush, polystyrene 24x29x1000, white
988178	Combo connector set 2 pcs. 0/90, natural aluminium
988175	Combo connector set 2 pcs. 90/0, natural aluminium
988177	Combo connector set 2 pcs. 0/0, natural aluminium
988141	Combo insulation end cap 2 pcs. transformer profile, white
988138	Combo insulation end cap 2 pcs. transformer profile, black
988140	Combo insulation end cap 2 pcs. connecting piece mounting / transformer profile, white
988139	Combo insulation end cap 2 pcs. connecting piece mounting / transformer profile, black


	€ 8.95
	€ 11.95
	€ 11.95
	€ 11.95
	€ 5.90
	€ 5.90
	€ 5.90
	€ 5.90

LUMINAIRE PROFILE

To complete your light lines within the various transformer and mounting profiles, the extensive range of accessories leaves nothing to be desired. Tools such as connectors with fall protection or cable holders significantly simplify installation. Depending on the nature of the transition to the mounting / transformer profile, you can cover it using the LT-0-20 or accentuate the resulting shadow gap with the LU-02-20. As a general rule, all luminaire profiles should be connected using connectors to prevent mechanical stress on the LED strips caused by differing expansion.



INSTALLATION INSTRUCTIONS LUMINAIRE PROFILE





PROFILE, SERIES COMBO, CLICK U-PROFILE


Housing

Aluminium

Article	Housing Color	Surface	Length	Price
970848	White	Anodised	1000 mm	€ 34.95
970842	Silver		1000 mm	€ 31.95
970845	Black		1000 mm	€ 34.95
970849	White	Anodised	2000 mm	€ 68.95
970843	Silver		2000 mm	€ 62.95
970846	Black		2000 mm	€ 68.95
970850	White	Anodised	3000 mm	€ 103.95
970844	Silver		3000 mm	€ 94.95
970847	Black		3000 mm	€ 103.95

Accessories

988184	Combo set 10 pcs. Mounting clip, height-adjustable V1, 10mm, blue		€ 29.50
988185	Combo set 10 pcs. Mounting clip, height-adjustable V2, 10mm, black		€ 29.50
988186	Combo set 10 pcs. Mounting clip, height-adjustable V3, 10mm, yellow		€ 29.50
988126	Combo cover, H-02-20, high, milky, 1 m		€ 18.95
988127	Combo cover, H-02-20, high, milky, 2 m		€ 36.95
988128	Combo cover, H-02-20, high, milky, 3 m		€ 55.95
988122	Combo cover, B-02-20, wide, milky, 1 m		€ 14.95
988120	Combo cover, B-02-20, wide, milky, 2 m		€ 28.95
988121	Combo cover, B-02-20, wide, milky, 3 m		€ 42.95
988123	Combo click cover V4-HL25 opal, 1 m		€ 11.95
988124	Combo click cover V4-HL25 opal, 2 m		€ 22.95
988125	Combo click cover V4-HL25 opal, 3 m		€ 34.95
988148	Combo end cap 2 pcs. U-light profile, P-LU-02-20, grey		€ 5.90
988146	Combo end cap 2 pcs. U-light profile, P-LU-02-20, white		€ 5.90
988145	Combo end cap 2 pcs. U-light profile, P-LU-02-20, black		€ 5.90
988147	Combo end cap 2 pcs. U-light profile, B-LU-02-20, white		€ 13.90
988142	Combo end cap 2 pcs. U-light profile, H-LU-02-20, grey		€ 7.90
988144	Combo end cap 2 pcs. U-light profile, H-LU-02-20, white		€ 7.90
988143	Combo end cap 2 pcs. U-light profile, H-LU-02-20, black		€ 7.90



PROFILE, SERIES COMBO, CLICK T-PROFILE

Housing		Aluminium		
Article	Housing Color	Surface	Length	Price
970866	 White	Anodised	1000 mm	€ 39.95
970860	 Silver		1000 mm	€ 35.95
970863	 Black		1000 mm	€ 39.95
970867	 White	Anodised	2000 mm	€ 80.95
970861	 Silver		2000 mm	€ 71.95
970864	 Black		2000 mm	€ 80.95
970868	 White	Anodised	3000 mm	€ 120.95
970862	 Silver		3000 mm	€ 107.95
970865	 Black		3000 mm	€ 120.95

Accessories

988184	Combo set 10 pcs. Mounting clip, height-adjustable V1, 10mm, blue		€ 29.50
988185	Combo set 10 pcs. Mounting clip, height-adjustable V2, 10mm, black		€ 29.50
988186	Combo set 10 pcs. Mounting clip, height-adjustable V3, 10mm, yellow		€ 29.50
988122	Combo cover, B-02-20, wide, milky, 1 m		€ 14.95
988120	Combo cover, B-02-20, wide, milky, 2 m		€ 28.95
988121	Combo cover, B-02-20, wide, milky, 3 m		€ 42.95
988123	Combo click cover V4-HL-25 opal, 1 m		€ 11.95
988124	Combo click cover V4-HL-25 opal, 2 m		€ 22.95
988125	Combo click cover V4-HL-25 opal, 3 m		€ 34.95
988126	Combo cover, H-02-20, high, milky, 1 m		€ 18.95
988127	Combo cover, H-02-20, high, milky, 2 m		€ 36.95
988128	Combo cover, H-02-20, high, milky, 3 m		€ 55.95
988158	Combo end cap 2 pcs. T-light profile, P-LT-02-20, grey		€ 7.90
988160	Combo end cap 2 pcs. T-light profile, P-LT-02-20, white		€ 7.90
988159	Combo end cap 2 pcs. T-light profile, P-LT-02-20, black		€ 7.90
988155	Combo end cap 2 pcs. T-light profile, H-LT-02-20, grey		€ 7.90
988157	Combo end cap 2 pcs. T-light profile, H-LT-02-20, white		€ 7.90
988156	Combo end cap 2 pcs. T-light profile, H-LT-02-20, black		€ 7.90
988198	Plano click/flat/hinge wing recessed mounting spring set (2 pieces)		€ 3.95





ALUMINIUM PROFILES

- 652 linear light in 5 steps
 - 656 assembly
 - 658 homogeneous light image
 - 660 U-profiles - flat + high - built-in / built-on
 - 684 T-profiles - flat + high - built in
 - 702 H- and groove-profiles
 - 710 step/plinth/angle/corner-profiles - built-in/built-on
 - 734 dry construction profiles
 - 754 tile profiles
 - 770 profiles for outdoor usw - walkable/trafficable
- 

LINEAR LIGHT IN 5 STEPS

STEP BY STEP TO BECOMING A LINEAR LIGHT

PROFESSIONAL!

It has never been quicker and easier to put together an individually and perfectly coordinated linear light in max. 5 steps. Test how quickly and easily you can put your personal project into practice.

1

CHOOSE YOUR PROFILE

Whether for indoor or outdoor use, for wide or narrow LED stripes, whether the profile is to be should be low or high. Matching to this you can choose between different shapes and light transmittance of the covers.

2

CHOOSE THE RIGHT LED STRIPE

You can choose between strips for indoor or outdoor use, with one or more light colours, high-power strips for basic lighting or fewer lumens for ambient lighting. Various cut sizes and LED spacing also perfectly round off our range here.



3

SELECT THE REQUIRED POWER SUPPLY

In addition to the various protection classes for the respective place of use and voltages, you can choose from different designs and power classes. Our range is complemented by power supplies that can be dimmed directly or controlled via Dali, KNX or 1-10V.

4

DO YOU NEED A CONTROLLER TO STEER?

In this category, you can select the appropriate control controller or LED dimmer according to requirements and customer wishes. Whether control via radio, smartphone, DMX, Dali, etc. – almost no [control] wishes remain unfulfilled!



5

ACCESSORIES, MOUNTING MATERIAL & CO

In the last step, you will find everything that makes installation easier, faster and more comfortable and gives the linear desired light a perfect finish.





aluminium profiles



 
page 662



  
page 684




page 704




page 706



 
page 708




page 712




page 716




page 718



  
page 720



 
page 724




page 726




page 728




page 736




page 738




page 740




page 742




page 744




page 746




page 748




page 750




page 752




page 756




page 758




page 760




page 762




page 766




page 772




page 774




page 776




page 778




page 780





ASSEMBLY FOR PROFILES AND STRIPES

We provide our products individually made to measure on request.
You will receive the prices on request.



989100 – service package I – profile cut

profile is shortened to desired length, tolerance ± 1 mm | sawing loss 4 mm

989105 – drill hole end cap / profile

hole for cable outlet in end cap or profile



989200 – service package II – cover cut

cover is shortened to desired length, tolerance ± 1 mm | sawing loss 4 mm



989300 – service package III – stripe cut

LED stripe is adapted to desired length, taking into account segment and maximum total length, including soldering of a cable lead of the desired length and open, tinned wire ends

989305 – cable – connecting cable / cores 1 channel

989310 – cable – connecting cable / cores 2 channel

989315 – cable – connecting cable / cores 3 + 4 channel

989320 – cable – mini cable / cores 1 - 4 channel

989325 – cable – connecting cable / cores 5 channel

989301 – 2nd connecting cable

attachment of a 2nd connecting cable / cores for further connection with open tinned wire ends

989302 – connecting cable

attaching / soldering a fixed connection line / cores between 2 stripe pieces

[max. 1m connection line / cores incl., a longer connection will be charged by the metre]

original length and max. total length of the strip to be operated may not be exceeded by sections be exceeded

989350 – IP surcharge – sealing stripe

sealing a shortened IP stripe / gluing an end cap



989400 – service package IV – complete assembly

bringing together and assembling all components into a finished luminaire
incl. function test and cable flag

[for desired length, please add 2cm to the cut length of the LED stripe segment
for connection space, length tolerance ± 2 mm]




HOMOGENEOUS LIGHT IMAGE

How to achieve a homogeneous light image

In combination with a milky 40% cover and a matching LED stripe, a homogeneous light image can be created. The distance [pixel pitch] between the LEDs and the cover is decisive.

The rule of thumb here is:

The distance between the LEDs should be smaller than the distance between the LEDs and the cover.



PROFILE DESCRIPTION

mounting type: A = built-on
E = built-in

Width of the series [10 profile] / of
the matching LED stripe

AU - 01 - 10

basic form series

TRANSLUCENCY / LIGHT TRANSMISSION

95% clear 75% mat 40% milky




Illustration of various LED stripes with different pixel pitches in combination with three different light transmittances in the covers. This small selection clearly illustrates the optical differences of some LED stripes in combination with different covers.

120 LED/m
cutting option 50 mm / 6 LED



240 LED/m
cutting option 25 mm / 6 LED



700LED/m
cutting option 10 mm / 7 LED



COB 480 LED/m
cutting option 50 mm / 24 LED





With the kind support of BEST Bellemann Elektro Service Team GmbH, Rauenberg-Malschenberg



U- AND T-PROFILES

The profiles of these series are available in various designs. Thanks to their universal profile shape, they can be used flexibly in almost all areas. Thanks to their profile construction, they are ideally suited for the cover cut edges.




AU-01-05

·for LED strips up to 5.7 mm wide

Housing Aluminium
 Length 2000 mm

Article	Housing Color	Surface	Price
970081	 Silver	Matt / Anodised	€ 17.95
970085	 White	Matt / Powder-coated	€ 15.95







Cover | PMMA - Polymethyl methacrylate

Clear Milky

2 m **983551** **983555** € 11.953 m **983556** € 18.952 m **984055** € 11.952 m **984555** € 11.95**end caps set** | 2 pieces | Plastic | € 4.95

White Grey Black

**978660** **978661** **978662****979160** **979161** **979162****979660** **979661** **979662**




AU-02-05

·for LED strips up to 5.7 mm wide

Housing
Aluminium

Article	Housing Color	Surface	Length	Price
970180	 Silver	Matt / Anodised	1000 mm	€ 9.95
970181	 Silver	Matt / Anodised	2000 mm	€ 18.95
970183	 Black	Matt / Anodised	2000 mm	€ 18.95
970185	 White	Matt / Powder-coated	2000 mm	€ 18.95



Cover | PMMA - Polymethyl methacrylate

Clear Milky



1 m	983550	983554	€ 5.95
2 m	983551	983555	€ 11.95
3 m		983556	€ 18.95



2 m		984055	€ 11.95
-----	--	---------------	----------------



1 m		984554	€ 5.95
2 m		984555	€ 11.95

end caps set | 2 pieces | Plastic | € 4.95

White Grey Black




978670	978671	978672
---------------	---------------	---------------



979170	979171	979172
---------------	---------------	---------------



979670	979671
---------------	---------------






AU-01-08

·for LED strips up to 9.3 mm wide

Housing
 Aluminium

Article	Housing Color	Surface	Length	Price
970000	 Silver	Matt / Anodised	1000 mm	€ 11.95
970001	 Silver	Matt / Anodised	2000 mm	€ 23.95
970003	 Black	Matt / Anodised	2000 mm	€ 23.95
970008	 Silver	Matt / Anodised	3000 mm	€ 35.95
970005	 White	Matt / Powder-coated	2000 mm	€ 23.95



Cover | PMMA - Polymethyl methacrylate

Clear Matt Milky



1 m	983000	983002	983004	€ 7.95
2 m	983001	983003	983005	€ 17.95
3 m	983006	983007	983008	€ 25.95



1 m	983500	983502	983504	€ 7.95
2 m	983501	983503	983505	€ 17.95
3 m			983506	€ 25.95




1 m		984002	984004	€ 7.95
2 m		984003	984005	€ 17.95




1 m		984502	984504	€ 7.95
2 m		984503	984505	€ 17.95

end caps set | 2 pieces | Plastic | € 4.95


White Grey Black




978000	978001	978002
---------------	---------------	---------------



978500	978501	978502
---------------	---------------	---------------



979080	979081	979082
---------------	---------------	---------------



979580	979581	979582
---------------	---------------	---------------

Accessories

930347 3M double-sided adhesive tape 50,000x12x0.2 mm**987002** Set of 2 retaining clips for AU-08**987080** Universal holding clip mount (swivel) set of 2 pieces

€ 31.95



€ 3.95



€ 23.95






AU-02-08

·for LED strips up to 9.3 mm wide

Housing
 Aluminium

Article	Housing Color	Surface	Length	Price
970101	 Silver	Matt / Anodised	2000 mm	€ 28.95
970103	 Black	Matt / Anodised	2000 mm	€ 28.95
970108	 Silver	Matt / Anodised	3000 mm	€ 42.95
970105	 White	Matt / Powder-coated	2000 mm	€ 28.95



Cover | PMMA - Polymethyl methacrylate

Clear Matt Milky



2 m	983001	983003	983005	€ 17.95
3 m	983006	983007	983008	€ 25.95



2 m	983501	983503	983505	€ 17.95
3 m			983506	€ 25.95



2 m		984003	984005	€ 17.95
-----	--	---------------	---------------	----------------



2 m		984503	984505	€ 17.95
-----	--	---------------	---------------	----------------

end caps set | 2 pieces | Plastic | € 4.95

White Grey Black



978040	978041	978042
---------------	---------------	---------------



978540	978541	978542
---------------	---------------	---------------



979100	979101	979102
---------------	---------------	---------------



979600	979601	979602
---------------	---------------	---------------

Accessories

930347 3M double-sided adhesive tape 50,000x12x0.2 mm**987002** Set of 2 retaining clips for AU-08**987080** Universal holding clip mount (swivel) set of 2 pieces**€ 31.95****€ 3.95****€ 23.95**




AU-01-10

·for LED strips up to 11.3 mm wide

Housing Aluminium

Article	Housing Color	Surface	Length	Price
970020	 Silver	Matt / Anodised	1000 mm	€ 11.95
970021	 Silver	Matt / Anodised	2000 mm	€ 23.95
970023	 Black	Matt / Anodised	2000 mm	€ 23.95
970028	 Silver	Matt / Anodised	3000 mm	€ 35.95
970025	 White	Matt / Powder-coated	2000 mm	€ 23.95








Cover | PMMA - Polymethyl methacrylate

Clear Matt Milky

				
1 m	983010	983012	983014	€ 7.95
2 m	983011	983013	983015	€ 17.95
3 m	983016	983017	983018	€ 25.95
				
1 m	983510	983512	983514	€ 7.95
2 m	983511	983513	983515	€ 17.95
3 m	983516	983517	983518	€ 25.95
				
1 m		984012	984014	€ 7.95
2 m		984013	984015	€ 17.95
3 m		984017	984018	€ 25.95
				
1 m		984512	984514	€ 7.95
2 m		984513	984515	€ 17.95
3 m		984517	984518	€ 25.95
				
1 m	985010			€ 7.95
2 m	985011			€ 17.95
3 m	985016			€ 25.95

end caps set | 2 pieces | Plastic | € 4.95

White Grey Black

**978010 978011 978012****978510 978511 978512****979000 979001 979002****979500 979501 979502****980000 980001 980002**

Accessories

930348	3M double-sided adhesive tape 50,000x15x0.20 mm
987004	Set of 2 retaining clips for AU-10
987080	Universal holding clip mount (swivel) set of 2 pieces



€ 38.95



€ 3.95



€ 23.95

**Lighting design**

Interested in our lighting design service?

Your contact person will be happy to answer any questions you may have.




AU-02-10

·for LED strips up to 11.3 mm wide

Housing
 Aluminium

Article	Housing Color	Surface	Length	Price
970120	 Silver	Matt / Anodised	1000 mm	€ 14.95
970121	 Silver	Matt / Anodised	2000 mm	€ 28.95
970123	 Black	Matt / Anodised	2000 mm	€ 28.95
970128	 Silver	Matt / Anodised	3000 mm	€ 44.95
970125	 White	Matt / Powder-coated	2000 mm	€ 28.95



Cover | PMMA - Polymethyl methacrylate

Clear Matt Milky



1 m	983010	983012	983014	€ 7.95
2 m	983011	983013	983015	€ 17.95
3 m	983016	983017	983018	€ 25.95



1 m	983510	983512	983514	€ 7.95
2 m	983511	983513	983515	€ 17.95
3 m	983516	983517	983518	€ 25.95



1 m		984012	984014	€ 7.95
2 m		984013	984015	€ 17.95
3 m		984017	984018	€ 25.95



1 m		984512	984514	€ 7.95
2 m		984513	984515	€ 17.95
3 m		984517	984518	€ 25.95



1 m	985010			€ 7.95
2 m	985011			€ 17.95
3 m	985016			€ 25.95

end caps set | 2 pieces | Plastic | € 4.95

White Grey Black



978050	978051	978052
---------------	---------------	---------------



978550	978551	978552
---------------	---------------	---------------



979020	979021	979022
---------------	---------------	---------------



979520	979521	979522
---------------	---------------	---------------



980010	980011	980012
---------------	---------------	---------------

Accessories

930348 3M double-sided adhesive tape 50,000x15x0.20 mm**987004** Set of 2 retaining clips for AU-10**987080** Universal holding clip mount (swivel) set of 2 pieces

€ 38.95



€ 3.95



€ 23.95

**Onlineshop**

You can find more information about the products in the onlineshop:
Detailed images, videos, project reports, LDT files, EPREL data sheets and more.




AU-01-12

·for LED strips up to 13.3 mm wide

Housing Aluminium

Article	Housing Color	Surface	Length	Price
970040	 Silver	Matt / Anodised	1000 mm	€ 14.95
970041	 Silver	Matt / Anodised	2000 mm	€ 28.95
970043	 Black	Matt / Anodised	2000 mm	€ 28.95
970048	 Silver	Matt / Anodised	3000 mm	€ 42.95
970045	 White	Matt / Powder-coated	2000 mm	€ 28.95



Cover | PMMA - Polymethyl methacrylate

Clear Matt Milky

				
1 m	983020	983022	983024	€ 7.95
2 m	983021	983023	983025	€ 17.95
3 m	983028	983027	983026	€ 25.95





				
1 m	983520	983522	983524	€ 7.95
2 m	983521	983523	983525	€ 17.95
3 m	983527		983526	€ 25.95

				
1 m		984022	984024	€ 7.95
2 m		984023	984025	€ 17.95
3 m			984026	€ 25.95

				
1 m		984522	984524	€ 7.95
2 m		984523	984525	€ 17.95
3 m			984526	€ 25.95

end caps set | 2 pieces | Plastic | € 4.95

White Grey Black

**978020 978021 978022****978520 978521 978522****979010 979011 979012****979510 979511 979512**

Accessories

930348 3M double-sided adhesive tape 50,000x15x0.20 mm

€ 38.95

987006 Set of 2 retaining clips for AU-12

€ 3.95

987080 Universal holding clip mount (swivel) set of 2 pieces

€ 23.95






AU-02-12

·for LED strips up to 13.3 mm wide

Housing Aluminium

Article	Housing Color	Surface	Length	Price
970140	 Silver	Matt / Anodised	1000 mm	€ 15.95
970141	 Silver	Matt / Anodised	2000 mm	€ 31.95
970143	 Black	Matt / Anodised	2000 mm	€ 31.95
970148	 Silver	Matt / Anodised	3000 mm	€ 44.95
970145	 White	Matt / Powder-coated	2000 mm	€ 31.95



Cover | PMMA - Polymethyl methacrylate

Clear Matt Milky

				
1 m	983020	983022	983024	€ 7.95
2 m	983021	983023	983025	€ 17.95
3 m	983028	983027	983026	€ 25.95


				
1 m	983520	983522	983524	€ 7.95
2 m	983521	983523	983525	€ 17.95
3 m	983527		983526	€ 25.95

				
1 m		984022	984024	€ 7.95
2 m		984023	984025	€ 17.95
3 m			984026	€ 25.95

				
1 m		984522	984524	€ 7.95
2 m		984523	984525	€ 17.95
3 m			984526	€ 25.95

end caps set | 2 pieces | Plastic | € 4.95

White Grey Black

**978060** **978061** **978062****978560** **978561** **978562****979030** **979031** **979032****979530** **979531** **979532**

Accessories

930348 3M double-sided adhesive tape 50,000x15x0.20 mm


€ 38.95

987006 Set of 2 retaining clips for AU-12

€ 3.95

987080 Universal holding clip mount (swivel) set of 2 pieces

€ 23.95






AU-01-15

·For LED strips up to 16.3 mm wide

Housing Aluminium

Article	Housing Color	Surface	Length	Price
970060	 Silver	Matt / Anodised	1000 mm	€ 14.95
970061	 Silver	Matt / Anodised	2000 mm	€ 28.95
970063	 Black	Matt / Anodised	2000 mm	€ 28.95
970068	 Silver	Matt / Anodised	3000 mm	€ 42.95
970065	 White	Matt / Powder-coated	2000 mm	€ 28.95



Cover | PMMA - Polymethyl methacrylate

Clear Matt Milky



1 m	983030	983032	983034	€ 9.95
2 m	983031	983033	983035	€ 19.95
3 m	983038	983037	983036	€ 28.95



1 m	983530	983532	983534	€ 9.95
2 m	983531	983533	983535	€ 19.95
3 m		983539	983536	€ 28.95




1 m		984032	984034	€ 9.95
2 m		984033	984035	€ 19.95
3 m			984036	€ 28.95




1 m		984532	984534	€ 9.95
2 m		984533	984535	€ 19.95

end caps set | 2 pieces | Plastic | € 4.95


White Grey Black




978030	978031	978032
---------------	---------------	---------------



978530	978531	978532
---------------	---------------	---------------



979090	979091	979092
---------------	---------------	---------------



979590	979591	979592
---------------	---------------	---------------

Accessories

- 930349** 3M double-sided adhesive tape 50,000x20x0.20 mm
- 987008** Set of 2 retaining clips for AU-15
- 987080** Universal holding clip mount (swivel) set of 2 pieces

**€ 48.95****€ 3.95****€ 23.95**




AU-02-15

·For LED strips up to 16.3 mm wide

Housing Aluminium

Article	Housing Color	Surface	Length	Price
970160	 Silver	Matt / Anodised	1000 mm	€ 15.95
970161	 Silver	Matt / Anodised	2000 mm	€ 31.95
970163	 Black	Matt / Anodised	2000 mm	€ 31.95
970168	 Silver	Matt / Anodised	3000 mm	€ 44.95
970165	 White	Matt / Powder-coated	2000 mm	€ 31.95



Cover | PMMA - Polymethyl methacrylate

Clear Matt Milky



1 m	983030	983032	983034	€ 9.95
2 m	983031	983033	983035	€ 19.95
3 m	983038	983037	983036	€ 28.95



1 m	983530	983532	983534	€ 9.95
2 m	983531	983533	983535	€ 19.95
3 m		983539	983536	€ 28.95




1 m		984032	984034	€ 9.95
2 m		984033	984035	€ 19.95
3 m			984036	€ 28.95




1 m		984532	984534	€ 9.95
2 m		984533	984535	€ 19.95

end caps set | 2 pieces | Plastic | € 4.95


White Grey Black




978070	978071	978072
---------------	---------------	---------------



978570	978571	978572
---------------	---------------	---------------




979110	979111	979112
---------------	---------------	---------------



979610	979611	979612
---------------	---------------	---------------

Accessories

- 930349** 3M double-sided adhesive tape 50,000x20x0.20 mm
- 987008** Set of 2 retaining clips for AU-15
- 987080** Universal holding clip mount (swivel) set of 2 pieces

**€ 48.95****€ 3.95****€ 23.95**




AU-02-20

·For LED strips up to 21.3 mm wide

Housing Aluminium
 Surface Matt, Anodised

Article	Housing Color	Length	Price
970201	 Silver	2000 mm	€ 37.95
970202	 Silver	3000 mm	€ 59.95



Cover | PMMA - Polymethyl methacrylate

Clear Milky



1 m	983040	983044	€ 11.50
2 m	983041	983045	€ 21.95
3 m		983046	€ 32.95



1 m	984044	€ 11.50
2 m	984045	€ 21.95



1 m	984544	€ 11.50
2 m	984545	€ 21.95

end caps set | 2 pieces | Plastic | € 4.95

Grey



978161



978351



978361

Accessories

930350 3M double-sided adhesive tape 50,000x25x0.20 mm

987010 Set of 2 retaining clips for AU-20

987080 Universal holding clip mount (swivel) set of 2 pieces



€ 56.95

€ 3.95

€ 23.95






ET-01-05

·For LED strips up to 5.7 mm wide

Housing Aluminium
Length 2000 mm




Article	Housing Color	Surface	Price
975081	 Silver	Matt / Anodised	€ 17.95
975083	 Black	Matt / Anodised	€ 17.95
975085	 White	Matt / Powder-coated	€ 17.95



Cover | PMMA - Polymethyl methacrylate

	Clear	Milky	
			
1 m	983550	983554	€ 5.95
2 m	983551	983555	€ 11.95
3 m		983556	€ 18.95
			
2 m		984055	€ 11.95
			
1 m		984554	€ 5.95
2 m		984555	€ 11.95

end caps set | 2 pieces | Plastic | € 4.95

White	Grey	Black
		
978680	978681	978682
		
	979181	979182
		
	979681	979682






ET-01-08

·For LED strips up to 9.3 mm wide

Housing Aluminium




Article	Housing Color	Surface	Length	Price
975001	 Silver	Matt / Anodised	2000 mm	€ 26.95
975003	 Black	Matt / Anodised	2000 mm	€ 26.95
975008	 Silver	Matt / Anodised	3000 mm	€ 38.95
975005	 White	Matt / Powder-coated	2000 mm	€ 26.95



Cover | PMMA - Polymethyl methacrylate

	Clear	Matt	Milky	
				
1 m	983000	983002	983004	€ 7.95
2 m	983001	983003	983005	€ 17.95
3 m	983006	983007	983008	€ 25.95
				
1 m	983500	983502	983504	€ 7.95
2 m	983501	983503	983505	€ 17.95
3 m			983506	€ 25.95
				
1 m		984002	984004	€ 7.95
2 m		984003	984005	€ 17.95
				
1 m		984502	984504	€ 7.95
2 m		984503	984505	€ 17.95

end caps set | 2 pieces | Plastic | € 4.95

White	Grey	Black
		
978080	978081	978082
		
978580	978581	978582
		
979120	979121	979122
		
979620	979621	979622

Accessories

930347	3M double-sided adhesive tape 50,000x12x0.2 mm
987002	Set of 2 retaining clips for AU-08
987080	Universal holding clip mount (swivel) set of 2 pieces



€ 31.95



€ 3.95



€ 23.95






ET-02-08

·For LED strips up to 9.3 mm wide

Housing Aluminium




Article	Housing Color	Surface	Length	Price
975101	 Silver	Matt / Anodised	2000 mm	€ 31.95
975103	 Black	Matt / Anodised	2000 mm	€ 31.95
975108	 Silver	Matt / Anodised	3000 mm	€ 44.95
975105	 White	Matt / Powder-coated	2000 mm	€ 31.95



Cover | PMMA - Polymethyl methacrylate

	Clear	Matt	Milky	
				
1 m	983000	983002	983004	€ 7.95
2 m	983001	983003	983005	€ 17.95
3 m	983006	983007	983008	€ 25.95
				
1 m	983500	983502	983504	€ 7.95
2 m	983501	983503	983505	€ 17.95
3 m			983506	€ 25.95
				
1 m		984002	984004	€ 7.95
2 m		984003	984005	€ 17.95
				
1 m		984502	984504	€ 7.95
2 m		984503	984505	€ 17.95

end caps set | 2 pieces | Plastic | € 4.95

White	Grey	Black
		
978120	978121	978122
		
978620	978621	978622
		
979140	979141	979142
		
	979641	

Accessories

930347	3M double-sided adhesive tape 50,000x12x0.2 mm
987002	Set of 2 retaining clips for AU-08
987080	Universal holding clip mount (swivel) set of 2 pieces



€ 31.95



€ 3.95



€ 23.95






ET-01-10

·For LED strips up to 11.3 mm wide

Housing Aluminium

Article	Housing Color	Surface	Length	Price
975021	 Silver	Matt / Anodised	2000 mm	€ 26.95
975023	 Black	Matt / Anodised	2000 mm	€ 26.95
975028	 Silver	Matt / Anodised	3000 mm	€ 38.95
975025	 White	Matt / Powder-coated	2000 mm	€ 26.95



Cover | PMMA - Polymethyl methacrylate

Clear Matt Milky



1 m	983010	983012	983014	€ 7.95
2 m	983011	983013	983015	€ 17.95
3 m	983016	983017	983018	€ 25.95



1 m	983510	983512	983514	€ 7.95
2 m	983511	983513	983515	€ 17.95
3 m	983516	983517	983518	€ 25.95



1 m		984012	984014	€ 7.95
2 m		984013	984015	€ 17.95
3 m		984017	984018	€ 25.95




1 m		984512	984514	€ 7.95
2 m		984513	984515	€ 17.95
3 m		984517	984518	€ 25.95




1 m	985010			€ 7.95
2 m	985011			€ 17.95
3 m	985016			€ 25.95

end caps set | 2 pieces | Plastic | € 4.95


White Grey Black




978090	978091	978092
---------------	---------------	---------------




978590	978591	978592
---------------	---------------	---------------



979040	979041	979042
---------------	---------------	---------------



979540	979541	979542
---------------	---------------	---------------



980040	980041	980042
---------------	---------------	---------------

Accessories

930348 3M double-sided adhesive tape 50,000x15x0.20 mm**987004** Set of 2 retaining clips for AU-10**987080** Universal holding clip mount (swivel) set of 2 pieces

€ 38.95



€ 3.95




€ 23.95

**Lighting design**

Interested in our lighting design service?

Your contact person will be happy to answer any questions you may have.




ET-02-10

·For LED strips up to 11.3 mm wide

Housing
 Aluminium

Article	Housing Color	Surface	Length	Price
975121	 Silver	Matt / Anodised	2000 mm	€ 31.95
975123	 Black	Matt / Anodised	2000 mm	€ 31.95
975128	 Silver	Matt / Anodised	3000 mm	€ 44.95
975125	 White	Matt / Powder-coated	2000 mm	€ 31.95



Cover | PMMA - Polymethyl methacrylate

Clear Matt Milky



1 m	983010	983012	983014	€ 7.95
2 m	983011	983013	983015	€ 17.95
3 m	983016	983017	983018	€ 25.95



1 m	983510	983512	983514	€ 7.95
2 m	983511	983513	983515	€ 17.95
3 m	983516	983517	983518	€ 25.95



1 m		984012	984014	€ 7.95
2 m		984013	984015	€ 17.95
3 m		984017	984018	€ 25.95




1 m		984512	984514	€ 7.95
2 m		984513	984515	€ 17.95
3 m		984517	984518	€ 25.95




1 m	985010			€ 7.95
2 m	985011			€ 17.95
3 m	985016			€ 25.95

end caps set | 2 pieces | Plastic | € 4.95


White Grey Black




978130	978131	978132
---------------	---------------	---------------




978630	978631	978632
---------------	---------------	---------------



979060	979061	979062
---------------	---------------	---------------



979560	979561	979562
---------------	---------------	---------------



980060	980061
---------------	---------------

Accessories

930348 3M double-sided adhesive tape 50,000x15x0.20 mm**987004** Set of 2 retaining clips for AU-10**987080** Universal holding clip mount (swivel) set of 2 pieces**€ 38.95****€ 3.95****€ 23.95****Onlineshop**

You can find more information about the products in the onlineshop:
Detailed images, videos, project reports, LDT files, EPREL data sheets and more.




ET-01-12

·For LED strips up to 13.3 mm wide

Housing Aluminium
Length 2000 mm




Article	Housing Color	Surface	Price
975041	 Silver	Matt / Anodised	€ 31.95
975045	 White	Matt / Powder-coated	€ 31.95



Cover | PMMA - Polymethyl methacrylate

	Clear	Matt	Milky	
				
1 m	983020	983022	983024	€ 7.95
2 m	983021	983023	983025	€ 17.95
				
1 m	983520	983522	983524	€ 7.95
2 m	983521	983523	983525	€ 17.95
				
1 m		984022	984024	€ 7.95
2 m		984023	984025	€ 17.95
				
1 m		984522	984524	€ 7.95
2 m		984523	984525	€ 17.95

end caps set | 2 pieces | Plastic | € 4.95

White	Grey	Black
		
978100	978101	978102
		
978600	978601	978602
		
979050	979051	979052
		
979550	979551	979552

Accessories

930348	3M double-sided adhesive tape 50,000x15x0.20 mm
987006	Set of 2 retaining clips for AU-12
987080	Universal holding clip mount (swivel) set of 2 pieces



€ 38.95




€ 3.95



€ 23.95






ET-02-12

·For LED strips up to 13.3 mm wide

Housing
 Aluminium




Article	Housing Color	Surface	Length	Price
975141	 Silver	Matt / Anodised	2000 mm	€ 35.95
975143	 Black	Matt / Anodised	2000 mm	€ 35.95
975148	 Silver	Matt / Anodised	3000 mm	€ 54.95
975145	 White	Matt / Powder-coated	2000 mm	€ 35.95



Cover | PMMA - Polymethyl methacrylate

	Clear	Matt	Milky	
				
1 m	983020	983022	983024	€ 7.95
2 m	983021	983023	983025	€ 17.95
3 m	983028	983027	983026	€ 25.95
				
1 m	983520	983522	983524	€ 7.95
2 m	983521	983523	983525	€ 17.95
3 m	983527		983526	€ 25.95
				
1 m		984022	984024	€ 7.95
2 m		984023	984025	€ 17.95
3 m			984026	€ 25.95
				
1 m		984522	984524	€ 7.95
2 m		984523	984525	€ 17.95
3 m			984526	€ 25.95

end caps set | 2 pieces | Plastic | € 4.95

White	Grey	Black
		
978140	978141	978142
		
978640	978641	978642
		
979070	979071	979072
		
	979571	979572

Accessories

930348	3M double-sided adhesive tape 50,000x15x0.20 mm
987006	Set of 2 retaining clips for AU-12
987080	Universal holding clip mount (swivel) set of 2 pieces



€ 38.95



€ 3.95



€ 23.95






ET-01-15

·For LED strips up to 16.3 mm wide

Housing Aluminium
Length 2000 mm




Article	Housing Color	Surface	Price
975063	Black	Matt / Anodised	€ 31.95
975065	White	Matt / Powder-coated	€ 31.95



Cover | PMMA - Polymethyl methacrylate

	Clear	Matt	Milky	
				
1 m	983030	983032	983034	€ 9.95
2 m	983031	983033	983035	€ 19.95
				
1 m	983530	983532	983534	€ 9.95
2 m	983531	983533	983535	€ 19.95
				
1 m		984032	984034	€ 9.95
2 m		984033	984035	€ 19.95
				
1 m		984532	984534	€ 9.95
2 m		984533	984535	€ 19.95

end caps set | 2 pieces | Plastic | € 4.95

White	Grey	Black
		
978110	978111	978112
		
978610	978611	978612
		
979130	979131	979132
		
979630	979631	979632

Accessories

930349	3M double-sided adhesive tape 50,000x20x0.20 mm
987008	Set of 2 retaining clips for AU-15
987080	Universal holding clip mount (swivel) set of 2 pieces



€ 48.95



€ 3.95



€ 23.95






ET-02-15

·For LED strips up to 16.3 mm wide

Housing
 Aluminium




Article	Housing Color	Surface	Length	Price
975161	 Silver	Matt / Anodised	2000 mm	€ 35.95
975163	 Black	Matt / Anodised	2000 mm	€ 35.95
975168	 Silver	Matt / Anodised	3000 mm	€ 54.95
975165	 White	Matt / Powder-coated	2000 mm	€ 35.95



Cover | PMMA - Polymethyl methacrylate

	Clear	Matt	Milky	
				
1 m	983030	983032	983034	€ 9.95
2 m	983031	983033	983035	€ 19.95
3 m	983038	983037	983036	€ 28.95
				
1 m	983530	983532	983534	€ 9.95
2 m	983531	983533	983535	€ 19.95
3 m		983539	983536	€ 28.95
				
1 m		984032	984034	€ 9.95
2 m		984033	984035	€ 19.95
3 m			984036	€ 28.95
				
1 m		984532	984534	€ 9.95
2 m		984533	984535	€ 19.95

end caps set | 2 pieces | Plastic | € 4.95

White	Grey	Black
		
978150	978151	978152
		
978650	978651	978652
		
979150	979151	979152
		
979650	979651	979652

Accessories

930349	3M double-sided adhesive tape 50,000x20x0.20 mm
987008	Set of 2 retaining clips for AU-15
987080	Universal holding clip mount (swivel) set of 2 pieces



€ 48.95



€ 3.95



€ 23.95





With the kind support of BEST Bellemann Elektro Service Team GmbH, Rauenberg-Malschenberg



H- AND GROOVE-PROFILES

Groove and H-profiles are offered with a comprehensive range of mounting accessories and are hard to beat in terms of versatility. The range of accessories includes cable suspensions, tension springs, sliding blocks and much more.




AU-03-12

For LED strips up to 13.3 mm wide

Housing	Aluminium
Surface	Matt, Anodised
Length	2000 mm

Article	Housing Color	Price
970231	 Silver	€ 37.95



Cover | PMMA - Polymethyl methacrylate

	Clear	Matt	Milky	
				
1 m	983020	983022	983024	€ 7.95
2 m	983021	983023	983025	€ 17.95
3 m	983028	983027	983026	€ 25.95
				
1 m	983520	983522	983524	€ 7.95
2 m	983521	983523	983525	€ 17.95
3 m	983527		983526	€ 25.95
				
1 m		984022	984024	€ 7.95
2 m		984023	984025	€ 17.95
3 m			984026	€ 25.95
				
1 m		984522	984524	€ 7.95
2 m		984523	984525	€ 17.95
3 m			984526	€ 25.95

end caps set | 2 pieces | Plastic | € 4.95

Grey



978291



978711



979221



979721

Accessories

987020 Universal sliding block/longitudinal connector, set of 2 pieces



€ 7.95

987060 Cable suspension (swivel), set of 2 pieces



€ 35.95






ET-04-12

For LED strips up to 13.3 mm wide

Housing	Aluminium
Surface	Matt, Anodised
Length	2000 mm

Article	Housing Color	Price
975231	 Silver	€ 39.95



Cover | PMMA - Polymethyl methacrylate

	Clear	Matt	Milky	
				
1 m	983020	983022	983024	€ 7.95
2 m	983021	983023	983025	€ 34.95
3 m	983028	983027	983026	€ 25.95
				
1 m	983520	983522	983524	€ 7.95
2 m	983521	983523	983525	€ 17.95
3 m	983527		983526	€ 25.95
				
1 m		984022	984024	€ 7.95
2 m		984023	984025	€ 17.95
3 m			984026	€ 25.95
				
1 m		984522	984524	€ 7.95
2 m		984523	984525	€ 17.95
3 m			984526	€ 25.95

end caps set | 2 pieces | Plastic

Grey	Silver	
		
	978301	€ 4.95
	988021	€ 21.95
		
	978721	€ 4.95
		
	979231	€ 4.95
		
	979731	€ 4.95

Accessories

987020 Universal sliding block/longitudinal connector, set of 2 pieces

€ 7.95

987040 Sliding block with tensioning springs, set of 2 pieces

€ 7.95






AU-10-12

For LED strips up to 13 mm wide

Housing
Aluminium

Article	Housing Color	Surface	Length	Price
970280	 Silver	Matt / Anodised	2000 mm	€ 35.95
970281	 Silver	Matt / Anodised	3000 mm	€ 54.95
970284	 White	Matt / Powder-coated	2000 mm	€ 35.95
970285	 White	Matt / Powder-coated	3000 mm	€ 54.95



Cover | Polycarbonate

Clear Milky Black




2 m	983096	983090	983093	€ 23.95
3 m	983097	983091	983094	€ 35.95
20 m	983098	983092		€ 199.95

end caps set | Aluminium | € 19.95

Silver



980021



Accessories

980023 Mounting clip, set (2 pieces)

987025 Sliding block/longitudinal connector

987026 Sliding block/corner connector 120°

987027 Sliding block/corner connector 90°



€ 4.95

€ 9.95

€ 9.95

€ 9.95

Accessories for **970280, 970281**

980020 end caps set aluminium 2 pieces

19,95 €

980021 end caps set aluminium 2 pieces

19,95 €

980020



980021





With the kind support of Albtherme Waldbronn / Ziegler Technics buero@ziegler-technics.de

**STEP-, SOCKET-, ANGLE-, CORNER-PROFILES**

The perfect light is not always planned from the very start. With the mounting and corner profiles, you can also integrate linear light at a later stage.




AL-01-10

For LED strips up to 11.3 mm wide

Housing Aluminium
Surface Matt, Anodised

Article	Housing Color	Length	Price
970503	Silver	2000 mm	€ 59.95
970502	Silver	3000 mm	€ 94.95



Cover | PMMA - Polymethyl methacrylate

Cover | accessible polycarbonate*

Clear Matt Milky



1 m	983010	983012	983014	€ 7.95
1 m			983080*	€ 11.50
2 m	983011	983013	983015	€ 17.95
2 m			983081*	€ 21.95
3 m	983016	983017	983018	€ 25.95
3 m			983082*	€ 32.95
4 m	983060	983061	983062	€ 33.95

end caps set | 2 pieces (left/right) | Plastic | € 4.95

Grey



978191

Accessories

930105 Assembly adhesive 310 ml



€ 35.95







AL-02-10

For LED strips up to 11.3 mm wide

Housing Aluminium
Surface Matt, Anodised

Article	Housing Color	Length	Price
970520	 Silver	1000 mm	€ 30.95
970523	 Silver	2000 mm	€ 59.95
970522	 Silver	3000 mm	€ 94.95



Cover | PMMA - Polymethyl methacrylate


Clear Matt Milky



1 m	983010	983012	983014	€ 7.95
2 m	983011	983013	983015	€ 17.95
3 m	983016	983017	983018	€ 25.95
4 m	983060	983061	983062	€ 33.95

end caps set | 2 pieces (left/right) | Plastic | € 4.95

Grey



978201

Accessories

930105 Assembly adhesive 310 ml



€ 35.95






AV-01-20

For LED strips up to 22 mm wide

Housing Aluminium
Surface Matt, Anodised
Length 2000 mm


Article	Housing Color	Price
970460	Silver	€ 35.95



Cover | PMMA - Polymethyl methacrylate

Clear

Milky

			
1 m	983040	983044	€ 11.50
2 m	983041	983045	€ 21.95
3 m		983046	€ 32.95
			
1 m		984044	€ 11.50
2 m		984045	€ 21.95
			
1 m		984544	€ 11.50
2 m		984545	€ 21.95

Accessories

930105	Assembly adhesive 310 ml		€ 35.95
---------------	--------------------------	---	----------------







AV-02-20

For LED strips up to 22 mm wide




Housing	Aluminium
Surface	Matt, Anodised
Length	2000 mm

Article	Housing Color	Price
970470	Silver	€ 35.95



Cover | PMMA - Polymethyl methacrylate

	Clear	Matt	Milky
			
1 m	983040	983044	€ 11.50
2 m	983041	983045	€ 21.95
3 m		983046	€ 32.95
			
3 m		983539	€ 28.95
			
1 m		984044	€ 11.50
2 m		984045	€ 21.95
			
1 m		984544	€ 11.50
2 m		984545	€ 21.95



Accessories

930105 Assembly adhesive 310 ml



€ 35.95






AM-01-10

·For LED strips up to 11.3 mm wide

Housing Aluminium

Article	Housing Color	Surface	Length	Price
970301	 Silver	Matt / Anodised	2000 mm	€ 37.95
970303	 Black	Matt / Anodised	2000 mm	€ 37.95
970308	 Silver	Matt / Anodised	3000 mm	€ 59.95
970305	 White	Matt / Powder-coated	2000 mm	€ 37.95



Cover | PMMA - Polymethyl methacrylate

Clear Matt Milky




1 m	983010	983012	983014	€ 7.95
2 m	983011	983013	983015	€ 17.95
3 m	983016	983017	983018	€ 25.95
4 m	983060	983061	983062	€ 33.95



1 m	983510	983512	983514	€ 7.95
2 m	983511	983513	983515	€ 17.95
3 m	983516	983517	983518	€ 25.95
4 m	983560	983561	983562	€ 33.95

end caps set | 2 pieces | Plastic | € 4.95

White Grey Black



978700	978701	978702
---------------	---------------	---------------

Accessories

930105 Assembly adhesive 310 ml



€ 35.95







AM-02-10

For LED strips up to 11.3 mm wide

Housing Aluminium
Surface Matt, Anodised

Article	Housing Color	Length	Price
970602	Silver	2000 mm	€ 82.95
970600	Silver	3000 mm	€ 124.95
970601	Black	3000 mm	€ 124.95



Cover | PMMA - Polymethyl methacrylate

	Clear	Matt	Milky	
				
1 m	983010	983012	983014	€ 7.95
2 m	983011	983013	983015	€ 17.95
3 m	983016	983017	983018	€ 25.95
4 m	983060	983061	983062	€ 33.95

				
1 m	983510	983512	983514	€ 7.95
2 m	983511	983513	983515	€ 17.95
3 m	983516	983517	983518	€ 25.95
4 m	983560	983561	983562	€ 33.95

				
1 m		984012	984014	€ 7.95
2 m		984013	984015	€ 17.95
3 m		984017	984018	€ 25.95
4 m		984010	984011	€ 33.95

end caps set | 2 pieces (left/right) | Plastic

Grey	Black	
		
978241	978242	€ 4.95





AV-01-10

·For LED strips up to 11.3 mm wide

Housing Aluminium

Article	Housing Color	Surface	Length	Price
970401	 Silver	Matt / Anodised	2000 mm	€ 35.95
970404	 Silver	Matt / Anodised	3000 mm	€ 54.95
970403	 White	Matt / Powder-coated	2000 mm	€ 35.95




Photo: Daniel Wieser . Architectural photography, Karlsruhe

Cover | PMMA - Polymethyl methacrylate

Clear Matt Milky



1 m	983010	983012	983014	€ 7.95
2 m	983011	983013	983015	€ 17.95
3 m	983016	983017	983018	€ 25.95
4 m	983060	983061	983062	€ 33.95



1 m	983510	983512	983514	€ 7.95
2 m	983511	983513	983515	€ 17.95
3 m	983516	983517	983518	€ 25.95
4 m	983560	983561	983562	€ 33.95



1 m		984012	984014	€ 7.95
2 m		984013	984015	€ 17.95
3 m		984017	984018	€ 25.95
4 m		984010	984011	€ 33.95








1 m		984512	984514	€ 7.95
2 m		984513	984515	€ 17.95
3 m		984517	984518	€ 25.95
4 m		984510	984511	€ 33.95



1 m	985010			€ 7.95
2 m	985011			€ 17.95
3 m	985016			€ 25.95

end caps set | 2 pieces | Plastic | € 4.95

White Grey

**978170** **978171**

Accessories

930105 Assembly adhesive 310 ml**930348** 3M double-sided adhesive tape 50,000x15x0.20 mm

€ 35.95

€ 38.95

**Lighting design**

Interested in our lighting design service?

Your contact person will be happy to answer any questions you may have.




EV-04-12

For LED strips up to 13.3 mm wide

Housing Aluminium
Surface Matt, Anodised

Article	Housing Color	Length	Price
975411	 Silver	2000 mm	€ 39.95
975412	 Silver	3000 mm	€ 61.95



Cover | PMMA - Polymethyl methacrylate





	Clear	Matt	Milky	
				
1 m	983020	983022	983024	€ 7.95
2 m	983021	983023	983025	€ 17.95
3 m	983028	983027	983026	€ 25.95

				
1 m	983520	983522	983524	€ 7.95
2 m	983521	983523	983525	€ 17.95
3 m	983527		983526	€ 25.95

				
1 m		984022	984024	€ 7.95
2 m		984023	984025	€ 17.95
3 m			984026	€ 25.95

				
1 m		984522	984524	€ 7.95
2 m		984523	984525	€ 17.95
3 m			984526	€ 25.95

end caps set | Plastic | € 4.95



Accessories

930105	Assembly adhesive 310 ml
987006	Set of 2 retaining clips for AU-12
987080	Universal holding clip mount (swivel) set of 2 pieces



€ 35.95
€ 3.95
€ 23.95





AV-05-12

For LED strips up to 12 mm wide

Housing Aluminium
Surface Matt, Anodised

Article	Housing Color	Length	Price
970550	Silver	2000 mm	€ 39.95
970551	Silver	3000 mm	€ 59.95



Cover | Polycarbonate

Milky



2 m 983100 € 23.95
3 m 983101 € 35.95




2 m 984570 € 23.95
3 m 984571 € 35.95



2 m 985570 € 23.95
3 m 985571 € 35.95

end caps set | 2 pieces
1x installation material | Aluminium | € 34.95

Silver



978370



979760



980550





AV-05-15

For LED strips up to 15 mm wide

Housing Aluminium
Surface Matt, Anodised

Article	Housing Color	Length	Price
970560	 Silver	2000 mm	€ 49.95
970561	 Silver	3000 mm	€ 79.95



Cover | Polycarbonate

Milky



2 m	983110	€ 30.95
3 m	983111	€ 44.95




2 m	984580	€ 30.95
3 m	984581	€ 44.95




2 m	985580	€ 30.95
3 m	985581	€ 44.95

end caps set | 2 pieces
1x installation material | Aluminium

Silver



978380	€ 34.95
---------------	----------------



979770	€ 34.95
---------------	----------------



980560	€ 34.95
---------------	----------------






AV-05-25

·For LED strips up to 25 mm wide or two 12 mm wide

Housing Aluminium
Surface Matt, Anodised



Article	Housing Color	Length	Price
970570	 Silver	2000 mm	€ 69.95
970571	 Silver	3000 mm	€ 99.95



Cover | Polycarbonate

	Milky		
			
2 m	983120	€ 35.95	
3 m	983121	€ 54.95	
			
2 m	984590	€ 35.95	
3 m	984591	€ 54.95	
			
2 m	985590	€ 35.95	
3 m	985591	€ 54.95	

end caps set | 2 pieces
1x installation material | Aluminium
Silver

	
978390	€ 34.95
	
979780	€ 34.95
	
980570	€ 34.95





With the kind support of BEST Bellemann Elektro Service Team GmbH, Rauenberg-Malschenberg



DRY CONSTRUCTION PROFILES

Our dry construction profiles offer you full creative freedom. Redefine linear light – whether as a primary light or for accent lighting.



EL-02-12

· For LED strips up to 14 mm wide

Housing
 Aluminium

Article	Housing Color	Surface	Length	Price
975491	Silver	Matt / Anodised	2000 mm	€ 82.95
975496	Silver	Matt / Anodised	3000 mm	€ 124.95
975495	White	Matt / Powder-coated	2000 mm	€ 82.95



Cover | PMMA - Polymethyl methacrylate

end caps set | 2 pieces (left/right)
1x installation material | Plastic

	Clear	Matt	Milky	
				
1 m	983020	983022	983024	€ 7.95
2 m	983021	983023	983025	€ 17.95
3 m	983028	983027	983026	€ 25.95

White	Grey	
		
978250	978251	€ 4.95
	978252	€ 34.95

Accessories

930105	Assembly adhesive 310 ml		€ 35.95
930346	3M double-sided adhesive tape 50,000x10x0.2 mm		€ 29.95
987020	Universal sliding block/longitudinal connector, set of 2 pieces		€ 7.95
987040	Sliding block with tensioning springs, set of 2 pieces		€ 7.95






ET-03-10

· For LED strips up to 12 mm wide

Housing Aluminium


Article	Housing Color	Surface	Length	Price
975471	 Silver	Matt / Anodised	2500 mm	€ 59.95
975476	 Silver	Matt / Anodised	3000 mm	€ 75.95
975475	 White	Matt / Powder-coated	2500 mm	€ 59.95





Cover | PMMA - Polymethyl methacrylate

	Clear	Matt	Milky	
				
1 m	983010	983012	983014	€ 7.95
2 m	983011	983013	983015	€ 17.95
3 m	983016	983017	983018	€ 25.95
4 m	983060	983061	983062	€ 33.95
				
1 m		984012	984014	€ 7.95
2 m		984013	984015	€ 17.95
3 m		984017	984018	€ 25.95
4 m		984010	984011	€ 33.95
				
1 m		984512	984514	€ 7.95
2 m		984513	984515	€ 17.95
3 m		984517	984518	€ 25.95
4 m		984510	984511	€ 33.95

end caps set | 2 pieces | Plastic | € 4.95

White	Grey
	
978260	978261

	
979200	979201

	
979700	979701

Accessories

930105	Assembly adhesive 310 ml		€ 35.95
970762	Support profile, LED support T-01-10		€ 7.95
987020	Universal sliding block/longitudinal connector, set of 2 pieces		€ 7.95
987040	Sliding block with tensioning springs, set of 2 pieces		€ 7.95






EL-03-10

· For LED strips up to 12 mm wide

Housing Aluminium

Article	Housing Color	Surface	Length	Price
975483	 Silver	Matt / Anodised	2000 mm	€ 59.95
975486	 Silver	Matt / Anodised	3000 mm	€ 94.95
975485	 White	Matt / Powder-coated	2500 mm	€ 79.95



Cover | PMMA - Polymethyl methacrylate

	Clear	Matt	Milky	
				
1 m	983010	983012	983014	€ 7.95
2 m	983011	983013	983015	€ 17.95
3 m	983016	983017	983018	€ 25.95
4 m	983060	983061	983062	€ 33.95
				
1 m		984012	984014	€ 7.95
2 m		984013	984015	€ 17.95
3 m		984017	984018	€ 25.95
4 m		984010	984011	€ 33.95
				
1 m		984512	984514	€ 7.95
2 m		984513	984515	€ 17.95
3 m		984517	984518	€ 25.95
4 m		984510	984511	€ 33.95

end caps set | 2 pieces (left/right) | Plastic | € 4.95

White	Grey
	
978270	978271
	
979210	979211
	
979710	979711


Accessories for 975483, 975485, 975486

970762 Support profile, LED support T-01-10



€ 7.95






EL-04-12

- for LED strips up to 14 mm wide
- for plasterboard 12.5 mm thick

Housing	Aluminium
Surface	Natural
Length	3000 mm

Article	Housing Color	Price
975530	Silver	€ 99.95



Cover | Polycarbonate

Milky



2 m	983090	€ 23.95
3 m	983091	€ 35.95



Photo: Daniel Vieser. Architectural photography, Karlsruhe





EU-01-36

· For LED strips up to 36 mm wide

Housing	Aluminium
Surface	Natural
Length	3000 mm

Article	Housing Color	Price
975501	Silver	€ 124.95



Cover | PMMA - Polymethyl methacrylate


Milky



3 m	985601	€ 42.95
-----	--------	---------

end caps set | 2 pieces
1x installation material | Aluminium | € 21.95

Grey



978175	€ 21.95
--------	---------

Accessories

985605	Dummy cover
--------	-------------



€ 30.95






EU-02-36

· For LED strips up to 36 mm wide

Housing	Aluminium
Surface	Matt, Anodised
Length	3000 mm

Article	Housing Color	Price
975525	Silver	€ 129.95



Cover | PMMA - Polymethyl methacrylate
 Milky



3 m	985601	€ 42.95
-----	---------------	----------------

Accessories

985605	Dummy cover
---------------	-------------



€ 30.95

**Lighting design**

Interested in our lighting design service?

Your contact person will be happy to answer any questions you may have.




EU-10-12

· For LED strips up to 12 mm wide

Housing	Aluminium
Surface	Matt, Anodised
Length	3000 mm

Article	Housing Color	Price
975511	 Silver	€ 59.95



Cover | Polycarbonate

Milky



2 m	983090	€ 23.95
3 m	983091	€ 35.95







EV-11-12

· For LED strips up to 12 mm wide

Housing	Aluminium
Surface	Matt, Anodised
Length	3000 mm

Article	Housing Color	Price
975516	 Silver	€ 69.95



Cover | Polycarbonate
 Milky



2 m	983090	€ 23.95
3 m	983091	€ 35.95






EV-12-12

· For LED strips up to 12 mm wide

Housing	Aluminium
Surface	Matt, Anodised
Length	3000 mm

Article	Housing Color	Price
975521	 Silver	€ 59.95



Cover
| Polycarbonate
Milky



2 m	983090	€ 23.95
3 m	983091	€ 35.95





With the kind support of BEST Bellemann Elektro Service Team GmbH, Rauenberg-Malschenberg



TILE PROFILES

Tile profiles play to every corner and closing area. Do away with conventional tile end profiles and set a new standard with linear light.



EL-01-08

- for LED strips up to 9.3 mm wide
- for tile thickness up to max. 9 mm


Housing

Aluminium

Surface

Matt, Anodised


Article	Housing Color	Length	Price
975331	Silver	2500 mm	€ 53.95
975334	Silver	3000 mm	€ 64.95



Cover
| PMMA - Polymethyl methacrylate

	Clear	Matt	Milky	
1 m	983000	983002	983004	€ 7.95
2 m	983001	983003	983005	€ 17.95
3 m	983006	983007	983008	€ 25.95

end caps set
| 2 pieces | Plastic | € 4.95








EL-03-12

- for LED strips up to 13.3 mm wide
- for tile thickness up to max. 12 mm

Housing
Aluminium

Article	Housing Color	Surface	Length	Price
975360	 Silver	Matt / Anodised	1250 mm	€ 28.95
975361	 Silver	Matt / Anodised	2500 mm	€ 59.95
975365	 White	Matt / Powder-coated	2500 mm	€ 59.95



Cover | PMMA - Polymethyl methacrylate

	Clear	Matt	Milky	
				
1 m	983020	983022	983024	€ 7.95
2 m	983021	983023	983025	€ 17.95
3 m	983028	983027	983026	€ 25.95
				
1 m		984022	984024	€ 7.95
2 m		984023	984025	€ 17.95
3 m			984026	€ 25.95






EA-03-12

· For LED strips up to 12 mm wide


Housing
 Aluminium

Article	Housing Color	Surface	Length	Price
975390	 Silver	Matt / Anodised	2000 mm	€ 38.95
975391	 Silver	Matt / Anodised	3000 mm	€ 59.95
975394	 White	Matt / Powder-coated	2000 mm	€ 38.95
975395	 White	Matt / Powder-coated	3000 mm	€ 59.95



Cover | PMMA - Polymethyl methacrylate

	Clear	Matt	Milky	
				
1 m	983000	983002	983004	€ 7.95
2 m	983001	983003	983005	€ 17.95
3 m	983006	983007	983008	€ 25.95
				
1 m		984002	984004	€ 7.95
2 m		984003	984005	€ 17.95





EV-01-08

- for LED strips up to 9.3 mm wide
- for tile thickness up to max. 9 mm


Housing

Aluminium

Surface

Matt, Anodised

Article	Housing Color	Length	Price
975341	Silver	2500 mm	€ 79.95
975344	Silver	3000 mm	€ 99.95



Cover | PMMA - Polymethyl methacrylate

	Clear	Matt	Milky	
				
1 m	983000	983002	983004	€ 7.95
2 m	983001	983003	983005	€ 17.95
3 m	983006	983007	983008	€ 25.95
				
1 m		985504		€ 30.95
2 m		985505		€ 17.95
3 m		985508		€ 25.95

end caps set | 2 pieces | Plastic | € 4.95








EV-01-12

- for LED strips up to 13.3 mm wide
- for a tile thickness of up to max. 12 mm

Housing	Aluminium
Length	2500 mm

Article	Housing Color	Surface	Price
975371	 Silver	Matt / Anodised	€ 99.95
975375	 White	Matt / Powder-coated	€ 99.95



Cover | PMMA - Polymethyl methacrylate

	Clear	Matt	Milky	
				
1 m	983020	983022	983024	€ 7.95
2 m	983021	983023	983025	€ 17.95
3 m	983028	983027	983026	€ 25.95





EV-02-08

- for LED strips up to 9.3 mm wide
- for a tile thickness of up to 9 mm


Housing

Aluminium

Surface

Matt, Anodised

Article	Housing Color	Length	Price
975351	Silver	2500 mm	€ 79.95
975353	Silver	3000 mm	€ 99.95



Cover | PMMA - Polymethyl methacrylate

	Clear	Matt	Milky	
				
1 m	983000	983002	983004	€ 7.95
2 m	983001	983003	983005	€ 17.95
3 m	983006	983007	983008	€ 25.95
				
1 m		985504		€ 30.95
2 m		985505		€ 17.95
3 m		985508		€ 25.95

end caps set | 2 pieces | Plastic | € 4.95



978231



980511






EV-02-12

- for LED strips up to 13.3 mm wide
- for a tile thickness of up to max. 12 mm

Housing Aluminium
Length 2500 mm

Article	Housing Color	Surface	Price
975381	 Silver	Matt / Anodised	€ 99.95
975385	 White	Matt / Powder-coated	€ 99.95



Cover | PMMA - Polymethyl methacrylate
Clear Matt Milky

					
1 m	983020	983022	983024	€ 7.95	
2 m	983021	983023	983025	€ 17.95	
3 m	983028	983027	983026	€ 25.95	






With the kind support of BEST Bellemann Elektro Service Team GmbH, Rauenberg-Malschenberg



PROFILES FOR OUTDOOR USE

Outdoor areas have different requirements than indoor areas. Our IP profiles are walkable and passable and inspire as a highlight in any outdoor design.



AU-04-12

·For LED strips up to 12.3 mm wide

Housing Aluminium
 Surface Matt, Anodised

Article	Housing Color	Length	Price
970723	 Silver	2000 mm	€ 23.95
970724	 Silver	3000 mm	€ 35.95




Onlineshop
 You can find more information about the products in the onlineshop:
 Detailed images, videos, project reports, LDT files, EPREL data sheets and more.

Cover | PMMA - Polymethyl methacrylate
Milky



2 m	988025	€ 19.95
3 m	988028	€ 28.95

end caps set | 2 pieces (left/right) | Plastic | € 4.95
Grey



981001


Accessories

930104 Natural stone sealant 310 ml



€ 39.95





ET-05-12

·For LED strips up to 12.3 mm wide

Housing	Aluminium
Surface	Matt, Anodised
Length	3000 mm

Article	Housing Color	Price
975724	 Silver	€ 35.95





Photo: Daniel Wieser . Architectural photography, Karlsruhe

Cover | PMMA - Polymethyl methacrylate
Milky



2 m	988025	€ 19.95
3 m	988028	€ 28.95

end caps set | 2 pieces (left/right) | Plastic | € 4.95
Grey



981011	€ 4.95
---------------	---------------

Accessories

930104 Natural stone sealant 310 ml



€ 39.95

Photo: Daniel Vieser - Architectural photography, Karlsruhe






AU-05-15

· For LED strips up to 15.6 mm wide

Housing	Aluminium
Surface	Natural
Length	2000 mm

Article	Housing Color	Price
970741	 Silver	€ 42.95



Cover | PMMA - Polymethyl methacrylate
Milky



1 m	988084	€ 11.50
2 m	988085	€ 21.95

end caps set | 2 pieces (left/right) | Plastic | € 4.95
Grey



981031	€ 4.95
---------------	---------------

Accessories

930104 Natural stone sealant 310 ml



€ 39.95

970764 Support profile, LED support T-01-15



€ 7.95






ET-05-15

·For LED strips up to 15.6 mm wide

Housing	Aluminium
Surface	Matt, Anodised
Length	2000 mm

Article	Housing Color	Price
975741	 Silver	€ 42.95




With the kind support of LED-TEC, Grlan/Italien | Foto: fotoeichhorn

Cover | PMMA - Polymethyl methacrylate
Milky



1 m	988084	€ 11.50
2 m	988085	€ 21.95

end caps set | 2 pieces (left/right) | Plastic | € 4.95
Grey



981041	€ 4.95
---------------	---------------

Accessories

930104 Natural stone sealant 310 ml



€ 39.95

970764 Support profile, LED support T-01-15



€ 7.95

With the kind support of LED-TEC, Grlan/Italien | Foto: fotoeichhorn







EU-01-12

·For LED strips up to 12 mm wide

Housing	Aluminium
Surface	Matt, Anodised
Length	2000 mm

Article	Housing Color	Price
975781	 Silver	€ 79.95



Cover | PMMA - Polymethyl methacrylate
Milky



1 m	988054	€ 11.50
2 m	988055	€ 21.95

end caps set | 2 pieces (left/right) | Plastic | € 4.95

Grey



981021	€ 4.95
---------------	---------------

Accessories

930104 Natural stone sealant 310 ml

970762 Support profile, LED support T-01-10

990109 Foam underlay



€ 39.95



€ 7.95



€ 7.95






LED STRIPES

- 786 COB
- 800 12V
- 802 24V
- 840 48V
- 854 230V
- 856 Mounting material for LED strips



led stripes



page 786
COB LED stripes



page 800
12V LED stripes



page 802
24V LED stripes



page 826
24V D FLEX SIDE VIEW



page 832
24V D FLEX TOP VIEW



page 838
24V OMNIFLEX



page 840
48V LED stripes



page 854
230V LED stripes



page 856
Material assembly
for LED stripes




COB STRIPES

These LED strips are ideal if the focus is on a homogeneous light pattern.



COB 24V-10W SAUNA IP67



- UV-resistant
- durably temperature-resistant [-10°C to 105°C]
- Lifetime 75,000h L70B50 / 50,000h L80B10
- 2 m model ideal for home saunas with 2 m internal dimensions
- extra long supply line, Incl. mounting material

(c) Segment Length	50 mm	(l1) Length End Cap	10 mm
(a) Light Beam Angle	180 Degree	(l2) Primary Cable Length	1.8 m
(r1) Bending Radius min.	50 mm	Rated Input 1m	10 W
(h1) Height	5.5 mm	Rated Input Voltage	24 V/DC
(h2) Height End Cap	6.5 mm	CRI (Ra)	90
(h3) Height Hose	5.5 mm	Control	Dimmable via optional controller
(b1) Width	12 mm	Working Temperature	-10 to 105 °C
(b2) Width end cap	14.2 mm	Channels	1
(b3) Width Hose	12 mm		

Article	Colour Temperature	(l3) Secondary Cable Length	Luminous Efficiency 1m	Luminous Flux 1m	Length	Price
840409	2700 K		85 lm/W	850 lm	2000 mm	€ 99.95
840411	2700 K	1.8 m	85 lm/W	850 lm	5000 mm	€ 224.95
840410	3000 K		90 lm/W	900 lm	2000 mm	€ 99.95
840412	3000 K	1.8 m	90 lm/W	900 lm	5000 mm	€ 224.95




Accessories

- 930737 Supply cable for 24 V COB Sauna stripe
- 930738 Connector for 24 V COB Sauna stripe
- 930736 Silicone end cap set of 2 pieces for 24 V COB Sauna stripe
- 930740 Plastic profile 1 m for 24 V COB Sauna stripe
- 930741 Plastic profile 2 m for 24 V COB Sauna stripe
- 930739 Silicone clamps for 24 V COB Sauna stripe
- 930850 Silicone adhesive 10 ml



- € 12.95
- € 17.95
- € 0.95
- € 4.95
- € 9.95
- € 1.95
- € 4.95

COB 24V-15W SAUNA IP67



- for saunas and steam baths
- available as RGB or RGBW [2,700K] variant
- UV-resistant
- durably temperature-resistant [-10°C to 105°C]
- 2 m model ideal for home saunas with 2 m internal dimensions
- extra long supply line
- lifetime 75,000h L70B50 / 50,000 L80B10
- incl. mounting material

(r1) Bending Radius min.	50 mm	(l1) Length End Cap	10 mm
(h1) Height	5 mm	(l2) Primary Cable Length	1.8 m
(h2) Height End Cap	6.5 mm	Rated Input 1m	15 W
(h3) Height Hose	5 mm	Rated Input Voltage	24 V/DC
(b1) Width	14 mm	Control	Dimmable via optional controller
(b2) Width end cap	16.2 mm	Working Temperature	-10 to 105 °C
(b3) Width Hose	14 mm		

Article	Colour Temp.	(c) Segment Length	(l3) Length	Lum. Efficiency 1m	Luminous Flux 1m	Length	Price
840413		50 mm		30 lm/W	450 lm	2000 mm	€ 139.95
840415		50 mm	1.8 m	30 lm/W	450 lm	5000 mm	€ 314.95
840414	2700 K	83.3 mm		40 lm/W	600 lm	2000 mm	€ 149.95
840416	2700 K	83.3 mm	1.8 m	40 lm/W	600 lm	5000 mm	€ 334.95



Accessories

- 930797** Silicone end cap set of 2 pieces for 24 V COB RGB/RGBW Sauna stripe
- 930803** Plastic profile 1 m for 24 V COB RGB/RGBW Sauna stripe
- 930804** Plastic profile 2 m for 24 V COB RGB/RGBW Sauna stripe
- 930802** Silicone clamps for 24 V COB RGB/RGBW Sauna stripe
- 930850** Silicone adhesive 10 ml



- € 0.95
- € 5.95
- € 11.95
- € 1.95
- € 4.95

Accessories for **840413, 840415**

- 930798** Supply cable for 24 V COB RGB Sauna stripe
- 930799** Connector for 24 V COB RGB Sauna stripe



- € 12.95
- € 17.95

Accessories for **840414, 840416**


- 930800** Supply cable for 24 V COB RGBW Sauna stripe
- 930801** Connector for 24 V COB RGBW Sauna stripe



- € 12.95
- € 17.95



COB 48V-15W FACADE LONG RUN IP67



- for weather-exposed building facades
- for outdoor areas with direct sunlight
- UV-resistant
- permanently temperature-resistant (-40°C to 95°C)
- long service life with 75,000h L70B50 / 50,000h L80B10
- solder-free accessories
- 3M VHB 5604A adhesive tape with silicone primer pre-treatment

(c) Segment Length	100 mm	Rated Input 1m	15 W
(a) Light Beam Angle	120 Degree	Rated Input Voltage	48 V/DC
(r1) Bending Radius min.	50 mm	Control	Dimmable via optional controller
(l1) Length End Cap	10 mm	Working Temperature	-40 to 95 °C
(l2) Primary Cable Length	1 m		
(l3) Secondary Cable Length	1 m		

Article	Colour Temperature	(b2) Width	(h2) Height	Luminous Flux 1m	Length	EEI	Price
840428	RGB	15,5 mm	5.5 mm	380 lm	15000 mm		€ 899.95
840429	RGB	15,5 mm	5.5 mm	380 lm	5000 mm		€ 324.95
840426	WW CW 2700-6500 K	14,2 mm	6.5 mm	610 lm	15000 mm		€ 674.95
840427	WW CW 2700-6500 K	14,2 mm	6.5 mm	610 lm	5000 mm		€ 249.95
840420	WW 2700 K	14,2 mm	6.5 mm	1575 lm	15000 mm		€ 499.95
840423	WW 2700 K	14,2 mm	6.5 mm	1800 lm	5000 mm		€ 179.95
840421	WW 3000 K	14,2 mm	6.5 mm	1650 lm	15000 mm		€ 499.95
840424	WW 3000 K	14,2 mm	6.5 mm	1650 lm	5000 mm		€ 179.95
840422	NW 4000 K	14,2 mm	6.5 mm	1800 lm	15000 mm		€ 499.95
840425	NW 4000 K	14,2 mm	6.5 mm	1800 lm	5000 mm		€ 179.95



Accessories

930850	Silicone adhesive 10 ml		€ 4.95
843279	MULTI-LED dimmer 1-4 channels, DMX/auto/manual, 12-48 V, 20 A, flicker-free		€ 114.95

Accessories for **840420, 840421, 840422**

862276	BASIC, DIM, CV, LCP240AD-1H48 V		€ 219.95
---------------	---------------------------------	---	----------

Accessories for **840420, 840421, 840422, 840423, 840424, 840425**

930737	Supply cable for 24 V COB Sauna stripe		€ 12.95
930738	Connector for 24 V COB Sauna stripe		€ 17.95

Accessories for **840420, 840421, 840422, 840423, 840424, 840425, 840426, 840427**

930736	Silicone end cap set of 2 pieces for 24 V COB Sauna stripe		€ 0.95
930739	Silicone clamps for 24 V COB Sauna stripe		€ 1.95
930740	Plastic profile 1 m for 24 V COB Sauna stripe		€ 4.95
930741	Plastic profile 2 m for 24 V COB Sauna stripe		€ 9.95
843341	DALI 2 PWM dimmer CV 2CH 12-48V, 8A/CH, DT6		€ 84.95
843501	RF-smart, starter set LED single/CCT, 12-48 V, 20 A incl. remote control		€ 99.95

Accessories for **840420, 840421, 840422, 840426, 840428**

862272	LONG-FLAT, CV, LT-240-48		€ 159.95
862281	Long-Flat, DIM, CV, 48 V 50-150 W		€ 159.95
872125	CV, HLG-600H-48 A		€ 489.95
872126	DIM, CV, HLG-600H-48B		€ 499.95
872145	IP, CV, V6-320-48		€ 219.95

Accessories for **840423, 840424, 840425**

862273	BASIC, DIM, CV, LCP75AD-1H48 V		€ 129.95
862275	BASIC, DIM, CV, LCP150AD-1H48 V		€ 169.95
872115	CV, PWM-200-48 KN		€ 244.95

Accessories for **840423, 840424, 840425, 840427, 840429**

862269	Long-Flat, DIM, CV, 48 V 50-150 W		€ 129.95
862270	LONG-FLAT, CV, LT-100-48		€ 96.95
862271	LONG-FLAT, CV, LT-150-48		€ 129.95
862274	BASIC, DIM, CV, 48 V 34-100 W		€ 144.95
862283	Long-Flat, DIM, CV, 48 V 50-150 W		€ 99.95
872142	LED power supply, IP, DIM, CV, 48 V, 33-100 W		€ 169.95
872143	LED power supply, IP, DIM, CV, 48 V, 66-200 W		€ 206.95


Accessories for **840426, 840427**

930865	End cap for Facade Long Run series		€ 8.95
930866	Connecting cable for Facade Long Run series		€ 12.95
843342	DALI 2 PWM dimmer CV 2CH 12-48V, 8A/CH, DT8		€ 84.95

Accessories for **840428, 840429**

930797	Silicone end cap set of 2 pieces for 24 V COB RGB/RGBW Sauna stripe		€ 0.95
930798	Supply cable for 24 V COB RGB Sauna stripe		€ 12.95
930799	Connector for 24 V COB RGB Sauna stripe		€ 17.95
930802	Silicone clamps for 24 V COB RGB/RGBW Sauna stripe		€ 1.95
930803	Plastic profile 1 m for 24 V COB RGB/RGBW Sauna stripe		€ 5.95
930804	Plastic profile 2 m for 24 V COB RGB/RGBW Sauna stripe		€ 11.95
843343	DALI 2 PWM dimmer CV 4CH 12-48V, 4A/CH, DT6		€ 94.95
843502	RF-smart, starter set RGB/W/CCT, 12-48 V, 20 A incl. remote, IP20		€ 99.95


COB 48V-18,5W FACADE LONG RUN IP67



- for weather-exposed building facades
- for outdoor areas with direct sunlight
- UV-resistant
- permanently temperature-resistant (-40°C to 95°C)
- long service life with 75,000h L70B50 / 50,000h L80B10
- solder-free accessories
- 3M VHB 5604A adhesive tape with silicone primer pre-treatment

(c) Segment Length	100 mm	(l2) Primary Cable Length	1 m
(a) Light Beam Angle	120 Degree	(l3) Secondary Cable Length	1 m
(r1) Bending Radius min.	50 mm	Rated Input 1m	18.5 W
(h1) Height	5,0 mm	Rated Input Voltage	48 V/DC
(h2) Height End Cap	5.5 mm	CRI (Ra)	90
(h3) Height Hose	5.5 mm	Control	Dimmable via optional controller
(b1) Width	12 mm	Working Temperature	-40 to 95 °C
(b2) Width end cap	14 mm	Channels	4
(b3) Width Hose	14 mm		
(l1) Length End Cap	10 mm		

Article	Colour Temperature	Luminous Efficiency 1m	Luminous Flux 1m	Length	Price
840432	3000 K	64 lm/W	890 lm	5000 mm	€ 379.95
840430	3000 K	64 lm/W	890 lm	15000 mm	€ 999.95
840433	4000 K	45 lm/W	1010 lm	5000 mm	€ 379.95
840431	4000 K	45 lm/W	1010 lm	15000 mm	€ 999.95



Accessories

930800	Supply cable for 24 V COB RGBW Sauna stripe		€ 12.95
930801	Connector for 24 V COB RGBW Sauna stripe		€ 17.95
930797	Silicone end cap set of 2 pieces for 24 V COB RGB/RGBW Sauna stripe		€ 0.95
930803	Plastic profile 1 m for 24 V COB RGB/RGBW Sauna stripe		€ 5.95
930804	Plastic profile 2 m for 24 V COB RGB/RGBW Sauna stripe		€ 11.95
930802	Silicone clamps for 24 V COB RGB/RGBW Sauna stripe		€ 1.95
930850	Silicone adhesive 10 ml		€ 4.95
843502	RF-smart, starter set RGB/W/CCT, 12-48 V, 20 A incl. remote, IP20		€ 99.95
843343	DALI 2 PWM dimmer CV 4CH 12-48V, 4A/CH, DT6		€ 94.95
843344	DALI 2 PWM dimmer CV 4CH 12-48V, 4A/CH, DT8		€ 94.95
843279	MULTI-LED dimmer 1-4 channels, DMX/auto/manual, 12-48 V, 20 A, flicker-free		€ 114.95

Accessories for **840430, 840431**


862272	LONG-FLAT, CV, LT-240-48		€ 159.95
862281	Long-Flat, DIM, CV, 48 V 50-150 W		€ 159.95
872125	CV, HLG-600H-48 A		€ 489.95
872126	DIM, CV, HLG-600H-48B		€ 499.95
872145	IP, CV, V6-320-48		€ 219.95

Accessories for **840432, 840433**

862269	Long-Flat, DIM, CV, 48 V 50-150 W		€ 129.95
862270	LONG-FLAT, CV, LT-100-48		€ 96.95
862271	LONG-FLAT, CV, LT-150-48		€ 129.95
862274	BASIC, DIM, CV, 48 V 34-100 W		€ 144.95
862283	Long-Flat, DIM, CV, 48 V 50-150 W		€ 99.95
872142	LED power supply, IP, DIM, CV, 48 V, 33-100 W		€ 169.95
872143	LED power supply, IP, DIM, CV, 48 V, 66-200 W		€ 206.95




COB 24V-10W SHORT CUT IP20



•high-performance adhesive tape 3M 300MP

(p) LED Distance	1.74 mm	Luminous Flux 1m	960 lm
(c) Segment Length	50 mm	Length	5000 mm
(a) Light Beam Angle	120 Degree	Rated Input 1m	10.5 W
(r1) Bending Radius min.	50 mm	Rated Input Voltage	24 V/DC
(h1) Height	2 mm	CRI (Ra)	90
(b1) Width	10 mm	Control	Dimmable via optional controller
(I2) Primary Cable Length	1 m	Working Temperature	-10 to 60 °C
(I3) Secondary Cable Length	1 m	Channels	2
Colour Temperature	2700-6500 K		
Luminous Efficiency 1m	91.43 lm/W		


Article	Colour Temperature	Price
840374	WW CW 2700-6500 K	€ 299.95



Lighting design
 Interested in our lighting design service?
 Your contact person will be happy to answer any questions you may have.




COB 24V-12W STANDARD IP20



•high-performance adhesive 3M VHB5604A


(p) LED Distance	2.08 mm	Length	5000 mm
(c) Segment Length	50 mm	Rated Input Voltage	24 V/DC
(a) Light Beam Angle	120 Degree	CRI (Ra)	90
(r1) Bending Radius min.	50 mm	Control	Dimmable via optional controller
(h1) Height	2 mm	Working Temperature	-15 to 50 °C
(b1) Width	10 mm	Channels	1
(l2) Primary Cable Length	1 m		
(l3) Secondary Cable Length	1 m		

Article	Colour Temperature	Luminous Efficiency 1m	Luminous Flux 1m	Rated Input 1m	Price
840296	WW 3000 K	89.6 lm/W	1120 lm	12.5 W	€ 159.95
840304	NW 4000 K	94.17 lm/W	1130 lm	12.0 W	€ 159.95



Aluminium profiles
 In the »Aluminum profiles« section you will find the right profile for every application with various covers and installation options.

COB 24V-16W STANDARD IP20



·high-performance adhesive tape 3M 300MP


(p) LED Distance	1.19 mm	Luminous Flux 1m	660 lm
(c) Segment Length	50 mm	Length	5000 mm
(a) Light Beam Angle	120 Degree	Rated Input 1m	16.5 W
(r1) Bending Radius min.	50 mm	Rated Input Voltage	24 V/DC
(h1) Height	2.2 mm	Control	Dimmable via optional controller
(b1) Width	10 mm	Working Temperature	-10 to 60 °C
(I2) Primary Cable Length	1 m	Channels	3
(I3) Secondary Cable Length	1 m		
Luminous Efficiency 1m	40 lm/W		

Article	Price
840375 	€ 399.95



Power supply units
You can find the right power supply unit in various designs and with the required voltage and power in the »Power supply units« section.


COB 24V-15W PERFORMANCE IP20



· Adhesive tape 3M 200MP [Art. 840323] / 3M 300MP [Art. 840324]

(p) LED Distance	2.08 mm	Luminous Flux 1m	1600 lm
(c) Segment Length	50 mm	Length	5000 mm
(a) Light Beam Angle	180 Degree	Rated Input Voltage	24 V/DC
(r1) Bending Radius min.	50 mm	CRI (Ra)	90
(h1) Height	2 mm	Control	Dimmable via optional controller
(b1) Width	10 mm	Working Temperature	-15 to 50 °C
(l2) Primary Cable Length	1 m	Channels	1
(l3) Secondary Cable Length	1 m		
Luminous Efficiency 1m	106.66 lm/W		



Article	Colour Temperature	Rated Input 1m	Price
840323	WW 3000 K	16.0 W	€ 179.95
840324	NW 4000 K	15.0 W	€ 179.95



Aluminium profiles

In the »Aluminum profiles« section you will find the right profile for every application with various covers and installation options.

COB 24V-15W PERFORMANCE IP67



- Including mounting material
- adhesive tape 3M 200MP [Art. 840321] / 3M 300MP [Art. 840322]

(p) LED Distance	2.08 mm	(l3) Secondary Cable Length	1 m
(c) Segment Length	50 mm	Luminous Efficiency 1m	100 lm/W
(a) Light Beam Angle	180 Degree	Luminous Flux 1m	1500 lm
(r1) Bending Radius min.	50 mm	Length	5000 mm
(h1) Height	2 mm	Rated Input 1m	15 W
(h2) Height End Cap	6 mm	Rated Input Voltage	24 V/DC
(h3) Height Hose	5 mm	CRI (Ra)	90
(b1) Width	10 mm	Control	Dimmable via optional controller
(b2) Width end cap	15 mm	Type of IP Protection	Silicone
(b3) Width Hose	14 mm	Working Temperature	-15 to 50 °C
(l1) Length End Cap	10 mm	Channels	1
(l2) Primary Cable Length	1 m		

Article	Colour Temperature	Price
840321	WW 3000 K	€ 199.95
840322	NW 4000 K	€ 199.95




Power supply units
You can find the right power supply unit in various designs and with the required voltage and power in the »Power supply units« section.

12V LED STRIPES

These LED strips are ideally suited for all standard applications and special assemblies with the most diverse requirements. With voltages of 12V, different protection classes, lumens, number of LEDs, power and much more, you too can find the right LED strip for your application.




SMD 12V-7W SHORT CUT IP20



• high-performance adhesive 3M 9448A

(p) LED Distance	8.33 mm	Length	5000 mm
(c) Segment Length	25 mm	Rated Input Voltage	12 V/DC
(a) Light Beam Angle	120 Degree	CRI (Ra)	90
(r1) Bending Radius min.	20 mm	Control	Dimmable via optional controller
(h1) Height	3 mm	Working Temperature	-15 to 50 °C
(b1) Width	8 mm	Channels	1
(l2) Primary Cable Length	1 m		
(l3) Secondary Cable Length	1 m		

Article	Colour Temperature	Luminous Efficiency 1m	Luminous Flux 1m	Rated Input 1m	EEL	Price
840164	2700 K	81.43 lm/W	570 lm	7.0 W		€ 89.95
840165	3000 K	85.38 lm/W	555 lm	6.5 W		€ 89.95
840166	4000 K	95.71 lm/W	670 lm	7.0 W		€ 89.95
840167	6500 K	90 lm/W	630 lm	7.0 W		€ 89.95

**Onlineshop**


You can find more information about the products in the onlineshop:
Detailed images, videos, project reports, LDT files, EPREL data sheets and more.

24V LED STRIPES

These LED strips are ideal for all standard applications and special assemblies with a wide range of requirements. With voltages of 24V, different protection classes, lumens, number of LEDs, power and much more, you too will find the right LED strip for your application.




SMD 24V-20W POWER IP20



· high-performance adhesive 3M 9448A


(p) LED Distance	8.33 mm	Luminous Flux 1m	1600 lm
(c) Segment Length	50 mm	Length	5000 mm
(a) Light Beam Angle	120 Degree	Rated Input 1m	21 W
(r1) Bending Radius min.	20 mm	Rated Input Voltage	24 V/DC
(h1) Height	2 mm	CRI (Ra)	95
(b1) Width	10 mm	Control	Dimmable via optional controller
(l2) Primary Cable Length	1 m	Working Temperature	-15 to 50 °C
(l3) Secondary Cable Length	1 m	Channels	1
Colour Temperature	3000 K		
Luminous Efficiency 1m	76.2 lm/W		

Article Price

840122  € 194.95**Aluminium profiles**

In the »Aluminum profiles« section you will find the right profile for every application with various covers and installation options.

SMD 24V-10W LONG RUN IP20



•high-performance adhesive 3M 9448A

(p) LED Distance	8.33 mm	Luminous Flux 1m	705 lm
(c) Segment Length	50 mm	Length	10000 mm
(a) Light Beam Angle	120 Degree	Rated Input 1m	9.5 W
(r1) Bending Radius min.	20 mm	Rated Input Voltage	24 V/DC
(h1) Height	2 mm	CRI (Ra)	90
(b1) Width	10 mm	Control	Dimmable via optional controller
(l2) Primary Cable Length	1 m	Working Temperature	-15 to 50 °C
(l3) Secondary Cable Length	1 m	Channels	1
Colour Temperature	3000 K		
Luminous Efficiency 1m	74.21 lm/W		

Article	Price
840291 	€ 399.95

CV



1 CH

IP20



A
t
G


G



Aluminium profiles
In the »Aluminum profiles« section you will find the right profile for every application with various covers and installation options.




SMD 24V-10W SLIM IP20



·high-performance adhesive 3M 9448A


(p) LED Distance	8.33 mm	Length	5000 mm
(c) Segment Length	50 mm	Rated Input 1m	9.6 W
(a) Light Beam Angle	120 Degree	Rated Input Voltage	24 V/DC
(r1) Bending Radius min.	20 mm	CRI (Ra)	90
(h1) Height	3 mm	Control	Dimmable via optional controller
(b1) Width	5 mm	Working Temperature	-15 to 50 °C
(l2) Primary Cable Length	1 m	Channels	1
(l3) Secondary Cable Length	1 m		

Article	Colour Temperature	Luminous Efficiency 1m	Luminous Flux 1m	Price
840158	WW 2700 K	80 lm/W	770 lm	€ 79.95
840159	WW 3000 K	85 lm/W	820 lm	€ 79.95



Aluminium profiles
 In the »Aluminum profiles« section you will find the right profile for every application with various covers and installation options.


SMD 24V-11W SLIM IP20



· high-performance adhesive 3M 9448A



(p) LED Distance	3.8 mm	Length	5000 mm
(c) Segment Length	26.3 mm	Rated Input Voltage	24 V/DC
(a) Light Beam Angle	120 Degree	CRI (Ra)	90
(r1) Bending Radius min.	20 mm	Control	Dimmable via optional controller
(h1) Height	2 mm	Working Temperature	-15 to 50 °C
(b1) Width	4 mm	Channels	1
(l2) Primary Cable Length	1 m		
(l3) Secondary Cable Length	1 m		

Article	Colour Temperature	Luminous Efficiency 1m	Luminous Flux 1m	Rated Input 1m	Price
840175	2700 K	90.45 lm/W	995 lm	11.0 W	€ 169.95
840210	3000 K	99.09 lm/W	1090 lm	11.0 W	€ 169.95
840267	4000 K	95.65 lm/W	1100 lm	11.5 W	€ 169.95

**Power supply units**

You can find the right power supply unit in various designs and with the required voltage and power in the »Power supply units« section.

SMD 24 V-11 W CCT SLIM IP20



•high-performance adhesive tape 3M 200MP

(p) LED Distance	10.2 mm	Luminous Flux 1m	1025 lm
(c) Segment Length	71.4 mm	Length	5000 mm
(a) Light Beam Angle	120 Degree	Rated Input 1m	11 W
(r1) Bending Radius min.	50 mm	Rated Input Voltage	24 V/DC
(h1) Height	1.2 mm	CRI (Ra)	90
(b1) Width	5 mm	Control	Dimmable via optional controller
(l2) Primary Cable Length	1 m	Working Temperature	-10 to 60 °C
(l3) Secondary Cable Length	1 m	Channels	2
Colour Temperature	3000-6500 K		
Luminous Efficiency 1m	93.18 lm/W		

Article	Colour Temperature	Price
840350	WW CW 3000-6500 K	€ 124.95

CV

2 CH

IP20


A
↑
G

E



Aluminium profiles
 In the »Aluminum profiles« section you will find the right profile for every application with various covers and installation options.

SMD 24V-12W SLIM IP65



•Including mounting material

•high-performance adhesive tape 3M 200MP


(p) LED Distance	5.1 mm	Colour Temperature	3000-6500 K
(c) Segment Length	71.4 mm	Luminous Efficiency 1m	85.6 lm/W
(a) Light Beam Angle	120 Degree	Luminous Flux 1m	1070 lm
(r1) Bending Radius min.	50 mm	Length	5000 mm
(h1) Height	5.3 mm	Rated Input 1m	12.5 W
(h2) Height End Cap	5.3 mm	Rated Input Voltage	24 V/DC
(h3) Height Hose	3.7 mm	CRI (Ra)	90
(b1) Width	5 mm	Control	Dimmable via optional controller
(b2) Width end cap	10 mm	Type of IP Protection	Silicone hose
(b3) Width Hose	7.4 mm	Working Temperature	-10 to 60 °C
(l1) Length End Cap	10.2 mm	Channels	2
(l2) Primary Cable Length	1 m		
(l3) Secondary Cable Length	1 m		

Article Colour Temperature

Price

840349 3000-6500 K


€ 149.95



Power supply units

You can find the right power supply unit in various designs and with the required voltage and power in the »Power supply units« section.

SMD 24V-11W STANDARD IP20



·high-performance adhesive 3M 9448A

(p) LED Distance	8.33 mm	Luminous Flux 1m	500 lm
(c) Segment Length	50 mm	Length	5000 mm
(a) Light Beam Angle	110 Degree	Rated Input 1m	11 W
(r1) Bending Radius min.	20 mm	Rated Input Voltage	24 V/DC
(h1) Height	2 mm	CRI (Ra)	60
(b1) Width	5 mm	Control	Dimmable via optional controller
(l2) Primary Cable Length	1 m	Working Temperature	-15 to 50 °C
(l3) Secondary Cable Length	1 m	Channels	3
Luminous Efficiency 1m	45.45 lm/W		

Article	Price
840276 	€ 109.95

CV



3 CH

IP20






Aluminium profiles

In the »Aluminum profiles« section you will find the right profile for every application with various covers and installation options.

SMD 24V-11W STANDARD IP67




·Including mounting material

·high-performance adhesive 3M 9448A

(p) LED Distance	5.5 mm	(l2) Primary Cable Length	1 m
(c) Segment Length	33.3 mm	(l3) Secondary Cable Length	1 m
(a) Light Beam Angle	120 Degree	Length	5000 mm
(r1) Bending Radius min.	50 mm	Rated Input Voltage	24 V/DC
(h1) Height	5.5 mm	CRI (Ra)	90
(h2) Height End Cap	6.5 mm	Control	Dimmable via optional controller
(h3) Height Hose	5.5 mm	Type of IP Protection	Silicone hose
(b1) Width	11.5 mm	Working Temperature	-15 to 50 °C
(b2) Width end cap	12.5 mm	Channels	1
(b3) Width Hose	11.5 mm		
(l1) Length End Cap	10 mm		


Article	Colour Temperature	Luminous Efficiency 1m	Luminous Flux 1m	Rated Input 1m	EEL	Price
840186	2700 K	78.26 lm/W	900 lm	11.5 W		€ 184.95
840187	3000 K	84.55 lm/W	930 lm	11.0 W		€ 184.95



Power supply units

You can find the right power supply unit in various designs and with the required voltage and power in the »Power supply units« section.

SMD 24V-13W STANDARD IP20



·high-performance adhesive 3M 9448A

(p) LED Distance	16.66 mm	Luminous Flux 1m	580 lm
(c) Segment Length	100 mm	Length	5000 mm
(a) Light Beam Angle	120 Degree	Rated Input 1m	13 W
(r1) Bending Radius min.	20 mm	Rated Input Voltage	24 V/DC
(h1) Height	3 mm	Control	Dimmable via optional controller
(b1) Width	10 mm	Working Temperature	-15 to 50 °C
(l2) Primary Cable Length	1 m	Channels	3
(l3) Secondary Cable Length	1 m		
Luminous Efficiency 1m	44.62 lm/W		

Article	Price
840254 	€ 134.95

CV



3 CH



IP20





Aluminium profiles
In the »Aluminum profiles« section you will find the right profile for every application with various covers and installation options.

SMD 24V-13W STANDARD IP67




- Including mounting material
- high-performance adhesive 3M 9448A

(p) LED Distance	16.66 mm	Luminous Flux 1m	670 lm
(c) Segment Length	100 mm	Length	5000 mm
(a) Light Beam Angle	120 Degree	Rated Input 1m	13.5 W
(r1) Bending Radius min.	50 mm	Rated Input Voltage	24 V/DC
(h1) Height	6 mm	Control	Dimmable via optional controller
(b1) Width	13 mm	Type of IP Protection	Silicone hose
(l2) Primary Cable Length	1 m	Working Temperature	-15 to 50 °C
(l3) Secondary Cable Length	1 m	Channels	3
Luminous Efficiency 1m	49.6 lm/W		

Article Price


840256  **€ 159.95**



Power supply units

You can find the right power supply unit in various designs and with the required voltage and power in the »Power supply units« section.

SMD 24V-14W STANDARD IP20



·high-performance adhesive 3M 9448A



(a) Light Beam Angle	120 Degree	Rated Input 1m	14 W
(r1) Bending Radius min.	20 mm	Rated Input Voltage	24 V/DC
(l2) Primary Cable Length	1 m	Control	Dimmable via optional controller
(l3) Secondary Cable Length	1 m		

Article	Colour Temp.	(p) Distance	(c) Length	(h1) Height	(b1) Width	Luminous Flux 1m	Length	EEL	Price
840147	RGB	10.4 mm	83.3 mm	2 mm	10 mm	665 lm	5000 mm		€ 169.95
840178	WW 2700 K	5.56 mm	33.4 mm	3 mm	8 mm	1110 lm	5000 mm		€ 124.95
840179	WW 3000 K	5.56 mm	33.4 mm	3 mm	8 mm	1100 lm	5000 mm		€ 124.95
930512	WW 3000 K	5.56 mm	33.4 mm	3 mm	8 mm	1100 lm	50000 mm		€ 1169.95
840180	NW 4000 K	5.56 mm	33.4 mm	3 mm	8 mm	1220 lm	5000 mm		€ 124.95



Aluminium profiles
In the »Aluminum profiles« section you will find the right profile for every application with various covers and installation options.

SMD 24V-15W STANDARD IP67



•Including mounting material

•high-performance adhesive 3M 9448A

(p) LED Distance	16.7 mm	Colour Temperature	3000 K
(c) Segment Length	100 mm	Luminous Efficiency 1m	49 lm/W
(a) Light Beam Angle	120 Degree	Luminous Flux 1m	740 lm
(r1) Bending Radius min.	50 mm	Length	5000 mm
(h1) Height	5.5 mm	Rated Input 1m	15 W
(h2) Height End Cap	6.5 mm	Rated Input Voltage	24 V/DC
(h3) Height Hose	5.5 mm	CRI (Ra)	80
(b1) Width	14.5 mm	Control	Dimmable via optional controller
(b2) Width end cap	15.5 mm	Type of IP Protection	Silicone hose
(b3) Width Hose	14.5 mm	Working Temperature	-15 to 50 °C
(l1) Length End Cap	10 mm	Channels	4
(l2) Primary Cable Length	1 m		
(l3) Secondary Cable Length	1 m		

Article Price


840239  € 174.95



Power supply units

You can find the right power supply unit in various designs and with the required voltage and power in the »Power supply units« section.

SMD 24 V-16 W RGBNW STANDARD IP20



·high-performance adhesive tape 3M 200MP

(p) LED Distance	16.66 mm	Luminous Flux 1m	775 lm
(c) Segment Length	166.66 mm	Length	5000 mm
(a) Light Beam Angle	120 Degree	Rated Input 1m	16.5 W
(r1) Bending Radius min.	50 mm	Rated Input Voltage	24 V/DC
(h1) Height	2 mm	CRI (Ra)	80
(b1) Width	10 mm	Control	Dimmable via optional controller
(l2) Primary Cable Length	1 m	Working Temperature	-10 to 60 °C
(l3) Secondary Cable Length	1 m	Channels	4
Colour Temperature	4000 K		
Luminous Efficiency 1m	46.97 lm/W		

Article	Price
840353  	€ 149.95

CV



4 CH

IP20




A
↑
G

G



Aluminium profiles
In the »Aluminum profiles« section you will find the right profile for every application with various covers and installation options.


SMD 24V-16W RGBWW STANDARD IP20



· high-performance adhesive 3M 9448A


(p) LED Distance	16.66 mm	Luminous Efficiency 1m	51.25 lm/W
(c) Segment Length	100 mm	Luminous Flux 1m	820 lm
(a) Light Beam Angle	120 Degree	Rated Input 1m	16 W
(r1) Bending Radius min.	50 mm	Rated Input Voltage	24 V/DC
(h1) Height	3 mm	CRI (Ra)	80
(b1) Width	10 mm	Control	Dimmable via optional controller
(l2) Primary Cable Length	1 m	Working Temperature	-15 to 50 °C
(l3) Secondary Cable Length	1 m	Channels	4
Colour Temperature	3000 K		

Article		Length	Price
840236	RGB WW	5000 mm	€ 144.95
930517	RGB WW	50000 mm	€ 1299.95

**Power supply units**

You can find the right power supply unit in various designs and with the required voltage and power in the »Power supply units« section.


SMD 24V-16W STANDARD IP44



•high-performance adhesive tape 3M 200MP


(p) LED Distance	16.66 mm	Length	5000 mm
(c) Segment Length	166.66 mm	Rated Input 1m	16 W
(a) Light Beam Angle	120 Degree	Rated Input Voltage	24 V/DC
(r1) Bending Radius min.	50 mm	CRI (Ra)	80
(b1) Width	10 mm	Control	Dimmable via optional controller
(l2) Primary Cable Length	1 m	Type of IP Protection	Silicone
(l3) Secondary Cable Length	1 m	Working Temperature	-10 to 60 °C
Colour Temperature	4000 K	Channels	4
Luminous Efficiency 1m	4781 lm/W		
Luminous Flux 1m	765 lm		

Article	Price
840373 RGB NW	€ 159.95



Aluminium profiles
 In the »Aluminum profiles« section you will find the right profile for every application with various covers and installation options.


SMD 24V-17W STANDARD IP20



(p) LED Distance	8.33 mm	Luminous Flux 1m	1765 lm
(c) Segment Length	50 mm	Length	5000 mm
(a) Light Beam Angle	120 Degree	Rated Input 1m	17.2 W
(r1) Bending Radius min.	50 mm	Rated Input Voltage	24 V/DC
(h1) Height	2 mm	CRI (Ra)	90
(b1) Width	10 mm	Control	Dimmable via optional controller
(l2) Primary Cable Length	1 m	Working Temperature	-10 to 40 °C
(l3) Secondary Cable Length	1 m	Channels	2
Colour Temperature	2700-6500 K		
Luminous Efficiency 1m	103 lm/W		


Article Colour Temperature

Price

840378 2700-6500 K**€ 199.95****Power supply units**

You can find the right power supply unit in various designs and with the required voltage and power in the »Power supply units« section.

SMD 24V-20W POWER IP20



•high-performance adhesive 3M 9448A


(a) Light Beam Angle	120 Degree	Rated Input 1m	20 W
(r1) Bending Radius min.	20 mm	Rated Input Voltage	24 V/DC
(h1) Height	2 mm	CRI (Ra)	90
(b1) Width	10 mm	Control	Dimmable via optional controller
(l2) Primary Cable Length	1 m	Working Temperature	-15 to 50 °C
(l3) Secondary Cable Length	1 m	Channels	1
Length	5000 mm		

Article	Colour Temperature	(p) LED Distance	(c) Segment Length	Luminous Efficiency 1m	Luminous Flux 1m	EEL	Price
840192	WW 2700 K	4.16 mm	25 mm	65.68 lm/W	1215 lm		€ 164.95
840193	WW 3000 K	4.16 mm	25 mm	84.47 lm/W	1605 lm		€ 164.95
840194	NW 4000 K	4.16 mm	25 mm	88.5 lm/W	1770 lm		€ 164.95
840124	CW 6000 K	8.33 mm	50 mm	86 lm/W	1720 lm		€ 194.95



Aluminium profiles
In the »Aluminum profiles« section you will find the right profile for every application with various covers and installation options.

SMD 24V-23W POWER IP20



· high-performance adhesive 3M 9448A


(p) LED Distance	6.25 mm	Length	5000 mm
(c) Segment Length	50 mm	Rated Input 1m	23 W
(a) Light Beam Angle	110 Degree	Rated Input Voltage	24 V/DC
(r1) Bending Radius min.	20 mm	CRI (Ra)	90
(h1) Height	2 mm	Control	Dimmable via optional controller
(b1) Width	10 mm	Working Temperature	-15 to 50 °C
(l2) Primary Cable Length	1 m	Channels	1
(l3) Secondary Cable Length	1 m		

Article	Colour Temperature	Luminous Efficiency 1m	Luminous Flux 1m	Price
840331	3000 K	130.9 lm/W	3010 lm	€ 249.95
840332	4000 K	136.1 lm/W	3130 lm	€ 249.95

**Power supply units**

You can find the right power supply unit in various designs and with the required voltage and power in the »Power supply units« section.


SMD 24V-23W POWER IP44



·high-performance adhesive 3M 9448A


(p) LED Distance	6.25 mm	Rated Input 1m	23 W
(c) Segment Length	50 mm	Rated Input Voltage	24 V/DC
(a) Light Beam Angle	110 Degree	CRI (Ra)	90
(r1) Bending Radius min.	20 mm	Control	Dimmable via optional controller
(h1) Height	3 mm	Type of IP Protection	Silicone
(b1) Width	10 mm	Working Temperature	-15 to 50 °C
(l2) Primary Cable Length	1 m	Channels	1
(l3) Secondary Cable Length	1 m		
Length	5000 mm		

Article	Colour Temperature	Luminous Efficiency 1m	Luminous Flux 1m	Price
840333	WW 3000 K	115.2 lm/W	2650 lm	€ 259.95
840334	NW 4000 K	120.9 lm/W	2780 lm	€ 259.95



Aluminium profiles
In the »Aluminum profiles« section you will find the right profile for every application with various covers and installation options.


SMD 24 V-22 W RGBW POWER IP20



• high-performance adhesive 3M 9448A


(p) LED Distance	10.4 mm	Length	5000 mm
(c) Segment Length	62.5 mm	Rated Input 1m	22 W
(a) Light Beam Angle	110 Degree	Rated Input Voltage	24 V/DC
(r1) Bending Radius min.	20 mm	CRI (Ra)	60
(h1) Height	2 mm	Control	Dimmable via optional controller
(b1) Width	12 mm	Working Temperature	-15 to 50 °C
(l2) Primary Cable Length	1 m	Channels	4
(l3) Secondary Cable Length	1 m		

Article	Colour Temperature	Luminous Efficiency 1m	Luminous Flux 1m	Price
840308	 3000 K	43.41 lm/W	955 lm	€ 179.95
840309	 4000 K	44.77 lm/W	985 lm	€ 179.95

**Power supply units**

You can find the right power supply unit in various designs and with the required voltage and power in the »Power supply units« section.

SMD 24V-28W POWER PLUS IP20



·high-performance adhesive tape 3M 200MP

(p) LED Distance	8.33 mm	Luminous Flux 1m	1055 lm
(c) Segment Length	50 mm	Length	5000 mm
(a) Light Beam Angle	120 Degree	Rated Input 1m	28 W
(r1) Bending Radius min.	50 mm	Rated Input Voltage	24 V/DC
(h1) Height	2 mm	CRI (Ra)	60
(b1) Width	12 mm	Control	Dimmable via optional controller
(l2) Primary Cable Length	1 m	Working Temperature	-10 to 60 °C
(l3) Secondary Cable Length	1 m	Channels	3
Luminous Efficiency 1m	37.68 lm/W		

Article	Price
840352 	€ 189.95

CV



3 CH



IP20





Aluminium profiles
In the »Aluminum profiles« section you will find the right profile for every application with various covers and installation options.

SMD 24V-28W POWER PLUS IP44




• high-performance adhesive tape 3M 200MP

(p) LED Distance	8.33 mm	Luminous Efficiency 1m	38 lm/W
(c) Segment Length	50 mm	Luminous Flux 1m	1045 lm
(a) Light Beam Angle	120 Degree	Length	5000 mm
(r1) Bending Radius min.	50 mm	Rated Input 1m	27.5 W
(h1) Height	2.6 mm	Rated Input Voltage	24 V/DC
(h2) Height End Cap	3 mm	CRI (Ra)	60
(b1) Width	12 mm	Control	Dimmable via optional controller
(b2) Width end cap	12.5 mm	Type of IP Protection	Silicone
(l1) Length End Cap	15 mm	Working Temperature	-10 to 60 °C
(l2) Primary Cable Length	1 m	Channels	3
(l3) Secondary Cable Length	1 m		

Article Price

840351  € 214.95



Power supply units



You can find the right power supply unit in various designs and with the required voltage and power in the »Power supply units« section.

SIDE VIEW

The LED strip is arranged / installed vertically, allowing the Flex-Stripe to be bent to the left and right.
[Note the minimum bending radius in each case.]




NEON 24V-10W D FLEX LINE MINI SIDE-VIEW IP44



•Including mounting material

(p) LED Distance	8.33 mm	Luminous Flux 1m	285 lm
(c) Segment Length	50 mm	Length	5000 mm
(a) Light Beam Angle	112 Degree	Rated Input 1m	10 W
(r1) Bending Radius min.	50 mm	Rated Input Voltage	24 V/DC
(h1) Height	12 mm	CRI (Ra)	90
(b1) Width	6.5 mm	Control	Dimmable via optional controller
(l2) Primary Cable Length	3 m	Type of IP Protection	Silicone
(l3) Secondary Cable Length	3 m	Working Temperature	-25 to 45 °C
Colour Temperature	3000 K	Channels	1
Luminous Efficiency 1m	30 lm/W		

Article Price

840376  € 359.95

Accessories

930443	Profile for D Flex Line
930444	Flex profile for D Flex Line
930530	Assembly kit for D Flex Line 6.5 x 12.0 mm
930593	Gel adhesive for bonding the end caps 3 g




€ 12.95


€ 21.95

€ 9.95

€ 5.95




NEON 24V-8W D FLEX LINE MINI SIDE-VIEW IP68



(p) LED Distance	8.33 mm	Colour Temperature	3000 K
(c) Segment Length	50 mm	Luminous Efficiency 1m	36.88 lm/W
(a) Light Beam Angle	112 Degree	Luminous Flux 1m	295 lm
(r1) Bending Radius min.	50 mm	Length	5000 mm
(h1) Height	12 mm	Rated Input 1m	8 W
(h2) Height End Cap	15 mm	Rated Input Voltage	24 V/DC
(h3) Height Hose	12 mm	CRI (Ra)	80
(b1) Width	5 mm	Control	Dimmable via optional controller
(b2) Width end cap	8 mm	Type of IP Protection	PVC cover
(b3) Width Hose	6 mm	Working Temperature	-25 to 45 °C
(l1) Length End Cap	12 mm	Channels	1
(l2) Primary Cable Length	3 m		
(l3) Secondary Cable Length	3 m		

Article Price

840283  **€ 559.95**



Accessories


930443	Profile for D Flex Line
930444	Flex profile for D Flex Line
930530	Assembly kit for D Flex Line 6.5 x 12.0 mm
930593	Gel adhesive for bonding the end caps 3 g



€ 12.95
€ 21.95
€ 9.95
€ 5.95




NEON 24V-10W D FLEX LINE SIDE-VIEW IP68



- Spot-free homogeneous illumination
- Very easy installation using adapted profiles
- UV- and salt water-resistant IP68
- Ultra-flexible and therefore very versatile
- Light-fast polyurethane encapsulation
- Including mounting material

(a) Light Beam Angle	125 Degree	Colour Temperature	3000 K
(r1) Bending Radius min.	150 mm	Length	5000 mm
(h1) Height	20 mm	Rated Input 1m	10.5 W
(h2) Height End Cap	22.5 mm	Rated Input Voltage	24 V/DC
(h3) Height Hose	20 mm	CRI (Ra)	80
(b2) Width end cap	13 mm	Control	Dimmable via optional controller
(b3) Width Hose	12 mm	Type of IP Protection	PVC cover
(l1) Length End Cap	11.5 mm	Working Temperature	-25 to 45 °C
(l2) Primary Cable Length	3 m		
(l3) Secondary Cable Length	3 m		

Article		(p) LED Distance	(c) Segment Length	Luminous Efficiency 1m	Luminous Flux 1m	Channels	Price
840287		6.94 mm	41,67 mm	35.05 lm/W	368 lm	1	€ 799.95
840290		11.91 mm	71,43 mm	20 lm/W	210 lm	4	€ 799.95



Accessories

- 930447** Profile for D Flex Line SIDE
- 930451** Flex profile for D Flex Line Side
- 930532** Assembly kit for D Flex Line 12.0 x 20.0 mm
- 930593** Gel adhesive for bonding the end caps 3 g




TOP VIEW

The LED strip is arranged / installed horizontally, allowing the Flex-Stripe to be bent upwards and downwards.
[Note the minimum bending radius in each case.]



NEON 24V-10W D FLEX LINE TOP-VIEW IP68




- Spot-free homogeneous illumination
- Very easy installation using adapted profiles
- UV- and salt water-resistant IP68
- Ultra-flexible and therefore very versatile
- Light-fast polyurethane encapsulation
- Including mounting material

(p) LED Distance	6.94 mm	Colour Temperature	3000 K
(c) Segment Length	41.67 mm	Luminous Efficiency 1m	49.05 lm/W
(a) Light Beam Angle	117 Degree	Luminous Flux 1m	515 lm
(r1) Bending Radius min.	150 mm	Length	5000 mm
(h1) Height	15 mm	Rated Input 1m	10.5 W
(h2) Height End Cap	18 mm	Rated Input Voltage	24 V/DC
(h3) Height Hose	15 mm	CRI (Ra)	80
(b1) Width	10 mm	Control	Dimmable via optional controller
(b2) Width end cap	18 mm	Type of IP Protection	PVC cover
(b3) Width Hose	16 mm	Working Temperature	-25 to 45 °C
(l1) Length End Cap	11.5 mm	Channels	1
(l2) Primary Cable Length	3 m		
(l3) Secondary Cable Length	3 m		

Article Price

840288 **WW** **€ 749.95**



Accessories

- 930448** Profile for D Flex Line TOP anodised aluminium
- 930449** Profile for D Flex Line TOP plastic
- 930533** Assembly kit for D Flex Line 16.0 x 15.0 mm
- 930593** Gel adhesive for bonding the end caps 3 g



€ 14.95


€ 11.95

€ 10.95

€ 5.95



NEON 24 V-10 W D FLEX LINE TOP-VIEW WIDE IP68




- Spot-free homogeneous illumination
- Very easy installation using adapted profiles
- UV- and salt water-resistant IP68
- Ultra-flexible and therefore very versatile
- Light-fast polyurethane encapsulation
- Including mounting material

(p) LED Distance	6.94 mm	Colour Temperature	3000 K
(c) Segment Length	41.67 mm	Luminous Efficiency 1m	69.52 lm/W
(a) Light Beam Angle	180 Degree	Luminous Flux 1m	730 lm
(r1) Bending Radius min.	150 mm	Length	5000 mm
(h1) Height	10 mm	Rated Input 1m	10.5 W
(h2) Height End Cap	12 mm	Rated Input Voltage	24 V/DC
(h3) Height Hose	10 mm	CRI (Ra)	80
(b1) Width	8 mm	Control	Dimmable via optional controller
(b2) Width end cap	12 mm	Type of IP Protection	PVC cover
(b3) Width Hose	10 mm	Working Temperature	-25 to 45 °C
(l1) Length End Cap	8 mm	Channels	1
(l2) Primary Cable Length	3 m		
(l3) Secondary Cable Length	3 m		

Article Price

840285  € 479.95



Accessories

- 930445** Profile for D Flex Line MINI plastic
- 930446** Profile for D Flex Line MINI anodised aluminium
- 930531** Assembly kit for D Flex Line 10.0 x 10.0 mm




€ 10.95

€ 14.95

€ 10.95

NEON 24 V-10 W RGB D FLEX LINE TOP-VIEW IP68



- Spot-free homogeneous illumination
- Very easy installation using adapted profile
- UV and salt water-resistant IP68
- Ultra-flexible and therefore very versatile
- Light-fast polyurethane encapsulation

(p) LED Distance	8.33 mm	(l3) Secondary Cable Length	3 m
(c) Segment Length	50 mm	Luminous Efficiency 1m	44712 lm/W
(a) Light Beam Angle	180 Degree	Luminous Flux 1m	315 lm
(r1) Bending Radius min.	150 mm	Length	5000 mm
(h1) Height	10 mm	Rated Input 1m	10 W
(h2) Height End Cap	12 mm	Rated Input Voltage	24 V/DC
(h3) Height Hose	10 mm	CRI (Ra)	80
(b1) Width	8 mm	Control	Dimmable via optional controller
(b2) Width end cap	12 mm	Type of IP Protection	PVC cover
(b3) Width Hose	10 mm	Working Temperature	-25 to 45 °C
(l1) Length End Cap	8 mm	Channels	3
(l2) Primary Cable Length	3 m		

Article	Price
840286 	€ 519.95





Accessories

930445	Profile for D Flex Line MINI plastic
930446	Profile for D Flex Line MINI anodised aluminium
930531	Assembly kit for D Flex Line 10.0 x 10.0 mm
930593	Gel adhesive for bonding the end caps 3 g



NEON 24 V-10 W RGBW D FLEX LINE TOP-VIEW IP68




- Spot-free homogeneous illumination
- Very easy installation using adapted profile
- UV and salt water-resistant IP68
- Ultra-flexible and therefore very versatile
- Light-fast polyurethane encapsulation

(p) LED Distance	11.9 mm	Colour Temperature	3000 K
(c) Segment Length	71.43 mm	Luminous Efficiency 1m	30.48 lm/W
(a) Light Beam Angle	117 Degree	Luminous Flux 1m	320 lm
(r1) Bending Radius min.	150 mm	Length	5000 mm
(h1) Height	15 mm	Rated Input 1m	10.5 W
(h2) Height End Cap	18 mm	Rated Input Voltage	24 V/DC
(h3) Height Hose	15 mm	CRI (Ra)	80
(b1) Width	12 mm	Control	Dimmable via optional controller
(b2) Width end cap	18 mm	Type of IP Protection	PVC cover
(b3) Width Hose	16 mm	Working Temperature	-25 to 45 °C
(l1) Length End Cap	11.5 mm	Channels	4
(l2) Primary Cable Length	3 m		
(l3) Secondary Cable Length	3 m		

Article Price

840289  € 779.95



Accessories

- 930448** Profile for D Flex Line TOP anodised aluminium
- 930449** Profile for D Flex Line TOP plastic
- 930533** Assembly kit for D Flex Line 16.0 x 15.0 mm
- 930593** Gel adhesive for bonding the end caps 3 g



€ 14.95


€ 11.95

€ 10.95



€ 5.95

NEON 24V-8W OMNIFLEX MINI IP67

The OMNIFLEX 24V 8W IP67 LED strip is available in three different light colors [2,700 K, 3,000 K, 4,000 K]. With a length of 5 meters, it enables flexible use in different areas. Uniform illumination is guaranteed thanks to the point-free light distribution. The very small bending radii in all directions allow a great deal of design freedom when creating shapes. Straight lines are also no problem. All variants are possible thanks to the extensive range of accessories. With a primary and secondary feed of 300 cm each, flexible installation is guaranteed. Thanks to its salt water and UV resistance and IP67 protection rating, the OMNIFLEX LED strip is also ideal for outdoor use.



NEON 24V-8W OMNIFLEX MINI IP67



- Spot-free light pattern for homogeneous illumination
- Neon effect
- Small bending radius in all directions provides a great deal of freedom
- Minimum bending radius to the front: 60 mm/to the side: 100 mm
- 300 cm long primary and secondary infeed
- UV- and salt water-resistant
- A comprehensive range of accessories enables you to customise your design
- Including mounting material

(p) LED Distance	6.25 mm	(l2) Primary Cable Length	3 m
(c) Segment Length	100 mm	(l3) Secondary Cable Length	3 m
(a) Light Beam Angle	120 Degree	Length	5000 mm
(r1) Bending Radius min.	100 mm	Rated Input 1m	8 W
(r2) Bending Radius Left / Right	60 mm	Rated Input Voltage	24 V/DC
(h1) Height	10 mm	CRI (Ra)	80
(h2) Height End Cap	10 mm	Control	Dimmable via optional controller
(h3) Height Hose	10 mm	Type of IP Protection	Silicone hose
(b1) Width	10 mm	Working Temperature	-10 to 55 °C
(b2) Width end cap	10 mm	Channels	1
(b3) Width Hose	10 mm		
(l1) Length End Cap	10 mm		

Article	Colour Temperature	Luminous Efficiency 1m	Luminous Flux 1m	EEL	Price
840417	WW 2700 K	90 lm/W	720 lm		€ 299.95
840418	WW 3000 K	93 lm/W	744 lm		€ 299.95
840419	NW 4000 K	100 lm/W	800 lm		€ 299.95



Accessories

- 930846** Assembly clamps set of 10 pieces for neon Omniflex Mini
- 930847** Aluminium profile 1 m for neon Omniflex Mini
- 930849** Flexible stainless steel profile 5 m for neon Omniflex Mini



€ 4.95
€ 9.95
€ 69.95

48V LED STRIPES

Our new LED stripes in 48V technology offer users numerous advantages. The key advantage: Compared to 12V and 24V stripes, 48V stripes allow longer running lengths. By comparison, conventional LED stripes with lower output voltage require a new feed after only 2.5 metres [single-sided feed] or 5 metres [feed from both sides], for continuous operation. LED stripes with 48V can be used up to a length of 25 metres [single-sided feed] or feed] or 50 metres [feed on both sides] - perfect for lighting coves, long corridors and simplified integration into existing installations, that only allow a single-sided feed.

Advantages of 48V LED stripes

- 48V = lower current
- 48V = longer running length
- 48V = thinner wire cross-sections
- 48V = faster installation
- 48V = more versatile applications
- 48V = lower brightness drop

In addition to the advantages mentioned above, our new 48V LED stripes have a very long service life of up to 75,000h for L70B50

and 50,000h for L80B10. Thanks to reel-to-reel production, the 48V LED stripes have no soldered joints. As we have set ourselves the goal to become climate-neutral, the LED stripes are packaged in an environmentally friendly paper-based packaging.


In addition to the new 48V LED stripes, we of course also offer accessories in the form of power supply units and controllers for the relevant control protocols [RF, DALI, KNX etc.] in order to cover all potential future applications for 48V stripes.





Photo: Daniel Vieser. Architectural photography, Karlsruhe

SMD 48V-10W LONG RUN CCT IP20




(p) LED Distance	4.46 mm	Luminous Efficiency 1m	120 lm/W
(c) Segment Length	125 mm	Luminous Flux 1m	1200 lm
(a) Light Beam Angle	120 Degree	Rated Input 1m	10 W
(r1) Bending Radius min.	50 mm	Rated Input Voltage	48 V/DC
(h1) Height	2.5 mm	CRI (Ra)	90
(b1) Width	10 mm	Control	Dimmable via optional controller
(l2) Primary Cable Length	1 m	Working Temperature	-10 to 55 °C
(l3) Secondary Cable Length	1 m	Channels	2
Colour Temperature	2700-6500 K		

Article		Length	Price
840438	WW CW	5000 mm	€ 194.95
840434	WW CW	15000 mm	€ 584.95
840436	WW CW	50000 mm	€ 1949.95




Power supply units
 You can find the right power supply unit in various designs and with the required voltage and power in the »Power supply units« section.

SMD 48V-10W LONG RUN CCT IP67




(p) LED Distance	4.46 mm	(l3) Secondary Cable Length	1 m
(c) Segment Length	125 mm	Colour Temperature	2700-6500 K
(a) Light Beam Angle	120 Degree	Luminous Efficiency 1m	110 lm/W
(r1) Bending Radius min.	50 mm	Luminous Flux 1m	1100 lm
(h1) Height	2.5 mm	Rated Input 1m	10 W
(h2) Height End Cap	6.5 mm	Rated Input Voltage	48 V/DC
(h3) Height Hose	5 mm	CRI (Ra)	90
(b1) Width	10 mm	Control	Dimmable via optional controller
(b2) Width end cap	14.2 mm	Type of IP Protection	Silicone hose
(b3) Width Hose	12 mm	Working Temperature	-10 to 55 °C
(l1) Length End Cap	10 mm	Channels	2
(l2) Primary Cable Length	1 m		

Article		Length	Price
840439	WW CW	5000 mm	€ 214.95
840435	WW CW	15000 mm	€ 644.95
840437	WW CW	50000 mm	€ 2149.95



SMD 48V-10W LONG RUN RGB+CCT IP20




(p) LED Distance	5.56 mm	Luminous Efficiency 1m	80 lm/W
(c) Segment Length	167 mm	Luminous Flux 1m	800 lm
(a) Light Beam Angle	120 Degree	Rated Input 1m	10 W
(r1) Bending Radius min.	50 mm	Rated Input Voltage	48 V/DC
(h1) Height	2.5 mm	CRI (Ra)	90
(b1) Width	12 mm	Control	Dimmable via optional controller
(l2) Primary Cable Length	1 m	Working Temperature	-10 to 55 °C
(l3) Secondary Cable Length	1 m	Channels	5
Colour Temperature	2700-6500 K		

Article		Length	Price
840452	RGB WW CW	5000 mm	€ 249.95
840448	RGB WW CW	15000 mm	€ 749.95
840450	RGB WW CW	50000 mm	€ 2499.95




Aluminium profiles
In the »Aluminum profiles« section you will find the right profile for every application with various covers and installation options.

SMD 48V-10W LONG RUN RGB+CCT IP67




(p) LED Distance	5.56 mm	(l3) Secondary Cable Length	1 m
(c) Segment Length	167 mm	Colour Temperature	2700-6500 K
(a) Light Beam Angle	120 Degree	Luminous Efficiency 1m	75 lm/W
(r1) Bending Radius min.	50 mm	Luminous Flux 1m	750 lm
(h1) Height	2.5 mm	Rated Input 1m	10 W
(h2) Height End Cap	6.5 mm	Rated Input Voltage	48 V/DC
(h3) Height Hose	6 mm	CRI (Ra)	90
(b1) Width	12 mm	Control	Dimmable via optional controller
(b2) Width end cap	16.5 mm	Type of IP Protection	Silicone hose
(b3) Width Hose	14.5 mm	Working Temperature	-10 to 55 °C
(l1) Length End Cap	10 mm	Channels	5
(l2) Primary Cable Length	1 m		

Article		Length	Price
840453		5000 mm	€ 274.95
840449		15000 mm	€ 824.95
840451		50000 mm	€ 2749.95



SMD 48V-10W LONG RUN RGB+W IP20




(p) LED Distance	8.9 mm	Rated Input 1m	10 W
(c) Segment Length	125 mm	Rated Input Voltage	48 V/DC
(a) Light Beam Angle	120 Degree	CRI (Ra)	90
(r1) Bending Radius min.	50 mm	Control	Dimmable via optional controller
(h1) Height	2.5 mm	Working Temperature	-10 to 55 °C
(b1) Width	12 mm	Channels	4
(l2) Primary Cable Length	1 m		
(l3) Secondary Cable Length	1 m		

Article	Colour Temperature	Luminous Efficiency 1m	Luminous Flux 1m	Length	EEL	Price
840458	RGB WW 3000 K	66 lm/W	660 lm	5000 mm		€ 249.95
840454	RGB WW 3000 K	66 lm/W	660 lm	15000 mm		€ 749.95
840456	RGB WW 3000 K	66 lm/W	660 lm	50000 mm		€ 2499.95
840464	RGB NW 4000 K	70 lm/W	700 lm	5000 mm		€ 249.95
840460	RGB NW 4000 K	70 lm/W	700 lm	15000 mm		€ 749.95
840462	RGB NW 4000 K	70 lm/W	700 lm	50000 mm		€ 2499.95




SMD 48V-10W LONG RUN RGB+W IP67




(c) Segment Length	125 mm	(l2) Primary Cable Length	1 m
(a) Light Beam Angle	120 Degree	(l3) Secondary Cable Length	1 m
(r1) Bending Radius min.	50 mm	Rated Input 1m	10 W
(h1) Height	2.5 mm	Rated Input Voltage	48 V/DC
(h2) Height End Cap	6.5 mm	CRI (Ra)	90
(h3) Height Hose	6 mm	Control	Dimmable via optional controller
(b1) Width	14.5 mm	Type of IP Protection	Silicone hose
(b2) Width end cap	16.5 mm	Working Temperature	-10 to 55 °C
(b3) Width Hose	14.5 mm	Channels	4
(l1) Length End Cap	10 mm		

Article	Colour Temperature	(p) LED Distance	Luminous Efficiency 1m	Luminous Flux 1m	Length	Price
840459	RGB WW 3000 K	8.9 mm	60 lm/W	600 lm	5000 mm	€ 274.95
840455	RGB WW 3000 K	8.9 mm	60 lm/W	600 lm	15000 mm	€ 824.95
840457	RGB WW 3000 K	8.9 mm	60 lm/W	600 lm	50000 mm	€ 2749.95
840463	RGB NW 4000 K	5.5 mm	65 lm/W	650 lm	50000 mm	€ 2749.95
840465	RGB NW 4000 K	8.9 mm	65 lm/W	650 lm	5000 mm	€ 274.95
840461	RGB NW 4000 K	8.9 mm	65 lm/W	650 lm	15000 mm	€ 824.95



SMD 48V-10W LONG RUN RGB IP20



(p) LED Distance	7.14 mm	Luminous Flux 1m	550 lm
(c) Segment Length	100 mm	Rated Input 1m	10 W
(a) Light Beam Angle	120 Degree	Rated Input Voltage	48 V/DC
(r1) Bending Radius min.	50 mm	CRI (Ra)	65
(h1) Height	2.5 mm	Control	Dimmable via optional controller
(b1) Width	10 mm	Working Temperature	-10 to 55 °C
(l2) Primary Cable Length	1 m	Channels	3
(l3) Secondary Cable Length	1 m		
Luminous Efficiency 1m	55 lm/W		



Article		Length	Price
840446		5000 mm	€ 134.95
840399		15000 mm	€ 399.95
840407		50000 mm	€ 1329.95

CV

3 CH


IP20

SMD 48V-10W LONG RUN RGB IP67




(p) LED Distance	7.14 mm	(l3) Secondary Cable Length	1 m
(a) Light Beam Angle	120 Degree	Luminous Efficiency 1m	51 lm/W
(r1) Bending Radius min.	50 mm	Luminous Flux 1m	510 lm
(h1) Height	2.5 mm	Rated Input 1m	10 W
(h2) Height End Cap	6.5 mm	Rated Input Voltage	48 V/DC
(h3) Height Hose	4.5 mm	CRI (Ra)	65
(b1) Width	10 mm	Control	Dimmable via optional controller
(b2) Width end cap	14.2 mm	Working Temperature	-10 to 55 °C
(b3) Width Hose	12 mm	Channels	3
(l1) Length End Cap	10 mm		
(l2) Primary Cable Length	1 m		

Article	(c) Segment Length	Length	Type of IP Protection	Price
840400	100 mm	15000 mm	Silicone hose	€ 459.95
840408	100 mm	50000 mm	Silicone hose	€ 1529.95
840447	125 mm	5000 mm		€ 149.95



SMD 48V-10W LONG RUN SINGLE IP20




(p) LED Distance	7.14 mm	Rated Input 1m	10 W
(c) Segment Length	100 mm	Rated Input Voltage	48 V/DC
(a) Light Beam Angle	120 Degree	CRI (Ra)	90
(r1) Bending Radius min.	50 mm	Control	Dimmable via optional controller
(h1) Height	2.5 mm	Working Temperature	-10 to 55 °C
(l2) Primary Cable Length	1 m	Channels	1
(l3) Secondary Cable Length	1 m		

Article	Colour Temperature	(b1) Width	Luminous Efficiency 1m	Luminous Flux 1m	Length	EEL	Price
840440	WW 2700 K	10 mm	121 lm/W	1210 lm	5000 mm		€ 109.95
840393	WW 2700 K	10 mm	121 lm/W	1210 lm	15000 mm		€ 339.95
840401	WW 2700 K	10 mm	121 lm/W	1210 lm	50000 mm		€ 1129.95
840394	WW 3000 K	10 mm	124 lm/W	1240 lm	15000 mm		€ 339.95
840402	WW 3000 K	10 mm	124 lm/W	1240 lm	50000 mm		€ 1129.95
840442	WW 3000 K	12 mm	124 lm/W	1240 lm	5000 mm		€ 109.95
840395	NW 4000 K	10 mm	130 lm/W	1300 lm	15000 mm		€ 339.95
840403	NW 4000 K	10 mm	130 lm/W	1300 lm	50000 mm		€ 1129.95
840444	NW 4000 K	12 mm	130 lm/W	1300 lm	5000 mm		€ 109.95




SMD 48V-10W LONG RUN SINGLE IP67




- Ideal for coved lighting and long run lengths
- Up to 50 m in single section with single-/double-sided infeed
- 3M 300 LSE [IP20] strong adhesive tape/3M VHB 5604A with primer pre-treatment [IP67]

(p) LED Distance	7.14 mm	(l3) Secondary Cable Length	1 m
(c) Segment Length	100 mm	Rated Input 1m	10 W
(a) Light Beam Angle	120 Degree	Rated Input Voltage	48 V/DC
(r1) Bending Radius min.	50 mm	CRI (Ra)	90
(h1) Height	2.5 mm	Control	Dimmable via optional controller
(h2) Height End Cap	6.5 mm	Type of IP Protection	Silicone hose
(h3) Height Hose	4.5 mm	Working Temperature	-10 to 55 °C
(b1) Width	10 mm	Channels	1
(l1) Length End Cap	10 mm		
(l2) Primary Cable Length	1 m		

Article	Colour Temp.	(b2) Width	(b3) Width Hose	Luminous Efficiency 1m	Luminous Flux 1m	Length	Price
840396 WW	2700 K	14.2 mm	12 mm	109 lm/W	1090 lm	15000 mm	€ 399.95
840404 WW	2700 K	14.2 mm	12 mm	109 lm/W	1090 lm	50000 mm	€ 1324.95
840441 WW	2700 K	14.5 mm	14.5 mm	109 lm/W	1090 lm	50000 mm	€ 129.95
840397 WW	3000 K	14.2 mm	12 mm	112 lm/W	1120 lm	15000 mm	€ 399.95
840405 WW	3000 K	14.2 mm	12 mm	112 lm/W	1120 lm	50000 mm	€ 1324.95
840443 WW	3000 K	14.5 mm	14.5 mm	112 lm/W	1120 lm	50000 mm	€ 129.95
840398 NW	4000 K	14.2 mm	12 mm	118 lm/W	1180 lm	15000 mm	€ 399.95
840406 NW	4000 K	14.2 mm	12 mm	118 lm/W	1180 lm	50000 mm	€ 1324.95
840445 NW	4000 K	14.5 mm	14.5 mm	118 lm/W	1180 lm	50000 mm	€ 129.95



SMD 48V-4W LONG RUN IP20



·high-performance adhesive tape 3M 200MP

(p) LED Distance	12.8 mm	(l2) Primary Cable Length	1 m
(c) Segment Length	166.66 mm	(l3) Secondary Cable Length	1 m
(a) Light Beam Angle	120 Degree	Rated Input 1m	4 W
(r1) Bending Radius min.	50 mm	Rated Input Voltage	48 V/DC
(h1) Height	1.3 mm	CRI (Ra)	80
(h2) Height End Cap	2.6 mm	Control	Dimmable via optional controller
(b1) Width	10 mm	Working Temperature	-15 to 50 °C
(b2) Width end cap	10.5 mm	Channels	1
(l1) Length End Cap	15 mm		

Article	Colour Temperature	Luminous Efficiency 1m	Luminous Flux 1m	Length	Price
840318	WW 3000 K	121 lm/W	485 lm	15000 mm	€ 289.95
840337	WW 3000 K	121 lm/W	485 lm	50000 mm	€ 999.95
840320	NW 4000 K	133 lm/W	530 lm	15000 mm	€ 289.95
840339	NW 4000 K	133 lm/W	530 lm	50000 mm	€ 999.95

CV

1 CH


IP20

A
↑
G

E

SMD 48V-4W LONG RUN IP44


IP44



· high-performance adhesive tape 3M 200MP

(p) LED Distance	12.8 mm	(l3) Secondary Cable Length	1 m
(c) Segment Length	166.66 mm	Rated Input 1m	4 W
(a) Light Beam Angle	120 Degree	Rated Input Voltage	48 V/DC
(r1) Bending Radius min.	50 mm	CRI (Ra)	80
(h1) Height	2.6 mm	Control	Dimmable via optional controller
(h2) Height End Cap	2.6 mm	Type of IP Protection	Silicone
(b1) Width	10 mm	Channels	1
(b2) Width end cap	10.5 mm		
(l1) Length End Cap	15 mm		
(l2) Primary Cable Length	1 m		

Article	Colour Temperature	Luminous Efficiency 1m	Luminous Flux 1m	Length	Working Temperature	Price
840317	3000 K	100 lm/W	400 lm	15000 mm	-15 to 50 °C	€ 349.95
840338	3000 K	100 lm/W	400 lm	50000 mm	-10 to 60 °C	€ 1124.95
840319	4000 K	114 lm/W	455 lm	15000 mm	-15 to 50 °C	€ 349.95
840340	4000 K	114 lm/W	455 lm	50000 mm	-10 to 60 °C	€ 1124.95



230V LED STRIPES


This LED stripe is ideally suited if the requirements and focus are on flexible, water-protected and long-lasting lighting routes in indoor and outdoor areas.

Due to the voltage of 230V, no additional power supply unit is required. The delivery is ready for connection with mounted Schuko plug and moulded endcap.

Applications of large distances, such as on buildings or hotel corridors can be operated in one piece up to 50m.




SMD 230V-14W LONG RUN IP65



- 230 V direct connection
- Ready to connect using IP44 shaped plug and end cap
- Total length to be operated up to 50 m
- Including mounting material

(p) LED Distance	11.9 mm	(l1) Length End Cap	27 mm
(c) Segment Length	166.7 mm	(l2) Primary Cable Length	3 m
(a) Light Beam Angle	120 Degree	(l3) Secondary Cable Length	3 m
(r1) Bending Radius min.	150 mm	Rated Input 1m	14 W
(h1) Height	13.2 mm	Rated Input Voltage	220-240 V/AC
(h2) Height End Cap	18 mm	CRI (Ra)	80
(h3) Height Hose	13.2 mm	Type of IP Protection	PVC cover
(b1) Width	17 mm	IP Protection Type Plug	IP 44
(b2) Width end cap	21.8 mm	Working Temperature	-10 to 60 °C
(b3) Width Hose	17 mm	Channels	1

Article	Colour Temperature	Luminous Efficiency 1m	Luminous Flux 1m	Length	EEL	Price
840390	WW 2700 K	103 lm/W	1442 lm	15000 mm		€ 769.95
840391	WW 2700 K	103 lm/W	1442 lm	50000 mm		€ 2499.95
840386	WW 3000 K	105 lm/W	1470 lm	15000 mm		€ 769.95
840387	WW 3000 K	105 lm/W	1470 lm	50000 mm		€ 2499.95
840388	NW 4000 K	114 lm/W	1596 lm	15000 mm		€ 769.95
840389	NW 4000 K	114 lm/W	1596 lm	50000 mm		€ 2499.95



Accessories

930689	End cap set of 2 pieces for 230 V LED stripe
930690	Supply cable with shaped plug for 230 V LED stripe
930691	Flex connector for 230 V LED stripe
930692	Mounting clamp set of 10 pieces for 230 V LED stripe
930693	Plastic profile 1 m for 230 V LED stripe
930809	Plastic profile 2 m for 230 V LED stripe

	€ 4.95
	€ 34.95
	€ 24.95
	€ 9.95
	€ 14.95
	€ 24.95



ASSEMBLY KIT FOR IP65/IP67 LED STRIPS

Set comprises:

- 15 silicone retaining clips
- 30 stainless steel screws
- Five end caps
- Supplied without silicone/adhesive

Housing	Silicone	
Article	for Stripes with outer dimensions	Price
840293	11-12 mm	€ 4.95
840294	13-15 mm	€ 4.95
840295	17-19 mm	€ 4.95
840392	8-10 mm	€ 4.95



3M™ DOUBLE-SIDED ADHESIVE TAPE

- For installing aluminium profiles/LED strips on smooth surfaces
- Not suitable for IP65/67 silicone strips

Length	50 m	Height	0.2 mm
--------	------	--------	--------

Article	Width	Price
930345	8 mm	€ 27.95
930346	10 mm	€ 29.95
930347	12 mm	€ 31.95
930348	15 mm	€ 38.95
930349	20 mm	€ 48.95
930350	25 mm	€ 56.95



3M™ DOUBLE-SIDED ADHESIVE TAPE FOR SILICONE SURFACES

- Special adhesive tape for LED strips with silicone tube/full potting
- High solvent resistance
- Excellent temperature resistance
- Strong initial bond
- High adhesive strength on most silicone surfaces and on substrates that are difficult to bond

Length	55 m	Height	0.127 mm
--------	------	--------	----------

Article	Width	Price
930405	10 mm	€ 209.95
930406	12 mm	€ 249.95







POWER SUPPLIES

862 DC - CV

878 DC - CC

892 AC - CV





page 868



page 868



page 869



page 869



page 870



page 870



page 871



page 871



page 872



page 872



page 873



page 874

power supplies



□
page 875



□
page 875



■
page 876



■
page 881



■
page 881



□
page 882



■
page 882



■
page 883



■
page 884



■
page 884



■
page 885



■
page 885



□
page 886




□
page 886



■
page 889



□
page 890



□
page 890



□
page 892



■
page 892



■
page 893

PLANNING ELECTRICAL INSTALLATIONS EVEN BETTER

You will certainly notice the new technical data when browsing through our power supplies and ask yourself what it is all about? In future, we would like to support you even better in the planning and dimensioning of your installations. The background to this is that more and more power supplies for lighting are already being installed in standard buildings [directly in the luminaires or as an external power supply].

Due to the inrush currents inherent in the design, e.g. after a power failure and the subsequent simultaneous start of all power supplies, an overload of the circuit breakers may occur. In order to be able to take this into account during the planning stage, we provide you with the necessary data for all our power supplies.

WIRE CROSS SECTION

When installing voltage-stable [CV] or current-stable [CC] power supply units and associated components, always ensure that the cable cross-sections are sufficiently dimensioned, especially with regard to the dependence of the cable length.

The specified cable cross-sections [mm²] were adapted to the commercially available cross-sections. The maximum cable length of 10 m should not be exceeded. »Red values« must be avoided urgently.

12 V	2 m	5 m	10 m	12 m
25 W	0,25	0,75	1,50	[2,50]
50 W	0,75	1,50	4,00	[4,00]
75 W	1,00	2,50	4,00	[6,00]
100 W	1,50	4,00	6,00	[10,00]
125 W	1,50	4,00	10,00	[10,00]
150 W	2,50	6,00	10,00	-
200 W	2,50	6,00	-	-
300 W	4,00	10,00	-	-
400 W	6,00	-	-	-

24 V	2 m	5 m	10 m	12 m
25 W	0,25	0,25	0,50	[0,50]
50 W	0,25	0,50	0,75	[1,00]
75 W	0,25	0,75	1,00	[1,50]
100 W	0,50	0,75	1,50	[2,50]
125 W	0,50	1,00	2,50	[2,50]
150 W	0,50	1,50	2,50	[4,00]
200 W	0,75	1,50	4,00	[4,00]
300 W	1,00	2,50	6,00	-
400 W	1,50	4,00	6,00	-

48 V	2 m	5 m	10 m	12 m
25 W	0,25	0,25	0,25	[0,25]
50 W	0,25	0,25	0,25	[0,25]
75 W	0,25	0,25	0,50	[0,50]
100 W	0,25	0,25	0,50	[0,50]
125 W	0,25	0,25	0,50	[0,75]
150 W	0,25	0,50	0,75	[0,75]
200 W	0,25	0,50	1,00	[1,00]
300 W	0,25	0,75	1,50	[1,50]
400 W	0,50	1,00	2,50	[2,50]

HOW MANY POWER SUPPLY UNITS
PER CIRCUIT BREAKER?

The maximum number of power supply units that may be connected to the respective circuit breaker is directly dependent on the inrush current. In our quick finders you will find the number for the most common types of circuit breaker [B10A, B16A, C10A, C16A].

CAPACITIVE LOAD OF POWER SUPPLIES

Due to their design, power supplies sometimes represent very different capacitive loads. Especially in combination with motion detectors, twilight switches or switching/dimming actuators, this value [as with the capacitor in nF/pF], which is available for many power supplies and specified in our quick finders, plays an important role with regard to the suitability and durability of all components. Please also refer to the manufacturer's data sheets.

electr. data		dimmable via						usage / design			electrical limit values		power supply	
voltage	power	leading cut-off	1 - 10V	touch dimmer (push)	DALI	KNX	indoor	outdoor	design		capacitive load	max. quantity per automatic circuit breaker	item number	page
12V	20 W						x		flat		938uF	B10A=17, B16A=27, C10A=36, C16A=58	862232	869
12V	2,5-25 W	x					x		basic		31.16nF	B10=35, B16=56, C10=35, C16=56	862240	873
12V	40 W						x		basic		251.7nF	B10A=11, B16A=18, C10A=24, C16A=39	862162	870

DO YOU KNOW OUR LONG-FLAT
POWER SUPPLIES?

The popular Long-Flat power supply series for installation in ceiling coves, shadow gaps or all other installation situations with limited space is now available in on/off and trailing edge dimmable versions in 12V, 24V and 48V in a wide range of versions from 45-240W.

All Long-Flat power supplies can be found on page 869.



electr. data		dimmable via						usage / design			electrical limit values		power supply	
voltage	power	leading out-off		1 - 10V	touch dimmer [push]	DALI	KNX	indoor	outdoor	design	capacitive load	max. quantity per automatic circuit breaker	item number	page
12V	4 W							x	x	mini		B10A=17, B16A=28, C10A=37, C16A=59	872127	868
12V	6 W							x		flat	38.83nF	B10A=17, B16A=28, C10A=37, C16A=59	872629	869
12V	12 W							x	x	octo	101uF	B10A=17, B16A=27, C10A=36, C16A=58	862229	868
12V	12 W							x		flat		B10A=17, B16A=27, C10A=36, C16A=58	862231	869
12V	20 W							x		flat	938uF	B10A=17, B16A=27, C10A=36, C16A=58	862232	869
12V	2,5-25 W	x						x		basic	31.16nF	B10=35, B16=56, C10=35, C16=56	862240	873
12V	40 W							x		basic	251.7nF	B10A=11, B16A=18, C10A=24, C16A=39	862162	870
12V	40 W							x	x	IP	621.5nF	B10A=5, B16A=9, C10A=12, C16A=19	872082	870
12V	40 W							x	x	IP		B10A=6, B16A=9, C10A=10, C16A=16	872097	871
12V	40 W		x	x	x			x		basic		B10A=18, B16A=28, C10A=36, C16A=56	862253	875
12V	45 W							x		long-flat	462.1nF	B10A=5, B16A=9, C10A=12, C16A=19	862123	869
12V	50 W							x		flat	485.5nF	B10A=11, B16A=18, C10A=24, C16A=39	862121	869
12V	12-50 W	x						x		basic	1924uF	B10A=17, B16A=28, C10A=17, C16A=28	862220	873
12V	60 W							x		long-flat	462.1nF	B10A=5, B16A=9, C10A=12, C16A=19	862093	869
12V	60 W							x	x	IP		B10A=6, B16A=9, C10A=10, C16A=16	872098	871
12V	60 W						x	x	x	IP		B10A=6, B16A=9, C10A=10, C16A=16	872109	876
12V	75 W							x		basic	870nF	B10A=11, B16A=18, C10A=24, C16A=39	862127	870
12V	75 W							x	x	IP	621.5nF	B10A=5, B16A=8, C10A=10, C16A=16	872084	870
12V	75 W		x	x	x			x		basic		B10A=10, B16A=16, C10A=20, C16A=32	862254	875
12V	90 W							x	x	IP		B10A=2, B16A=3, C10A=3, C16A=6	872099	871
12V	100 W							x		basic	842.2nF	B10A=3, B16A=5, C10A=7, C16A=11	862165	870
12V	100 W							x	x	IP	621.5nF	B10A=3, B16A=5, C10A=7, C16A=11	872093	870
12V	100 W							x		long-flat	462.1nF	B10A=3, B16A=5, C10A=7, C16A=11	862125	869
12V	33-100 W	x						x	x	IP	93,14nF	B10=7, B16=15, C10=7, C16=15	872135	874
12V	34-100 W	x						x		basic	146,34nF	B10=7, B16=15, C10=7, C16=15	862241	873
12V	120 W							x	x	IP		B10A=2, B16A=4, C10A=4, C16A=6	872100	871

electr. data		dimmable via					usage / design			electrical limit values		power supply	
voltage	power	leading out-off	1 - 10V	touch dimmer (push)	DALI	KNX	indoor	outdoor	design	capacitive load	max. quantity per automatic circuit breaker	item number	page
12V	120 W					x	x		IP		B10A=2, B16A=4, C10A=4, C16A=6	872110	876
12V	150 W						x		long-flat	462.1nF	B10A=3, B16A=5, C10A=6, C16A=10	862172	869
12V	150 W						x		basic	591.2nF	B10A=2, B16A=4, C10A=6, C16A=9	862167	869
12V	150 W						x	x	IP	621.5nF	B10A=2, B16A=4, C10A=6, C16A=9	872086	870
12V	66-200 W	x					x	x	IP	148,64nF	B10=3, B16=7, C10=3, C16=7	872137	874
12V	200 W						x	x	IP	621.5nF	B10A=2, B16A=3, C10A=4, C16A=7	872088	870
12V	200 W					x	x		IP		B10A=2, B16A=4, C10A=4, C16A=6	872111	876
24V	4 W						x	x	mini		B10A=59, B16A=94, C10A=123, C16A=197	872128	868
24V	6 W						x		flat	43.5nF	B10A=17, B16A=28, C10A=37, C16A=59	872630	869
24V	12 W						x	x	octo	620uF	B10A=17, B16A=27, C10A=36, C16A=58	862230	868
24V	12 W						x		flat	311uF	B10A=17, B16A=27, C10A=36, C16A=58	862233	869
24V	20 W						x		flat	446uF	B10A=17, B16A=27, C10A=36, C16A=58	862234	869
24V	2,5-25 W	x					x		basic	9520uF	B10=35, B16=56, C10=35, C16=56	862221	873
24V	30W	x					x		long-flat		B16A=25, C16A=40	862277	873
24V	12-30W			x	x		x		long-flat		B10A=27, B16A=44, C10A=44, C16A=70	872146	876
24V	40 W						x		basic	762nF	B10A=11, B16A=18, C10A=24, C16A=39	862163	870
24V	40 W						x	x	IP	626.3nF	B10A=5, B16A=9, C10A=12, C16A=19	872083	870
24V	40 W						x	x	IP		B10A=6, B16A=9, C10A=10, C16A=16	872101	871
24V	40 W		x	x	x		x		basic		B10A=18, B16A=28, C10A=36, C16A=56	862255	875
24V	45 W						x		long-flat	451.2nF	B10A=5, B16A=9, C10A=12, C16A=19	862124	869
24V	12-50 W	x					x		basic	10520uF	B10A=17, B16A=28, C10A=17, C16A=28	862222	873
24V	50 W						x		flat	604.5nF	B10A=11, B16A=18, C10A=24, C16A=39	862122	869
24V	60 W						x		long-flat	451.2nF	B10A=5, B16A=9, C10A=12, C16A=19	862094	869
24V	60 W						x	x	IP		B10A=6, B16A=9, C10A=10, C16A=16	872102	871
24V	60 W					x	x		IP		B10A=6, B16A=9, C10A=10, C16A=16	872112	876
24V	12-60 W	x					x	x	*			872045	872

electr. data		dimmable via					usage / design			electrical limit values		power supply	
voltage	power	leading cut-off	1 - 10V	touch dimmer [push]	DALI	KNX	indoor	outdoor	design	capacitive load	max. quantity per automatic circuit breaker	item number	page
24V	60W	x					x		long-flat		B16A= 25, B16A=40	862278	873
24V	26-60W			x	x		x		long-flat		B10A=23, B16A=37, C10A=37, C16A=59	872147	876
24V	75 W						x		basic	760nF	B10A=11, B16A=18, C10A=24, C16A=39	862164	870
24V	75 W						x	x	IP	626.3nF	B10A=5, B16A=8, C10A=10, C16A=16	872085	870
24V	75 W		x	x	x		x		basic		B10A=10, B16A=16, C10A=20, C16A=32	862256	875
24V	25-75W	x					x		long-flat		B10A=2, B16A=4 C10A=5, C16A=9	862282	872
24V	90 W						x	x	IP		B10A=2, B16A=3, C10A=3, C16A=6	872103	871
24V	100 W						x		basic	724.2nF	B10A=3, B16A=5, C10A=7, C16A=11	862166	870
24V	33-100 W	x					x		IP	94,13nF	B10=7, B16=15, C10=7, C16=15	872136	874
24V	34-100 W	x					x		basic	140.74nF	B10=7, B16=15, C10=7, C16=15	862242	873
24V	100 W						x		long-flat	451.2nF	B10A=3, B16A=5, C10A=7, C16A=11	862126	869
24V	100 W						x	x	IP	626.3nF	B10A=3, B16A=5, C10A=7, C16A=11	872094	870
24V	120 W						x	x	IP		B10A=2, B16A=4, C10A=4, C16A=6	872104	871
24V	120 W					x	x	x	IP		B10A=2, B16A=4, C10A=4, C16A=6	872113	876
24V	150 W						x		basic	591.2nF	B10A=2, B16A=4, C10A=6, C16A=9	862168	870
24V	150 W						x		long-flat	451.2nF	B10A=3, B16A=5, C10A=6, C16A=10	862173	869
24V	150 W						x	x	IP	626.3nF	B10A=2, B16A=4, C10A=6, C16A=9	872087	870
24V	30-150 W	x					x	x	*			872046	872
24V	50-150 W	x					x		long-flat		B10A=2, B16A=3, C10A=4, C16A=7	862268	872
24V	150 W		x	x	x		x		basic		B10A=5, B16A=9, C10A=10 C16A=18	862262	875
24V	45-150W			x	x		x		long-flat		B10A=11, B16A=17 C10A=17, C16A=27	872148	876
24V	200 W					x	x		IP		B10A=2, B16A=4, C10A=4, C16A=6	872114	876
24V	66-200 W	x					x	x	IP	148.64nF	B10=3, B16=7, C10=3, C16=7	872138	874
24V	240 W						x	x	IP	626.3nF	B10A=2, B16A=3, C10A=4, C16A=7	872089	870
24V	240 W						x		long-flat	5600uF	B10A=1, B16A=2, C10A=3, C16A=5	862265	869
24V	80-240W	x					x		long-flat		B10A=2, B16A=3 C10A=4, C16A=6	862280	872

electr. data		dimmable via					usage / design			electrical limit values		power supply	
voltage	power											item number	page
		leading cut-off	1 - 10V	touch dimmer [push]	DALI	KNX	indoor	outdoor	design	capacitive load	max. quantity per automatic circuit breaker		
24V	240 W		x	x	x		x		basic		B10A=3, B16A=5, C10A=6, C16A=10	862263	875
24V	320 W						x	x	IP	626.3nF	B10A=2, B16A=3, C10A=4, C16A=6	872091	870
48V	40 W						x	x	IP		B10A=6, B16A=9, C10A=10, C16A=16	872105	871
48V	60 W						x	x	IP		B10A=6, B16A=9, C10A=10, C16A=16	872106	871
48V	25-75W	x					x		long-flat		B10A=2, B16A=4 C10A=5, C16A=9	862283	872
48V	75 W		x	x	x		x		basic		B10A=10, B16A=16, C10A=20, C16A=32	862273	875
48V	90 W						x	x	IP		B10A=2, B16A=3, C10A=3, C16A=6	872107	871
48V	33-100 W	x					x		IP	6,6uF	B10=3 B16=5, C10=7, C16=11	872142	874
48V	34-100 W	x					x		basic	140,74nF	B10=7 B16=15, C10=7, C16=15	862274	873
48V	100 W						x		long-flat	451.2nF	B10A=3, B16A=5, C10A=7, C16A=11	862270	869
48V	120 W						x	x	IP		B10A=2, B16A=4, C10A=4, C16A=6	872108	871
48V	150 W		x	x	x		x		basic		B10A=5, B16A=9, C10A=10 C16A=18	862275	875
48V	50-150 W	x					x		long-flat		B10A=2, B16A=3, C10A=4, C16A=7	862269	872
48V	150 W						x		long-flat	451.2nF	B10A=3, B16A=5, C10A=6, C16A=10	862271	869
48V	80-240W	x					x		long-flat		B10A=2, B16A=3 C10A=4, C16A=6	862281	872
48V	320 W						x	x	IP	626.3nF	B10A=2, B16A=3, C10A=4, C16A=6	872145	870
48V	66-200 W	x					x	x	IP	6,6uF	B10=2, B16=3, C10=4 C16=7	872143	874
48V	200 W					x	x		IP		B10A=2, B16A=4, C10A=4, C16A=6	872115	876
48V	240 W		x	x	x		x		basic		B10A=3, B16A=5, C10A=6, C16A=10	862276	875
48V	240 W						x		long-flat	5600uF	B10A=1, B16A=2, C10A=3, C16A=5	862272	869
48V	600 W						x	x	IP		B10A=1, B16A=1, C10A=1, C16A=2	872125	871
48V	600 W		x				x	x	IP		B10A=1, B16A=1, C10A=1, C16A=2	872126	875

power supplies design



mini



round / octo



flat



basic



long-flat



IP

* special design



DEKO-LIGHT POWER SUPPLY UNITS CV | MINI DESIGN

- Flicker-free
- Secured against short circuits and overloads

Housing	Plastic	Height	21 mm
Power	4 W	Rated Input Voltage	220-240 V/AC
Length	53 mm	Mounting Location	Inside, Outside
Width	27 mm		

Article		Output Voltage	Output Current	Price
872127	■	12 V/DC	0-330 mA	€ 12.95
872128	■	24 V/DC	0-170 mA	€ 12.95



DEKO-LIGHT POWER SUPPLY UNITS CV IP | OCTO DESIGN

- Flicker-free
- Secured against short circuits and overloads

Housing	Plastic	Height	24 mm
Power	12 W	Rated Input Voltage	220-240 V/AC
Length	50 mm	Mounting Location	Inside, Outside
Width	48 mm		

Article		Output Voltage	Output Current	Price
862229	■	12 V/DC	0-1000 mA	€ 21.95
862230	■	24 V/DC	0-500 mA	€ 21.95



DEKO-LIGHT POWER SUPPLY UNITS CV | FLAT DESIGN

- Ideal for concealed mounting in ceiling coves
- Flicker-free
- Secured against short circuits and overloads
- Overheating protection



Housing	Plastic	Mounting Location	Inside
Rated Input Voltage	220-240 V/AC		

Article		Output Voltage	Power	Output Current	Length	Width	Height	Price
872629	■	12 V/DC	6.0 W	0-500 mA	98 mm	46 mm	11 mm	€ 16.95
862231	■	12 V/DC	12.0 W	0-1000 mA	128 mm	50 mm	13 mm	€ 21.95
862232	■	12 V/DC	20.0 W	0-1670 mA	128 mm	50 mm	13 mm	€ 25.95
862121	■	12 V/DC	50.0 W	0-4160 mA	185 mm	62 mm	22 mm	€ 52.95
872630	■	24 V/DC	6.0 W	0-250 mA	98 mm	46 mm	11 mm	€ 16.95
862233	■	24 V/DC	12.0 W	0-500 mA	128 mm	50 mm	13 mm	€ 21.95
862234	■	24 V/DC	20.0 W	0-830 mA	128 mm	50 mm	13 mm	€ 25.95
862122	■	24 V/DC	50.0 W	0-2100 mA	185 mm	62 mm	22 mm	€ 52.95



DEKO-LIGHT POWER SUPPLY UNITS CV | LONG-FLAT DESIGN

- Ideal for concealed mounting in ceiling coves
- Flicker-free
- Secured against short circuits and overloads
- Overheating protection



Housing	Plastic	Mounting Location	Inside
Rated Input Voltage	220-240 V/AC		

Article		Output Voltage	Power	Output Current	Length	Width	Height	Price
862123	■	12 V/DC	45.0 W	0-3750 mA	251 mm	30 mm	16 mm	€ 49.95
862093	□	12 V/DC	60.0 W	0-5000 mA	305 mm	30 mm	17 mm	€ 59.95
862125	■	12 V/DC	100.0 W	0-8340 mA	312 mm	30 mm	18.2 mm	€ 96.95
862172	■	12 V/DC	132.0 W	0-11000 mA	335 mm	30 mm	21.6 mm	€ 129.95
862124	■	24 V/DC	45.0 W	0-1870 mA	251 mm	30 mm	16 mm	€ 49.95
862094	□	24 V/DC	60.0 W	0-2500 mA	305 mm	30 mm	18.2 mm	€ 59.95
862126	■	24 V/DC	100.0 W	0-4170 mA	312 mm	30 mm	18.2 mm	€ 96.95
862173	■	24 V/DC	150.0 W	0-6250 mA	335 mm	30 mm	21.6 mm	€ 129.95
862265	■	24 V/DC	240.0 W	0-10000 mA	357 mm	32 mm	23 mm	€ 159.95
862270	■	48 V/DC	100.0 W	0-2080 mA	312 mm	30 mm	18.2 mm	€ 96.95
862271	■	48 V/DC	150.0 W	0-3125 mA	335 mm	30 mm	21.6 mm	€ 129.95
862272	■	48 V/DC	240.0 W	0-5000 mA	357 mm	32 mm	22.5 mm	€ 159.95



DEKO-LIGHT POWER SUPPLY UNITS CV | BASIC DESIGN

- Flicker-free
- Secured against short circuits and overloads
- Overheating protection



Housing

Plastic

Mounting Location

Inside

Rated Input Voltage

220-240 V/AC

Article		Output Voltage	Power	Output Current	Length	Width	Height	Price
862162		12 V/DC	40.0 W	0-3300 mA	166 mm	52 mm	24 mm	€ 46.95
862127		12 V/DC	75.0 W	0-6300 mA	184 mm	61 mm	32 mm	€ 74.95
862165		12 V/DC	100.0 W	0-8300 mA	184 mm	61 mm	32 mm	€ 96.95
862167		12 V/DC	150.0 W	0-12500 mA	210 mm	67 mm	34 mm	€ 129.95
862163		24 V/DC	40.0 W	0-1700 mA	166 mm	52 mm	24 mm	€ 46.95
862164		24 V/DC	75.0 W	0-3100 mA	184 mm	61 mm	32 mm	€ 74.95
862166		24 V/DC	100.0 W	0-4200 mA	184 mm	61 mm	32 mm	€ 96.95
862168		24 V/DC	150.0 W	0-6250 mA	210 mm	67 mm	34 mm	€ 129.95



DEKO-LIGHT POWER SUPPLY UNITS CV IP | IP DESIGN

- Robust housing
- Flicker-free
- Secured against short circuits and overloads
- Overheating protection



Housing

Aluminium

Mounting Location

Inside, Outside

Rated Input Voltage

100-240 V/AC

Article		Output Voltage	Power	Output Current	Length	Width	Height	Price
872082		12 V/DC	40.0 W	0-3340 mA	176 mm	58 mm	30.5 mm	€ 74.95
872084		12 V/DC	75.0 W	0-6250 mA	186 mm	64 mm	39 mm	€ 94.95
872093		12 V/DC	100.0 W	0-8340 mA	186 mm	64 mm	39 mm	€ 114.95
872086		12 V/DC	150.0 W	0-12500 mA	191 mm	70 mm	40 mm	€ 149.95
872088		12 V/DC	200.0 W	0-16670 mA	249 mm	72 mm	41 mm	€ 179.95
872083		24 V/DC	40.0 W	0-1670 mA	176 mm	58 mm	30.5 mm	€ 74.95
872085		24 V/DC	75.0 W	0-3125 mA	186 mm	64 mm	39 mm	€ 94.95
872094		24 V/DC	100.0 W	0-4170 mA	186 mm	64 mm	39 mm	€ 114.95
872087		24 V/DC	150.0 W	0-6250 mA	191 mm	70 mm	40 mm	€ 149.95
872089		24 V/DC	240.0 W	0-10000 mA	249 mm	72 mm	40 mm	€ 184.95
872091		24 V/DC	320.0 W	0-13340 mA	252 mm	90 mm	44 mm	€ 219.95
872145		48 V/DC	320.0 W	0-6660 mA	252 mm	90 mm	44 mm	€ 219.95



MEANWELL POWER SUPPLY UNITS CV IP | NPF SERIES

- Flicker-free
- Secured against short circuits and overloads
- Overheating protection
- Robust housing



Housing	Plastic	Mounting Location	Inside, Outside
Rated Input Voltage	90-305 V/AC		

Article		Output Voltage	Power	Output Current	Length	Width	Height	Price
872097		12 V/DC	40.0 W	0-3340 mA	150 mm	53 mm	35 mm	€ 84.95
872098		12 V/DC	60.0 W	0-5000 mA	150 mm	53 mm	35 mm	€ 94.95
872099		12 V/DC	90.0 W	0-7500 mA	171 mm	63 mm	37.5 mm	€ 119.95
872100		12 V/DC	120.0 W	0-10000 mA	191 mm	63 mm	37.5 mm	€ 139.95
872101		24 V/DC	40.0 W	0-1670 mA	150 mm	53 mm	35 mm	€ 84.95
872102		24 V/DC	60.0 W	0-2500 mA	150 mm	53 mm	35 mm	€ 94.95
872103		24 V/DC	90.0 W	0-3750 mA	171 mm	63 mm	37.5 mm	€ 119.95
872104		24 V/DC	120.0 W	0-5000 mA	191 mm	63 mm	37.5 mm	€ 139.95
872105		48 V/DC	40.0 W	0-840 mA	150 mm	53 mm	35 mm	€ 84.95
872106		48 V/DC	60.0 W	0-1250 mA	150 mm	53 mm	35 mm	€ 94.95
872107		48 V/DC	90.0 W	0-1880 mA	171 mm	63 mm	37.5 mm	€ 119.95
872108		48 V/DC	120.0 W	0-2500 mA	191 mm	63 mm	37.5 mm	€ 139.95



MEANWELL POWER SUPPLY UNITS CV IP | ELG/HLG SERIES

- Output voltage/current can be adjusted via potentiometer
- Flicker-free
- Secured against short circuits and overloads
- Overheating protection



Housing	Aluminium	Width	144 mm
Output Voltage	48 V/DC	Height	48.5 mm
Power	600 W	Rated Input Voltage	90-305 V/AC
Output Current	0-12500 mA	Mounting Location	Inside, Outside
Length	280 mm		

Article	Price
872125	€ 489.95





ABN LED SAFETY TRANSFORMER CV DIM IP

- Safety transformer [DC] in accordance with DIN 2006-7 EN 61558-2-6: 2010-04
- Reinforced double insulation [separate primary and secondary winding]
- Additional insulating plastic parts
- More stringent test conditions
- Suitable for applications in areas of increased personal protection in accordance with DIN EN 61558 for operating lights in swimming pools, fountains, wet rooms or similar.
- Primary dimming possible using leading-edge phase dimmers
- Maximum load: 80 % output in continuous operation



Housing	Plastic	Channels	1
Output Voltage	24 V/DC	Mounting Location	Inside, Outside
Rated Input Voltage	220-240 V/AC		

Article		Power	Length	Width	Height	Price
872045		12.0-60.0 W	150 mm	90 mm	70 mm	€ 369.95
872046		30.0-150.0 W	176 mm	116 mm	110 mm	€ 619.95




DEKO-LIGHT NETZGERÄTE CV DIM / BAUFORM LONG-FLAT

- dimmable with leading/trailing edge phase dimmers
- ideal for retrofitting existing installations, as primarily dimmable with
- rotary/push-button dimmers [C-compatible]
- long, compact design
- not combinable with PWM dimmers such as RF, DMX, DALI, KNX
- flicker-free
- short-circuit and overload-proof
- overheating protection



Housing	Plastic	Channels	1
Width	32 mm	Mounting Location	Inside

Article		Output Voltage	Power	Length	Height	Rated Input Voltage	Price
862282		24 V/DC	25.0-75.0 W	400 mm	21.6 mm	198-264 V/AC	€ 99.95
862268		24 V/DC	50.0-150.0 W	400 mm	21.6 mm	220-240 V/AC	€ 129.95
862280		24 V/DC	80.0-240.0 W	443 mm	23 mm	220-240 V/AC	€ 159.95
862283		48 V/DC	25.0-75.0 W	400 mm	21.6 mm	198-264 V/AC	€ 99.95
862269		48 V/DC	50.0-150.0 W	400 mm	21.6 mm	220-240 V/AC	€ 129.95
862281		48 V/DC	80.0-240.0 W	443 mm	23 mm	220-240 V/AC	€ 159.95






KPG POWER SUPPLY UNITS CV DIM / LONG-FLAT DESIGN

- Can be dimmed using trailing-edge phase dimmers
- Ideal for retrofitting existing installations, since it can be dimmed primarily with rotary/push-button dimmers [C-compatible]
- Long, extremely compact design
- Cannot be combined with PWM dimmers such as RF, DMX, DALI or KNX
- Flicker-free
- Secured against short circuits and overloads
- Overheating protection



Housing	Polycarbonate	Rated Input Voltage	220-240 V/AC
Output Voltage	24 V/DC	Channels	1
Width	30 mm	Mounting Location	Inside
Height	18.5 mm		

Article		Power	Length	Price
862277		0.0-30.0 W	260 mm	€ 114.95
862278		0.0-60.0 W	300 mm	€ 179.95



DEKO-LIGHT POWER SUPPLY UNITS CV DIM | BASIC DESIGN

- Can be dimmed using leading-edge/trailing-edge phase dimmers
- Ideal for retrofitting existing installations, since it can be dimmed primarily with rotary/push-button dimmers (C-compatible)
- Cannot be combined with PWM dimmers such as RF, DMX, DALI or KNX
- Flicker-free
- Secured against short circuits and overloads
- Overheating protection



Housing	Plastic	Channels	1
Rated Input Voltage	220-240 V/AC	Mounting Location	Inside

Article		Output Voltage	Power	Length	Width	Height	Price
862240		12 V/DC	9.6-25.0 W	128 mm	52 mm	30 mm	€ 54.95
862220		12 V/DC	12.0-50.0 W	184 mm	61 mm	32 mm	€ 74.95
862241		12 V/DC	34.0-100.0 W	210 mm	67 mm	34 mm	€ 144.95
862221		24 V/DC	9.6-25.0 W	128 mm	52 mm	30 mm	€ 54.95
862222		24 V/DC	12.0-50.0 W	184 mm	61 mm	32 mm	€ 74.95
862242		24 V/DC	34.0-100.0 W	210 mm	67 mm	34 mm	€ 144.95
862274		48 V/DC	34.0-100.0 W	210 mm	67 mm	34 mm	€ 144.95



DEKO-LIGHT POWER SUPPLY UNITS CV DIM IP | IP DESIGN

- Can be dimmed using leading-edge/trailing-edge phase dimmers
- Ideal for retrofitting existing installations, since it can be dimmed primarily with rotary/push-button dimmers [C-compatible]
- Cannot be combined with PWM dimmers such as RF, DMX, DALI or KNX
- Robust housing
- Flicker-free
- Secured against short circuits and overloads
- Overheating protection



Housing	Aluminium	Channels	1
Height	40 mm	Mounting Location	Inside, Outside
Rated Input Voltage	220-240 V/AC		

Article		Output Voltage	Power	Length	Width	Price
872135	■	12 V/DC	33.0-100.0 W	191 mm	70 mm	€ 169.95
872137	■	12 V/DC	66.0-200.0 W	249 mm	72 mm	€ 206.95
872136	■	24 V/DC	33.0-100.0 W	191 mm	70 mm	€ 169.95
872138	■	24 V/DC	66.0-200.0 W	249 mm	72 mm	€ 206.95
872142	■	48 V/DC	33.0-100.0 W	191 mm	70 mm	€ 169.95
872143	■	48 V/DC	66.0-200.0 W	249 mm	72 mm	€ 206.95





DEKO-LIGHT POWER SUPPLY UNITS CV DIM | LCP DALI

- Can be dimmed using DALI2/DALI1
- Can be dimmed using 0-10 V/1-10 V
- Can be dimmed using touch dimmer via 230 V push-button (iPush)
- New Intelli-Push function [shortcut synchronises all connected power supply units when needed]
- Power supply unit and PWM dimmer in one device
- Secured against short circuits and overloads
- Overheating protection



Housing	Plastic	Channels	1
Rated Input Voltage	220-240 V/AC	Mounting Location	Inside

Article		Output Voltage	Power	Length	Width	Height	Price
862253		12 V/DC	40.0 W	185 mm	42.5 mm	28.5 mm	€ 99.95
862254		12 V/DC	75.0 W	295 mm	40 mm	32 mm	€ 129.95
862255		24 V/DC	40.0 W	185 mm	42.5 mm	28.5 mm	€ 99.95
862256		24 V/DC	75.0 W	295 mm	40 mm	32 mm	€ 129.95
862262		24 V/DC	150.0 W	295 mm	40 mm	32 mm	€ 169.95
862263		24 V/DC	240.0 W	360 mm	40 mm	32 mm	€ 219.95
862273		48 V/DC	75.0 W	295 mm	40 mm	32 mm	€ 129.95
862275		48 V/DC	150.0 W	295 mm	40 mm	32 mm	€ 169.95
862276		48 V/DC	240.0 W	360 mm	40 mm	32 mm	€ 219.95



MEANWELL POWER SUPPLY UNITS CV DIM IP | ELG/HLG SERIES

- Can be dimmed using 0-10 V/1-10 V
- Flicker-free, secured against short circuits and overloads
- Overheating protection



Housing	Aluminium	Height	48.5 mm
Output Voltage	48 V/DC	Rated Input Voltage	90-305 V/AC
Power	600 W	Channels	1
Length	280 mm	Mounting Location	Inside, Outside
Width	144 mm		

Article		Price
872126		€ 499.95





KPG POWER SUPPLY UNITS CV DALI / LONG-FLAT DESIGN

- Can be dimmed using DALI1/DALI2
- Power supply unit and DALI PWM dimmer in one device
- Extremely compact design
- Flicker-free
- Secured against short circuits and overloads
- Overheating protection



Housing	Aluminium	Rated Input Voltage	100-305 V/AC
Output Voltage	24 V/DC	Channels	1
Width	30 mm	Mounting Location	Inside, Outside

Article		Power	Length	Height	Price
872146		12.0-30.0 W	300 mm	16 mm	€ 64.95
872147		26.0-60.0 W	350 mm	18 mm	€ 79.95
872148		45.0-150.0 W	350 mm	18 mm	€ 129.95



MEANWELL POWER SUPPLY UNITS CV DIM | PWM KNX

- Can be dimmed using KNX bus
- Flicker-free, secured against short circuits and overloads
- Overheating protection



Housing	Plastic	Channels	1
Rated Input Voltage	90-305 V/AC	Mounting Location	Inside

Article		Output Voltage	Power	Length	Width	Height	Price
872109		12 V/DC	60.0 W	150 mm	53 mm	35 mm	€ 159.95
872110		12 V/DC	120.0 W	191 mm	63 mm	37.5 mm	€ 209.95
872111		12 V/DC	200.0 W	195 mm	68 mm	39.5 mm	€ 244.95
872112		24 V/DC	60.0 W	150 mm	53 mm	35 mm	€ 159.95
872113		24 V/DC	120.0 W	191 mm	63 mm	37.5 mm	€ 209.95
872114		24 V/DC	200.0 W	195 mm	68 mm	39.5 mm	€ 244.95
872115		48 V/DC	200.0 W	195 mm	68 mm	39.5 mm	€ 244.95





electr. data			dimmable via				usage / design			electrical limit values		power supply	
current strength	power	voltage	leading out-off	touch dimmer (push)	DALI	KNX	indoor	outdoor	design	capacitive load	max. quantity per automatic circuit breaker	item number	page
260 mA	6,0-12,0W	23-46V	x				x		basic		B10A= 17, B16A=28 C10A=37, C16A=59	862285	885
350 mA	0,9-3,9W	2,5-11V					x	x	mini		B10A=70, B16A=112, C10A=140, C16A=224	872129	881
350 mA	2,1-4,0W	6-12V	x				x	x	mini	10.00nF	B10A=35, B16A=56, C10A=74, C16A=118	872132	884
350 mA	0,7-6,0W	2-18V					x		flat	40.44nF	B10A=17, B16A=28, C10A=37, C16A=59	872628	882
350 mA	3,2-8,0W	9-23V					x		round	200uF	B10A=17, B16A=28, C10A=37, C16A=59	862212	881
350 mA	3,9-9,0W	11-26V	x				x		basic		B10A=17, B16A=28, C10A=37, C16A=59	862202	885
350 mA	6,0-10,0W	17-29V					x		mini		B10A=57, B16A=92, C10A=57, C16A=92	862239	882
350 mA	6,3-12,0W	18-35V	x				x		basic	20,65pF	B10A=17, B16A=28, C10A=37, C16A=59	862203	885
350 mA	0,7-12,0W	2-35V					x		flat	194,0uF	B10A=11, B16A=18, C10A=24, C16A=39	862223	882
350 mA	6,3-12,0W	18-37V	x				x	x	octo	190uF	B10A=35, B16A=56, C10A=74, C16A=118	862235	884
350 mA	9,1-15,0W	26-43V	x				x		basic		B10A=38, B16A=61, C10A=38, C16A=61	862266	886
350 mA	0,7- 18,0W	2-52V					x		basic	147nF	B10A=17, B16A=28, C10A=37, C16A=59	180512	883
350 mA	9,8- 20,0W	28-57V	x				x		basic		B10A=11, B16A=18, C10A=24, C16A=39	862204	885
350 mA	0,7- 20,0W	2-57V					x		flat	195uF	B10A=11, B16A=18, C10A=24, C16A=39	862224	882
450 mA	9,9-19,0W	22-42V	x				x		quick		B10A=11, B16A=18, C10A=24, C16A=39	862257	885
500 mA	2,0-4,0W	4-8V					x	x	mini	85,0pF	B10A=70, B16A=112, C10A=140, C16A=224	872130	881
500 mA	2,0-4,0W	4-8V	x				x	x	mini	4.75nF	B10A=35, B16A=56, C10A=74, C16A=118	872014	884
500 mA	1,0-6,0W	2-12V					x		flat	38.48nF	B10A=17, B16A=28, C10A=37, C16A=59	862130	882
500 mA	3,0-8,0W	6-16V					x		round	62.96nF	B10A=11, B16A=18, C10A=24, C16A=39	862128	881
500 mA	1,0- 12,0W	2-24V					x		flat	298uF	B10A=11, B16A=18, C10A=24, C16A=39	862225	882
500 mA	6,5-10,0W	13-20V					x		mini		B10A=57, B16A=92, C10A=57, C16A=92	862238	882
500 mA	6,0- 12,0W	12-24V	x				x	x	octo	186uF	B10A=35, B16A=56, C10A=74, C16A=118	862236	884
500 mA	1,0- 18,0W	2-38V					x		basic	147nF	B10A=17, B16A=28, C10A=37, C16A=59	180513	883
500 mA	1,0- 20,0W	2-40V					x		flat	292uF	B10A=11, B16A=18, C10A=24, C16A=39	862226	882
500 mA	10,0-20,0W	20-40V	x				x		basic		B10A=11, B16A=18, C10A=24, C16A=39	862205	885
500 mA	15,0-30,0W	30-60V					x		basic	366nF	B10A=11, B16A=18, C10A=24, C16A=39	862196	883
500 mA	20,0-40,0W	40-80V					x		basic	356nF	B10A=8, B16A=14, C10A=18, C16A=29	862197	883
500 mA	20,0-40,0W	40-80V	x				x		basic	29.84nF	B10A=35, B16A=56, C10A=35, C16A=56	862136	885

electr. data			dimmable via				usage / design			electrical limit values		power supply	
current strength	power	voltage	leading cut-off	touch dimmer (push)	DALI	KNX	indoor	outdoor	design	capacitive load	max. quantity per automatic circuit breaker	item number	page
700 mA	1,7-4,0 W	2-6V					x	x	mini	82pF	B10A=70, B16A=112, C10A=140, C16A=224	872131	881
700 mA	2,0-4,0 W	2,5-6V	x				x	x	mini	10nF	B10A=35, B16A=56, C10A=74, C16A=118	872134	884
700 mA	1,4-6,0 W	2-9V					x		flat	40.44nF	B10A=17, B16A=28, C10A=37, C16A=59	862048	882
700 mA	4,2-8,0 W	6-12V					x		round	46.24nF	B10A=11, B16A=18, C10A=24, C16A=39	862129	881
700 mA	1,4- 12,0 W	2-17V					x		flat	427uF	B10A=11, B16A=18, C10A=24, C16A=39	862227	882
700 mA	7,0- 12,0 W	10-17V	x				x	x	octo	188uF	B10A=35, B16A=56, C10A=74, C16A=118	862237	884
700 mA	1,4- 18,0 W	2-26V					x		basic	147nF	B10A=17, B16A=28, C10A=37, C16A=59	180514	883
700 mA	1,4- 20,0 W	2-29V					x		flat	295uF	B10A=11, B16A=18, C10A=24, C16A=39	862228	882
700 mA	9,8- 20,0 W	14-28V	x				x		basic		B10A=11, B16A=18, C10A=24, C16A=39	862207	885
700 mA	9,1-30,0 W	13-43V					x		basic		B10A=11, B16A=18, C10A=24, C16A=39	862198	883
700 mA	20,3-35,0 W	29-57V					x		basic	359,3nF	B10A=8, B16A=14, C10A=18, C16A=29	862199	883
700 mA	19,6-40,0 W	28-56V	x				x		basic		B10A=35, B16A=56, C10A=35, C16A=56	862208	885
900mA	19,8-40,0 W	22-44V					x		basic	13.5pF	B10A=8, B16A=14, C10A=18, C16A=29	862157	883
900mA	19,8-40,0 W	22-44V	x				x		basic	30nF	B10A=35, B16A=56, C10A=35, C16A=56	862264	885
1050 mA	20,0-40,0 W	19-38V					x		basic		B10A=8, B16A=14, C10A=18, C16A=29	862201	883
1050 mA	20,0-40,0 W	19-38V	x				x		basic		B10A=35, B16A=56, C10A=35, C16A=56	862209	885
1050 mA	23,5-45,0 W	22-43V	x				x		basic	33,46nF	B10A=35, B16A=56, C10A=35, C16A=56	862210	885
1050 mA	23,1-45,0 W	22-43V	x				x		quick	33,46nF	B10A=35, B16A=56, C10A=35, C16A=56	862258	885
1300 mA	26,0-50,0 W	20-39V	x				x		basic		B10A=35, B16A=56, C10A=35, C16A=56	862211	885
1500 mA	40,0-60,0 W	27-42V	x				x		quick		B10A=25, B16A=41, C10A=25, C16A=41	862259	885

power supplies design



mini



round / octo



flat



basic



long-flat



IP

* special design


electr. data			dimmable via				usage / design			electrical limit values		power supply	
current strength	power	voltage	leading out-off	touch dimmer (push)	DALI	KNX	indoor	outdoor	design	capacitive load	max. quantity per automatic circuit breaker	item number	page
MULTI*	3,2- 20,0 W	9-40V	x				x		basic		B10A=46, B16A=74, C10A=93, C16A=149	862141	886
MULTI*	3,2- 12,0 W	15-54V		x	x		x		basic		B10A=23, B16A=37, C10A=46, C16A=74	862190	889
MULTI*	5,0- 25,0 W	20-60V		x	x		x		basic		B10A=23, B16A=37, C10A=46, C16A=74	862191	889
MULTI*	8,75- 45,0 W	21-70V		x	x		x		basic		B10A=12, B16A=20, C10A=25, C16A=40	862192	889
MULTI*	14,7- 45,0 W	14-43V		x	x		x		basic		B10A=12, B16A=20, C10A=25, C16A=40	862193	889
MULTI*	26,3- 75,5 W	25-71V		x	x		x		basic		B10A=3, B16A=5, C10A=6, C16A=10	862194	889
MULTI*	2,1- 25,2 W	6-54V		x	x		x		*		B10A=16, B16A=26, C10A=27, C16A=44	862246	890
MULTI*	0,70 - 42,00 W	2-100V		x	x		x		*		B10A=16, B16A=26, C10A=27, C16A=44	862247	890
MULTI*	1,0- 60,3 W	2-90V		x	x		x		*		B10A=15, B16A=25, C10A=20, C16A=32	862248	890

* Due to the large number of possible settings, please refer to the detailed technical data on the specified product page.


TIPS AND TRICKS FOR CURRENT-STABLE POWER SUPPLIES


In contrast to voltage-stable power supplies [CV], current-stable power supply units, often abbreviated to CC [constant current], the output current is stable. This important factors that must be taken into focus during planning and installation.

- Do not connect LEDs to CC power supply units below voltage, as this can damage them and cause them to fail after a short period of operation.
- if possible: 1 luminaire = 1 power supply
- if necessary: operate max. 2 luminaires in a series connection on one power supply unit.
However, the voltage range and the power of the power supply must be checked carefully.



Netzgerätedaten prüfen! Check driver data!





Installationshinweis für Netzgerät stromstabil [CC]: LED nicht unter Spannung anschließen!
installation instruction for power supply constant current [CC]: Don't connect LED under voltage!



DEKO-LIGHT POWER SUPPLY UNITS CC | MINI DESIGN

- Flicker-free
- Secured against short circuits and overloads
- Overheating protection



Housing	Plastic	Height	21 mm
Length	53 mm	Rated Input Voltage	220-240 V/AC
Width	27 mm	Mounting Location	Inside, Outside

Article		Output Current	Power	Output Voltage	Price
872129	■	350 mA	0.9-3.9 W	2.5-11 V/DC	€ 12.95
872130	■	500 mA	2.0-4.0 W	4-8 V/DC	€ 12.95
872131	■	700 mA	1.7-4.0 W	2.5-6 V/DC	€ 12.95



DEKO-LIGHT POWER SUPPLY UNITS CC | ROUND DESIGN

- Flicker-free
- Secured against short circuits and overloads
- Overheating protection



Housing	Plastic	Rated Input Voltage	100-240 V/AC
Height	22 mm	Mounting Location	Inside
Ø	53 mm		

Article		Output Current	Power	Output Voltage	Price
862212	■	350 mA	3.2-8.0 W	9-23 V/DC	€ 20.95
862128	■	500 mA	3.0-8.0 W	6-16 V/DC	€ 20.95
862129	■	700 mA	4.2-8.0 W	6-12 V/DC	€ 20.95



HEP POWER SUPPLY UNITS CC | G5S10W

- Compact design
- Flicker-free
- Secured against short circuits and overloads
- Overheating protection



Housing	Plastic	Height	20 mm
Length	58.1 mm	Rated Input Voltage	220-240 V/AC
Width	39.1 mm	Mounting Location	Inside

Article		Output Current	Power	Output Voltage	Price
862239		350 mA	6.0-10.0 W	17-29 V/DC	€ 26.95
862238		500 mA	6.5-10.0 W	13-32 V/DC	€ 26.95



DEKO-LIGHT POWER SUPPLY UNITS CC | FLAT DESIGN

- Flicker-free
- Secured against short circuits and overloads
- Overheating protection



Housing	Plastic	Mounting Location	Inside
Rated Input Voltage	220-240 V/AC		

Article		Output Current	Power	Output Voltage	Length	Width	Height	Price
872628		350 mA	0.7-6.0 W	2-18 V/DC	98 mm	46 mm	11 mm	€ 17.95
862223		350 mA	0.7-12.0 W	2-35 V/DC	128 mm	50 mm	13 mm	€ 24.95
862224		350 mA	0.7-20.0 W	2-57 V/DC	128 mm	50 mm	13 mm	€ 28.95
862130		500 mA	1.0-6.0 W	2-12 V/DC	98 mm	46 mm	11 mm	€ 17.95
862225		500 mA	1.0-12.0 W	2-24 V/DC	128 mm	50 mm	13 mm	€ 24.95
862226		500 mA	1.0-20.0 W	2-40 V/DC	128 mm	50 mm	13 mm	€ 28.95
862048		700 mA	1.4-6.0 W	2-9 V/DC	98 mm	46 mm	11 mm	€ 17.95
862227		700 mA	1.4-12.0 W	2-17 V/DC	128 mm	50 mm	13 mm	€ 24.95
862228		700 mA	1.4-20.0 W	2-29 V/DC	128 mm	50 mm	13 mm	€ 28.95



DEKO-LIGHT POWER SUPPLY UNITS CC | BASIC DESIGN

- Flicker-free
- Secured against short circuits and overloads
- Overheating protection



Housing	Plastic	Mounting Location	Inside
Rated Input Voltage	220-240 V/AC		

Article		Output Current	Power	Output Voltage	Length	Width	Height	Price
180512	■	350 mA	0.7-18.0 W	2-52 V/DC	115 mm	45 mm	21 mm	€ 23.95
180513	■	500 mA	1.0-18.0 W	2-38 V/DC	115 mm	45 mm	21 mm	€ 23.95
862196	■	500 mA	15.0-30.0 W	30-60 V/DC	127 mm	43 mm	28 mm	€ 26.95
862197	■	500 mA	20.0-40.0 W	40-80 V/DC	127 mm	43 mm	28 mm	€ 29.95
180514	■	700 mA	1.4-18.0 W	2-26 V/DC	115 mm	45 mm	21 mm	€ 23.95
862198	■	700 mA	14.0-30.0 W	21-43 V/DC	127 mm	43 mm	28 mm	€ 26.95
862199	■	700 mA	20.0-40.0 W	29-57 V/DC	127 mm	43 mm	28 mm	€ 29.95
862157	■	900 mA	19.0-40.0 W	22-44 V/DC	127 mm	43 mm	28 mm	€ 29.95
862201	■	1050 mA	20.0-40.0 W	19-38 V/DC	127 mm	43 mm	28 mm	€ 29.95

CC

SELV

1 CH

IP20





DEKO-LIGHT POWER SUPPLY UNITS CC DIM | MINI DESIGN

- Can be dimmed using leading-edge/trailing-edge phase dimmers
- Secured against short circuits and overloads
- Overheating protection



Housing	Plastic	Mounting Location	Inside, Outside
Rated Input Voltage	220-240 V/AC		

Article		Output Current	Power	Output Voltage	Length	Width	Height	Price
872132	■	350 mA	2.1-4.0 W	6-12 V/DC	48 mm	30 mm	20 mm	€ 19.95
872014	■	500 mA	2.0-4.0 W	4-8 V/DC	53 mm	27 mm	21 mm	€ 19.95
872134	■	700 mA	2.0-4.0 W	2.5-6 V/DC	48 mm	30 mm	20 mm	€ 19.95



DEKO-LIGHT POWER SUPPLY UNITS CC DIM | OCTO DESIGN

- Can be dimmed using leading-edge/trailing-edge phase dimmers
- Flicker-free
- Secured against short circuits and overloads
- Overheating protection



Housing	Plastic	Height	24 mm
Length	50 mm	Rated Input Voltage	220-240 V/AC
Width	48 mm	Mounting Location	Inside, Outside

Article		Output Current	Power	Output Voltage	Price
862235	■	350 mA	6.3-12.0 W	18-37 V/DC	€ 29.95
862236	■	500 mA	6.0-12.0 W	12-24 V/DC	€ 29.95
862237	■	700 mA	7.0-12.0 W	10-17 V/DC	€ 29.95



DEKO-LIGHT POWER SUPPLY UNITS CC DIM | BASIC DESIGN



- Can be dimmed using trailing-edge phase dimmers
- Flicker-free
- Short circuit, overload and overheating protection

Housing	Plastic	Mounting Location	Inside
Rated Input Voltage	220-240 V/AC		



Article		Output Current	Power	Output Voltage	Length	Width	Height	Price
862285		260 mA	6.0-12.0 W	23-46 V/DC	115 mm	39 mm	22 mm	€ 32.95
862202		350 mA	4.5-9.0 W	13-26 V/DC	115 mm	39 mm	22 mm	€ 28.95
862203		350 mA	6.3-12.0 W	18-35 V/DC	115 mm	39 mm	22 mm	€ 36.95
862204		350 mA	9.8-20.0 W	28-57 V/DC	127 mm	44 mm	28 mm	€ 39.95
862205		500 mA	10.0-20.0 W	20-40 V/DC	127 mm	44 mm	28 mm	€ 39.95
862136		500 mA	20.0-40.0 W	40-80 V/DC	166 mm	52 mm	24 mm	€ 46.95
862207		700 mA	9.8-19.6 W	14-28 V/DC	127 mm	44 mm	28 mm	€ 39.95
862208		700 mA	19.0-40.0 W	28-56 V/DC	166 mm	52 mm	24 mm	€ 46.95
862264		900 mA	19.6-40.0 W	22-44 V/DC	166 mm	52 mm	25 mm	€ 46.95
862209		1050 mA	20.0-40.0 W	19-38 V/DC	166 mm	52 mm	25 mm	€ 46.95
862210		1050 mA	23.0-45.0 W	22-43 V/DC	166 mm	52 mm	25 mm	€ 49.95
862211		1300 mA	25.0-50.0 W	20-39 V/DC	166 mm	52 mm	25 mm	€ 51.95



DEKO-LIGHT POWER SUPPLY UNITS CC DIM | QUICK DESIGN

- Particularly quick and easy to install with integrated three-pin feed-through wiring
- Push terminals for wires from 0.5 to 1.5 mm²
- Push terminals also on secondary side
- No additional installation material required
- Can be dimmed using compatible [C-compatible] trailing-edge phase dimmers
- Flicker-free
- Secured against short circuits and overloads
- Overheating protection

Housing	Plastic	Height	32 mm
Length	208 mm	Rated Input Voltage	220-240 V/AC
Width	60 mm	Mounting Location	Inside



Article		Output Current	Power	Output Voltage	Price
862257		450 mA	9.9-19.0 W	22-42 V/DC	€ 36.95
862258		1050 mA	23.1-44.1 W	22-42 V/DC	€ 46.95
862259		1500 mA	40.5-63.0 W	27-42 V/DC	€ 56.95



HEP POWER SUPPLY UNIT CC DIM | G6LT15W350LR-Z

- Can be dimmed using trailing-edge phase dimmers
- Flicker-free
- Secured against short circuits and overloads
- Overheating protection



Housing	Plastic	Width	40.4 mm
Output Current	350 mA	Height	22 mm
Power	9.1-15 W	Rated Input Voltage	220-240 V/AC
Output Voltage	26-43 V/DC	Mounting Location	Inside
Length	85 mm		

Article	Price
862266 ☐	€ 32.95




DEKO-LIGHT POWER SUPPLY UNITS CC DIM | BASIC MULTI-CURRENT

- Can be dimmed using leading-edge/trailing-edge phase dimmers
- Short-circuit-proof, overload protection, overheating protection



Housing	Plastic	Height	28.5 mm
Length	150 mm	Rated Input Voltage	200-240 V/AC
Width	42.5 mm	Mounting Location	Inside

Article	Technical Description	Price
862141 ☐	350 mA/3.20-14.0 W/9-40 V	€ 46.95
	400 mA/3.60-16.0 W/9-40 V	
	450 mA/4.00-18.0 W/9-40 V	
	500 mA/4.50-20.0 W/9-40 V	
	550 mA/5.00-19.8 W/9-36 V	
	600 mA/5.40-19.8 W/9-33 V	
	650 mA/5.90-19.5 W/9-30 V	
	700 mA/6.30-19.6 W/9-28 V	






DEKO-LIGHT MULTI-CURRENT DALI 2.0 POWER SUPPLIES DALI 2
IE-12D | IE-25D | IE-45D | IE-45HD | IE-75D

A must for every electrician: the new MULT-CC DALI 2.0 power supplies from DEKO-LIGHT are a real all-purpose weapon for universal use.

They can be controlled via DALI1 or DALI2 [fully upward and downward compatible] or via Intelli-Push. In this case, the multi-current-power supplies do not require any additional control components and are controlled by means of cost-effective 230V standard push-buttons. With the new Intelli-Push function, they also have a pioneering synchronisation option if one of the connected power supplies no longer runs synchronously with the others.

In addition, the MULTI-power supplies can also be operated undimmed without control as a reliable and universal power supplier. With a total of five models, the new DALI series covers a CC current range from 180mA to 1600mA and power ratings from 4 to 75 watts.

- plastic housing
- compact housing design
- suitable for indoor use
- flicker free
- short-circuit proof and overload protection
- overheat control
- current range adjustable via DIP switch
- DALI 2 BUS ready according to IEC 62386
- fully downward compatible with DALI 1
- dimming range: 1-100%
- dimmable via DALI or touch dimmer function [push] new Intelli-Push function [key combination synchronises all connected power supplies]
- can also be operated without control as universal power supply unit universal power supply [no dimming function]
- 3.2-75 watts and 37 CC variants in only 3 different housing sizes



controllable with DALI2, DALI1 or by touch dim using a regular 230V push-button

TOUCH-DIM / INTELLI-PUSH VIA 230V PUSH BUTTON
WITHOUT ADDITIONAL CONTROL:

- | | |
|-----------------------------|---|
| press button short | switch lamp on/off |
| press button long | dim lamp bright/dark/bright |
| press button for 15 seconds | All connected power supplies are synchronised to the same brightness. |



DEKO-LIGHT POWER SUPPLY UNITS CC DIM | MULTI-CURRENT DALI

- Can be dimmed using Dali1/Dali2
- Can be dimmed using 230 V push button [on/off, brightness]
- Intelli-Push function [shortcut synchronises all connected power supply units when needed]
- Current range adjustable using DIP switch
- Can be operated without actuation/dimming
- Dimming range 1-100 %
- Flicker-free
- Short circuit/overload protection, overheating protection

Housing	Plastic	Mounting Location	Inside
Rated Input Voltage	220-240 V/AC		

Article	Technical Description	Length	Width	Height	Price
862190	180 mA/3.2-9.8 W/18-54 V	119 mm	52 mm	22.5 mm	€ 59.95
	230 mA/4.0-12.0 W/18-52 V				
	260 mA/4.0-12.0 W/15-46 V				
	300 mA/4.5-12.0 W/15-42 V				
	350 mA/5.2-12.0 W/15-34 V				
	400 mA/6.0-12.0 W/15-30 V				
	450 mA/6.8-12.0 W/15-27 V				
862191	500 mA/7.5-12.0 W/15-24 V	119 mm	52 mm	22.5 mm	€ 64.95
	260 mA/5.0-15.5 W/20-60 V				
	350 mA/7.0-20.0 W/20-60 V				
	400 mA/8.0-24.0 W/20-60 V				
	450 mA/9.0-25.0 W/20-55 V				
	500 mA/10.0-25.0 W/20-50 V				
	550 mA/11.0-25.0 W/20-45 V				
862192	600 mA/12.0-25.0 W/20-42 V	135 mm	72 mm	24 mm	€ 69.95
	700 mA/14.0-25.0 W/20-36 V				
	350 mA/8.75-24.5 W/25-70 V				
	500 mA/12.5-35.0 W/25-70 V				
	600 mA/15.0-42.0 W/25-70 V				
	700 mA/17.5-45.0 W/25-64 V				
	800 mA/20.0-45.0 W/25-56 V				
862193	900 mA/22.5-45.0 W/25-50 V	135 mm	72 mm	24 mm	€ 69.95
	1,050 mA/25.0-45.0 W/21-43 V				
	1,050 mA/14.7-45.0 W/14-43 V				
	1,150 mA/16.1-45.0 W/14-39 V				
	1,200 mA/16.8-45.0 W/14-38 V				
	1,300 mA/18.2-45.0 W/14-35 V				
	1,400 mA/19.6-45.0 W/14-32 V				
862194	1,500 mA/21.0-45.0 W/14-30 V	159 mm	79 mm	30 mm	€ 84.95
	1,600 mA/22.4-45.0 W/14-28 V				
	1,050 mA 26.3-74.5 W/25-71 V				
	1,150 mA 28.8-74.8 W/25-65 V				
	1,200 mA 30.0-74.4 W/25-62 V				
	1,300 mA 32.5-75.5 W/25-58 V				
	1,400 mA 35.0-74.2 W/25-53 V				



MEANWELL POWER SUPPLY UNITS CC DIM | MULTI LCM DALI



- Can be dimmed using DALI2, DALI1 or Intelli-Push [Touch-Dim via 230 V button]
- Current range adjustable using DIP switch
- Can be operated without actuation/dimming
- Flicker-free



Housing	Plastic	Mounting Location	Inside
Height	23 mm		

Article	Technical Description	Length	Width	Rated Input Voltage	Price
862247	350 mA/0.7-35.0 W/2-100 V	123.5 mm	81.5 mm	180-295 V/AC	€ 104.95
	500 mA/1.0-40.0 W/2-80 V				
	600 mA/1.2-40.0 W/2-67 V				
	700 mA/1.4-40.0 W/2-57 V				
	900 mA/1.8-40.5 W/2-45 V				
862246	1,050 mA/2.1-42.0 W/2-40 V	105 mm	68 mm	180-277 V/AC	€ 89.95
	350 mA/2.1-18.9 W/6-54 V				
	500 mA/3.0-25.2 W/6-50 V				
	600 mA/3.6-25.2 W/6-42 V				
	700 mA/4.2-25.2 W/6-36 V				
862248	900 mA/5.4-25.2 W/6-28 V	123.5 mm	81.5 mm	180-295 V/AC	€ 109.95
	1,050 mA/6.3-25.2 W/6-24 V				
	500 mA/1.0-45.0 W/2-90 V				
	600 mA/1.2-54.0 W/2-90 V				
	700 mA/1.4-60.3 W/2-86 V				
	900 mA/1.8-60.3 W/2-67 V				
	1,050 mA/2.1-59.9 W/2-57 V				
	1,400 mA/2.8-59.0 W/2-42 V				



TCI POWER SUPPLY UNIT CC/CV DIM | JOLLY MD PUSH

- Dimmable with leading-edge phase dimmers
- Constant current [CC] or constant voltage [CV] can be adjusted via DIP switch
- Can be dimmed using leading-edge phase dimmers or Push [Touch-Dim via 230 V button]
- Master/slave operation of multiple power supply units via sync cable [accessory]



Housing	Plastic	Height	35 mm
Length	165 mm	Rated Input Voltage	220-240 V/AC
Width	48 mm	Mounting Location	Inside

Article	Technical Description	Price
561201	current constant	€ 94.95
	350 mA/0.7-16.5 W/2-47 V	
	500 mA/1.0-23.5 W/2-47 V	
	550 mA/1.1-25.9 W/2-47 V	
	700 mA/1.4-32.0 W/2-46 V	
	750 mA/1.5-32.0 W/2-43 V	
	voltage constant	
	12 V/10.0 W	
	24 V/20.0 W	
	28 V/22.0 W	



Accessories

561202 Sync cable



€ 10.95

electr. data		dimmable via				usage / design		electrical limit values			power supply	
current strength	power	electronic power supply	conventional transformer	leading edge	leading cut-off	indoor	outdoor	design	capacitive load	max. quantity per automatic circuit breaker	item number	page
electronic power supply units:												
12V	0,0-70,0 W	x			x	x		basic	97.79nF	B10A=8, B16A=14, C10A=18, C16A=29	180515	892
12V	0,0-105,0 W	x			x	x		basic	139.58nF	B10A=5, B16A=9, C10A=12, C16A=19	180529	892

wound transformers:

12V	11,5-20,0 W		x	x		x		*				000097	892
12V	34,5-60,0 W		x	x		x		*				000099	892
12V	43,5-75,0 W		x	x		x	x	*				000140	893
12V	60,5-105,0 W		x	x		x		*				000107	892
12V	86,5-150,0 W		x	x		x		*				000103	892
12V	86,5-150,0 W		x	x		x	x	*				000141	893
12V	115,0-200,0 W		x	x		x		*				000104	892
12V	172,5-300,0 W		x	x		x		*				000106	892
12V	172,5-300,0 W		x	x		x	x	*				000142	893
12V	287,5-500,0 W		x	x		x		*				000109	892

DEKO-LIGHT TRANSFORMER CV DIM | ULTRA HALOGEN 12 VOLT/AC

- Can be dimmed using trailing-edge phase dimmers
- 11.5 V lamp-friendly voltage
- Flicker-free
- Secured against short circuits and overloads
- Overheating protection
- 180515: 0-70 W halogen or 0-50 W LED/max. 6 LEDs
- 180529: 0-105 W halogen or 0-50 W LED/max. 6 LEDs



Housing	Plastic	Height	28 mm
Output Voltage	11.5 V/AC	Rated Input Voltage	220-240 V/AC
Length	113 mm	Mounting Location	Inside
Width	44 mm		

Article		Power	Price
180515		0.0-70.0 W	€ 17.95
180529		0.0-105.0 W	€ 22.95



ABN TRANSFORMERS CV DIM | 12 VOLT/AC

- Conventional wound transformer [L load]
- 11.5 V lamp-friendly voltage
- Can be dimmed using leading-edge phase dimmers



Housing	Plastic	Rated Input Voltage	220-240 V/AC
Output Voltage	11.5 V/AC	Mounting Location	Inside

Article		Power	Apparent power	Length	Width	Height	Price
000097		11.5-20.0 W	20 VA	82 mm	56 mm	50 mm	€ 89.95
000099		34.5-60.0 W	60 VA	100 mm	70 mm	61 mm	€ 129.95
000107		60.0-105.0 W	105 VA	107 mm	78 mm	66 mm	€ 159.95
000103		86.5-150.0 W	150 VA	130 mm	88 mm	78 mm	€ 189.95
000104		115.0-200.0 W	200 VA	130 mm	88 mm	88 mm	€ 219.95
000106		172.0-300.0 W	300 VA	130 mm	88 mm	103 mm	€ 239.95
000109		287.5-500.0 W	500 VA	177 mm	107 mm	130 mm	€ 429.95



Accessories for 000103, 000104, 000106			
000111	Housing Pyra 120-300 VA		€ 19.95
Accessories for 000107			
000110	Housing Pyra 105 VA		€ 19.95



ABN TRANSFORMERS CV DIM IP | 12 VOLT/AC

- Housing made of UV-resistant plastic
- Conventional wound transformer [L load]
- 11.5 V lamp-friendly voltage
- Primary connection line 1.9 m [H05RR-F 2x0.75 mm²]
- Secondary connection line 0.5 m [H05RR-F 2x2.5 mm²]
- Can be dimmed using leading-edge phase dimmers



Housing	Plastic	Rated Input Voltage	220-240 V/AC
Output Voltage	11.5 V/AC	Mounting Location	Inside, Outside

Article		Power	Apparent power	Length	Width	Height	Price
000140	■	43.0-75.0 W	75 VA	108 mm	81 mm	66 mm	€ 169.95
000141	■	86.0-150.0 W	150 VA	130 mm	93 mm	78 mm	€ 209.95
000142	■	172.0-300.0 W	300 VA	130 mm	93 mm	102 mm	€ 269.95

CV

1 CH

IP67





CONTROLLER

- 898 RF-Smart
 - 920 Casambi Bluetooth
 - 922 DMX controller / dimmer
 - 926 DALI PWM dimmer
- 

controller



page 901



page 904



page 906



page 907



page 908



page 913



page 914



page 917



page 918



page 919




page 920



page 920



☒ ☐
page 921



☐
page 921



☒
page 922



☒
page 923



☒
page 924



☒
page 925



☐
page 927



☐
page 928



☐
page 928



☐
page 929



☐
page 929

RF-SMART: COMPONENTS

We hereby present the multifunctional RF-smart control system from DEKO-LIGHT. It enables the switching and dimming of devices with 230V mains voltage and offers LED dimmers for LED strips with 1-5 channels from 12V to 48V voltage. Dimmers in IP67 design are available for outdoor use. The system is complemented by luminaires with an integrated RF module, such as outdoor spotlights and LED retrofit luminaires. RF-smart components can be controlled with RF radio remote controls and Zigbee 3.0 compatible radio modules. This enables control via smartphone, tablet or voice and offers comprehensive smart home functions. Installation is quick and easy.



simple control via RF remote controls



smart control via ZigBee 3.0



control via push-button

remote controls

The remote controls can be used to control the components on different channels in one or more zones. The remote controls are available as mobile versions or for wall mounting.

- 1 zone [1-2 oder 3-5 channels]
- 4 zones [1-5 channels]
- 8 zones [1-5 channels]
- power supply via 2x AAA batteries [3V]
- 230V direct connection [optional]



PIR motion detector

The PIR motion detector detects movement at an angle of 120° and a range of 1 to 7 metres - ideal for precise, energy-efficient lighting control.

- power supply via 1x CR123A battery



page 918

repeater

With the repeater, the wireless range of the remote controls can be extended by up to 30 metres.

- 230V AC



page 917

illuminants

The LED retrofit illuminants are equipped with an RF-smart radio module and fit into standard GU10 and E27 sockets.

- GU10 RGB+CCT
- E27 A60/MAX RGB+CCT
- 230V AC
- controllable via remote control and ZigBee 3.0



page 938



page 941



page 942

luminaires

The RF-smart lights are equipped with a ZigBee-compatible wireless module and can therefore also be controlled via the market-leading smart home systems from Amazon, Google & Co.

- FLOOD RGB+CCT
- SPOT RGB+CCT
- 230V AC
- IP67 / IP44
- controllable via remote control and ZigBee 3.0



page 580



page 546

Triac dimmer

The triac dimmers work with phase cut-off dimming and enable the switching and/or dimming of devices with 230V mains voltage.

- 230V AC
- IP20 / IP67
- on/off, Dimmen
- controllable via remote control, push-button and ZigBee 3.0



page 904



page 905

LED dimmer

The LED dimmers can be used to control LED stripes with 1-5 channels and 12V to 48V voltage.

- 12-48V DC
- IP20 / IP67
- on/off, dimming, automatic programmes, RGB/CCT colour settings
- controllable via remote control, push-button and ZigBee 3.0



page 906



page 907



LIVING SPACE

The choice is yours: equip existing luminaires and LED stripes with a remote-controllable dimmer, replace the illuminants with an LED retrofit version or benefit from ZigBee compatibility to control the lighting via Amazon Alexa and other smart home assistants.

- living spaces
- garden
- path lighting



TRADE

Whether in shops, a bar or on exhibition stands - with RF-smart you can set up and programme different lighting zones and control them via mobile and permanently installed remote controls.

- shop fitting
- Bar/Restaurant
- Hotel
- trade fair



COMPANY

Modern company buildings are becoming ever smarter and, thanks to the progressive networking of all components – including lighting – are making their contribution to energy efficiency and therefore also to positive sales development.

- offices
- meeting rooms
- foyers



DEKO-LIGHT RF-SMART STARTER-SET 1 230V TRIAC DIMMER + RF-REMOTE CONTROL

- Dimmable brightness
- Intelli-Push dim function [on/off, brightness] via potential-free push-button
- Can be controlled with all RF-smart wireless remote controls [2.4 GHz, range approx. 30 m]
- Can be controlled with all Zigbee 3.0 compatible controllers/apps such as Amazon Echo [Alexa], Google Assistant, Tuya [relevant gateway required, outdoor range up to 100 m]
- Program and remote control synchronisation when operating multiple RF-smart components [repeater function]
- Control of 230 V [R/C] components
- Minimum brightness adjustable in ten steps
- Adjustable switch mode [dimming disabled]
- Up to 10x LED-LM/7x LED ballast units can be connected [max. 300 W for R/C loads]
- One control zone
- Remote control requires 2x AAA batteries [not included in the scope of delivery]
- Set consisting of: 1x 843503 + 1x 843508

Housing	Plastic	Output Current	1.36 A
Length	25 mm	Rated Input Voltage	100-240 V/AC
Width	70 mm	Control	RF-Smart, Trailing-edge dimmer, ZigBee 3.0, Intelli Push-Dim
Height	70 mm		
Power	1.0-300 W	Channels	1

Article	Price
843500	€ 99.95





DEKO-LIGHT RF-SMART STARTER-SET 2 LED-DIMMER
+ RF-REMOTE CONTROL SINGLE/CCT

- Dimmable brightness and colour saturation
- Intelli-Push dim function [on/off, brightness] via potential-free push-button
- Can be controlled with all RF-smart wireless remote controls [2.4 GHz, range approx. 30 m]
- Can be controlled with all Zigbee 3.0 compatible controllers/apps such as Amazon Echo [Alexa], Google Assistant, Tuya [relevant gateway required, outdoor range up to 100 m]
- Program and remote control synchronisation when operating multiple RF-smart components [repeater function]
- Control of single/CCT components
- Flicker-free [images/videos]
- Power: max. 20 A/controller, max. 10 A/channel
- 12 V = 240 W, 24 V = 480 W, 48 V = 960 W
- One control zone
- Remote control requires 2x AAA batteries [not included in the scope of delivery]
- Set consisting of: 1x 843505 + 1x 843508

Housing	Plastic	Rated Input Voltage	12-48 V/DC
Length	24 mm	Control	RF-Smart, ZigBee 3.0, Intelli Push-Dim
Width	70 mm	Channels	1, 2
Height	70 mm		
Output Current	20 A		

Article	Price
843501	€ 99.95





DEKO-LIGHT RF-SMART STARTER-SET 3 LED-DIMMER
+ RF-REMOTE CONTROL RGB/RGBW/RGB+CCT

- Dimmable brightness and colour saturation
- 16 million adjustable colours and adjustable colour temperature
- 18 pre-installed automatic programs
- Intelli-Push dim function [on/off, brightness] via potential-free push-button
- Can be controlled with RF-smart wireless remote controls [2.4 GHz, range approx. 30 m]
- Can be controlled with all Zigbee 3.0 compatible controllers/apps such as Amazon Echo [Alexa], Google Assistant, Tuya [relevant gateway required, outdoor range up to 100 m]
- Program and remote control synchronisation when operating multiple RF-smart components [repeater function]
- Control of RGB/RGBW/RGB+CCT components
- Flicker-free [images/videos]
- Power: max. 20 A/controller, max. 10 A/channel
- 12 V = 240 W, 24 V = 480 W, 48 V = 960 W
- One control zone
- Remote control requires 2x AAA batteries [not included in the scope of delivery]
- Set consisting of: 1x 843505 + 1x 843510

Housing	Plastic	Rated Input Voltage	12-48 V/DC
Length	23 mm	Control	RF-Smart, ZigBee 3.0, Intelli Push-Dim
Width	47 mm	Channels	3, 4, 5
Height	120 mm		
Output Current	20 A		

Article	Price
843502	€ 99.95





DEKO-LIGHT RF-SMART TRIAC DIMMER 230 V

- Dimmable brightness
- Intelli-Push dim function [on/off, brightness] via potential-free push-button
- Can be controlled with RF-smart wireless remote controls [2.4 GHz, range approx. 30 m, not included in the scope of delivery]
- Can be controlled with all Zigbee 3.0 compatible controllers/apps such as Amazon Echo [Alexa], Google Assistant, Tuya [relevant gateway required, outdoor range up to 100 m]
- Program and remote control synchronisation when operating multiple RF-smart components [repeater function]
- Control of 230 V (R/C) components
- Minimum brightness adjustable in ten steps
- Adjustable switch mode [dimming disabled]
- Up to 10x LED-LM/7x LED ballast units can be connected [max. 300 W for R/C loads]

Output Current	1.36 A	Power	1.0-300 W
Housing	Plastic	Rated Input Voltage	100-240 V/AC
Length	25 mm	Control	RF-Smart, Trailing-edge dimmer, ZigBee 3.0, Intelli Push-Dim
Width	49 mm		
Height	49 mm	Channels	1

Article		Price
843503		€ 69.95





DEKO-LIGHT RF-SMART OUTDOOR TRIAC-DIMMER 230V

- Dimmable brightness
- Intelli-Push dim function [on/off, brightness] via potential-free push-button
- Can be controlled with RF-smart wireless remote controls [2.4 GHz, range approx. 30 m, not included in the scope of delivery]
- Can be controlled with all Zigbee 3.0 compatible controllers/apps such as Amazon Echo [Alexa], Google Assistant, Tuya [relevant gateway required, outdoor range up to 100 m]
- Program and remote control synchronisation when operating multiple RF-smart components [repeater function]
- Control of 230 V (R/C) components
- Minimum brightness adjustable in ten steps
- Adjustable switch mode [dimming disabled, additional load relays can be connected]
- Up to 10x LED-LM/7x LED ballast units can be connected [max. 300 W for R/C loads]
- IP67 outdoor distribution board with up to four cable entry points from 4-14 mm and two blanking plugs

Output Current	1.36 A	Power	1.0-300 W
Housing	Plastic	Rated Input Voltage	100-240 V/AC
Length	170 mm	Control	RF-Smart, Trailing-edge dimmer, ZigBee 3.0, Intelli Push-Dim
Width	155 mm		
Height	65 mm	Channels	1

Article	Price
843504	€ 89.95






DEKO-LIGHT RF-SMART LED-DIMMER 5-IN-1,
5 CHANNEL SINGLE/CCT/RGB/RGBW/RGB+CCT

- Dimmable brightness and colour saturation
- 16 million adjustable colours and adjustable colour temperature
- 18 pre-installed automatic programs
- Intelli-Push dim function [on/off, brightness] via potential-free push-button
- Can be controlled with RF-smart wireless remote controls [2.4 GHz, range approx. 30 m, not included in the scope of delivery]
- Can be controlled with all Zigbee 3.0 compatible controllers/apps such as Amazon Echo [Alexa], Google Assistant, Tuya [relevant gateway required, outdoor range up to 100 m]
- Program and remote control synchronisation when operating multiple RF-smart components [repeater function]
- Control of single/CCT/RGB/RGBW/RGB+CCT components
- Flicker-free [images/videos]
- Power: max. 20 A/controller, max. 10 A/channel
- 12 V = 240 W, 24 V = 480 W, 48 V = 960 W

Housing	Plastic	Rated Input Voltage	12-48 V/DC
Length	120 mm	Control	RF-Smart, ZigBee 3.0, Intelli Push-Dim
Width	23 mm	Channels	1, 2, 3, 4, 5
Height	47 mm		
Output Current	20 A		

Article	Price
843505 	€ 69.95






**DEKO-LIGHT RF-SMART OUTDOOR LED-DIMMER 5-IN-1,
5 CHANNEL SINGLE/CCT/RGB/RGBW/RGB+CCT**

- Dimmable brightness and colour saturation
- 16 million adjustable colours and adjustable colour temperature
- 18 pre-installed automatic programs
- Can be controlled with RF-smart wireless remote controls [2.4 GHz, range approx. 30 m, not included in the scope of delivery]
- Can be controlled with all Zigbee 3.0 compatible controllers/apps such as Amazon Echo [Alexa], Google Assistant, Tuya [relevant gateway required, outdoor range up to 100 m]
- Program and remote control synchronisation when operating multiple RF-smart components [repeater function]
- Control of single/CCT/RGB/RGBW/RGB+CCT components
- Flicker-free [images/videos]
- Power: max. 20 A/controller, max. 10 A/channel
- 12 V = 240 W, 24 V = 480 W, 48 V = 960 W
- Input/output pre-fitted on each 20 cm connecting cable

Housing	Plastic	Output Current	20 A
Length	185 mm	Rated Input Voltage	12-48 V/DC
Width	31 mm	Control	RF-Smart, ZigBee 3.0
Height	87 mm	Channels	1, 2, 3, 4, 5

Article	Price
843506	€ 109.95





DEKO-LIGHT RF-SMART RF-REMOTE CONTROL SINGLE/CCT

- Dimmable brightness
- Adjustable colour temperature, if necessary
- One control zone
- Range approx. 30 m
- Can be used as a wall-mounted or hand-held remote control [magnetic holder included in the scope of delivery]
- Very simple installation and operation
- Battery-operated with 2x AAA [not included in the scope of delivery]
- Low power consumption
- Control of single/CCT components

Housing	Plastic	Rated Input Voltage	3 V/DC
Length	24 mm	Control	RF-Smart
Ø	70 mm	Channels	1, 2

Article		Price
843508		€ 38.95
843509		€ 38.95





DEKO-LIGHT RF-SMART RF-REMOTE CONTROL RGB/RGBW/RGB+CCT

- Dimmable brightness
- Adjustable colour saturation and colour temperature, if necessary
- 16 million adjustable colours
- Automatic programs can be controlled
- One control zone
- Range approx. 30 m
- Can be used as a wall-mounted or hand-held remote control [magnetic holder included in the scope of delivery]
- Very simple installation and operation
- Battery-operated with 2x AAA [not included in the scope of delivery]
- Low power consumption
- Control of RGB/RGBW/RGB+CCT components

Housing	Plastic	Rated Input Voltage	3 V/DC
Length	24 mm	Control	RF-Smart
Ø	70 mm	Channels	3, 4, 5

Article		Price
843510		€ 38.95
843511		€ 38.95





DEKO-LIGHT RF-SMART RF REMOTE CONTROL, 3 ZONES, SINGLE

- Dimmable brightness
- Up to three different control zones
- Three storable scenes
- Range approx. 30 m
- Can be used as a stand/handheld remote control
- Very simple installation and operation
- Battery-operated with 2x AAA [not included in the scope of delivery]
- Low power consumption
- Controls single components

Housing	Plastic	Rated Input Voltage	3 V/DC
Length	143 mm	Control	RF-Smart
Width	57 mm	Channels	1
Height	44 mm		

Article	Price
843523 	€ 49.95








DEKO-LIGHT RF-SMART RF REMOTE CONTROL, 3 ZONES, SINGLE/CCT

- Dimmable brightness
- Up to three different control zones
- Three storable scenes
- Range approx. 30 m
- Can be used as a stand/handheld remote control
- Very simple installation and operation
- Battery-operated with 2x AAA [not included in the scope of delivery]
- Low power consumption
- Controls CCT and/or single components

Housing	Plastic	Rated Input Voltage	3 V/DC
Length	143 mm	Control	RF-Smart
Width	57 mm	Channels	1, 2
Height	44 mm		

Article	Price
843524 	€ 49.95



1 CH

2 CH

IP20





DEKO-LIGHT RF-SMART RF-REMOTE CONTROL, 3 ZONES
SINGLE/CCT/RGB/RGBW/RGB+CCT

- Dimmable brightness
- Can be used as a stand/handheld remote control
- Adjustable colour saturation and colour temperature, if necessary
- 16 million adjustable colours, if necessary
- Separate white light button
- Automatic program and program speed can be controlled
- Up to three different control zones
- Range approx. 30 m
- Very simple installation and operation
- Battery-operated with 2x AAA [not included in the scope of delivery]
- Low power consumption
- Controls single/CCT/RGB/RGBW/RGB+CCT components

Housing	Plastic	Rated Input Voltage	3 V/DC
Length	143 mm	Control	RF-Smart
Width	57 mm	Channels	1, 2, 3, 4, 5
Height	44 mm		

Article	Price
843525 	€ 49.95



1 CH

2 CH

3 CH

4 CH

5 CH

IP20





**DEKO-LIGHT RF-SMART RF-REMOTE CONTROL 8 ZONES
SINGLE/CCT/RGB/RGBW/RGB+CCT**

- Dimmable brightness
- Adjustable colour saturation and colour temperature, if necessary
- 16 million adjustable colours, if necessary
- Separate white light button
- Automatic program and program speed can be controlled
- Up to eight different control zones
- Range approx. 30 m
- Wall bracket included in the scope of delivery
- Very simple installation and operation
- Battery-operated with 2x AAA [not included in the scope of delivery]
- Low power consumption
- Control of single/CCT/RGB/RGBW/RGB+CCT components

Housing	Plastic	Rated Input Voltage	3 V/DC
Length	19 mm	Control	RF-Smart
Width	153 mm	Channels	1, 2, 3, 4, 5
Height	47 mm		

Article	Price
843512 	€ 49.95





DEKO-LIGHT RF-SMART RF-WALL REMOTE CONTROL 4 ZONES, 3V, SINGLE/CCT/RGB/RGBW/RGB+CCT

- Dimmable brightness
- Adjustable colour saturation and colour temperature, if necessary
- 16 million adjustable colours, if necessary
- Automatic program and program speed can be controlled
- Separate white light button
- Up to four different control zones
- Range approx. 30 m
- Magnetic wall bracket included in the scope of delivery
- Very simple installation and operation
- Battery-operated with 2x AAA [not included in the scope of delivery]
- Low power consumption
- Control of single/CCT/RGB/RGBW/RGB+CCT components

Housing	Plastic	Rated Input Voltage	3 V/DC
Length	86 mm	Control	RF-Smart
Width	86 mm	Channels	1, 2, 3, 4, 5
Height	16 mm		

Article	Price
843513 ☐	€ 69.95






DEKO-LIGHT RF-SMART RF WALL-MOUNTED REMOTE CONTROL, 4 ZONES, 230 V, SINGLE/CCT/RGB/RGBW/RGB+CCT

- Wall-mounted remote control for fixed installation
- Dimmable brightness
- Adjustable colour saturation and colour temperature, if necessary
- 16 million adjustable colours, if necessary
- Automatic program and program speed can be controlled
- Separate white light button
- Up to four different control zones
- Range approx. 30 m
- Simple operation
- Installation on 68 mm single switch box
- 230 V/AC mains operation
- Low power consumption
- Control of single/CCT/RGB/RGBW/RGB+CCT components

Housing	Plastic	Rated Input Voltage	100-240 V/AC
Length	86 mm	Control	RF-Smart
Width	86 mm	Channels	1, 2, 3, 4, 5
Height	9 mm		

Article	Price
843522 ☐	€ 74.95





DEKO-LIGHT RF-SMART RF WALL-MOUNTED REMOTE CONTROL, 8 ZONES, SINGLE/CCT/RGB/RGBW/RGB+CCT

- Dimmable brightness
- Adjustable colour saturation and colour temperature, if necessary
- 16 million adjustable colours, if necessary
- Automatic program and program speed can be controlled
- Separate white light button
- Up to eight different control zones
- Range approx. 30 m
- Delayed switch-off function [60 s]
- Simple commissioning
- Battery-operated with 2x AAA [not included in the scope of delivery]
- Numerous installation options [68 mm switch socket for operating with optional 230 V power supply]
- Low power consumption
- Control of single/CCT/RGB/RGBW/RGB+CCT components

Housing	Plastic	Rated Input Voltage	3 V/DC
Length	20 mm	Control	RF-Smart
Width	106 mm	Channels	1, 2, 3, 4, 5
Height	146 mm		

Article	Price
843514 ☐	€ 109.95



Accessories

872144	RF-smart, 230 V power supply for 8-zone wall-mounted remote control (3 V DC)
--------	--



€ 16.95



DEKO-LIGHT RF-SMART RF-REPEATER

- Extends the range of an RF remote control by up to 30 m
- Supports up to 12 remote controls and/or 12 zones simultaneously
- Suitable for outdoor and indoor use
- Incl. 1 m connecting cable with IP44 mains plug
- Compatible with all RF-smart remote controls

Housing	Plastic	Height	34 mm
Length	103 mm	Rated Input Voltage	100-240 V/AC
Width	34 mm	Control	RF-Smart

Article		Price
843507	☐	€ 34.95





DEKO-LIGHT RF-SMART PIR MOTION DETECTOR

- Can be rotated/swivelled 360°
- Self-adhesive magnetic holder included in the scope of delivery
- Very simple installation and operation
- Detection angle: 120°
- Detection range: 1-7 m
- RF range: approx. 30 m
- Switches on all RF-smart dimmers, lights/lamps (even when combined with other RF-smart remote controls)
- Motion detector can switch several dimmers, lights/lamps at the same time
- Controls the night light mode of all RF-smart dimmers, lights/lamps (843512 required for programming)
- Preset switching time and daylight threshold value
- Switching time can be adjusted (843512 required for programming)
- Daylight threshold value can be adjusted (843512 required for programming)
- Battery-operated with 1x CR123A [not included in the scope of delivery]
- Low power consumption

Housing	Plastic	Rated Input Voltage	3 V/DC
Height	56 mm	Control	RF-Smart
Ø	49 mm	Channels	1

Article	Price
843527	€ 38.95

1 CH

IP54

Accessories

843528	RF-smart, Photo battery for PIR motion detector, CR 123 A, lithium 3 V / 1600 mAh		€ 9.95
843503	RF-smart, Triac dimmer, 230 V, 300 W, IP20		€ 69.95
843504	RF-smart, Triac dimmer, 230 V, 300 W, IP67		€ 89.95
843505	RF-smart, LED dimmer 5-in-1, 5 channel, 12-48 V, 20 A, IP20		€ 69.95
843506	RF-smart, LED dimmer 5-in-1, 5 channel, 12-48 V, 20 A, IP67		€ 109.95
843532	RF-smart, GU10, Zigbee, 4 W, RGB+2700-6500 K, 25 Degree		€ 46.95
843533	RF-smart, E27, Zigbee, 6 W, RGB+2700-6500 K, 220 Grad		€ 46.95
843534	RF-smart, E27, Zigbee, 12 W, RGB+2700-6500 K, 220 Grad		€ 64.95
843518	RF-smart, Flood, 230 V, 30 W, RGB+CCT, IP65		€ 249.95
843519	RF-smart, Flood, 230 V, 50 W, RGB+CCT, IP65		€ 349.95
843520	RF-smart, Flood, 230 V, 100 W, RGB+CCT, IP65		€ 549.95
843521	RF-smart, Spot, 230 V, 25 W, RGB+CCT, IP65		€ 239.95
843530	Eventus RF-smart, 30W, RF+Zigbee, RGB/CCT, white		€ 199.95
843531	Eventus RF-smart, 30W, RF+Zigbee, RGB/CCT, black		€ 199.95




RF-SMART DMX GATEWAY

- RF gateway for operation on standard DMX controllers
- Easy to couple DMX systems to the RF-smart system
- Controls all RF-smart dimmers, lights/lamps (even when combined with other RF-smart remote controls)
- DMX start address can be adjusted via menu keys
- Status LED
- Up to 16 differently controllable zones of 1-5 channels
- Suitable for single/CCT/RGB/W+CCT components
- Occupies 80 DMX channels (regardless of actual channel usage)
- Power supply via supplied USB cable (USB power adapter 5 VDC not included in the scope of delivery)
- Does not support the RF-smart repeater function
- RF range: approx. 30 m

Housing	Plastic	Power	2.5 W
Length	188 mm	Rated Input Voltage	5 V/DC
Width	47 mm	Control	RF-Smart
Height	23 mm	Channels	1, 2, 3, 4, 5

Article	Price
843529	€ 59.95



Accessories

- 830887 USB-A plug-in power supply 5 V DC, 1,000 mA, black
- 843503 RF-smart, Triac dimmer, 230 V, 300 W, IP20
- 843504 RF-smart, Triac dimmer, 230 V, 300 W, IP67
- 843505 RF-smart, LED dimmer 5-in-1, 5 channel, 12-48 V, 20 A, IP20
- 843506 RF-smart, LED dimmer 5-in-1, 5 channel, 12-48 V, 20 A, IP67
- 843532 RF-smart, GU10, Zigbee, 4 W, RGB+2700-6500 K, 25 Degree
- 843533 RF-smart, E27, Zigbee, 6 W, RGB+2700-6500 K, 220 Grad
- 843534 RF-smart, E27, Zigbee, 12 W, RGB+2700-6500 K, 220 Grad
- 843518 RF-smart, Flood, 230 V, 30 W, RGB+CCT, IP65
- 843519 RF-smart, Flood, 230 V, 50 W, RGB+CCT, IP65
- 843520 RF-smart, Flood, 230 V, 100 W, RGB+CCT, IP65
- 843521 RF-smart, Spot, 230 V, 25 W, RGB+CCT, IP65
- 843530 Eventus RF-smart, 30W, RF+Zigbee, RGB/CCT, white
- 843531 Eventus RF-smart, 30W, RF+Zigbee, RGB/CCT, black

	€ 8.95
	€ 69.95
	€ 89.95
	€ 69.95
	€ 109.95
	€ 46.95
	€ 46.95
	€ 64.95
	€ 249.95
	€ 349.95
	€ 549.95
	€ 239.95
	€ 199.95
	€ 199.95



CASAMBI BLUETOOTH CBU-TED | 230 V SWITCHING/DIMMING

- suitable for R loads [incandescent bulb, high-voltage halogen]
- suitable for C loads [dimmable high-voltage LED, electrical power supply units]
- Power in switching range: incandescent bulb, high-voltage halogen, high-voltage LED, electrical ballasts: max. 150 W
- Output in dimming range: dimmable high-voltage LED, electrical ballasts: max. 50 W/ max. two components
- suitable for 230 V AC lights
- Install the Casambi module in a distributor box, suspended ceiling or similar
- Control and configuration via smartphone app
- Free smartphone app [Android and Apple]

Housing	Plastic	Power	1.0-50 W
Length	40.4 mm	Rated Input Voltage	220-240 V/AC
Width	36.3 mm	Control	Casambi
Height	14 mm	Channels	1

Article		Price
843008	☐	€ 144.95



1 CH

IP20





CASAMBI BLUETOOTH CBU-ASD | DALI/0-10 V | 1-10 V

- Module generates either DALI, 0-10 V or 1-10 V control signal
- Control signal for each ballast unit or power supply unit
- Install the Casambi module in a distributor box, suspended ceiling or similar
- Control and configuration via smartphone app
- Free smartphone app [Android and Apple]

Housing	Plastic	Rated Input Voltage	220-240 V/AC
Length	56.5 mm	Control	Casambi
Width	35.8 mm	Channels	1
Height	22.3 mm		

Article		Price
843011	☐	€ 149.95



1 CH

IP20






CASAMBI BLUETOOTH CBU-PWM4 | LED ONE-TO FOUR-CHANNEL DIMMER

- Module suitable for controlling 12 V/24 V LED strips
- One to four channels [WW, CW, WW-CW, RGB, RGBW]
- Power: 144 W at 24 V, 72 W at 12 V
- Install the Casambi module in a distributor box, suspended ceiling or similar
- Control and configuration via smartphone app
- Free smartphone app [Android and Apple]

Housing	Plastic	Output Current	6 A
Length	72.6 mm	Rated Input Voltage	12-24 V/DC
Width	30 mm	Control	Casambi
Height	18 mm	Channels	1, 2, 3, 4

Article	Price
843037 ☐	€ 179.95



CASAMBI BLUETOOTH WALL-MOUNTED CONTROLLER XPRESS

- Bluetooth wall controller compatible with Casambi system
- Installation with screws or adhesive tape
- No wiring required
- Battery operation [3 V button cell]
- Configured via smartphone app
- Controlled via free smartphone app [Android and Apple]

Housing	Plastic	Height	12 mm
Length	90 mm	Rated Input Voltage	3 V/DC
Width	90 mm	Control	Casambi

Article	Price
843049 ☒	€ 399.95
843050 ☐	€ 399.95





EUROLITE DMX-CONTROLLER LED COLOR CHIEF

- Simple, intuitive DMX control and programming via display
- Innovative lighting control for catering, bars, event spaces etc.
- USB connection for storing data, restoring programming and updating firmware
- Up to eight individually controllable zones/devices
- Easy control of LED strips, lights, headlights and similar with 1 to 6 colours or light effects with up to 30 channels
- Extensive, pre-installed device library with many common applications
- Further devices can be easily added manually
- Eight colour effects are directly selectable
- For each device, three additional channels can be freely allocated [for example for special functions, movements or similar]
- 24 storage locations for permanently stored light moods (scene memory)
- Cycle control for programmed running lights via music signal
- Function keys for blackout, auto, music control and strobe effect
- Total dimming, blending time between individual scenes convenient to adjust
- 3-pin XLR connection
- Operation as rack installation [19 inch/3 height units] or tabletop device
- Plug-in power supply (included in scope of delivery)

Housing	Metal	Height	85 mm
Length	482 mm	Rated Input Voltage	100-240 V/AC
Width	132 mm	Channels	1, 2, 3, 4, 5, 6

Article	Price
843047 	€ 469.95




1 CH

2 CH

3 CH

4 CH

5 CH

6 CH

IP20



Accessories

882271	DMX adapter cable CAT5 to DMX XLR plug
819066	DMX connecting cable IP20 1 m
819070	DMX connecting cable IP20 5 m
819072	DMX connecting cable IP20 10 m
843279	MULTI-LED dimmer 1-4 channels, DMX/auto/manual, 12-48 V, 20 A, flicker-free
843054	DMX/RDM 4 CH CC decoder
843273	LED dimmer R-DMX 3+1 channel/12-24 V

	€ 54.95
	€ 9.95
	€ 21.95
	€ 34.95
	€ 114.95
	€ 119.95
	€ 86.95



DEKO-LIGHT MULTI-DIMMER 4, 4-CHANNEL 3-IN-1 CONTROL/PWM DIMMER

- Simple programming of all settings via display and four-button operating menu
- 3-in-1 control: DMX/automatic/manual
- Use as 1-, 2-, 3- or 4-channel dimmer
- 24 pre-installed colour change programs [automatic mode]
- All 4 channels can be dimmed individually [manual colour mixing]
- Flicker-free 2 kHz for images and videos
- Saves the last mode after power failure (memory function)
- DMX signal/master-slave can be plugged in via CAT5
- Power:
 - 4x 60 W [240 W] at 12 V
 - 4x 120 W [480 W] at 24 V
 - 4x 240 W [960 W] at 48 V
 - max. 20 A [4x 5 A per channel]

Housing	Metal	Output Current	20 A
Length	116 mm	Rated Input Voltage	12-48 V/DC
Width	57 mm	Channels	1, 2, 3, 4
Height	26.8 mm		

Article	Price
843279 	€ 114.95

CV

DMX



1 CH

2 CH

3 CH

4 CH

IP20







DEKO-LIGHT R-DMX 3+1

- Compliant with DMX 512/1990, RDM protocol/2009
- Supports automatic DMX addressing
- Incl. top-hat-rail adapter
- Incl. 2 m CAT5 cable [RJ45]
- Flicker-free
- Connection: Screw terminals
- Power:
 - 4x 48 W [192 W] at 12 V
 - 4x 96 W [384 W] at 24 V
 - max. 16 A [4x 4 A per channel]

Housing	Metal	Output Current	16 A
Length	120 mm	Rated Input Voltage	12-24 V/DC
Width	43 mm	Channels	1, 2, 3, 4
Height	23 mm		

Article	Price
843273 	€ 86.95

CV

DMX

1 CH

2 CH

3 CH

4 CH

IP20



DECO-LIGHT LED DMX/R-DMX DIMMER 4 CC

- Simple programming of all settings via display and four-button operating menu
- Can be controlled using DMX
- Use as a one to four-channel dimmer
- Controls four independent constant-current [CC] LED lights via any conventional DMX or RDM DMX controller
- Constant current for each channel can be individually adjusted between 200 and 1,600 mA in increments of 50 mA
- Output voltage for CC-compatible lights: 1-42 V
- Flicker-free 2 kHz for images and videos
- Secured against short circuits and overloads
- Connection: Screw terminals
- Performance: max. 4x 60 W

Housing	Metal	Output Current	200-1600 mA
Length	135 mm	Rated Input Voltage	12-50 V/DC
Width	69 mm	Channels	1, 2, 3, 4
Height	36 mm		

Article	Price
843054 	€ 119.95

CC

DMX



1 CH

2 CH

3 CH

4 CH

IP20







DALI TRIAC DIMMER

- Can be controlled using DALI1/DALI2, DT6, one channel
- Can alternatively be controlled using push-dim button [8-230 V/AC]
- Dimmable brightness/trailing-edge phase dimmers
- Adjustable minimum brightness [push-dim only]
- Optimal for extending DALI systems or installing in Triac dimmable lighting due to its compact size
- LED output [C load] max. 200 W/230 V/max. 10x LM or ECG
- Halogen output [R load] 400 W/230 V, no limit on the number of lamps
- Power consumption at DALI bus: max. 2 mA

Housing	Plastic	Output Current	1.8 A
Length	45.5 mm	Rated Input Voltage	100-240 V/AC
Width	45.5 mm	Control	DALI 1 / DT6, DALI 2 /
Height	20.3 mm		DT6, Push-Dim
Power	1.0-400 W	Channels	1

Article	Price
843340 	€ 74.95



Accessories
930942 DIN rail/mounting adapter for Dali Triac dimmer



€ 1.95



DEKO-LIGHT DALI LED PWM DIMMER 12-48 V, 1/2 CHANNEL

- DT6 = occupies 2 Dali channels
- 2x 1-channel mode (WW/CW) or 1x 2 channel mode (WW-CW, CCT)
- Can be dimmed 0-100 %, overload protection, reverse polarity protection
- Flicker-free, suitable for videos (PWM 2 kHz)
- For 12 V-48 V DC (CV) LED strips/lights
- Output power: 2x 8 A = 16 A

Housing	Plastic	Rated Input Voltage	12-48 V/DC
Length	167 mm	Control	DALI 1 / DT6, DALI 2 / DT6
Width	51 mm	Channels	1, 2
Height	23 mm		
Output Current	16 A		

Article	Price
843341 ☐	€ 84.95



DEKO-LIGHT DALI DT8 LED PWM DIMMER 12-48 V, 2 CHANNEL

- DT8 = occupies 1 Dali channel
- 1x 2-channel mode (WW-CW, CCT)
- Can be dimmed 0-100 %, overload protection, reverse polarity protection
- Flicker-free, suitable for videos (PWM 2 kHz)
- For 12 V-48 V DC (CV) LED strips/lights
- Output power: 2x 8 A = 16 A

Housing	Plastic	Rated Input Voltage	12-48 V/DC
Length	167 mm	Control	DALI 1 / DT8, DALI 2 / DT8
Width	51 mm	Channels	2
Height	23 mm		
Output Current	16 A		

Article	Price
843342 ☐	€ 84.95





DEKO-LIGHT DALI LED PWM DIMMER 12-48 V, 3/4 CHANNEL

- DT6 = occupies 4 Dali channels
- 1x 3-channel mode (RGB) or 1x 4-channel mode (RGBW)
- Can be dimmed 0-100 %, overload protection, reverse polarity protection
- Flicker-free, suitable for videos (PWM 2 kHz)
- For 12 V-48 V DC (CV) LED strips/lights
- Output power: 4x 4 A = 16 A

Housing	Plastic	Rated Input Voltage	12-48 V/DC
Length	167 mm	Control	DALI 1 / DT6, DALI 2 / DT6
Width	51 mm	Channels	1, 2, 3, 4
Height	23 mm		
Output Current	16 A		

Article	Price
843343 ☐	€ 94.95



DEKO-LIGHT DALI DT8 LED PWM DIMMER 12-48 V, 4 CHANNEL

- DT8 = occupies 1 Dali channel
- 1x 4-channel mode (RGBW)
- Can be dimmed 0-100 %, overload protection, reverse polarity protection
- Flicker-free, suitable for videos (PWM 2 kHz)
- For 12 V-48 V DC (CV) LED strips/lights
- Output power: 4x 4 A = 16 A

Housing	Plastic	Rated Input Voltage	12-48 V/DC
Length	167 mm	Control	DALI 1 / DT8, DALI 2 / DT8
Width	51 mm	Channels	4
Height	23 mm		
Output Current	16 A		

Article	Price
843344 ☐	€ 94.95







ILLUMINANTS

934 MR16 / GU53

935 G9 - GU10

939 E27

943 R7s - GX53





illuminant



page 934



page 934



page 935



page 936



page 936



page 937



page 939



page 939



page 939



page 940



page 940



page 940



page 943



LEDVANCE LED MR16

Housing	Glass	Ø	50 mm
Light Beam Angle	36 Degree	Rated Input Voltage	12 V/AC/DC
Life Time L70 / B50	15000 h	CRI (Ra)	80
Length	46 mm		



Article	Housing Color	Colour Temperature	Luminous Flux	Power	Power Consumption	EEL	Price
180288	Colourless	3000 K	210 lm	2.1 W	3 kWh/1000h		€ 9.95
180258	Colourless	3000 K	345 lm	3.8 W	4 kWh/1000h		€ 9.95
180183	Colourless	4000 K	230 lm	2.6 W	3 kWh/1000h		€ 9.95
180259	Colourless	4000 K	345 lm	3.8 W	4 kWh/1000h		€ 9.95

MR16
GU5,3

CV

IP20

1 CH



LEDVANCE LED MR16 DIMMABLE

Housing	Glass	Rated Input Voltage	12 V/AC/DC
Light Beam Angle	36 Degree	CRI (Ra)	90
Life Time L70 / B50	25000 h	Control	Dimmable via optional power supply unit
Length	44 mm		
Ø	50 mm		



Article	Housing Color	Colour Temperature	Luminous Flux	Power	Power Consumption	EEL	Price
180263	Colourless	3000 K	230 lm	3.4 W	4 kWh/1000h		€ 13.95
180255	Colourless	3000 K	345 lm	5.0 W	5 kWh/1000h		€ 14.95
180289	Colourless	3000 K	621 lm	6.8 W	7 kWh/1000h		€ 19.95
180264	Colourless	4000 K	230 lm	3.4 W	4 kWh/1000h		€ 13.95
180265	Colourless	4000 K	345 lm	5.0 W	5 kWh/1000h		€ 14.95

MR16
GU5,3

CV

IP20

1 CH

LEDVANCE LED P PIN G9

Housing	Plastic	Life Time L70 / B50	15000 h
Colour Temperature	2700 K	Rated Input Voltage	220-240 V/AC
Light Beam Angle	300 Degree	CRI (Ra)	80



Article	Housing Color		Luminous Flux	Power	Power Consumption	Height	Ø	EEL	Price
180295	 Colourless		200 lm	1.9 W	2 kWh/1000h	43 mm	14 mm		€ 7.95
180287	 Colourless		320 lm	2.6 W	3 kWh/1000h	43 mm	14 mm		€ 9.95
180286	 Colourless		470 lm	4.2 W	5 kWh/1000h	49 mm	18 mm		€ 12.95

G9	CV	IP20	1 CH	
----	----	------	------	---



Technical data sheet
New in the onlineshop: The technical data sheets offer even more information:
Light and energy data, light distribution curves, dimensional drawings and more.

LEDVANCE LED GU10

Housing	Glass	Life Time L70 / B50	15000 h
Colour Temperature	2700 K	Length	54 mm
Luminous Flux	350 lm	Ø	50 mm
Power	4.3 W	Rated Input Voltage	220-240 V/AC
Light Beam Angle	36 Degree	CRI (Ra)	80
Power Consumption	5 kWh/1000h		



Article	Housing Color		Price
180275	Silver		€ 6.95

GU10

CV

IP20

1 CH

A
t
G

F



PHILIPS MASTERVALUE LED GU10 DIMMABLE

Housing	Glass	Rated Input Voltage	220-240 V/AC
Life Time L70 / B50	25000 h	CRI (Ra)	90
Length	54 mm	Control	Trailing-edge dimmer
Ø	50 mm	Channels	1



Article	Housing Color		Colour Temperature	Luminous Flux	Power	Light Beam Angle	Power Consumption	Price
180209	Silver		2700 K	270 lm	3.7 W	36 Degree	4 kWh/1000h	€ 13.95
180208	Silver		2700 K	355 lm	4.8 W	36 Degree	5 kWh/1000h	€ 14.95
180049	Silver		2700 K	355 lm	4.9 W	60 Degree	5 kWh/1000h	€ 14.95
180099	Silver		3000 K	365 lm	4.9 W	36 Degree	5 kWh/1000h	€ 14.95
180050	Silver		3000 K	365 lm	4.9 W	60 Degree	5 kWh/1000h	€ 14.95
180139	Silver		3000 K	575 lm	6.2 W	36 Degree	7 kWh/1000h	€ 20.95
180053	Silver		4000 K	380 lm	4.9 W	36 Degree	5 kWh/1000h	€ 14.95
180051	Silver		4000 K	380 lm	4.9 W	60 Degree	5 kWh/1000h	€ 14.95
180149	Silver		4000 K	575 lm	6.2 W	36 Degree	7 kWh/1000h	€ 20.95

GU10

IP20

1 CH

A
t
G

F



OSRAM PARATHOM LED GU10 DIMMABLE

Housing	Glass	Length	52 mm
Colour Temperature	2700 K	Ø	50 mm
Luminous Flux	575 lm	Rated Input Voltage	220-240 V/AC
Power	7 W	CRI (Ra)	90
Light Beam Angle	60 Degree	Control	Trailing-edge dimmer
Power Consumption	7 kWh/1000h	Channels	1
Life Time L70 / B50	25000 h		



Article	Housing Color		Price
180285	Silver	WW	€ 14.95

GU10

IP20

1 CH

A
t
G

F



Lighting design
Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.



DEKO-LIGHT RF-SMART LAMP GU10 RGB+CCT WITH RF-ZIGBEE-CONTROL

- brightness and color saturation dimmable
- 16 million colors and color temperature adjustable
- 18 automatic programs pre-installed
- program and remote control synchronization when operating several RF-smart components [repeater function]
- controllable with RF-smart radio remote controls [2.4 GHz, range approx. 30 m, not included in scope of delivery]
- controllable with all Zigbee 3.0 compatible controllers / apps such as Amazon Echo [Alexa], Google Assistant, Tuya [corresponding gateway required, outdoor range up to 100 m]

Housing	Plastic	Length	57 mm
Colour Temperature	2700-6500 K	Ø	50 mm
Luminous Flux	300 lm	Rated Input Voltage	100-240 V/AC
Power	4 W	CRI (Ra)	80
Light Beam Angle	25 Degree	Control	RF-Smart, ZigBee 3.0
Power Consumption	4 kWh/1000h	Channels	5
Life Time L70 / B50	50000 h		

Article	Housing Color	Colour Temperature	Price
843532	☐ White	2700-6500 K	€ 46.95



Accessories

843510	RF-smart, remote control, white, 1 zone, RGB/RGBW/RGB+CCT, IP20		€ 38.95
843511	RF-smart, remote control, black, 1 zone, RGB/RGBW/RGB+CCT, IP20		€ 38.95
843513	RF-smart, wall remote control, white, 3 V, 4 zones, single/CCT/RGB/W/+CCT		€ 69.95
843514	RF-smart, wall remote control, white, 8 zones, single/CCT/RGB/RGBW/RGB+CCT		€ 109.95
843522	RF-smart, wall remote control, white, 230 V, 4 zones, single/CCT/RGB/W/+CCT		€ 74.95
843523	RF-smart, Standard Remote, black, 3 zones, Single		€ 49.95
843524	RF-smart, Standard Remote, black, 3 zones, Single/CCT		€ 49.95
843525	RF-smart, Standard Remote, black, 3 zones, Single/CCT/RGB/RGBW/RGB+CCT		€ 49.95
843512	RF-smart, remote control, black, 8 zones, single/CCT/RGB/RGBW/RGB+CCT		€ 49.95
843527	RF-smart, PIR motion detector, white, 120deg/7m, 3V		€ 38.95
843529	RF-smart, DMX-Gateway, 5V DC, 16 Zonen Single/CCT/RGB/W+CCT		€ 59.95




PHILIPS MAS VLE E27 ST64 DIMMABLE

Housing	Glass	Rated Input Voltage	220-240 V/AC
Light Beam Angle	330 Degree	Control	Trailing-edge dimmer
Life Time L70 / B50	15000 h	Channels	1



Article	Housing Color	Colour Temperature	Luminous Flux	Power	Height	Ø	EEL	Price
180359	Gold	1800 K	250 lm	4.0 W	143 mm	65 mm		€ 39.95
180360	Colourless	2700 K	806 lm	5.9 W	140 mm	64 mm		€ 21.95




PHILIPS COREPRO LEDBULB E27 A60 DIMMABLE

Housing	Glass	Power Consumption	4 kWh/1000h
Colour Temperature	2700 K	Life Time L70 / B50	15000 h
Luminous Flux	470 lm	Rated Input Voltage	220-240 V/AC
Power	3.4 W	CRI (Ra)	90
Light Beam Angle	150 Degree	Control	Trailing-edge dimmer
Length	104 mm	Channels	1
Ø	60 mm		



Article	Housing Color	Price
180214	White	€ 12.95




LEDVANCE LED RETROFIT E27 A60 DIMMABLE

Housing	Glass	Power Consumption	7 kWh/1000h
Colour Temperature	2700 K	Life Time L70 / B50	15000 h
Luminous Flux	805 lm	Rated Input Voltage	220-240 V/AC
Power	7 W	CRI (Ra)	80
Light Beam Angle	320 Degree	Control	Trailing-edge dimmer
Length	105 mm	Channels	1



Article	Housing Color	Price
180253	Colourless	€ 8.95




LEDVANCE LED CLASSIC E27 A75 DIMMABLE

Housing	Glass	Power Consumption	8 kWh/1000h
Colour Temperature	2700 K	Life Time L70 / B50	15000 h
Luminous Flux	1055 lm	Rated Input Voltage	220-240 V/AC
Power	7.5 W	CRI (Ra)	80
Light Beam Angle	360 Degree	Control	Trailing-edge dimmer
Height	105 mm	Channels	1
Ø	60 mm		



Article	Housing Color	Price
180277	Colourless	€ 12.95




LEDVANCE LED CLA150 E27 DIMMABLE

Housing	Glass	Power Consumption	18 kWh/1000h
Colour Temperature	2700 K	Life Time L70 / B50	15000 h
Luminous Flux	2452 lm	Rated Input Voltage	220-240 V/AC
Power	18 W	CRI (Ra)	80
Light Beam Angle	330 Degree	Control	Trailing-edge dimmer
Height	141 mm	Channels	1
Ø	70 mm		



Article	Housing Color	Price
180361	White	€ 27.95




PHILIPS MASTER LEDSPOT E27 PAR 30 DIMMABLE

Housing	Glass	Life Time L70 / B50	25000 h
Power	9.5 W	Rated Input Voltage	220-240 V/AC
Light Beam Angle	25 Degree	CRI (Ra)	90
Length	86 mm	Control	Trailing-edge dimmer
Power Consumption	10 kWh/1000h	Channels	1



Article	Colour Temperature	Luminous Flux	Ø	Price
180278	3000 K	760 lm	95 mm	€ 42.95
180249	4000 K	820 lm	96 mm	€ 42.95





DEKO-LIGHT RF SMART LAMP E27 A60 RGB+CCT RF-ZIGBEE-CONTROLLABLE

- **Brightness and color saturation dimmable**
- **16 million colors and color temperature adjustable**
- **18 automatic programs pre-installed**
- **Program and remote control synchronization when operating several RF-smart components [repeater function]**
- **controllable with RF-smart radio remote controls [2.4 GHz, range approx. 30 m, not included in scope of delivery]**
- **controllable with all Zigbee 3.0 compatible controllers / apps such as Amazon Echo [Alexa], Google Assistant, Tuya [corresponding gateway required, outdoor range up to 100 m]**

Housing	Plastic	Power Consumption	6 kWh/1000h
Luminous Flux	550 lm	Life Time L70 / B50	50000 h
Power	6 W	Rated Input Voltage	100-240 V/AC
Light Beam Angle	220 Degree	CRI (Ra)	80
Length	100 mm	Control	RF-Smart, ZigBee 3.0
Ø	57 mm	Channels	5

Article	Housing Color	Colour Temperature	Price
843533	☐ White	2700-6500 K	€ 46.95



Accessories

843510	RF-smart, remote control, white, 1 zone, RGB/RGBW/RGB+CCT, IP20		€ 38.95
843511	RF-smart, remote control, black, 1 zone, RGB/RGBW/RGB+CCT, IP20		€ 38.95
843513	RF-smart, wall remote control, white, 3 V, 4 zones, single/CCT/RGB/W/+CCT		€ 69.95
843514	RF-smart, wall remote control, white, 8 zones, single/CCT/RGB/RGBW/RGB+CCT		€ 109.95
843522	RF-smart, wall remote control, white, 230 V, 4 zones, single/CCT/RGB/W/+CCT		€ 74.95
843523	RF-smart, Standard Remote, black, 3 zones, Single		€ 49.95
843524	RF-smart, Standard Remote, black, 3 zones, Single/CCT		€ 49.95
843525	RF-smart, Standard Remote, black, 3 zones, Single/CCT/RGB/RGBW/RGB+CCT		€ 49.95
843512	RF-smart, remote control, black, 8 zones, single/CCT/RGB/RGBW/RGB+CCT		€ 49.95
843527	RF-smart, PIR motion detector, white, 120deg/7m, 3V		€ 38.95
843529	RF-smart, DMX-Gateway, 5V DC, 16 Zonen Single/CCT/RGB/W+CCT		€ 59.95



DEKO-LIGHT RF-SMART LAMP E27 MAX RGB+CCT WITH RF-ZIGBEE-CONTROL

- brightness and color saturation dimmable
- 16 million colors and color temperature adjustable
- 18 automatic programs pre-installed
- program and remote control synchronization when operating several RF-smart components [repeater function]
- controllable with RF-smart radio remote controls [2.4 GHz, range approx. 30 m, not included in scope of delivery]
- controllable with all Zigbee 3.0 compatible controllers / apps such as Amazon Echo [Alexa], Google Assistant, Tuya [corresponding gateway required, outdoor range up to 100 m]

Housing	Plastic	Power Consumption	12 kWh/1000h
Luminous Flux	1100 lm	Life Time L70 / B50	50000 h
Power	12 W	Rated Input Voltage	100-240 V/AC
Light Beam Angle	220 Degree	CRI (Ra)	80
Length	147 mm	Control	RF-Smart, ZigBee 3.0
Ø	70 mm	Channels	5

Article	Housing Color	Colour Temperature	Price
843534	☐ White	2700-6500 K	€ 64.95



Accessories

843510	RF-smart, remote control, white, 1 zone, RGB/RGBW/RGB+CCT, IP20		€ 38.95
843511	RF-smart, remote control, black, 1 zone, RGB/RGBW/RGB+CCT, IP20		€ 38.95
843513	RF-smart, wall remote control, white, 3 V, 4 zones, single/CCT/RGB/W/+CCT		€ 69.95
843514	RF-smart, wall remote control, white, 8 zones, single/CCT/RGB/RGBW/RGB+CCT		€ 109.95
843522	RF-smart, wall remote control, white, 230 V, 4 zones, single/CCT/RGB/W/+CCT		€ 74.95
843523	RF-smart, Standard Remote, black, 3 zones, Single		€ 49.95
843524	RF-smart, Standard Remote, black, 3 zones, Single/CCT		€ 49.95
843525	RF-smart, Standard Remote, black, 3 zones, Single/CCT/RGB/RGBW/RGB+CCT		€ 49.95
843512	RF-smart, remote control, black, 8 zones, single/CCT/RGB/RGBW/RGB+CCT		€ 49.95
843527	RF-smart, PIR motion detector, white, 120deg/7m, 3V		€ 38.95
843529	RF-smart, DMX-Gateway, 5V DC, 16 Zonen Single/CCT/RGB/W+CCT		€ 59.95

ISOLED LED GX53

Housing	Aluminium	Height	28 mm
Power	6 W	Ø	75 mm
Light Beam Angle	120 Degree	Rated Input Voltage	220-240 V/AC
Power Consumption	6 kWh/1000h	CRI (Ra)	80
Life Time L70 / B50	25000 h		



Article	Housing Color	Colour Temperature	Luminous Flux	Price
180196	☐ White	 3000 K	500 lm	€ 21.95
180195	☐ White	 4000 K	525 lm	€ 21.95

GX53

IP20

1 CH



A

↑

G

D




Onlineshop
You can find more information about the products in the onlineshop:
Detailed images, videos, project reports, LDT files, EPREL data sheets and more.





ACCESSOERIES

- 948 indoor
- 951 outdoor
- 959 chemical products



□
page 948



■
page 949



■
page 950



□
page 950



■
page 951



■ ■
page 951



page 951



■
page 957



■
page 958



page 959





SAFETY SPACER

- For safe installation of downlights in ceilings with insulating material
- Creates the necessary clearance around the light to enable better air circulation
- Observe the installation requirements of the specific light.
- For ceiling installation rings from dia. 62 to 90 mm



Housing	Plastic	Ø	62 mm
Height	80 mm		

Article	Housing Color	Price
829063	 Black	€ 3.95

SOCKET GU5,3

- Heat-resistant connecting cable
- Ceramic fitting



Housing	Ceramic	Secondary Connection End	Open cables
Rated Input Voltage	12 V/AC/DC	Connection Type	Open cables
Power	35 W		

Article	Housing Color	Length	Secondary Cable Length	Price
100200	 White	150 mm	0.15 m	€ 0.95
100250	 White	500 mm	0.5 m	€ 1.65




SOCKET GU10 (PROTECTION CLASS II)

Housing	Ceramic	Primary Cable Length	15 cm
Length	150 mm	Primary Connection End	With free strand / conductor ends
Rated Input Voltage	220-240 V/AC		
Power	35 W		



Article	Housing Color	Price
100202	 White	€ 1.95



SOCKET GU10 (SAFETY CLASS I)

- With spacer and connection box
- Separate connection for protective conductors
- When using installation rings, VDE regulations require a screw connection between the spacer and installation ring

Housing	Ceramic	Power	35 W
Length	100 mm	Primary Cable Length	10 cm
Rated Input Voltage	220-240 V/AC	Primary Connection End	Screw terminal

Article	Housing Color	Price
100204	☐ White	€ 3.95



DEKO-LIGHT QUICK CONNECTION BOX 2-WAY 230 V

- Fast through-wiring of power supplies or lamps
- 3-pin quick terminal for cables from 0.5 to 1.5 mm²
- 15 cm pre-installed 3-pin cable for connecting SKI/SKII power supply units/lamps
- Quick-action closure secured with additional screw
- For inserting into ceilings with a round cut-out from 68 mm and a 25 mm ceiling cavity

Housing	Plastic	Rated Input Voltage	220-240 V/AC
Length	80 mm	Rated Current	16 A
Width	40 mm	Primary Connection End	Connection box IP20
Height	25 mm	Secondary Connection End	Open cables

Article	Housing Color	Price
930694	☒ Black	€ 5.95



TRIAC-DIMMER TRAILING EDGE

Suitable for dimming:

- **R loads (incandescent bulb) 10-350 W**
- **C loads (electrical ballasts) 10-350 W**
- **Max. five ballasts**
- **Adjustable minimum load/brightness**
- **Perfectly matched to DEKO-LIGHT power supply units**
- **Suitable for 68 mm flush-mounted/cavity wall sockets**



Housing	Plastic	Power	355 W
Length	83.5 mm	Control	Trailing-edge dimmer
Width	83.5 mm	Rated Current	1.6 A
Height	43.5 mm	Connection Type	Clamp
Rated Input Voltage	220-240 V/AC		

Article	Housing Color	Price
930060	White	€ 66.95



OVERVOLTAGE PROTECTION WITH CONTROL DISPLAY

- **Compact protection of lights in the event of problems with the mains supply**
- **Prevents premature failure**
- **In the event of a fault, the overvoltage protection trips, protecting the light by disconnecting it from the mains supply**
- **Control LED to indicate the operating status**
- **Suitable for single-phase, non-dimmable lights**
- **With mounting bracket for installation in light fittings or junction boxes**



Housing	Plastic	Rated Current	10 A
Length	37 mm	Primary Connection End	With free strand / conductor ends
Width	30 mm		
Height	20 mm	Secondary Connection End	Open cables
Rated Input Voltage	230-277 V/AC	Connection Type	Open cables

Article	Housing Color	Price
843055	Black	€ 19.95





GROUND SPIKE WITH THREADED BUSHING

- Robust design
- For anchoring surface-mounted spotlights in soil

Article	Housing Color	Housing	Thread	Length	Ø	Price
930426	Dark grey	Aluminium	M5	170 mm	33 mm	€ 9.95
700230	Black	Plastic	M5	210 mm	50 mm	€ 4.95
700229	Black	Plastic	M6	160 mm	43 mm	€ 4.95
730349	Black	Plastic	M6	210 mm	45 mm	€ 6.95
930427	Dark grey	Aluminium	M10	219 mm	43.8 mm	€ 11.95



WALL BRACKET/DISPLAY ARM

- Robust housing
- Load capacity: max. 4.5 kg
- Ideal for illuminating advertising boards on façades
- Accessories for façade lighting
- Supplied without installation materials due to wide range of possible applications

Housing	Metal	Width	150 mm
Length	800 mm	Height	100 mm

Article	Housing Color	Price
930659	Black	€ 59.95



WEIPU HQ SOCKET / PLUG | 2-PIN



Housing	Plastic	Rated Current	8.5 A
Rated Input Voltage	12-48 V/DC		

Article	Connection Type	Price
940058	WEIPU socket 2-pole	€ 13.95
940059	WEIPU socket 2-pole	€ 13.95
940060	WEIPU plug 2-pole	€ 13.95





WEIPU HQ SOCKET / PLUG | 4-PIN

Housing	Plastic	Rated Current	8.5 A
Rated Input Voltage	12-48 V/DC		



Article	Connection Type	Price
940062	WEIPU plug 4-pole	€ 14.95
940061	WEIPU socket 4-pole	€ 14.95
940063	WEIPU socket 4-pole	€ 14.95



WEIPU HQ SOCKET / PLUG | 5-PIN

Housing	Plastic	Rated Input Voltage	12-48 V/DC
Length	65 mm	Rated Current	8.5 A
Height	25 mm		



Article	Connection Type	Price
940056	WEIPU socket 5-pole	€ 15.95
940057	WEIPU plug 5-pole	€ 15.95



WEIPU HQ FEEDER CABLE | SOCKET 2-PIN

Housing	Plastic	Rated Current	8.5 A
Rated Input Voltage	12-48 V/DC	Connection Type	WEIPU socket 2-pole



Article	Length	Price
940037	1000 mm	€ 22.95
940038	3000 mm	€ 29.95
940039	5000 mm	€ 37.95





WEIPU HQ FEEDER CABLE | SOCKET 4-PIN



Housing	Plastic	Rated Current	8.5 A
Rated Input Voltage	12-48 V/DC	Connection Type	WEIPU socket 4-pole

Article	Length	Price
940033	1000 mm	€ 27.95
940034	3000 mm	€ 42.95
940035	5000 mm	€ 55.95



WEIPU HQ FEEDER CABLE | SOCKET 5-PIN



Housing	Plastic	Rated Current	8.5 A
Rated Input Voltage	12-48 V/DC	Connection Type	WEIPU socket 5-pole

Article	Length	Price
940029	1000 mm	€ 31.95
940030	3000 mm	€ 47.95
940031	5000 mm	€ 59.95



WEIPU HQ CONNECTION CABLE | 2-PIN



Housing	Plastic	Secondary Connection End	WEIPU socket 2-pole
Rated Input Voltage	12-48 V/DC	Connection Type	WEIPU plug 2-pole
Rated Current	8.5 A		

Article	Length	Price
940049	1000 mm	€ 34.95
940050	3000 mm	€ 42.95
940051	5000 mm	€ 49.95





WEIPU HQ CONNECTION CABLE | 4-PIN

Housing	Plastic	Secondary Connection End	WEIPU socket 4-pole
Rated Input Voltage	12-48 V/DC	Connection Type	WEIPU plug 4-pole
Rated Current	8.5 A		



Article	Length	Price
940045	1000 mm	€ 42.95
940046	3000 mm	€ 56.95
940047	5000 mm	€ 68.95



WEIPU HQ CONNECTION CABLE | 5-PIN

Housing	Plastic	Secondary Connection End	WEIPU socket 5-pole
Rated Input Voltage	12-48 V/DC	Connection Type	WEIPU plug 5-pole
Rated Current	8.5 A		



Article	Length	Price
940041	1000 mm	€ 47.95
940042	3000 mm	€ 60.95
940043	5000 mm	€ 72.95



WEIPU DISTRIBUTOR BOX

- for wiring 12V/24V/48V DC outdoor components
- reverse polarity protected
- Robust design
- 2 socket outlets

Housing	Plastic	Height	38 mm
Length	57 mm	Rated Input Voltage	12-48 V/DC
Width	57 mm	Rated Current	8.5 A



Article	Secondary Connection End	Connection Type	Price
730300	WEIPU socket 2-pole	WEIPU plug 2-pole	€ 64.95
730301	WEIPU socket 4-pole	WEIPU plug 4-pole	€ 68.95
940010	WEIPU socket 5-pole	WEIPU plug 5-pole	€ 78.95






MULTI OUTDOOR CABLE CONNECTOR | CONNECTION SLEEVE

- Watertight M25 cable glands
- For two cables measuring 4-14 mm
- For two to five wires measuring 0.5-4 mm²
- Adapter sleeves included in scope of delivery

Housing	PA 6.6 - Polyamide 6.6	Height	32.56 mm
Length	112.53 mm	Rated Input Voltage	12-450 V/AC
Width	29.5 mm	Rated Current	24 A

Article	Housing Color	Price
930571	■ Black, Yellow	€ 9.95

IP68
max.2m



MULTI OUTDOOR Y-SHAPED CABLE CONNECTOR | CONNECTION SLEEVE

- Waterproof M25 cable glands
- For three cables measuring 4-14 mm (adapter sleeves included in the scope of delivery)
- For two to three wires measuring 0.5-4 mm²

Housing	PA 6.6 - Polyamide 6.6	Height	32.56 mm
Length	139.71 mm	Rated Input Voltage	12-450 V/AC
Width	71.88 mm	Rated Current	24 A

Article	Housing Color	Price
930573	■ Black, Yellow	€ 10.95

IP68
max.2m



MULTI OUTDOOR CABLE DISTRIBUTOR TWO-WAY

- For wiring low-voltage and 230 V outdoor components
- Robust housing
- For wires measuring 0.5-2.5 mm²
- For two cables measuring 5-12 mm
- Versatile thanks to the adapter sleeves included in the scope of delivery
- Watertight M20 cable glands
- Cover: Quick-action coupling (screwless)

Housing	PA 6.6 - Polyamide 6.6	Rated Input Voltage	12-450 V/AC
Height	46.31 mm	Rated Current	24 A
Ø	65.33 mm		

Article	Housing Color	Price
930578	Black	€ 6.95



MULTI OUTDOOR CABLE DISTRIBUTOR TWO-WAY

- Watertight M20 cable glands
- For two cables measuring 5-12 mm
- Adapter sleeves included in scope of delivery
- For wires measuring 0.5-2.5 mm²
- Screwed cover (screws included in scope of delivery)

Housing	PA 6.6 - Polyamide 6.6	Height	42 mm
Length	125 mm	Rated Input Voltage	12-450 V/AC
Width	70 mm	Rated Current	24 A

Article	Housing Color	Price
930712	Black	€ 9.95





MULTI OUTDOOR CABLE DISTRIBUTOR FOUR-WAY

- Watertight M25 cable glands
- For two to four cables measuring 4-14 mm
- Adapter sleeves and two blanking plugs included in scope of delivery
- For wires measuring 0.5-4.0 mm²
- Screwed cover (screws included in scope of delivery)

Housing	PA 6.6 - Polyamide 6.6	Height	35.3 mm
Length	112.54 mm	Rated Input Voltage	12-450 V/AC
Width	93.3 mm	Rated Current	24 A

Article	Housing Color	Price
930575	Black	€ 11.95



MULTI OUTDOOR CABLE DISTRIBUTOR FOUR-WAY

- Watertight M25 cable glands
- For two to four cables measuring 4-14 mm
- Adapter sleeves and two blanking plugs included in scope of delivery
- For wires measuring 0.5-4.0 mm²
- Screwed cover (screws included in scope of delivery)

Housing	PA 6.6 - Polyamide 6.6	Height	35.3 mm
Length	112.54 mm	Rated Input Voltage	12-450 V/AC
Width	93.3 mm	Rated Current	24 A

Article	Housing Color	Price
930735	Black	€ 19.95





MULTI OUTDOOR CABLE DISTRIBUTORTEN-WAY

- Watertight M25 cable glands
- For two to ten cables measuring 4-14 mm
- Adapter sleeves and eight blanking plugs included in scope of delivery
- For wires measuring 0.5-4 mm²
- Screwed cover (screws included in scope of delivery)
- For wiring low-voltage and 230 V outdoor components
- Versatile thanks to the adapter sleeves included in the scope of delivery

Housing	PA 6.6 - Polyamide 6.6	Height	49.1 mm
Length	182.95 mm	Rated Input Voltage	12-450 V/AC
Width	135.3 mm	Rated Current	24 A

Article	Housing Color	Price
930574	Black	€ 39.95

IP68
max.2m



Onlineshop
 You can find more information about the products in the onlineshop:
 Detailed images, videos, project reports, LDT files, EPREL data sheets and more.

GEL ADHESIVE FOR BONDING END CAPS

- Cyanoacrylate instant adhesive
- 3 g tube
- Strong initial bond
- Excellent adhesion to almost all surfaces, such as metals, steel, stainless steel, zinc-plated steel, aluminium, plastics (e.g. ABS, GFRP, hard PC) and ceramic materials
- Curing time: 8-12 hours
- Observe the safety and application instructions



Article	Price
930593	€ 5.95

ASSEMBLY ADHESIVE

- Bond+Seal Power
- 310 ml cartridge
- Heavy-duty, elastic 1-component structural adhesive
- Excellent adhesion to almost all surfaces, such as metals, steel, stainless steel, galvanised steel, aluminium, plastics (e.g. ABS, GFRP, hard PVC) or ceramic materials
- UV-resistant
- Approved for use with foodstuffs according to NSF (NSF, P1 registered: 136996)
- High degree of initial strength
- Can be painted over with all commercially available paint systems (except alkyd resin paints)



Article	Price
930105	€ 35.95

NATURAL STONE SEALANT

- 310 ml cartridge
- Suitable for bonding profile covers and for use in wet rooms
- Does not attack the surface of LEDs/strips
- Permanently elastic
- Highly resistant to weathering, UV and ageing and excellent colour fastness
- Ideal for high loads outdoors



Article	Price
930104	€ 39.95

ELECTRIC CHARACTERISTICS

- CV
constant voltage
- CC
constant current
- SELV
safety extra-long voltage
- flicker free
- solar panel
- USB charging socket
- battery operation

LAMP

- E14
base of lamp

FUNCTIONALITY

- swivel-mounted +
rotatable and swivel-mounted + rotatable
- radiation direction

SURFACE

- NANO coating IP XX [see product description]
lotus effect: Water rolls off and takes all dirty surface
particles with it.
- surface paintable /
individual design

CONTROL

- movement sensor [IR / HF]
- presence detector
- DMX control
- dimmable
- 1 CH

4-6 CH

number of channels
- emergency power supply

SAFETY

- IP65
IP protection class
- walkable
- passable
- safety lamp control gear
- components may be installed on fixtures of materials,
the fire behavior of which is not always known.
- max. surface temperature of lamp control gear
- lights with limited surface temperature
- protection class I
- protection class II
[protective isolation]
- protection class III
[protective low voltage]



**LIGHT COLOURS / CHANNELS**

Depending on the LED equipment, different colours can be mixed with the luminaire via the individual RGB / RGBW channels.

**SELECTABLE LIGHT COLOUR**

Luminaires with this function allow the light colour to be adjusted and therefore offer a wide range of applications.

**HCL**

HCL stands for "Human Centric Lighting" and means the tuning of artificial light indoors to natural daylight and the human biorhythm.

**DIM TO WARM**

The dim-to-warm function automatically adjusts the light colour when a luminaire is dimmed. The rule is: the lower the luminous intensity, the warmer the light colour.

**COLOUR RENDERING INDEX RA**

The colour rendering index Ra describes the measure of the correspondence of the perceived light colour between an existing lighting situation and a reference light source. The higher the Ra value, the better/natural the colour rendering.

**COLOUR CONSISTENCY SDCM**

The SDCM value describes the standard deviation of an LED from the target colour location and is a measure of production-related colour differences between LEDs with identical values. The higher the value, the greater the colour deviation. The maximum valid deviation is 6 SDCM.

**UGR**

The UGR value indicates how glare-free a luminaire is, thus avoiding disturbing reflections. The lower the UGR value, the more glare-free a luminaire emits its light. Luminaires with a UGR value < 19 are suitable for office environments and workplaces.

**POWER SWITCH**

Luminaires with an integrated power switch can be switched in wattage and operated in several power levels. The power reduction enables flexible adjustment of the light intensity and is usually carried out via a dip switch on the unit.

**PHASE SWITCH**

The required phase conductor phase [L1, L2 or L3] can be selected manually using the integrated phase switch. This enables flexible installation and even load distribution in the network - particularly useful for multi-phase lighting systems or in commercial applications with multiple circuits.

**TOOL-FREE INSTALLATION**

These luminaires are delivered with pre-assembled components and can be mounted without additional tools. This saves time during installation and enables particularly simple and efficient conversion in the event of renovation or refurbishment.

**CORRIDOR FUNCTION**

With the DALI corridor function [Corridor Dim], the lighting is lowered to a predefined dimming level when no one is present and automatically raised when motion is detected.

**CONTROLLABLE VIA ...**

The luminaire can be controlled via one of the following lighting control systems: RF smart [the new control system from DEKO-LIGHT for up to eight light zones], zigbee, DALI, RF [Radio Frequency], Bluetooth, WiFi.



BEG ELIGIBLE

Eligible luminaires under the BEG programme [Federal funding for efficient buildings] have a system luminous efficacy of at least 120 lm/W [140 lm/W for LED strips] and a service life of 50,000 hours at L80 [80 % luminosity].



SUITABLE FOR VDU WORKSTATIONS

These luminaires meet the requirements of DIN standard EN 12464-1 according to the lighting of indoor workplaces. With a luminance value of $L_{65} < 3000 \text{ cd/m}^2$, the luminaires are standard-compliant for glare-free VDU workstations.



PASSABLE

Drive-on recessed luminaires are generally used outdoors and can withstand particularly high pressure loads from pedestrians, vehicles and other objects. Drive-in luminaires have an IP protection of at least IP67.



FSC CERTIFIED

FSC® ["Forest Stewardship Council®"] is an international certification system. Luminaires with FSC® certification use only wood from sustainable forestry.



THROUGH-WIRING POSSIBLE

This luminaire enables through-wiring and can be connected in series with other luminaires. The advantage: luminaires with through-wiring require only one power connection, eliminating the need for costly laying of additional cables.



LIGHT CAN BE SWITCHED SEPARATELY

Separate connection phases allow the light to be switched independently of the socket.



IP PROTECTION

The IP protection class indicates the protection of live parts against the ingress of foreign bodies and contact [first digit] and against water [second digit] with two digits. The following applies: The higher the respective digit, the higher the protection.



SEAWATER RESISTANT

These lights have been developed for use in coastal regions and can withstand the increased salt and moisture in the environment – ideal for outdoor areas near the sea.



IK IMPACT RESISTANCE

The IK value [or IK impact resistance level] indicates how shock and impact resistant a luminaire or certain components of the luminaire are. The following applies: The higher the IK value [IK00 to IK10+], the greater the protection against external mechanical stress.



MIX'N MATCH

The modular system consists of a base, cylinder housing and reflector ring. These components can be combined individually - for a luminaire to suit your taste.



NIGHTSAVER

The downward-directed light reduces scattered light and provides targeted protection against light pollution.



LIGHT COLOUR SELECTABLE

Luminaires with the designation "CCT Dip" allow you to change the light colour via a small dip switch (usually in the steps 3000K / 4000K / 5000K). With their high application flexibility, CCT Dip luminaires offer customers who are still unsure about the light colour an enormous decision-making aid - and incidentally reduce your stock requirements.

The colour temperature [light colour] is specified in Kelvin [K] and determines how the respective light is perceived.

WW = warm white light	2.300 K to 3.300 K [high red component]
NW = neutral white light	3.300 K to 5.300 K
CW = cool white / daylight white light	5.300 K to 8.000 K [high blue content]


The following guide values apply as orientation for different rooms following guide values apply:

living and sleeping are	WW
kitchen and bathroom	WW NW
offices	NW
industry	NW CW
photo studio / architectural lighting	CW




HCL

HCL stands for "Human Centric Lighting" and means the simulation of lighting situations according to the biological day-night rhythm of humans. HCL matches artificial light indoors to natural daylight and promotes well-being, mood and health. Numerous DEKO-LIGHT luminaires can already be integrated into an HCL control system to adjust the light colours to the biorhythm. In addition, several LED stripes in different light colours can be combined in one profile and thus integrated into the HCL lighting design.



DIM TO WARM

With the dim-to-warm function, you not only adjust the luminous intensity downwards, but by simultaneously changing the light colour [e.g. from 3000 to 2000 K], you obtain a room mood adapted to the new situation. LED luminaires with dim-to-warm technology can therefore be used particularly flexibly.



DALI DIMMABLE

Luminaires that can be dimmed via DALI can be perfectly integrated into lighting/property management systems. The great advantage lies in the wiring: via DALI, all luminaires in a line can be individually addressed and controlled. But this variant is also suitable for individual luminaires: DALI dimmers without an address exist for this purpose, which address the power supply unit directly. The good news: most systems on the market already have DALI interfaces.



COLOUR RENDERING INDEX RA

The colour rendering index Ra is the measure of the correspondence of the perceived light colour between an existing lighting situation and a reference light source. The smaller the deviation, the better the colour rendition. A light source with Ra 100 reproduces all colours exactly. The lower the Ra value, the less precisely the colours are reproduced.

Standard values:

Incandescent bulb, halogen lamps

LED lamps

Compact fluorescent and energy-saving lamps

Fluorescent lamps

up to Ra 100

Ra 75-95

Ra 80-89

Ra 70-85



RA 70-80 medium colour rendition



RA 80-90 good colour rendition



RA 90-100 very good colour rendition



IK VALUE

In addition to the IP protection class, you should also keep an eye on the IK value of a luminaire, which is increasingly required within the scope of tenders and for installations in public spaces. The IK value [or IK impact resistance level] indicates how impact-resistant a luminaire or certain components are. IK00 offers no protection against external mechanical stress, IK10 or IK10+ means that the luminaire can withstand a 5 or 10 kg test weight from a distance of 40 or 50 cm.

There are eleven codes, corresponding to the impact energy that a enclosure can withstand. [source: wikipedia.org]

Code	impact energy in joules	corresponds to drop height in mass	
IK00	no protection		
IK01	0,14	7 cm	- 200 g
IK02	0,20	8 cm	- 250 g
IK03	0,35	14 cm	- 250 g
IK04	0,50	20 cm	- 250 g
IK05	0,70	28 cm	- 250 g
IK06	1,0	40 cm	- 250 g
IK07	2,0	40 cm	- 500 g
IK08	5,0	25 cm	- 2000 g
IK09	10,0	20 cm	- 5000 g
IK10	20,0	40 cm	- 5000 g
IK10+	50,0	50 cm	- 10000 g

IP PROTECTION ZONES

ZONE 3 | IP23

Outside zones 0 to 2, no special IP protection is necessary, provided no cleaning with direct water irradiation takes place.

ZONE 2 | IP44



In the areas 60 cm from zone 1, IP X4 protection applies.

ZONE 1 | IP65

In the wall area of the shower as well as in the tile area exposed to IP X5 is specified for the wall area of the shower and in the tile area exposed to splash water [max. 50 V].

ZONE 0 | IP67


In bathtubs and shower trays, low-voltage [max. 12 V] is absolutely required. The minimum IP protection is IP X7 [protected against water penetration].



PROTECTION TYPES AND INSULATION CLASSES

Luminaires and other electrical appliances have a housing that protects live parts from contact, moisture or other environmental influences. This protection depends on the respective area of application. In order to have an overview of the suitable application, all devices are assigned to a classified protection type and an insulation class.

IP67



1. digit	protection against foreign bodies and contact	2. digit	protection against water
0	no protection	0	no protection
1	arge foreign bodies [Ø > 50 mm] large body parts [e.g. back of the hand]	1	protection against vertically falling dripping water
2	medium-sized foreign bodies [Ø > 12 mm] finger	2	protection against dripping water falling at an angle [up to 15°]
3	small foreign bodies [Ø > 2,5 mm] tools and wires [Ø > 2,5 mm]	3	protection against water spray up to 60° from vertical
4	granular foreign bodies [Ø > 1 mm] tools and wires [Ø > 1 mm]	4	protection against splashing water on all sides
5	dust deposit complete protection against accidental contact	5	protection against jet water
6	dust entry complete protection against accidental contact	6	protection against jet water
		7	protection against temporary immersion
		8	protection against permanent immersion



EVERYTHING IN VIEW

Optik Eberle, retail trade, conversion

design:


Optik Eberle
Marktstraße 24
75305 Neuenbürg
optik-eberle.de

scope:

consulting, lighting design, 3D visualisation, product delivery

photo:

Andris Balodis



FLEXIBLE SHOPPING EXPERIENCE

EDEKA, retail trade, refurbishment

realisation:

meerLICHT
Lunser Dorfstraße 12
27321 Thedinghausen
meerlicht.de

scope:

consulting, lighting design, 3D visualisation, product delivery

photo:

Andris Balodis



DRAWING WITH LIGHT

La Croix Architekten, office, new building

design and lighting design:


La Croix Architekten
Reiteilstraße 8
76297 Stutensee
lacroix-architekten.de

scope:

product delivery

photos:

Daniel Wieser . Architekturfotografie, Hildesheim/Karlsruhe





OFFICE AND BIORHYTHM

EMSR, office building, new building

design and realisation:


EMSR-Technik GmbH
Dieselstraße 32
61200 Wölfersheim
emsrtechnik.de

scope:

consulting, lighting design, 3D visualisation, product delivery

photo:

Roman Schinzel



MODERN LOUNGE

Base One / Mohr Solutions, Ingenieure company building, conversion

design and realisation:

OKTEC GmbH
Wiesenstraße 8/1
73054 Eislängen
ok-tec.de

lighting design:


lighting design Rottke
lichtplanung-rottke.de

scope:

consulting, product delivery

photo:

Alexander Cevolani



LINEAR AND TRANSPARENT

mars solutions, office- and event areas, core refurbishment

design and realisation:

OKTEC GmbH
Wiesenstraße 8/1
73054 Eislängen
ok-tec.de

lighting design:

lighting design Rottke
lichtplanung-rottke.de

scope:

consulting, product delivery

photo:

Alexander Cevolani



MODERN THERAPY CENTRE

Physiotherapie Senger, practice rooms, refurbishment

design and realisation:

Elektro Huml GmbH
Egmatinger Straße 9
85635 Siegersbrunn
elektro-huml.de

scope:

consulting, lighting design, 3D visualisation, product delivery

photo:

Tanja Dörfner



MORE LIGHT AND QUALITY OF LIFE

Wilhelmshilfe e.V., nursing home, refurbishment

design and realisation:

OKTEC GmbH
Wiesenstraße 8/1
73054 Eislingen
ok-tec.de

lighting design:

lighting design Rottke
lichtplanung-rottke.de

scope:

consulting, lighting design, 3D visualisation, product delivery

photo:

Alexander Cevolani



MODERN LEARNING

Mühlbachschule, educational institution, refurbishment

design:

K+H | KILIAN + PARTNER
kh-architekten.de

realisation:

Endlichhofer Elektrotechnik
endlichhofer.de

lighting design:

Ingenieurbüro Markus Reuder
reuder.de

scope:

product delivery

photo:

Daniel Wieser . Architekturfotografie, Hildesheim/Karlsruhe



LIGHT FOR THE HIDDEN CHAMPION

WIBU-Systems, company, new building

design:

Architekturbüro archis
archis.de

project development:

IBA Immobilien
iba-heinze.de

project management:

mdbm
mdbm-baumanagement.de

general contractor:

Wolff+Müller
wolff-mueller.de

electrical installation:

Prinzing Elektrotechnik
prinzing-elektro.de

scope:

consulting, lighting design, product delivery

photos:

Andris Balodis





EVERY PLATE IN THE IDEAL LIGHT

Becks, restaurant, general refurbishment

design and realisation:

SH-Lichttechnik
Wörthstraße 74
72766 Reutlingen

lighting design:

Sven Hackius

scope:

consulting, product delivery

photo:

Andris Balodis



LIGHT IN THE ROCK

Mawell, hotel, new building

design:

KommInvest GmbH & Co. KG
komm-invest.de

realisation:

FARMBAU Fertigungssysteme GmbH
farmbau.eu

lighting design:

Lichtdesign Gommel

scope:

consulting, product delivery

photo:

Andris Balodis



GARDEN DREAM IN BERLIN

private building, garden landscape, new building

design and realisation:

Gärten von Klein GmbH & Co. KG
Gut-Asselborn Nr. 1
51429 Bergisch Gladbach
gaertenvonklein.de

lighting design:

Günter Klein

scope:

consulting, product delivery

photo:

Grit Erlebach



LINEARES LICHT BIS IN DEN LETZTEN WINKEL

private building, linear light, new building

design and realisation:

BEST – Bellemann Elektro Service Team GmbH
Letzenbergstraße 37a
69231 Rauenberg-Malschenberg

lighting design:

Michael Berger
best-elektro.de

scope:

product delivery

0

000097892
000099892
000103892
000104892
000106892
000107892
000109892
000140893
000141893
000142893

1

100032193
100078192
100079192
100084185
100088185
100089185
100111564
100114564
100116564
100122185
100123188
100124189
100125188
100133566
100138189
100139188
100140182
100141182
100142183
100143182
100144182
100145183
100146184
100147184
100148185
100149182
100150182
100151184
100152195
100153195
100154188
100156195
100157195
100158190
100159194
100160194
100200948
100202948
100204949
100250948
110038106
110039106
110040106
110041106
110042106
110043106
110044107
110045107
110046107
110047107
110048107
110049107
110050108
110051108
110052108
110053108
110054108
110055108
110056109
110057109
110058109
110059109
110060109
110061109

12241696
12241796
180049936
180050936
180051936
180053936
180099936
180139936
180149936
180183934
180195943
180196943
180208936
180209936
180214939
180249940
180253939
180255934
180258934
180259934
180263934
180264934
180265934
180275936
180277940
180278940
180285937
180286935
180287935
180288934
180289934
180295935
180359939
180360939
180361940
180512883
180513883
180514883
180515892
180529892
18073051
18073151
18073252
18073352
18073453
18073553
18073653
18073753
18074153
18074253
18074353

3

341183200
341184200
341194198
341195198
341196198
341200199
341201199
341202199
341203199
341236219
341237219
341242218
341243218
341249200
341250200
341333222
341334222
341335222
341336222
341337220, 223
341338220, 223
341339220, 223
341340220, 223
341341202

341342202
341343204
341344204
341345224
341346224
341347224
341348224
341349224
341350224
341351224
341352224
342146254
342147254
34214848
34215048
34217742
34217842
34217942
34218042
34218142
34218242
34218936, 40
34219036, 40
34219136, 40
34219236, 40
34219336, 40
34219436, 40
34219536, 40
34219636, 40
34219736, 40
34219836, 40
34219936, 40
34220036, 40
34220134
34220234
34220334
34220434
34220534
34220634
34220734
34220834
34220934
34221034
34221134
34221234
34221340
34221440
34221539
34221639
342219248
342220248
342221248
342228264
342229264
342230264
342231266
342232266
342233266
34223740
34223840
34223939
34224039
34224140
34224240
34224344
34224444
34224544
34224644
34224745
34224845
342251246
342252246
342253246
34225446
34225546
34225646
34225746
343016260

343022258
343025233
343026233
343030256
343032257
343034256
343035257
343037228
343038228
343039230
343040230
346015232
346016232
346025454
346026234
346027234
346028234
346032454
346033454
346034454
346035454
346036454
346037454
346063265
346064265
346065265
346066267
346067267
346068267
346086229
346087229
346088230
346089230
34800197
34800297
34800497
34800597
34802296
34802396
34802496
34802596
34805170
34805270
348069522
348070522
348071523
348072523
348099102
34810776
34812277
34812378
34812474
34812575
34812779
348128102
34815380
34815480
34815580
34815680
34815780
34815880
34815980
34816080
34816182
34816282
34816382
34816482
34816582
34816682
34816782
34816882
34817575
34817679
34817778
34817877
34817974
34818062
34818162

348182.....	62	348275.....	94	565380.....	117	565458.....	122
348183.....	62	348276.....	66	565381.....	117	565459.....	123
348184.....	62	348277.....	66	565382.....	117	565460.....	123
348185.....	62	348278.....	66	565383.....	117	565461.....	123
348186.....	60	348279.....	68	565384.....	117	565462.....	123
348187.....	60	348280.....	68	565385.....	124	565463.....	131
348188.....	60	348281.....	68	565386.....	124	565464.....	131
348189.....	60	348285.....	69	565387.....	124	565465.....	131
348190.....	60	348286.....	69	565388.....	118	565466.....	131
348191.....	60			565389.....	118	565467.....	131
348192.....	60			565390.....	118	565468.....	131
348193.....	60	5		565391.....	118	565469.....	131
348194.....	60	561201.....	890	565392.....	118	565470.....	131
348195.....	60	563009.....	212	565393.....	118	565471.....	131
348196.....	60	563010.....	212	565394.....	118	565472.....	131
348197.....	60	563011.....	212	565395.....	118	565473.....	131
348198.....	58	565007.....	166	565396.....	118	565474.....	131
348199.....	58	565010.....	166	565397.....	118	565475.....	131
348200.....	58	565172.....	174	565398.....	118	565476.....	131
348201.....	58	565173.....	174	565399.....	118	565477.....	131
348202.....	58	565180.....	167	565400.....	118	565478.....	131
348203.....	58	565181.....	167	565401.....	118	565479.....	131
348204.....	58	565182.....	168	565402.....	118	565480.....	131
348205.....	58	565183.....	168	565403.....	119	565481.....	132
348206.....	58	565184.....	169	565404.....	119	565482.....	132
348207.....	58	565185.....	169	565405.....	119	565483.....	132
348208.....	58	565193.....	126	565406.....	119	565484.....	132
348209.....	58	565194.....	127	565407.....	119	565485.....	132
348210.....	76	565220.....	178	565408.....	146	565486.....	132
348213.....	84	565221.....	178	565409.....	146	565487.....	132
348214.....	84	565245.....	129	565410.....	158	565488.....	132
348215.....	84	565246.....	129	565411.....	158	565489.....	132
348216.....	84	565250.....	152	565412.....	158	565490.....	132
348223.....	85	565251.....	152	565413.....	158	565491.....	132
348224.....	85	565252.....	152	565414.....	158	565492.....	132
348225.....	85	565282.....	128	565415.....	158	565493.....	132
348226.....	85	565283.....	128	565416.....	158	565494.....	132
348233.....	77	565284.....	128	565417.....	158	565495.....	132
348234.....	77	565285.....	128	565418.....	158	565496.....	132
348235.....	78	565315.....	156	565419.....	158	565497.....	132
348236.....	78	565316.....	156	565420.....	158	565498.....	132
348237.....	86	565317.....	156	565421.....	158	565499.....	133
348238.....	86	565318.....	156	565422.....	160	565500.....	133
348239.....	87	565327.....	172	565423.....	160	565501.....	133
348240.....	87	565328.....	172	565424.....	160	565502.....	133
348241.....	88	565329.....	172	565425.....	160	565503.....	133
348242.....	88	565332.....	156	565426.....	161	565504.....	133
348243.....	89	565337.....	124	565427.....	161	565505.....	133
348244.....	89	565338.....	124	565428.....	161	565506.....	133
348245.....	90, 93	565339.....	124	565429.....	161	565507.....	133
348246.....	90, 93	565342.....	150	565430.....	162	565508.....	133
348247.....	90, 93	565343.....	148	565431.....	162	565509.....	133
348248.....	90, 93	565344.....	151	565432.....	162	565510.....	133
348249.....	90, 93	565351.....	151	565433.....	162	565511.....	133
348250.....	90, 93	565352.....	170	565434.....	162	565512.....	133
348251.....	92	565353.....	170	565435.....	162	565513.....	133
348252.....	92	565354.....	150	565436.....	162	565514.....	133
348253.....	92	565355.....	116	565437.....	162	565515.....	133
348254.....	92	565356.....	116	565438.....	162	565516.....	133
348255.....	92	565357.....	116	565439.....	162	565517.....	134
348256.....	92	565358.....	116	565440.....	162	565518.....	134
348258.....	98	565359.....	116	565441.....	162	565519.....	134
348259.....	98	565360.....	116	565442.....	163	565520.....	134
348260.....	98	565361.....	148	565443.....	163	565521.....	134
348261.....	101	565362.....	156	565444.....	163	565522.....	134
348262.....	101	565363.....	156	565445.....	163	565523.....	134
348263.....	101	565364.....	156	565446.....	164	565524.....	134
348264.....	94	565365.....	156	565447.....	164	565525.....	134
348265.....	94	565366.....	156	565448.....	164	565526.....	134
348266.....	94	565371.....	116	565449.....	164	565527.....	134
348267.....	94	565372.....	116	565450.....	121	565528.....	134
348268.....	94	565373.....	116	565451.....	121	565529.....	134
348269.....	94	565374.....	116	565452.....	121	565530.....	134
348270.....	94	565375.....	116	565453.....	121	565531.....	134
348271.....	94	565376.....	116	565454.....	121	565532.....	134
348272.....	94	565377.....	116	565455.....	122	565533.....	134
348273.....	94	565378.....	116	565456.....	122	565534.....	134
348274.....	94	565379.....	116	565457.....	122	565535.....	135

700230	951	707149	402	707244	430	710066	356, 386
707036	423	707150	402	707245	430	710067	356, 386
707037	423	707151	402	707246	416	710068	356, 386
707038	423	707152	402	707247	416	710069	348
707039	423	707153	402	707248	416	710070	348
707040	422	707154	402	707249	326	710071	348
707041	422	707155	322	707250	326	710077	356, 386
707042	422	707156	322	707251	413	710078	359, 389
707043	422	707161	440	707252	413	710079	356, 386
707044	420	707162	440	707253	325	710082	361, 391
707054	423	707163	331	707254	325	710083	361, 391
707055	423	707164	331	707255	413	710084	359, 389
707056	422	707165	332	707256	413	710085	359, 389
707057	422	707166	332	707257	325	710086	359, 389
707079	414	707167	332	707258	325	710087	359, 389
707080	414	707168	332	710000	346	710088	359, 389
707081	414	707175	333	710001	346	710094	360, 390
707082	442	707176	333	710002	346	710095	360, 390
707083	442	707177	333	710003	346	710096	360, 390
707090	421	707178	333	710004	346	710097	364
707091	421	707183	438	710005	346	710098	364
707092	421	707184	438	710006	346	710099	364
707093	421	707185	328	710007	346	710103	356, 386
707094	418	707186	328	710008	346	710104	357, 387
707095	418	707187	329	710009	350	710105	357, 387
707096	418	707188	329	710010	350	710106	357, 387
707097	418	707189	406	710011	350	710107	348, 379
707098	418	707190	406	710012	350	710500	376
707099	418	707191	406	710013	350	710501	376
707100	418	707192	406	710014	350	710502	376
707101	418	707193	407	710015	352	710503	376
707102	418	707194	407	710016	352	710504	376
707103	418	707195	408	710017	352	710505	376
707104	418	707196	408	710018	352, 382	710506	378
707105	418	707197	408	710019	352, 382	710507	378
707106	418	707198	408	710020	352, 382	710508	378
707107	418	707199	409	710024	366, 394	710509	378
707108	418	707200	409	710025	366, 394	710510	378
707109	418	707201	330	710026	366, 394	710511	378
707110	403	707202	330	710027	354	710512	377
707111	403	707203	441	710028	354	710513	377
707112	403	707204	441	710029	354	710514	380
707113	403	707205	406	710030	354	710515	380
707114	403	707206	406	710031	354	710516	380
707115	403	707207	406	710032	354	710517	380
707116	436	707208	406	710033	355	710520	381
707117	436	707209	407	710034	355	710521	381
707118	436	707210	407	710035	355	710523	381
707119	436	707211	334	710036	353	710524	381
707120	436	707212	334	710037	353	710525	382
707121	436	707213	439	710038	353	710526	382
707122	436	707214	439	710039	351	710527	383
707123	436	707215	335	710040	351	710528	383
707124	432	707216	335	710041	351	710530	384
707125	432	707217	433	710042	351	710531	384
707126	432	707218	433	710043	351	710532	384
707127	432	707219	410	710044	351	710533	384
707128	432	707220	410	710045	349	710535	385
707129	432	707221	410	710046	349	710536	385
707130	399	707222	410	710047	349	710538	356, 386
707131	420	707223	411	710048	360, 390	710539	394
707132	440	707224	411	710049	360, 390	710540	394
707133	440	707226	294, 296	710050	360, 390	720000	308
707134	398	707227	294, 296	710051	363, 393	720001	308
707135	398	707228	294, 296	710052	363, 393	720002	308
707136	398	707229	298	710053	363, 393	720003	308
707137	398	707230	298	710054	366, 395	720004	308
707138	399	707231	298	710055	366, 395	720005	308
707139	399	707232	435	710056	366, 395	720006	310
707140	399	707233	435	710057	358, 388	720007	310
707141	408	707234	431	710058	358, 388	720008	310
707142	408	707235	431	710059	358, 388	720009	310
707143	408	707238	431	710060	367, 395	720010	311
707144	408	707239	431	710061	367, 395	720011	311
707145	409	707240	434	710062	367, 395	720012	312
707146	409	707241	434	710063	357, 387	720013	312
707147	402	707242	434	710064	357, 387	720014	312
707148	402	707243	434	710065	357, 387	720015	312

720016	313	730498	466	731191	494	733045	476
720017	313	730499	468	731192	494	733046	458
720018	313	730500	468	731193	496	733049	456
720019	313	730501	468	731194	496	733050	456
720020	315	730502	468	731195	496	733054	536
720021	315	730503	468	731196	490	733055	536
720022	314	730504	468	731197	490	733064	540
720023	314	730505	468	731198	490	733065	540
720024	315	730506	468	731199	493	733066	538
720025	315	730509	280	731200	493	733067	538
720026	314	730510	280	731201	493	733068	480
720027	314	730511	280	731202	487	733069	480
720028	316	731015	505	731203	487	733070	542
720029	316	731019	505	731204	487	733071	542
720030	316	731020	505	731205	486	733072	472
720031	316	731024	505	731206	486	733073	472
720032	318	731025	505	731207	486	763025	526
720033	318	731026	505	731208	492	763026	528
720034	318	731029	505	731209	492		
720035	318	731030	505	731210	492		
720036	317	731031	499	731211	484	8	
720037	317	731060	513	731212	484	829063	948
720038	316	731099	510	731213	484	836011	532
720039	316	731100	510	731214	485	836014	532
730007	465	731116	459	731215	485	836930	532
730009	464	731122	457	731216	485	836931	532
730032	465	731127	508	731217	489	840122	803
730034	498	731129	512	731218	489	840124	820
730209	572	731130	503	731219	489	840147	814
730248	572	731131	503	731220	495	840158	806
730255	570	731133	502	731221	495	840159	806
730262	574	731134	512	731222	495	840164	801
730266	571	731135	512	731223	506	840165	801
730267	571	731136	512	731224	506	840166	801
730276	568	731138	514	731225	507	840167	801
730289	570	731139	515	731226	507	840175	807
730292	574	731140	514	732049	573	840178	814
730296	567	731141	515	732050	573	840179	814
730300	954	731144	502	732064	582	840180	814
730301	954	731151	500	732071	556	840186	811
730330	513	731153	501	732072	556	840187	811
730331	513	731154	501	732079	557	840192	820
730336	565	731155	501	732080	557	840193	820
730349	951	731156	501	732094	549	840194	820
730408	522	731157	500	732095	549	840210	807
730419	284	731158	518	732096	583	840236	817
730424	284	731159	518	732097	583	840239	815
730425	284	731160	286	732098	583	840254	812
730432	574	731161	286	732102	583	840256	813
730434	574	731162	286	732105	582	840267	807
730447	562	731163	288	732108	550	840276	810
730450	285	731164	288	732109	551	840283	829
730454	569	731165	288	732110	552	840285	835
730455	285	731166	289	732127	550	840286	836
730459	563	731167	289	732128	551	840287	831
730470	561	731168	289	732129	552	840288	833
730474	560	731169	491	732137	553	840289	837
730475	560	731170	491	732143	573	840290	831
730478	560	731171	491	732147	581	840291	804
730479	560	731172	491	732148	581	840293	856
730480	576	731173	491	732149	581	840294	856
730481	576	731174	491	732150	581	840295	856
730482	576	731175	497	732151	581	840296	796
730483	280	731176	497	732152	581	840304	796
730484	282	731177	497	732156	274	840308	823
730485	283	731178	497	732157	277	840309	823
730486	280	731179	497	732158	274	840317	853
730487	282	731180	497	732159	277	840318	852
730488	283	731181	488	732160	548	840319	853
730489	280	731182	488	732161	548	840320	852
730490	282	731183	488	732162	270	840321	799
730491	283	731184	488	732163	272	840322	799
730492	470	731185	488	733004	478	840323	798
730493	470	731186	488	733040	474	840324	798
730494	470	731187	494	733041	474	840331	821
730495	466	731188	494	733042	474	840332	821
730496	466	731189	494	733043	476	840333	822
730497	466	731190	494	733044	476	840334	822

840337	852	840450	844	862163	870	862274	873
840338	853	840451	845	862164	870	862275	875
840339	852	840452	844	862165	870	862276	875
840340	853	840453	845	862166	870	862277	873
840349	809	840454	846	862167	870	862278	873
840350	808	840455	847	862168	870	862280	872
840351	825	840456	846	862172	869	862281	872
840352	824	840457	847	862173	869	862282	872
840353	816	840458	846	862180	365	862283	872
840373	818	840459	847	862181	365	862285	885
840374	794	840460	846	862182	365	872014	884
840375	797	840461	847	862183	365	872045	872
840376	827	840462	846	862184	365	872046	872
840378	819	840463	847	862185	365	872082	870
840386	855	840464	846	862190	889	872083	870
840387	855	840465	847	862191	889	872084	870
840388	855	843008	920	862192	889	872085	870
840389	855	843011	920	862193	889	872086	870
840390	855	843037	921	862194	889	872087	870
840391	855	843047	922	862196	883	872088	870
840392	856	843049	921	862197	883	872089	870
840393	850	843050	921	862198	883	872091	870
840394	850	843054	925	862199	883	872093	870
840395	850	843055	950	862201	883	872094	870
840396	851	843273	924	862202	885	872097	871
840397	851	843279	923	862203	885	872098	871
840398	851	843340	927	862204	885	872099	871
840399	848	843341	928	862205	885	872100	871
840400	849	843342	928	862207	885	872101	871
840401	850	843343	929	862208	885	872102	871
840402	850	843344	929	862209	885	872103	871
840403	850	843500	901	862210	885	872104	871
840404	851	843501	902	862211	885	872105	871
840405	851	843502	903	862212	881	872106	871
840406	851	843503	904	862220	873	872107	871
840407	848	843504	905	862221	873	872108	871
840408	849	843505	906	862222	873	872109	876
840409	787	843506	907	862223	882	872110	876
840410	787	843507	917	862224	882	872111	876
840411	787	843508	908	862225	882	872112	876
840412	787	843509	908	862226	882	872113	876
840413	788	843510	909	862227	882	872114	876
840414	788	843511	909	862228	882	872115	876
840415	788	843512	913	862229	868	872125	871
840416	788	843513	914	862230	868	872126	875
840417	839	843514	916	862231	869	872127	868
840418	839	843518	580	862232	869	872128	868
840419	839	843519	580	862233	869	872129	881
840420	790	843520	580	862234	869	872130	881
840421	790	843521	546	862235	884	872131	881
840422	790	843522	915	862236	884	872132	884
840423	790	843523	910	862237	884	872134	884
840424	790	843524	911	862238	882	872135	874
840425	790	843525	912	862239	882	872136	874
840426	790	843527	918	862240	873	872137	874
840427	790	843529	919	862241	873	872138	874
840428	790	843530	425	862242	873	872142	874
840429	790	843531	425	862246	890	872143	874
840430	792	843532	938	862247	890	872145	870
840431	792	843533	941	862248	890	872146	876
840432	792	843534	942	862253	875	872147	876
840433	792	862048	882	862254	875	872148	876
840434	842	862093	869	862255	875	872628	882
840435	843	862094	869	862256	875	872629	869
840436	842	862121	869	862257	885	872630	869
840437	843	862122	869	862258	885		
840438	842	862123	869	862259	885		
840439	843	862124	869	862262	875		
840440	850	862125	869	862263	875		
840441	851	862126	869	862264	885		
840442	850	862127	870	862265	869		
840443	851	862128	881	862266	886		
840444	850	862129	881	862268	872		
840445	851	862130	882	862269	872		
840446	848	862136	885	862270	869		
840447	849	862141	886	862271	869		
840448	844	862157	883	862272	869		
840449	845	862162	870	862273	875		
						9	
						930060	950
						930104	959
						930105	959
						930301..95, 225, 231, 327, 417	
						930302..95, 225, 231, 327, 417	
						930303..95, 225, 231, 327, 417	
						930345	856
						930346	856
						930347	856
						930348	856

930349.....	856	930624.....	455	940010.....	954	950267.....	596
930350.....	856	930625.....	455	940029.....	953	950268.....	596
930366..95, 225, 231, 327, 417		930626.....	455	940030.....	953	950269.....	596
930405.....	856	930627.....	455	940031.....	953	950270.....	597
930406.....	856	930628.....	455	940033.....	953	950271.....	597
930413.....	527	930629.....	455	940034.....	953	950272.....	597
930414.....	527	930630.....	455	940035.....	953	950273.....	597
930415.....	527	930631.....	455	940037.....	952	950274.....	597
930416.....	527	930659.....	951	940038.....	952	950275.....	597
930417.....	527	930694.....	949	940039.....	952	950276.....	597
930418.....	527	930712.....	956	940041.....	954	950277.....	597
930419.....	527	930735.....	957	940042.....	954	950278.....	597
930420.....	527	930842.....	214	940043.....	954	950279.....	597
930421.....	527	930843.....	215	940045.....	954	950280.....	597
930422.....	527	930860.....	214	940046.....	954	950281.....	597
930423.....	527	930861.....	215	940047.....	954	950282.....	597
930424.....	527	930908.....	50	940049.....	953	950283.....	597
930426.....	951	930909.....	50	940050.....	953	950284.....	597
930427.....	951	930913.....	54	940051.....	953	950285.....	597
930461.....	529	930914.....	54	940056.....	952	950286.....	597
930468.....	529	930965.....	50	940057.....	952	950287.....	597
930469.....	529	930966.....	50	940058.....	951	950918.....	598
930470.....	529	930967.....	113, 165	940059.....	951	950919.....	598
930471.....	529	930968.....	113, 165	940060.....	951	950920.....	598
930472.....	529	930969.....	113, 165	940061.....	952	950921.....	598
930473.....	529	930970.....	113, 165	940062.....	952	950922.....	598
930474.....	529	930971.....	113, 165	940063.....	952	950923.....	598
930475.....	529	930972.....	113, 165	950216.....	594	950924.....	598
930476.....	529	930973.....	113, 165	950217.....	594	950925.....	598
930477.....	529	930974.....	113, 165	950218.....	594	950926.....	598
930478.....	529	930975.....	113, 165	950219.....	594	950927.....	598
930480.....	214	930976.....	113, 165	950220.....	594	950928.....	598
930481.....	215	931007.....	209	950221.....	594	950929.....	598
930482.....	214	931009.....	209	950222.....	594	950930.....	598
930483.....	214	931010.....	211	950223.....	594	950931.....	598
930484.....	214	931012.....	211	950224.....	594	950932.....	598
930485.....	214	931013.....	209	950225.....	594	950933.....	598
930486.....	214	931015.....	209	950226.....	594	950934.....	598
930487.....	214	931016.....	211	950227.....	594	950935.....	598
930488.....	214	931018.....	211	950228.....	594	970000.....	666
930489.....	214	931019.....	209	950229.....	594	970001.....	666
930490.....	214	931021.....	209	950230.....	594	970003.....	666
930491.....	214	931022.....	211	950231.....	594	970005.....	666
930492.....	214	931024.....	211	950232.....	594	970008.....	666
930493.....	214	931025.....	209	950233.....	594	970020.....	670
930494.....	215	931027.....	209	950234.....	595	970021.....	670
930495.....	215	931028.....	211	950235.....	595	970023.....	670
930496.....	215	931030.....	211	950236.....	595	970025.....	670
930497.....	215	931031.....	209	950237.....	595	970028.....	670
930498.....	215	931033.....	209	950238.....	595	970040.....	674
930499.....	215	931034.....	211	950239.....	595	970041.....	674
930500.....	215	931036.....	211	950240.....	595	970043.....	674
930501.....	215	931037.....	209	950241.....	595	970045.....	674
930502.....	215	931039.....	209	950242.....	595	970048.....	674
930503.....	215	931040.....	211	950243.....	595	970060.....	678
930504.....	215	931042.....	211	950244.....	595	970061.....	678
930505.....	215	931043.....	113, 165	950245.....	595	970063.....	678
930512.....	814	931044.....	113, 165	950246.....	595	970065.....	678
930517.....	817	931045.....	113, 165	950247.....	595	970068.....	678
930571.....	955	931046.....	113, 165	950248.....	595	970081.....	662
930573.....	955	931047.....	113, 165	950249.....	595	970085.....	662
930574.....	958	931048.....	113, 165	950250.....	595	970101.....	668
930575.....	957	931049.....	113, 165	950251.....	595	970103.....	668
930578.....	956	931050.....	113, 165	950252.....	596	970105.....	668
930593.....	959	931051.....	113, 165	950253.....	596	970108.....	668
930611.....	454	931052.....	113, 165	950254.....	596	970120.....	672
930612.....	454	931053.....	95, 327, 417	950255.....	596	970121.....	672
930613.....	454	931054.....	95, 327, 417	950256.....	596	970123.....	672
930614.....	454	931055.....	95, 327, 417	950257.....	596	970125.....	672
930615.....	454	931056.....	95, 327, 417	950258.....	596	970128.....	672
930616.....	454	931057.....	95, 327, 417	950259.....	596	970140.....	676
930617.....	454	931058.....	95, 327, 417	950260.....	596	970141.....	676
930618.....	455	931059.....	225, 231	950261.....	596	970143.....	676
930619.....	455	931060.....	225, 231	950262.....	596	970145.....	676
930620.....	455	931061.....	225, 231	950263.....	596	970148.....	676
930621.....	455	931062.....	225, 231	950264.....	596	970160.....	680
930622.....	455	931063.....	225, 231	950265.....	596	970161.....	680
930623.....	455	931064.....	225, 231	950266.....	596	970163.....	680

970165.....	680	970831.....	643	975390.....	760
970168.....	680	970832.....	643	975391.....	760
970180.....	664	970833.....	639	975394.....	760
970181.....	664	970834.....	639	975395.....	760
970183.....	664	970835.....	639	975411.....	726
970185.....	664	970836.....	639	975412.....	726
970201.....	682	970837.....	639	975471.....	738
970202.....	682	970838.....	639	975475.....	738
970231.....	704	970839.....	639	975476.....	738
970280.....	708	970840.....	639	975483.....	740
970281.....	708	970841.....	639	975485.....	740
970284.....	708	970842.....	648	975486.....	740
970285.....	708	970843.....	648	975491.....	736
970301.....	720	970844.....	648	975495.....	736
970303.....	720	970845.....	648	975496.....	736
970305.....	720	970846.....	648	975501.....	744
970308.....	720	970847.....	648	975511.....	748
970401.....	724	970848.....	648	975516.....	750
970403.....	724	970849.....	648	975521.....	752
970404.....	724	970850.....	648	975525.....	746
970460.....	716	970860.....	649	975530.....	742
970470.....	718	970861.....	649	975724.....	774
970502.....	712	970862.....	649	975741.....	778
970503.....	712	970863.....	649	975781.....	780
970520.....	714	970864.....	649	988170.....	645
970522.....	714	970865.....	649	988171.....	645
970523.....	714	970866.....	649	988172.....	645
970550.....	728	970867.....	649	988173.....	645
970551.....	728	970868.....	649		
970560.....	730	970869.....	642		
970561.....	730	970870.....	642		
970570.....	732	970871.....	642		
970571.....	732	970872.....	642		
970572.....	622	975001.....	686		
970573.....	622	975003.....	686		
970574.....	622	975005.....	686		
970575.....	622	975008.....	686		
970576.....	622	975021.....	690		
970577.....	622	975023.....	690		
970578.....	623	975025.....	690		
970579.....	623	975028.....	690		
970580.....	623	975041.....	694		
970581.....	623	975045.....	694		
970582.....	623	975063.....	698		
970583.....	623	975065.....	698		
970584.....	624	975081.....	684		
970585.....	624	975083.....	684		
970586.....	624	975085.....	684		
970587.....	624	975101.....	688		
970588.....	624	975103.....	688		
970589.....	624	975105.....	688		
970600.....	722	975108.....	688		
970601.....	722	975121.....	692		
970602.....	722	975123.....	692		
970723.....	772	975125.....	692		
970724.....	772	975128.....	692		
970741.....	776	975141.....	696		
970800.....	634	975143.....	696		
970801.....	634	975145.....	696		
970802.....	634	975148.....	696		
970803.....	634	975161.....	700		
970804.....	635	975163.....	700		
970805.....	635	975165.....	700		
970806.....	635	975168.....	700		
970807.....	635	975231.....	706, 709		
970808.....	635	975331.....	756		
970809.....	635	975334.....	756		
970820.....	638	975341.....	762		
970821.....	638	975344.....	762		
970822.....	638	975351.....	766		
970823.....	638	975353.....	766		
970824.....	638	975360.....	758		
970825.....	638	975361.....	758		
970826.....	638	975365.....	758		
970827.....	638	975371.....	764		
970828.....	638	975375.....	764		
970829.....	643	975381.....	768		
970830.....	643	975385.....	768		

ETT Lighting d.o.o.
Dobrna 7
3204 Dobrna

Tel: + 386 3 780 10 70

info@ett-lighting.com
ett-lighting.com
ledsvetila.si